Welcome to Aggregator API Services.

The **Client 1.0 – AIR API** manages the complete flight booking process, from search to ticketing. It allows partners to search for flights, check fare rules, revalidate prices, select optional services, hold bookings, process payments, issue tickets, and reprint tickets.

The API supports temporary (hold) bookings and works with or without SSR selection (such as seats, meals, and baggage), providing flexibility throughout the booking flow.

Connectivity (Staging URLs and Credentials)

These web services are accessible via JSON-based APIs. All methods accept POST requests only and return responses in JSON format.

Service URLs (JSON)

- Domain/airlinehost/AirAPIService.svc/JSONService
- Domain.in/tradehost/TradeAPIService.svc/JSONService

Credentials

The Credentials will be shared through E-mail.

BarCode Integration:

To generate the barcode on the ticket printout at your end, you must capture and format the data as specified below.

Note: We do not provide any DDL or library for barcode generation. You are required to use a third-party DLL or library for implementing the barcode.

POST01 - Air_Search

The **Air_Search API** allows clients to search for available flights across multiple airlines based on the selected route, travel date, travel type, and passenger count. The response includes a list of available flights with fare details, cabin class, availability, and other relevant information required to proceed with pricing and booking.

a) APIAirSearchRequest

Name	Type	Description	Mandatory
Auth_Header	Object	This object holds API Authentication details	Yes
Travel_Type	Enum	This requires the Travel Type, Possible Values: 0 - DOMESTIC/1 - INTERNATIONAL	Yes
Booking_Type	Enum	This requires the BookingType. Values: 0 - ONE_WAY/ 1- ROUNDTRIP/ 2- SPECIALROUNDTRIP/3-MULTICITY	Yes
TripInfo	Object	This object holds the property of TripInfo	Yes
Adult_Count	Integer	This requires the Total number of adult	Yes

Child_Count	Integer	This requires the Total number of child	No
Infant_Count	Integer	This requires the Total number of infant	No
Class_Of_Travel	Enum	This requires the class of Travel. Possible values: 0-ECONOMY/ 1- BUSINESS/ 2- FIRST/ 3-PREMIUM_ECONOMY	Yes
InventoryType	Enum	This requires the Inventory type Possible Value : 0-RetailFare	Yes
Filtered_Airline	List(Object)	This object holds the list of AirlineCodes Ex: By search All Airline "Filtered_Airline":[{ "Airline_Code":"" }] By search particular Airline "Filtered_Airline":[{ "Airline_Code":"6E" }] By search more than one Airline "Filtered_Airline":[{ "Airline_Code":"6E" }, { "Airline_Code":"SG" }]	No

b) TripInfo

Name	Type	Description	Mandatory
Origin	String	This requires the Origin details	Yes
Destination	String	This requires the Destination details	Yes
TravelDate	String	This requires the Date of Journey. Date Format should be in **MM/DD/YYYY.**	Yes
Trip_Id	Integer	For Ongoing the TripId value should be 0, For Return the TripId value should be 1	Yes

c) Filtered_Airline

Name	Type	Description	Mandatory
Airline_Code	String	This requires the Airline code	No

Response Object : APIAirSearchResponse

a)*APIAirSearchResponse*

Name	Type	Description
Response_Header	Object	This object holds the property of ResponseHeader
Search_Key	String	This Key holds Search Details
TripDetails	List(Object)	This displays list of APITripDetail

b) *APITripDetail*

Name	Type	Description

Trip_Id	String	This displays trip id of search
Flights	List(Object)	This object holds the list of APIFlight

c) *APIFlight*

Name	Type	Description
Flight_Id	String	This displays the FlightId of the Flight.
Flight_Key	String	This key holds Flight details.
Origin	String	This displays the origin of the Journey
Destination	String	This displays the destination of the Journey
TravelDate	String	This displays the travelDate of the Journey
Segments	List(Object)	This object holds list of APISegment
Fares	List(Object)	This object holds list of APIFare
Airline_Code	String	If passed value as true, search result is fetched from DB, If false, data fetched from supplier.
Cached	Boolean	If passed value as true, search result is fetched from DB, If false, data fetched from supplier.
IsLCC	Boolean	This displays true when the flight is LCC
Block_Ticket_Allowed	Boolean	If true, block ticket allowed, If false, Block ticket not allowed.
GST_Entry_Allowed	Boolean	If true, GST entry allowed, If false,GST Entry not allowed.
Repriced	Boolean	It returns true after reprice done successfully. Otherwise false.
HasMoreClass	Boolean	Check has more class
InventoryType	Enum	This has the Inventory type Possible Values : 0-RetailFare
PromoCode	String	This displays the Promo code from supplier

d) *APISegment*

Name	Type	Description
Segment_Id	Integer	This displays the Segment id.
LegIndex	Integer	This displays the 0 based leg index for the Flight
Origin	String	This displays the origin
OriginTerminal	String	This displays the Origin Terminal

OriginCity	String	This displays the Origin City
Destination	String	This displays the segment Destination
DestinationTerminal	String	This displays the DestinationTerminal
DestinationCity	String	This displays the DestinationCity
AirlineCode	String	This displays the Airline Code
AirlineName	String	This displays the AirlineName
FlightNumber	String	This displays the FlightNumber
AircraftType	String	This displays the AircraftType
DepartureDateTime	String	This displays the DepartureDateTime
ArrivalDateTime	String	This displays the ArrivalDateTime
StopOver	List (String)	This displays the StopOver
ReturnFlight	Boolean	It has true when the Segment is ReturnSegment
Duration	String	This displays segment level Duration in HH:mm format. Using this duration have to calculate the total Journey duration.

e) *APIFare*

Name	Type	Description
FareId	Integer	This displays the unique Fare Id which needs to be passed in the upcoming requests
FareKey	Integers	This displays the unique Fare Key value.
Refundable	String	This displays the whether the fare is refundable or not.(True or False)
FareDetails	String	This displays the list of Fare Details passenger type wise
Foodonboard	String	This displays the meal is paid or free(P - Paid, F - Free)
SeatsAvailable	String	This displays the number of seats available in the fare
LastFewSeats	String	This displays the Last Few Seats
Warning	String	This displays the warming message like different destination, vis required etc.
PromptMessage	String	This displays the PRompt message if configured
GSTMandatory	String	This displays whether the GST is mandatory (True or False)

FareType	String	This displays Fare Type.

f) *APIFareDetails*

Name	Type	Description
PAXType	String	This requires the pax type. Possible Values :0-ADT/1- CHD/ 2- INF
FareClasses	List(Object)	This displays list of APIFareClass
BasicAmount	Double	This displays the BasicAmount
YQAmount	Double	This displays the YQ Amount
AirportTaxAmount	Double	This displays the AirportTaxAmount
AirportTaxes	List(Object)	This displays list ofAPIAirportTax
ServiceFeeAmount	Double	This displays the ServiceFeeAmount
TradeMarkupAmount	Double	This displays the TradeMarkupAmount
PromoDiscount	Double	This displays the PromoDiscount
GST	Double	This displays the GST
TDS	Double	This displays the TDS
GrossCommission	Double	This displays the GrossCommission
NetCommission	Double	This displays the NetCommission
CurrencyCode	String	This displays the CurrencyCode
TotalAmount	Double	This displays the TotalAmount
FreeBaggage	Object	This displays the FreeBaggage

g) *APIFareClass*

Name	Type	Description
Segment_Id	Integer	This provides the segmentId of the flight.
ClassCode	String	This displays class code of the segment.
ClassDesc	String	This displays the class desription fo the segment
FareBasis	String	This displays the fare basis code for the segment
Privileges	List(String)	This displays the privileges configured for the fare.

h) *APIAirportTax*

Name	Type	Description
TaxCode	String	This displays the TaxCode
TaxDesc	String	This displays the TaxDesc
TaxAmount	Double	This displays the TaxAmount

Request Headers

Content-Type

application/json

Accept

application/json

Bodyraw (json)


```
{
  "Auth_Header": {
      "UserId": "nomad",
      "Password": "6ozJI769@U",
      "IP_Address": "127.0.0.1",
      "Request_Id": "7FB45BA7-5A98-4B0A-B5ED-0DD591F7A572",
      "IMEI_Number": "xxxxxxxxxx"
  },
 "Travel_Type": 0,
 "Booking_Type": 2,
 "TripInfo": [
  {
    "Origin": "DEL",
    "Destination": "BOM",
    "TravelDate": "03/22/2026",
    "Trip_Id": 0
  },
  {
    "Origin": "BOM",
    "Destination": "DEL",
```

"TravelDate": "03/24/2026",
"Trip_Id": 1
}
],
"Adult_Count": 1,
"Child_Count": 1,
"Infant_Count": 1,
"Class_Of_Travel": 0,
"InventoryType": 0,
"Filtered_Airline": null
}

POST02 - Air_FareRule

The Air_FareRule API is used to retrieve the detailed fare rules and conditions applicable to the selected flight option. This API provides important information such as cancellation charges, rescheduling charges, refund policies, baggage allowances, and other fare-related restrictions defined by the airline. The fare rules returned by this API should be reviewed before proceeding with repricing and booking to ensure the selected flight meets the customer's requirements.

API Air Fare Rule Request

Name	Type	Description	Mandatory
AuthHeader	Object	This object holds API Authentication details	Yes
Search_Key	String	This key holds flight journey search detail	Yes
Flight_Key	String	This key holds selected flight detail	Yes
Fare_Id	String	This holds selected Fare Id	Yes

API Air Fare Rule Response

Name	Type	Description
ResponseHeader	Object	This object holds the property of Response Header
FareRules	List(Object)	This object holds list of Fare Rule detail

a) FareRules

Name	Type	Description

Segment_Id	String	This displays the segment id
FareRuleName	String	This displays the fare rule name
FareRuleDesc	String	This displays the fare rule description

Bodyraw (json) {


```
  "Auth_Header": {
    "UserId": "xxxxxxxxxx",
    "Password": "xxxxxxxxxx",
    "IP_Address": "xxxxxxxxxx",
    "Request_Id": "xxxxxxxxxx",
    "IMEI_Number": "xxxxxxxxxx"
  },
  "Search_Key":
"hZJGvxjxVtO7FHSsgfqjDJqMuFbsH02S9SFBPYAzVCNwvKo54vZl6hhwN4jnan3bAOpEpU+q6//MMTfJ
HYiIB0O5IGm8NRgL+YnaS27X3mh4sQZDJbOi/52YY+HnGb6UlyGANCyE8LomwWw+lqIJonuHx2TmAjP
7Tr/JjieMRVyfUCopx84+0zU1XDGofF35hnmW1apfsKJvAdqrcZxedxFSoe/lsHcKsyBpipU+yQtx7Yv7QoU
xl+suVcbml19FLTyhMSaR9BRSsvprJc5gwxA/UQDjb/747WbCMFxxGd+SJSsip7z0lejt/uptjiYO6AsYinkxX
9YSOyywVpmtsVBqhcE8apybCTA7k54wsa3tq+JCBlV9QeKSxKU+GBgrJLWx6Y3HGyKeo95a7U09/DvlL3
2EZ26I/78PH+qa/JBS9do4Mm0aCe+jmg66YTWV5jj6mXS/gy3Hlz5MAuAKHIwHn8fuVYGXANAYwLwTp
7pdVqv85ewx1KU8p5utEl+Setgz/2eOhoPSJv0r68QZBgaL1sEJRZE6SKecSVbotILlranLSAiAXUin3N4XUX
aaLTQTtC+2Nueaaa0SvmKSofbvD5Ki2lcD3/7kPPAQRN5+J3SxxeYu/k3ad4C5H23l9Rir0Ezc497XKUXyQo
ELP0DSRqVADD9O8BqL0FpMnA/iGCgaY3OaCj4f7KXalBl4",

  "Flight_Key":
"FK5632349256982866754$FK5533397719290506861$FK5543488752756723127$FK498924380115
0943403"
```


POST03 - Air_Reprice

The Air_Reprice API is used to revalidate and reprice the selected flight fare with the supplier before proceeding with the booking. This API ensures that the fare, availability, and other pricing components are still valid and up to date. The response returns the latest flight details with the repriced flag set to true, confirming whether the fare has changed or remains the same. This step is mandatory before booking to avoid fare mismatch or booking failures due to price changes.

API Air Reprice Request

Name	Type	Description	Mandatory
AuthHeader	Object	This object holds API Authentication details	Yes
Search_Key	String	This key holds search flight details	Yes

AirRepriceRequests	List(Object)	This object holds list of APIRepriceRequest detail	Yes
CustomerMobile	String	This requires customer mobile number. If you had pass the customer mobile number. Otherwise, pass the default AGENCY REGISTERED MOBILE NUMBER	Yes
GSTInput	String	This requires GST Input	No

a) Air Reprice Request

Name	Type	Description	Mandatory
Flight_Key	String	This Flight key has selected flight details	Yes
Fare_Id	String	This requires selected FareId from Flight searchresponse	Yes

API Air Reprice Response

Name	Type	Description
ResponseHeader	Object	This object holds the property of Response Header
AirRepriceResponses	List(Object)	This object holds the list of API Air Reprice Response
FrequentFlyerAccepted	Boolean	If true, Frequent Flyer accepted, If false, ,Frequent Flyer not accepted.

a) AirRepriceResponses

Name	Type	Description
Flight	Object	This object holds the property of Flight details
RequiredPAXDetails	List(Object)	This object holds the list of API Required PAX Detail for each PAXs. The property in the class defines the required values for the APITempBooking

b) RequiredPAXDetails

Name	Type	Description
Title	Boolean	If true, Title is required
FirstName	Boolean	If true, First Name is required
LastName	Boolean	If true, Last Name is required
Gender	Boolean	If true, Gender is required
Age	Boolean	If true, Age required
DOB	Boolean	If true, DOB required

PassportNumber	Boolean	If true, Passport Number required
PassportIssuingCountry	Boolean	If true, Passport Issuing Country required
PassportExpiry	Boolean	If true, Passport Expiry required
Nationality	Boolean	If true, Nationality required
Paxtype	Enum	This requires the Pax type. Possible Values :ADT-0/ CHD-1/ INF-2

c) Flight

Name	Type	Description
Flight_Id	String	This displays the Flight Id of the Flight.
Flight_Key	String	This key holds Flight details
Origin	String	This displays the origin of the Journey
Destination	String	This displays the destination of the Journey
TravelDate	String	This displays the travel Date of the Journey
Segments	List(Object)	This object holds list of API Segment
Fares	List(Object)	This object holds list of API Fare
Airline_Code	String	This displays the airline code.
Cached	Boolean	If passed value as true, search result is fetched from DB, If false, data fetched from supplier.
IsLCC	Boolean	This displays true when the flight is LCC
Block_Ticket_Allowed	Boolean	If true, block ticket allowed, If false,Block ticket not allowed.
GST_Entry_Allowed	Boolean	If true, GST entry allowed, If false, GST Entry not allowed.
Repriced	Boolean	It returns true after reprice done successfully. Otherwise false.
HasMoreClass	Boolean	Check has more class
InventoryType	Enum	This has the Inventory type Possible Values : RetailFare-0
PromoCode	String	This displays the Promo code from supplier

d) API Segment

Name	Type	Description
Segment_Id	Integer	This displays the Segment id.

LegIndex	Integer	This displays the 0 based leg index for the Flight
Origin	String	This displays the origin
OriginTerminal	String	This displays the Origin Terminal
OriginCity	String	This displays the Origin City
Destination	String	This displays the segment Destination
DestinationTerminal	String	This displays the Destination Terminal
DestinationCity	String	This displays the Destination City
AirlineCode	String	This displays the Airline Code
AirlineName	String	This displays the Airline Name
FlightNumber	String	This displays the Flight Number
AircraftType	String	This displays the Aircraft Type
DepartureDateTime	String	This displays the Departure Date Time
ArrivalDateTime	String	This displays the Arrival Date Time
StopOver	List (String)	This displays the Stop Over
ReturnFlight	Boolean	It has true when the Segment is Return Segment
Duration	String	This displays segment level Duration in HH : mm format. Using this duration have to calculate the total Journey duration.

e) API Fare

Name	**Type**	**Description**
FareId	String	This displays the Fare Id
FareKey	String	This displays the selected Fare Key
Refundable	Boolean	This denotes whether the fare is Refundable or not
FareDetails	List (Object)	This object has list of API Fare Detail
Foodonboard	String	This displays the Food onboard
SeatsAvailable	String	This displays the Seats Available
LastFewSeats	String	This displays the Last Few Seats

Warning	String	This displays the Warning
PromptMessage	String	This displays the Prompt Message
GSTMandatory	String	This displays the GST Mandatory
FareType	String	This requires the Fare type Possible Values :RetailFare -0/CouponFare-1/CorporateFare-2/SMEFare-3/RTSPLFare-4/DealFare-5

f) API Fare Detail

Name	**Type**	**Description**
PAXType	String	This requires the pax type. Possible Values :ADT-0/ CHD-1/ INF-2
FareClasses	List(Object)	This displays list ofAPI Fare Class
BasicAmount	Double	This displays the Basic Amount
YQAmount	Double	This displays the YQ Amount
AirportTaxAmount	Double	This displays the Airport Tax Amount
AirportTaxes	List(Object)	This displays list of API Airport Tax
ServiceFeeAmount	Double	This displays the Service Fee Amount
TradeMarkupAmount	Double	This displays the Trade Markup Amount
PromoDiscount	Double	This displays the Promo Discount
GST	Double	This displays the GST
TDS	Double	This displays the TDS
GrossCommission	Double	This displays the Gross Commission
NetCommission	Double	This displays the Net Commission
CurrencyCode	Double	This displays the Currency Code
TotalAmount	Double	This displays the Total Amount
FreeBaggage	Object	This displays the FreeBaggage

g) Fare Classes

Naem	**Type**	**Description**
Segment_Id	Integer	This displays the Segment Id
ClassCode	String	This displays the Class Code

ClassDesc	String	This displays the Class Description
FareBasis	String	This displays the Fare Basis
Privileges	List (string)	This displays the Privileges list

h) Airport Taxes

Name	Type	Description
TaxCode	String	This displays the Tax Code
TaxDesc	String	This displays the Tax Description
TaxAmount	Double	This displays the Tax Amount


```
{
  "Auth_Header": {
      "UserId": "xxxxxxxxxx",
      "Password": "***********",
      "IP_Address": "127.0.0.1",
      "Request_Id": "7FB45BA7-5A98-4B0A-B5ED-0DD591F7A572",
      "IMEI_Number": "xxxxxxxxxx"
   },
   "Search_Key":
"Sn2bwFI42VW/pGQ/O11uM90v1lgxTeGvyctVEk8PTUbhmhu1eT8JQnMVPcsJ/eoZie2yVS0GWt/sXm4
9gKtNXmT9rpXNVhJt4ceewnyy8YFr4YnTVffsB7HaM+LfNJQpOvXVeLGuLaMwx4nsgu98MAmmpF52rE
UpCBZfima8HF9rDA78NMSdUvZ2u/6Oxybh789PqMC/Adbe64izgnO7AiCpDRlu9TY1XrF0M9jxNbdHHJ
qsRHMVaisrG4Hs5N5myy8sFN4Z5ILskNNvkVxCsXyJ+fuVpLi8PU7Uvj0Jw6IIml2113MBGuo5ysyCaywM
m1y/ ==",
   "AirRepriceRequests": [
      {
         "Flight_Key":
"KEYZUS3soIEDavvG+Mmp4rgfGiBLQbSbeEcEg/AieJZuU33QqXSNl5rFkjXqnDy+Y0ub4ThbxdvGuIw+tP
3f5+ws+3Yve2iOvPh/5hVOBrqUhDtWvrG3lAyxHyI7u9eiAitT66mXoclh5uRYpHJCyDLvC1BUiGvYGFBwG
ey1i1J4x6pCngiI+LdQ4EzODCmcMQXsFdK+W6QI9JsBf5RLpSXNDlexebH6/Gwiug4BrV+cPuek2SC6TYV
GedfG3uHISI0seAT3r7bOiLSBAr
         "Fare_Id": "O5348078347583492490"
      }
```

,{

"Flight_Key": "KEY4NZIOGRXBnjjRnnXxFJty76CuNQe7Pa2xrW9GJ20lWbPPNM5scv+ZoFaak4WNB/NMYFoihCfnH1pB22zF0jkeT4sLH6hrBAiGh+BIulHevpKggmok+WCDDaZz6bcCjyBa71l86MIgml/S9r7HTSjMBwZv9KeNqNUAGIG7Xh30S7UQ4o7sYM68T9mGA6yNwbG7mSl3eUtlSEw5CXYDcuI3j5L6uHwOQaI/DxuwnAggkNLfcO8FPMqqp+",

"Fare_Id": "O5686649742382815696"

}

],

"Customer_Mobile": "9173456988",

"GST_Input": false,

"SinglePricing": true

},

"Fare_Id": "O4791733020558609072"

}

POST04 - Air_GetSSR

The Air_GetSSR API is used to retrieve the list of available special service requests for the selected flight, such as meals, baggage, seat preferences, and other airline-specific services. This API must be called using the Flight_Key obtained from the Air_Reprice API response to ensure that the SSR information is fetched for the correct and latest priced flight. The response provides the complete list of optional and mandatory services that can be added before proceeding with seat selection and booking.

Air API SSR Request

Name	Type	Description	Mandatory
AuthHeader	Object	This object holds API Authentication details	Yes
Search_Key	String	This requires the flight search key	Yes
AirSSRRequestDetails	List(Object)	This object holds list of Air SSR Request Detail	Yes

a)Air SSR Request Details

Name	Type	Description	Mandatory
Flight_Key	String	**This requires the selected flight key from Air_Reprice**	Yes

Air API SSR Response

Name	Type	Description
ResponseHeader	Object	This object holds the property of Response Header
SSRFlightDetails	List(Object)	This object holds the property of API SSR Flight Detail

a)SSR Flight Detail

Name	Type	Description
SSRDetails	List(Object)	This object holds the list of API SSR Detail

b) SSR Detail

Name	Type	Description
SSR_Type	Enum	This displays the SST type. Possible values: 0-BAGGAGE / 1-MEALS/ 2-COMPLIMENTORY_MEALS/ 3-SEAT/ 4-SPORTS/ 5-BAGOUTFIRST/ 6-LOUNGE/ 7-CELEBRATION/ 8-CARRYMORE/ 9-FASTFORWARD/ 10-WHEELCHAIR/ 11-FREQUENTFLYER/ 15-OTHERS
SSR_TypeName	String	This displays SSR_Type Name
SSR_TypeDesc	String	This displays SSR_Type Desc
SegmentWise	Boolean	This returns true for the SSR is by Segment Wise. It will false for Journey Wise
LegIndex	Integer	This displays Leg Index
Segment_Id	Integer	This displays Segment_Id
FlightID	String	This displays Flight ID
CurrencyCode	String	This displays Currency Code
TotalAmount	Double	This displays Total Amount
ApplicablePaxTypes	List	This displays Applicable Pax Types. Possible values are ADT/ CHD/ INF
SSR_Key	String	This displays SSR_Key
SSR_Status	Enum	This displays SSR Status. It is meaningless in SSR response. The SSR Status is meaningful in Air_GetSeatMap response only.


```
{
  "trackId": null,
  "Auth_Header": {
      "UserId": "xxxxxxxxxx",
```

"Password": "**********",

"IP_Address": "127.0.0.1",

"Request_Id": "7FB45BA7-5A98-4B0A-B5ED-0DD591F7A572",

"IMEI_Number": "xxxxxxxxxx"

},

"Search_Key":
"oUnUPIR7p9eRpHXfZC6HGodmBFKv7H7WwQYh4AkpviL5ZzjkqbWieqeeQZWVKxPjlaemIzcQGQPvZQ
9ZtTomzZnAecG1AhgLMq0KBqY2E2duTTUo4FZMiHmyl2ruJjAYNSlshvXWYhAzP9RNh2XxK/szujG1TcN
Ty+0UNhB4oCZiy9/jkRZFtwqDj1ueskZYEoJyQ2uBupuSPGI2xYf/zvSszya77k0tIT7ve5XfHvjfaz+o8O0wIv
91T0jboIBRoGpkWgrC+L8lv8jiDTC2h+l04abqJohBDHXVoiy35SR4cAqCyvB75GQa02WRLe1OUFoNXAfb
2/2+F/dhdHcOvQXFAxfZHrLP9woZR3gN3QRqeQrbCtN9m4Nhz2zHYc1LQszQurEf4VrC7RwhMNByPQL
G4aAT8GZr3zUtpYIm/K5tcMQPLrUmDOvqpsiBA1yiEQZSI8VLoeHjLFZuoeMiQ+p+R7KoGfSzi41r+dv+1
GsHyFVkp29KdPjjl8zneX6FknXeTjgp0ofiM7hdyl+lxyYVkDZWK3KC+KsyagVzAHMbwy8MOTHtWu8p7b
BbHwEWTjo2sa81dllQHaMrgsAzR3vi7pupQJmNUO4hn4+DmZHvrb7DlBM0PVngCAdeJ8EP6ztGY6AhY
3hYrE5S24/4t30FJ6CPRP98wyxzaDjYEWWntuMPwwO8rUaMemXmN0R6JOJQVxpiEe1fBADeotWFhq
Ns5HqwD2nH7n0CHhXYRQM=",

"AirSSRRequestDetails": [

{

"Flight_Key":
"KEY1LvAqSdrqfTTnAy1RqTDElVdBjyxz76sAQ3+a8rlvYSa81k8johlmG/RZbKZez/Hc9UbCNZ2R9dkJGQrZ
d3z+Irwswa0vn6FcrvnTH94WGsVXRE9BvAaMcRzu8ddtEuGKB+8TfgTq1CDs++/eI0R1mjND5J40xrxUws
+uBFD0bSXHFhto3H8XBKw8P4t+ ==="

}

]

}

POST05 - Air_GetSeatMap

The Air_GetSeatMap API is used to retrieve the seat layout and available seat options for the selected flight segments. This API must be called using the Flight_Key obtained from the Air_Reprice API response to ensure that seat availability is fetched for the correct and latest priced flight. The response provides detailed seat information, including available, occupied, and chargeable seats, which allows the user to select preferred seats before proceeding with the booking.

API Air Seat Map Request

Name	Type	Description	Mandatory
AuthHeader	Object	This object holds API Authentication details	Yes
Search_Key	String	This requires Search key from Flight search response	Yes

Flight_Key	List(string)	**This requires the selected flight key from Air_Reprice**	Yes
PAXDetails	List(Object)	This objects requires the list of Booking PAX Detail	Yes

a)PAX Details

Name	Type	Description	Mandatory
Pax_Id	Integer	This requires PAX id	Yes
Pax_type	String	This requires Pax type	Yes
Title	String	This requires Title	Yes
FirstName	String	This requires First Name	Yes
LastName	String	This requires Last Name	Yes
Gender	String	This requires Gender. Possible values 0/1 (0-Male, 1-Female)	Yes
Age	String	This requires Age	No
DOB	String	This requires DOB	No
PassportNumber	String	This requires Passport Number	No
PassportIssuingCountry	String	This requires Passport Issuing Country	No
PassportExpiry	String	This requires Passport Expiry	No
Nationality	String	This requires Nationality	No
FrequentFlyerDetails	List(object)	This requires list of Frequent Flyer Detail	No

b) Frequent Flyer Detail

Name	Type	Description	Mandatory
AirLineCode	String	This requires airline code	No
FrequentFlyerNumber	String	This requiresFrequentFlyerNumber	No

API Air Seat Map Response

Name	Type	Description
ResponseHeader	Object	This object holds the property of Response Header
AirSeatMaps	List(Object)	This holds list of API Air Seat Map

a) Air Seat Map

Name	Type	Description

FlightId	String	This displays flight id
SeatSegments	List(Object)	This object holds list of API Seat_Segment

b)Seat Segments

Name	Type	Description
LegIndex	Integer	This displays leg index
SeatRow	List(Object)	This object holds list of API Seat_Row

c) Seat Row

Name	Type	Description
SeatDetails	List(Object)	This object holds list of **APISSRDetail**

d) SSR Details

Name	Type	Description
SSR_Type	String	This displays value of SSR type. Possible values: 0-BAGGAGE/ 1-MEALS/ 2-COMPLIMENTORY_MEALS/ 3-SEAT/ 4-SPORTS/ 5-BAGOUTFIRST/ 6-LOUNGE/ 7-CELEBRATION/ 8-CARRYMORE/ 9-FASTFORWARD/ 10-WHEELCHAIR/ 11-FREQUENTFLYER/ 15-OTHERS
SSR_Type Name	String	This displays SSR_Type Name
SSR_Type Desc	String	This displays SSR_Type Desc
SegmentWise	String	This displays Segment Wise
LegIndex	Integer	This displays Leg Index

Segment_Id	Integer	This displays Segment_Id
FlightID	String	This displays Flight ID
CurrencyCode	String	This displays Currency Code
TotalAmount	Double	This displays Total Amount
ApplicablePaxTypes	String	This displays Applicable Pax Types. possible values are ADT/CHD/INF
SSR_Key	String	This displays SSRKey
SSR_Status	Enum	This displays SSR Status. Possible values are 0-ISLE\ 1-AVAILABLE\ 2-BLOCKED\ 3-BOOKED Note: SSR_Status In SEAT, 0-ISLE means its not seat, It denotes, it is an ISLE pathway to show in seatmap.


```
{
  "Auth_Header": {
    "UserId": "xxxxxxxxxx",
    "Password": "************",
    "IP_Address": "127.0.0.1",
    "Request_Id": "7FB45BA7-5A98-4B0A-B5ED-0DD591F7A572",
    "IMEI_Number": "xxxxxxxxxx"
  },
  "Search_Key":
"oUnUPIR7p9eRpHXfZC6HGodmBFKv7H7WwQYh4AkpviL5ZzjkqbWieqeeQZWVKxPjlaemIzc
```

QGQPvZQ9ZtTomzZnAecG1AhgLMq0KBqY2E2duTTUo4FZMiHmyl2ruJjAYNSlshvXWYhAzP9RNh2XxK//4t30FJ6CPRP98wyxzaDjYEWWntuMPwwO8rUaMemXmN0R6JOJQVxpiEe1fBADeotWFhqNs5HqwD2nH7n0CHhXYRQM=",

"Flight_Keys": [

"KEY1LvAqSdrqfTTnAy1RqTDElVdBjyxz76sAQ3+a8rlvYSa81k8johlmG/RZbKZez/Hc9UbCNZ2R9dkJGQrZd3z+Irwswa0vn6FcrvnTH94WGsVXRE9BvAaMcRzu8ddtEuGKB+8TfgTq1CDs++/eI0R1mjND5J40xrxUws+
+vzIwBPtlLIiu9xlNs3dpWntw5cECMF58WNQLD+tCZlUwo7FfJDLKh4RgdlV6aSIkOnnYwEvTqkJx046hCzlaCRPtQBJ3zE8RJg7ye43Zb7nuCL1plIIdFZ559KAwBWNsAMGJuKN44cNKSjhKxhz2N4G+JltCn18M1K+RQA=="

]

}

POST06 - Air_TempBooking

The Air_TempBooking API is used to generate a temporary booking reference number using the provided passenger and flight details. This API must be called using the Flight_Key obtained from the Air_Reprice API response to ensure that the reference is generated for the correct and latest priced flight. The number of passengers provided in this request must be the same as the number of passengers used in the Air_Search API.

Air Temp Booking Request

Name	Type	Description	Mandatory
AuthHeader	Object	This object holds API Authentication details	Yes
CustomerMobile	String	This requires the **AGENCY REGISTERED MOBILE NUMBER Mandatory.**	Yes
PassengerMobile	String	This requires the passenger mobile number	No
PassengerEmail	String	This requires the passenger email	No
PAXDetails	List(Object)	This object requires the Passenger details	Yes
GST	Boolean	This GST flag should be true when passing GST details to the booking.	No
GST_Number	String	This requires the Customer GST Number	No
GST_HolderName	String	This requires the GST holder name	No
GST_Address	String	This requires the GST holder address	No
GST_Phone	String	This requires the GST holder phone Number	No
GST_Email	String	This requires the GST holder EmailId	No

BookingFlightDetails	List(object)	This requires the Booking Flight Details	Yes
CostCenterId	Integer	This requires the Cost Center Id	No
ProjectId	Integer	This requires the Project Id	No
BookingRemark	String	This requires the BookingRemark	No

a)PAX Details

Name	Type	Description	Mandatory
Pax_Id	Integer	This requires the Pax id (1 based starting index)	Yes
Pax_type	String	This requires the PAX type 0-ADT/ 1-CHD/ 2-INF	Yes
Title	String	This requires the title Adult - MR, MRS, MS Child - MSTR, MISS Infant - MSTR, MISS	Yes
FirstName	String	This requires the first name	Yes
LastName	String	This requires the last name	Yes
Gender	String	This requires the gender. Possible values 0/1 (0-Male, 1-Female)	Yes
Age	String	This requires the Age	No
DOB	String	This requires the DOB and the format should be **MM/DD/YYYY** format.	No
PassportNumber	String	This requires the Passport Number	No
PassportIssuingCountry	String	This requires the Passport Issuing Country	No
PassportExpiry	String	This requires the Passport Expiry and the format should be **MM/DD/YYYY** format.	No
Nationality	String	This requires the Nationality	No
Pan Card Number	String	This requires the Pan Card Number	No
FrequentFlyerDetails	List(object)	This requires list of Frequent Flyer Detail	No

b) Frequent Flyer Detail

Name	Type	Description	Mandatory
AirLineCode	String	This requires the AirLineCode	No
FrequentFlyerNumber	String	This requires the Frequent Flyer Number	No

c) Booking Flight Detail

Name	Type	Description	Mandatory
Search_Key	String	This requires flight journey search APIAirSearchRequest details as Key	Yes
Flight_Key	String	This requires the selected flight key from Air_Reprice	Yes
BookingSSRDetails	List(Object)	This requires list of Booking SSR Detail	No

d) Booking SSR Detail

Name	Type	Description	Mandatory
Pax_Id	Integer	This requires the pax id	Yes
SSR_Key	String	This requires the SSR key	Yes

Air Temp Booking Response

Name	Type	Description
ResponseHeader	Object	This object holds the property of Response Header
BookingRefNo	String	This displays the booking reference number, this reference no. you have to use in Ref No in Add Payment method


```
{
  "Auth_Header": {
    "UserId": "xxxxxxxxxx",
    "Password": "***********",
    "IP_Address": "127.0.0.1",
    "Request_Id": "7FB45BA7-5A98-4B0A-B5ED-0DD591F7A572",
    "IMEI_Number": "xxxxxxxxxx"
  },
  "Customer_Mobile": "917987293535",
  "Passenger_Mobile": "917987293535",
  "WhatsAPP_Mobile": null,
  "Passenger_Email": "john4537@gmail.com",
  "PAX_Details": [
    {
      "Pax_Id": 1,
      "Pax_type": 0,
```

"Title": "Mr",
"First_Name": "JOHN",
"Last_Name": "SMITH",
"Gender": 0,
"Age": "30",
"DOB": "11/30/1995",
"Passport_Number": null,
"Passport_Issuing_Country": null,
"Passport_Expiry": null,
"Nationality": null,
"Pancard_Number": null,
"FrequentFlyerDetails": null
},
{
"Pax_Id": 2,
"Pax_type": 0,
"Title": "Mrs",
"First_Name": "MARY",
"Last_Name": "SMITH",
"Gender": 1,
"Age": "26",
"DOB": "02/15/1999",
"Passport_Number": null,
"Passport_Issuing_Country": null,
"Passport_Expiry": null,
"Nationality": null,
"Pancard_Number": null,
"FrequentFlyerDetails": null
},
{
"Pax_Id": 3,

"Pax_type": 1,
"Title": "Master",
"First_Name": "ALEX",
"Last_Name": "SMITH",
"Gender": 0,
"Age": "7",
"DOB": "07/13/2018",
"Passport_Number": null,
"Passport_Issuing_Country": null,
"Passport_Expiry": null,
"Nationality": null,
"Pancard_Number": null,
"FrequentFlyerDetails": null
},
{
"Pax_Id": 4,
"Pax_type": 1,
"Title": "Miss",
"First_Name": "EMMA",
"Last_Name": "SMITH",
"Gender": 1,
"Age": "8",
"DOB": "05/05/2017",
"Passport_Number": null,
"Passport_Issuing_Country": null,
"Passport_Expiry": null,
"Nationality": null,
"Pancard_Number": null,
"FrequentFlyerDetails": null
},
{

"Pax_Id": 5,
"Pax_type": 2,
"Title": "Master",
"First_Name": "NOAH",
"Last_Name": "SMITH",
"Gender": 0,
"Age": "0",
"DOB": "09/02/2025",
"Passport_Number": null,
"Passport_Issuing_Country": null,
"Passport_Expiry": null,
"Nationality": null,
"Pancard_Number": null,
"FrequentFlyerDetails": null
},
{
"Pax_Id": 6,
"Pax_type": 2,
"Title": "Master",
"First_Name": "LIFY",
"Last_Name": "SMITH",
"Gender": 0,
"Age": "1",
"DOB": "12/22/2024",
"Passport_Number": null,
"Passport_Issuing_Country": null,
"Passport_Expiry": null,
"Nationality": null,
"Pancard_Number": null,
"FrequentFlyerDetails": null
}

```
],
"GST": true,
"GST_Number": "26AAQCS4259Q1ZC",
"GST_HolderName": "Code Private Limited",
"GST_Address": "C/o Krishna Packaging, Part No. 6, SR. 336/2 6, Nearby Cricket Ground, Dadra and Nagar Haveli and Daman and Diu, 396210",
"BookingFlightDetails": [
  {
    "Search_Key": "oUnUPIR7p9eRpHXfZC6HGodmBFKv7H7WwQYh4AkpviL5ZzjkqbWieqeeQZWVKxPjlaemIzcQGQPvZQ9ZtTomzZnAecG1AhgLvrb7DlBM0PVngCAdeJ8EP6ztGY6AhY3hYrE5S24/4t30FJ6CPRP98wyxzaDjYEWWntuMPwwO8rUaMemXmN0R6JOJQVxpiEe1fBADeotWFhqNs5HqwD2nH7n0CHhXYRQM=",
    "Flight_Key": "KEY1LvAqSdrqfT9xsAEctjLLyCn3pCyMxJx7e9l0nNZfWteXTzok4ddo2NO8nGyB3Br2QZcavm+vzIwBPtlLIiu9xlNs3dpWntw5cECMF58WNQLD+tCZlUwo7FfJDLKh4RgdlV6aSIkOnnYwEvTqkJx046hCzlaCRPtQBJ3zE8RJg7ye43Zb7nuCL1plIIdFZ559KAwBWNsAMGJuKN44cNKSjhKxhz2N4G+JltCn18M1K+RQA==",
    "BookingSSRDetails": [
      {
        "Pax_Id": 1,
        "SSR_Key": "b6ByoxguAz8RiCG8ukVPAv0CyHurcAC3vYqB65gPgM1aywbSUQ3Vm1lYmV1j8q5E85F0jZpXqsufuDVtf+ +fnF1oKBFeGe9Q2XA57lIT0cu5Vk7SClC0fhNjFdJIOKCc7KDQF8d5"
      },
      {
        "Pax_Id": 1,
        "SSR_Key": "H9vMLpjAhFfV0hV8vk6VOrmuHVosVnqqojCnSiR1O/YaTrp0g9KwL+taEgqyHe/Vx5lUTUBV8pfhMs+R6Ljep+ /KHlt3qDjXzE2X7WyIKFcnzygk0032fhdWLC8gkAyTXSYJjgv791msNM4SrX2QZhLYwBw=="
      },
      {
        "Pax_Id": 1,
        "SSR_Key": "IYaqSyi+y/ouyPOl/ /tbRSPnH1V8z13IbKbzstNljpD/Q5q5NuVm9hSTBesQZ4eMnVOvsfi+wmkXVxhDgED9Obcs/ugny/YgOU13Eo4apXiNVW2k2LobwXE1WoN/856o0699GjeOf45X0flULX9MXUE/qeyUScTxSX4Anj69yWuWFmNIRND3X8qZGw=="
      },
```

{
"Pax_Id": 1,
"SSR_Key": "QUlGM6Dsg2sIkjLHEdZ17+t//NjxFyfK+ ="
},
{
"Pax_Id": 1,
"SSR_Key": "4HMUgHgkMUTIrsYPOSNMCKZLVW0OySKYB1QwahRFBSl/Qgp6jzZ396XirQSSEaxtMSSAGZ1k8nglWDPhhMR9ZRteN6I38SbzOumi/O2+ +/Ocg=="
},
{
"Pax_Id": 2,
"SSR_Key": "QrKZLePLlDNshWDAVvOJBmXmkvpIilLbVHJyvSR5VZO2yyvETgVkiahA/M30Wuax/ /Y7BRgWc2Aa+pO/wi8TvR1b1glvEeghbLi79ICb1w"
},
{
"Pax_Id": 2,
"SSR_Key": "G6nxw36Y7Ej0jw59+ ="
},
{
"Pax_Id": 2,
"SSR_Key": "IYaqSyi+y/ouyPOl/hqn57QmRWFoC99wrv+10n8fBeCIbTbX6+4Tz4tqpl2NwupQI43n6QOghP6fc+ik4Pz1KOBrsUS1Q1Cw/qmXzWR1fkoEw/ =="
},
{
"Pax_Id": 2,
"SSR_Key": "QUlGM6Dsg2sIkjLHEdZ17+t//NjxFyfK+ ="
},
{
"Pax_Id": 2,

"SSR_Key": "b6ByoxguAz8RiCG8ukVPAjGf/3rjNLv+/Du5nyqp1jqKa9U2KcCuQ/
/uRnhyxZiiTRjYpvNz8xg2RDDMgvSuxTD//v/etN/6pCnpucnWUsCxlQPndSHGOlU"

},

{

"Pax_Id": 3,

"SSR_Key":
"Hsi2VSBd7gzkabkYUY8qCklpcTS+Yg4O31zI0BCMdGhjsLD8f6GWLpaHVCucvlsknsMyDBM4S/krTNfSJy
zQOWK+
/MZWoyHHBmCEFbAII9vwqBtw1Oobe8v5bQ1285ZIkZKVIIXrGslAVJYWQJyjvA5dBAWAIEgRXKHRoYMt
PnlUd3cLVQX0bRw=="

},

{

"Pax_Id": 3,

"SSR_Key":
"uY4eq7huAGhuRdKTDNMuhN34AMScR2ONcajoV3VXqv+PO3zKVCy7mM91LDDBj70MUmKerDwzPc
BP8UrPrHKwL2MVoh9Oy4A/
/vXf+YsVHJrWjjCOq5fccAVdiCSLR3WzDDuna5oJvNMHHGAkTUvMFlBzcPja4IJlIlddJn6E8BHj"

},

{

"Pax_Id": 3,

"SSR_Key": "IYaqSyi+y/ouyPOl/
/m5JaXQQLmKgpmz0dUmpS3Y1RLGw+hNi/S8/foWET8MxtipscbSiN4XcCJ587cSovXYvXW16G63A0w=
="

},

{

"Pax_Id": 3,

"SSR_Key": "ipvxIhifvdtIUhjj4vpXdczvjmb+RTjlL3CneIUcah1mmPGQifv0vpG/
/4rdZyhMt7QDLSkUYLlbJJ42M9Uc0NmRe96dIFFqvi2M4EfjQ0EuvjVY2uMhSm7uMA3cHJwkCwK62uG
3/RY0S2YHoa8ac/xMoHL7xmMuw=="

},

{

"Pax_Id": 3,

"SSR_Key":
"b6ByoxguAz8RiCG8ukVPAoA1wXYJdnio1xiHzQyEbEsuDvq5h6b6p55lin8vND9XzhYz0WwC5drXcw9oU
0iNZxy/N0g6nNND8KkwkTxteSDarS487eJHwwYcT7IVI1WJkHi81PgGGR/pvoDX8me2DQuW8/ENcrpFq
0uE7fogvgXyqUZGtMQ/cxUcZMXZdnZto/ ==="

},
{
"Pax_Id": 4,
"SSR_Key":
"6a73hPMyqO0uFlItbA8KUeAIifEeQiHcqF6G3zB6ifjyfmAzDbo+SW5+uw+1Ghz4G3F8GT7V1Eu0Kkh/
rg4Nmlqe1zDPSDDxiwuVqoNnR4WRHcuo3AVhvfe58xnK7KQlZHtVzuf9OLYI5X94euFU+Jcsv+Ff8QYyhD
PpOnoNVxsiPSws8PRxe4ejjWRVXyr+XDWl0f5GzULU5IjC1Ed99ay6zUHM0F/9T3B5Fp"
},
{
"Pax_Id": 4,
"SSR_Key": "G6nxw36Y7Ej0jw59+
+hNYgd9QM9fULGJ/my32WoyFDLOovofCG1AtLv+ohAvJ/EDHv6rRzKFdDaSxwuowzIbE243too3r2AQ9
GARbBm//g0uQPuJMrGFqc0zbQUu8fSxk4Y8L9yvvtVZs1QAhd9EC84ExO72uitXWmf6zQ38OZaWCXeh
EkjJIHPLZ7fmhWZs1YCmEM="
},
{
"Pax_Id": 4,
"SSR_Key":
"IYaqSyi+y/ouyPOl/hqn57QmRWFoC99wrv+10n8fBeCIbTbX6+4Tz4tqpl2NwupQI43n6QOghP6fc+ik4P
z1KOBrsUS1Q1Cw/qmXzWR1fkoEw/RfRkvrfFE9j5sMlawi7E28Aovr7sx2nuSngUf5MbBNGerQVoRnjLjgj
DwI31seA3jYW00nmzazr6o/9NuHXkWb
/m5JaXQQLmKgpmz0dUmpS3Y1RLGw+hNi/S8/foWET8MxtipscbSiN4XcCJ587cSovXYvXW16G63A0w=
="
},
{
"Pax_Id": 4,
"SSR_Key":
"QUlGM6Dsg2sIkjLHEdZ17+t//NjxFyfK+CZxAyqv9GJTCXwi7ZIkT5odu6eHxLB1k7c3z4lKBiIUyBuNetcqfE
uXRup4tavXMfseJB9kvP /J8uL04PDGzmd2mDiIkKxe/crUCPDgje7JsW3uufiNaO0Q="
},
{
"Pax_Id": 4,
"SSR_Key":
"XZKAqAXnA8/WKqz2l+c8xBq5v8Cc7sQAsoDC9o7+qdcNJcJbA6az7vKmYOm/r3F++TxlB7lBH9bjrykT0
WnfNUZe83bCJrdfWZkIyutcCDRlq2tho9m6pJ6WpuDy4QpG3z4Fm93xxLYdT4SKAbW4Eair+fn3jW8PO
RQOkImbckMyH2SmpkCX+ldr1fbcr59iwRqYO9VU5qJMMkE2m"
}

```
        ]
      }
    ],
    "CostCenterId": 0,
    "ProjectId": 0,
    "BookingRemark": "Online Booking",
    "CorporateStatus": 0,
    "CorporatePaymentMode": 0,
    "MissedSavingReason": null,
    "CorpTripType": null,
    "CorpTripSubType": null,
    "TripRequestId": null,
    "BookingAlertIds": null
}
```


POST07-Add-Payment

The AddPayment API is used to record or process the agent payment for a booking. This API is typically called after the Air_TempBooking API for normal bookings where immediate payment is required. In the case of hold bookings, the payment step can be skipped initially, and payment can be made later to confirm the booking. After successful payment, the Air_Ticketing API should be called to complete and confirm the booking.

APIPaymentDebitRequest

Name	Type	Description	Mandatory
AuthHeader	Object	This object holds APIAuthentication details	Yes
RefNo	String	This require the Booking reference number, which you get while Air_TempBooking response.	Yes
ProductId	Int	This denotes the booking Products id For Airline its 1	Yes
TransactionType	Int	This denotes the TransactionType TransactionType - 0 (BOOKING) TransactionType - 1(SSR) TranscationType - 2 (Reschedule Online and for future use)	Yes
ClientRefNo	String	This requires the client reference number. It uses for tracking the transaction in future.	No

APIPaymentDebitResponse

Name	Type	Description
ResponseHeader	Object	This object holds the property of ResponseHeader
Amount	Double	Total amount.
Commission	Double	Commission amount
SGST	Double	SGST Amount
CGST	Double	CGST Amount
IGST	Double	IGST Amount
TDS	Double	TDS Amount
PaymentID	String	Payment ID

POST08 - Air_Ticketing

The Air_Ticketing API is used to confirm and commit the booking at the supplier or airline side and generate the final airline PNR. This API should be called after the temporary booking reference has been generated and payment has been completed successfully.

In some cases, the Air_Ticketing API may return an error with code "22-Failed". In such scenarios, the booking status must not be treated as failed immediately. Instead, the client must call the Air_Reprint API using the booking reference number to check the latest ticket status.

If the Ticket_Status_Id is 4, the booking status should be treated as Success. If the Ticket_Status_Id is 0, 2, 3, or 22, the booking status should be treated as InProcess and the booking status should be checked again after some time using the Air_Reprint API. For all other cases, the booking status should be treated as Failed.

API Air Ticketing Request

Name	Type	Description	Mandatory
AuthHeader	Object	This object holds API Authentication details	Yes
BookingRefNo	String	This require the Booking reference number	Yes
Ticketing_Type	String	This requires ticketting types , Possible values : Block_Ticket -0/ Book_Ticket- 1/ Book_Blocked_Ticket -2 You have to allow user Block_Ticket and Book_Blocked_Ticked based on the flag Block_Ticket_Allowed in API Flight object in Search\RePrice response.	Yes

API Air Ticketing Response

Name	Type	Description
ResponseHeader	Object	This object holds the property of Response Header

BookingRefNo	String	This displays the Booking reference number
AirlinePNRDetails	List(Object)	This displays the Airline PNR Detail

a)AirlinePNRDetails

Name	Type	Description
Flight_Id	String	This Displays the Flight Id
Status_Id	String	This requires the Status Id 11-Success, 22-Failed, 33-Block.
FailureRemark	String	This Displays the Failure Remark
AirlinePNRs	List(Object)	This Displays the **AirlinePNR**

b)AirlinePNR

Name	Type	Description
AirlineCode	String	This displays the Airline Code
AirlinePNR	String	This displays the AirlinePNR
SupplierRefNo	String	This displays the SupplierRefNo
RecordLocator	String	This displays the RecordLocator
CRSPNR	String	This displays the CRSPNR
CRSCode	String	This displays the CRSCode


```
{
 "Auth_Header": {
      "UserId": "xxxxxxxxxx",
      "Password": "***********",
      "IP_Address": "127.0.0.1",
      "Request_Id": "7FB45BA7-5A98-4B0A-B5ED-0DD591F7A572",
      "IMEI_Number": "xxxxxxxxxx"
   },
  "Booking_RefNo": "F-O06JAN264LMQX",
  "Ticketing_Type": "1"
}
```


POST09 - Air_Reprint

StartFragmentThe Air_Reprint API is used to retrieve the complete booking details for a given booking reference number or airline PNR. This API returns the full itinerary, passenger details, ticketing information, fare details, and current booking status. This API is commonly used to check the latest status of a booking, to display booking details to the customer, or to validate the final ticketing result after the Air_Ticketing process.EndFragment

Request Object - API Air Reprint Request

API Air_ReQuery Request

Name	Type	Description	Mandatory
AuthHeader	Object	This object holds API Authentication details	Yes
BookingRefNo	String	This requires Booking reference number	Yes
AirlinePNR	String	This requires the airline PNR	No

Response Object - API Air Reprint Response

API Air_Reprint Response

Name	Type	Description
ResponseHeader	Object	This object holds the property of Response Header
BookingRefNo	String	This displays Booking reference number
BookingDateTime	String	This displays Booking Date Time
RetailerDetail	Object	This displays Retailer Detail
CustomerDetail	Object	This displays Customer Detail
CompanyDetail	Object	This displays Company Detail
BookingType	Enum	This displays Booking Type. Possible values : 0-ONEWAY/1-ROUNDTRIP/ 2-SPECIALROUNDTRIP
TravelType	Enum	This displays Travel Type. Possible values : 0-DOMESTIC/1-INTERNATIONAL
AdultCount	Integer	This displays Adult Count
ChildCount	Integer	This displays Child Count
InfantCount	Integer	This displays Infant Count
ClassofTravel	Enum	This displays class of Travel 0-ECONOMY/1-BUSINESS / 2-FIRST/3-PREMIUMECONOMY
GST	Boolean	This displays GST

GSTIN	String	This displays GSTIN
PAXEmailId	String	This displays PAX Email Id
PAXMobile	String	This displays PAX Mobile
InvoiceNumber	String	This displays Invoice Number
BillerId	Integer	This displays Biller Id
AirPNRDetails	List (Object)	This displays list of API Air PNR With Detail
BookingPaymentDetail	List (Object)	This displays list of Payment Detail
Remark	String	This displays Remark
CorporatePaymentMode	Integer	This displays Corporate Payment Mode
AirRequeryResponseKey	String	This displays Air Requery Response Key

a)Air PNR Detail

Name	Type	Description
Ticket_Status_Id	String	This displays Ticket_Status_Id Possible values 0-Payment Pending ,1-Payment Failed, 2-Payment Received , 3-Onprogress, 4-Confirmed, 5-Failed, 6-Cancelled, 7-Blocked, 8-Rejected
Ticket_Status_Desc	String	This displays Ticket Status Desc Possible values : Unknown, Confirmed, Failed, Cancelled
TicketingDate	String	This displays Ticketing Date
Airline_Code	String	This displays Airline Code
Airline_Name	String	This displays Airline Name
Airline_PNR	String	This displays Airline PNR
Supplier_RefNo	String	This displays Supplier RefNo
CRS_PNR	String	This displays CRS PNR
Record_Locator	String	This displays Record Locator
CRS_Code	String	This displays CRS Code
Gross_Amount	String	This displays Gross Amount
Post_Markup	String	This displays Post Markup

Flights	List(object)	This object holds list of API Flight details
PAXTicketDetails	List(object)	This object holds list of API PAX Ticket Detail
BookingChangeRequests	List(object)	This object holds list of Booking Change Request
RetailerPostMarkup	Double	This displays Retailer Post Markup
FailureRemark	String	This displays Failure Remark

b)Booking Payment Detail

Name	Type	Description
Payment_Mode	Enum	This displays PaymentMode 0-PrePaid_Money / 1-Payment_Gateway/ 2-Prepaid_Money1/ 3-Prepaid_Money2
Currency_Code	String	This displays Currency Code
PaymentConfirmation_Number	String	This displays Payment Confirmation Number
Payment_Amount	String	This displays Payment Amount
Gateway_Charges	String	This displays Gateway Charges

c) PAX Ticket Detail

Name	Type	Description
TicketDetails	List(Object)	This holds the list of Ticket Detail
Pax_Id	Integer	This displays Pax id
Pax_type	String	Possible values are: 0-ADT/ 1-CHD/ 2-INF
Title	String	This displays Customer title
FirstName	String	This displays Customer first name
LastName	String	This displays Customer Last name
Gender	String	This displays Gender
Age	String	This displays Age
DOB	String	This displays DOB
PassportNumber	String	This displays Passport Number
PassportIssuingCountry	String	This displays Passport Issuing Country
PassportExpiry	String	This displays Passport Expiry

Nationality	String	This displays Nationality
Fares	List(Object)	This holds the list of API Fare
SSRDetails	List(Object)	This holds the list of API SSR Detail
TicketStatus	String	This displays the Ticket Status
FrequentFlyerDetails	List(Object)	This holds Frequent Flyer Details

d) Booking Change Request

Name	Type	Description
FlightId	String	This displays Flight Id
ChangeType	Enum	This displays change type. Possible values are 0-Cancellation / 1-Reschedule/2-SSR/3-Others
ChangeDateTime	String	This displays Change Date Time
ChangeFee	Double	This displays Change Fee
ChangeFare	Double	This displays Change Fare
GrossCommission	Double	This displays Gross Commission
NetCommission	Double	This displays Net Commission
CurrencyCode	String	This displays Currency Code
TotalAmount	Double	This displays Total Refund Amount

e) Ticket Detail

Name	Type	Description
Flight_Id	String	This displays the Flight Id
Ticket_Number	String	This displays Currency Code

f) Company Detail

Name	Type	Description
CompanyName	String	This displays Company Name
Address	String	This displays Address
City	String	This displays City
State	String	This displays State

Country	String	This displays Country
Pincode	String	This displays Pin code
Fax	String	This displays Fax
PhoneNo	String	This displays Phone No
MobileNo	String	This displays Mobile No
Email	String	This displays Email
Website	String	This displays Website
ContactPerson	String	This displays Contact Person
PANNo	String	This displays PAN No
GSTNo	String	This displays GST No
SACCode	String	This displays SAC Code
Logo	String	This displays Logo

g) Customer Detail

Name	Type	Description
CustomerName	String	This displays customer name
CustomerMobile	String	This displays customer mobile
CustomerEmail	String	This displays customer email

h) Retailer Detail

Name	Type	Description
RetailerId	String	This displays Retailer Id
RetailerCompanyName	String	This displays Retailer Company Name
SubRetailerId	String	This displays Sub Retailer Id
SubRetailerCompanyName	String	This displays Sub Retailer Company Name
RetailerName	String	This displays Retailer Name
OperatorName	String	This displays Operator Name
BookedByOperatorName	String	This displays Booked By Operator Name
RetailerAddress	String	This displays Retailer Address

RetailerArea	String	This displays Retailer Area
RetailerLandmark	String	This displays Retailer Landmark
RetailerCity	String	This displays Retailer City
RetailerState	String	This displays Retailer State
RetailerPincode	String	This displays Retailer Pincode
RetailerMobileNumber	String	This displays Retailer Mobile Number
RetailerEmailId	String	This displays Retailer Email Id
RetailerPANno	String	This displays Retailer PAN no
RetailerGSTno	String	This displays Retailer GST no

```
postman request POST 'https://BASE_URL/airlinehost/AirAPIService.svc/JSONService/Air_Reprint' \
  --header 'Content-Type: application/json' \
  --body '{
    "Auth_Header": {
        "UserId": "xxxxxxxxxx",
        "Password": "***********",
        "IP_Address": "127.0.0.1",
        "Request_Id": "7FB45BA7-5A98-4B0A-B5ED-0DD591F7A572",
        "IMEI_Number": "xxxxxxxxxx"
    },
    "Booking_RefNo": "F-O06JAN264LMQX"
}'
```

POST10 - Air_History

The Air_History API is used to retrieve the list of bookings based on the specified search criteria or conditions. This API allows clients to fetch booking records for reporting, reconciliation, and customer service purposes. The response can include booking details such as reference number, PNR, travel dates, passenger information, and current booking status depending on the filters applied in the request.

Request Object - APIAirHistoryRequest

AirHistory Request

Name	Type	Description	Mandatory

AuthHeader	Object	This object holds API Authentication details	Yes
Month	String	This requires Month of booking for July (eg: 07)	No
Year	String	This requires year of booking(eg:2020)	No
Type	String	This require Type. Possible values are 0 - BOOKING_DATE/ 1 - BOOKING_DATE_LIVE/ 2 - BOOKING_DATE_CANCELLED/ 3-BLOCKED	No
Fromdate	String	This requires From date (MM/dd/YYYY)	No
Todate	String	This requires To date(MM/dd/YYYY)	No

AirHistory Response

Name	Type	Description
ResponseHeader	Object	This object holds the property of Response Header
TicketHistory	List(Object)	This object holds the list of Ticket History

a)Ticket History

Name	Type	Description
Refno	String	This displays booking reference number
CustomerMobile	String	This displaysCustomerMobile
CustomerName	String	This displaysCustomerName
PassengerName	String	This displaysPassengerName
BookingType	String	String This displaysBookingType
TravelType	String	This displaysTravelType
TripDetails	String	This displaysTripDetails
ReqDate	String	This displaysReqDate
GrossAmount	String	This displays GrossAmount
CancellationCharges	String	This displays CancellationCharges
GatewayCharges	String	This displays GatewayCharges
AirlinePNR	String	This displays AirlinePNR
InvoiceNumber	String	This displays InvoiceNumber
TicketHistoryTrips	List(Object)	This object holds list of TicketHistoryTrip

b)Ticket History Trip

Name	Type	Description
Refno	String	This displays booking reference number
FlightId	String	This displays Flight Id
AirlinesName	String	This displays Airlines Name
Origin	String	This displays Origin
Destination	String	This displays Destination
TravelDate	String	This displays Travel Date
TicketDate	String	This displays Ticket Date
StatusDesc	String	This displays Status Description
Remarks	String	This displays Remarks
Status	String	This displays Status
BlockedExpiryDate	String	This displays Blocked Expiry Date


```
{
    "Auth_Header": {
      "UserId": "xxxxxxxxxx",
      "Password": "***********",
      "IP_Address": "127.0.0.1",
      "Request_Id": "7FB45BA7-5A98-4B0A-B5ED-0DD591F7A572",
      "IMEI_Number": "xxxxxxxxxx"
   },
   "Fromdate": "01/04/2024",
   "Month": "4",
   "Todate": "20/04/2024",
   "Type": "0",
   "Year": "2024"
}
```


POST11 - Air_Cancellation

The Air_Cancellation API is used to submit a cancellation request for an existing booking to the supplier or airline system. This API sends the cancellation request to the cancellation queue for

processing. The final cancellation status and applicable charges can be verified later using the appropriate booking status or reprint API.

Request Object - AirTicketCancellationRequest

AirTicketCancellationRequest

Name	Type	Description	Mandatory
AuthHeader	Object	This object holds API Authentication details	Yes
RefNo	String	This requires Booking reference number.	Yes
ReqRemarks	String	This requires Request Remarks.	No
CancelCode	String	This object holds list of **Air Ticket Cancellation Type**	No
AirTicketCancelDetails	List(object)	This object holds list of **Air Ticket Cancel Detail**	Yes
CancellationType	Integer	Full = 1,PartialSegmentAllPax = 2,PartialPaxAllSegment = 3,PartialPaxPartialSegment = 4	Yes

Cancellation Type and its Implementations

0-Normal Cancel: Online Cancellation - Selected Passengers and Sectors will be Auto cancelled with Applicable Penalty as per Airline.

1-Full Refund: Offline Cancellation - Selected Passengers and Sectors will be cancelled only if Full Refund is applicable.

2-No Show: Offline Cancellation.

a)AirTicketCancelDetail

Name	Type	Description	CancelCode
FlightId	String	This requires Flight Id Remarks.	No
PassengerId	String	This requires Passenger Id Remarks.	No
SegmentId	String	This requires Segment_Id Remarks.	No

b)AirTicketCancellationType

CancellationType	CancelCode	Description
0	015	Please cancel my ticket with Applicable Penalty
0	005	I cancelled the ticket directly with Airline
0	001	Other – Mentioned the reason in Request Remarks

CancellationType CancelCode Description

1	016	Flight Schedule Changed by Airline
1	005	I cancelled the ticket directly with Airline
1	004	Received a communication from Airline that Flight is not Operational
1	008	Flight Cancelled by the Airline
1	001	Other – Mentioned the reason in Request Remarks

CancellationType	CancelCode	Description
2	011	Claim No Show Tax Refund
2	001	Other – Mentioned the reason in Request Remarks

Response Object-AirTicketCancellationResponse

APIAirTicketCancellationResponse

Name	Type	Description
ResponseHeader	Object	This object holds the property of Response Header
ErrorDesc	String	This displays Error Description


```
{
  "Auth_Header": {
    "UserId": "xxxxxxxxxx",
    "Password": "***********",
    "IP_Address": "127.0.0.1",
    "Request_Id": "7FB45BA7-5A98-4B0A-B5ED-0DD591F7A572",
    "IMEI_Number": "xxxxxxxxxx"
  },
        "AirTicketCancelDetails":[
    {
      "PassengerId": "1",
      "SegmentId": "0"
          }
  ],
        "Airline_PNR": "FIGHKD",
        "RefNo": "F-O06JAN264LMQX",
```

"CancelCode": "005",

"ReqRemarks": "I cancelled the ticket directly with Airline",

"CancellationType" : 0

}

POST12 - Air_ReleasePNR

The Air_ReleasePNR API is used to release or cancel a previously blocked or held ticket. This API frees the reserved booking reference or PNR from the system when the booking is not intended to be completed, allowing the inventory and fare to be made available again for other bookings.

Request Object : AirReleasePNRRequest

AirReleasePNRRequest

Name	Type	Description	Mandatory
AuthHeader	Object	This object holds API Authentication details	Yes
Booking_RefNo	String	This requires Booking reference number	Yes
Airline_PNR	String	Airline PNR Number is given	No

Response Object-AirReleasePNRResponse

Name	Type	Description
ResponseHeader	Object	This object holds the property of Response Header
ErrorDesc	String	This displays Error Description

{

"Airline_PNR": "KEVG6H",

"Auth_Header": {

"UserId": "xxxxxxxxxx",

"Password": "**********",

"IP_Address": "127.0.0.1",

"Request_Id": "7FB45BA7-5A98-4B0A-B5ED-0DD591F7A572",

"IMEI_Number": "xxxxxxxxxx"

},

"Booking_RefNo": "F-O06JAN264LMQX"

}