PIZZA

SALES
PROJECT

WELCOME TO PIZZA SALES PROJECT

Overview

Analyzed a pizza sales dataset to understand sales performance, customer ordering behavior, and product popularity using SQL queries.

RETRIEVE THE TOTAL NUMBER OF ORDERS PLACED

```sql
SELECT
    COUNT(order_id) AS Total_orders
FROM
    orders;
```

Result Grid

	Total_orders
▶	21350

CALCULATE THE TOTAL REVENUE GENERATED FROM PIZZA SALES

```
SELECT
    ROUND(SUM(od.quantity * p.price), 2) AS total_revenue
FROM
    order_details AS od
        JOIN
    pizzas AS p ON p.pizza_id = od.pizza_id;
```

Result Grid

	total_revenue
▶	817860.05

IDENTIFY THE HIGHEST-PRICED PIZZA.

```
SELECT
    pt.name, p.price
FROM
    pizza_types AS pt
        JOIN
    pizzas AS p ON p.pizza_type_id = pt.pizza_type_id
ORDER BY p.price DESC
LIMIT 1;
```

Result Grid | Filter Rov

	name	price
▶	The Greek Pizza	35.95

IDENTIFY THE MOST COMMON PIZZA SIZE ORDERED

```sql
SELECT
    p.size, COUNT(od.quantity) AS order_quantity
FROM
    pizzas AS p
        JOIN
    order_details AS od ON p.pizza_id = od.pizza_id
GROUP BY p.size
ORDER BY order_quantity DESC;
```

Result Grid | Filter Ro

size	order_quantity
L	18526
M	15385
S	14137
XL	544
XXL	28

LIST THE TOP 5 MOST ORDERED PIZZA TYPES ALONG WITH THEIR QUANTITIES

```
SELECT
    p.pizza_type_id, COUNT(od.quantity) AS order_quantites
FROM
    pizzas AS p
        JOIN
    order_details AS od ON p.pizza_id = od.pizza_id
GROUP BY pizza_type_id
ORDER BY order_quantites DESC
LIMIT 5;
```

Result Grid | Filter Rows:

pizza_type_id	order_quantites
classic_dlx	2416
bbq_ckn	2372
hawaiian	2370
pepperoni	2369
thai_ckn	2315

2315

FIND THE TOTAL QUANTITY OF EACH PIZZA CATEGORY

```
SELECT
    pt.category, SUM(od.quantity) AS quantity
FROM
    pizza_types pt
        JOIN
    pizzas p ON pt.pizza_type_id = p.pizza_type_id
        JOIN
    order_details AS od ON p.pizza_id = od.pizza_id
GROUP BY pt.category
ORDER BY quantity DESC
LIMIT 5;
```

Result Grid | Filter

	category	quantity
▶	Classic	14888
	Supreme	11987
	Veggie	11649
	Chicken	11050

DETERMINE THE DISTRIBUTION OF ORDERS BY HOUR OF THE DAY

```sql
SELECT
    HOUR(order_time) AS hours, COUNT(order_id) AS hourly_orders
FROM
    orders
GROUP BY hours
ORDER BY hourly_orders DESC;
```

Result Grid | Filter Row

hours	hourly_orders
12	2520
13	2455
18	2399
17	2336
19	2009
16	1920
20	1642
14	1472

CATEGORY WISE DISTRIBUTION OF PIZZAS

```
SELECT
    category, COUNT(name)
FROM
    pizza_types
GROUP BY category;
```

Result Grid | Filter Rows:

category	COUNT(name)
Chicken	6
Classic	8
Supreme	9
Veggie	9

GROUP THE ORDERS BY DATE AND CALCULATE THE AVERAGE NUMBER OF PIZZAS ORDERED PER DAY

```sql
SELECT
    ROUND(AVG(quantity), 2) AS avg_order_per_day
FROM
    (SELECT
        o.order_date, SUM(od.quantity) AS quantity
    FROM
        orders AS o
    JOIN order_details AS od ON o.order_id = od.order_id
    GROUP BY o.order_date) AS order_quantity;
```

Result Grid | Filter

	avg_order_per_day
▶	138.47

DETERMINE THE TOP 3 MOST ORDERED PIZZA TYPES BASED ON REVENUE

```
SELECT
    pt.name, ROUND(SUM(od.quantity * p.price), 2) AS revenue
FROM
    pizza_types AS pt
        JOIN
    pizzas AS p ON p.pizza_type_id = pt.pizza_type_id
        JOIN
    order_details AS od ON od.pizza_id = p.pizza_id
GROUP BY pt.name
ORDER BY revenue DESC
LIMIT 3;
```

Result Grid | Filter Rows:

name	revenue
The Thai Chicken Pizza	43434.25
The Barbecue Chicken Pizza	42768
The California Chicken Pizza	41409.5

CALCULATE THE PERCENTAGE CONTRIBUTION OF EACH PIZZA TYPE TO TOTAL REVENUE

```
select pt.category, round(sum(od.quantity * p.price) /
(select round(sum(od.quantity * p.price),2) as total_sales
from order_details as od
join pizzas as p
on p.pizza_id = od.pizza_id) * 100,2) as revenue
from pizza_types as pt
join pizzas as p
on p.pizza_type_id = pt.pizza_type_id
join order_details as od
on od.pizza_id = p.pizza_id
group by pt.category
order by revenue desc
limit 3;
```

Result Grid

	category	revenue
▶	Classic	26.91
	Supreme	25.46
	Chicken	23.96

ANALYZE THE CUMULATIVE REVENUE GENERATED OVER TIME

```
select order_date, sum(revenue) over(order by order_date) as cum_revenue
from
(select o.order_date, sum(od.quantity * p.price) as revenue
from order_details as od
join pizzas as p
on od.pizza_id = p.pizza_id
join orders as o
on o.order_id = od.order_id
group by o.order_date) as sales;
```

Result Grid | Filter Rows:

order_date	cum_revenue
2015-01-01	2713.8500000000004
2015-01-02	5445.75
2015-01-03	8108.15
2015-01-04	9863.6
2015-01-05	11929.55
2015-01-06	14358.5
2015-01-07	16560.7

DETERMINE THE TOP 3 MOST ORDERED PIZZA TYPES BASED ON REVENUE FOR EACH PIZZA CATEGORY

```
select name, revenue
from
(select category, name, revenue,
rank() over(partition by category order by revenue desc) as rnk
from
(select pizza_types.category, pizza_types.name, sum((order_details.quantity) * pizzas.price) as revenue
from pizza_types
join pizzas
on pizza_types.pizza_type_id = pizzas.pizza_type_id
join order_details
on order_details.pizza_id = pizzas.pizza_id
group by pizza_types.category, pizza_types.name) as a) as b
where rnk <= 3;
```

THANK YOU