Timestamp (Second)	Execution time (ms)	Query
		No. of Queries:80
0.009	1	SET @@SESSION.sql_mode = ?;
0.042	1	select email from shaba_users where id=? LIMIT ?
0.043	1	SELECT `id` FROM `shaba_ep_domains` WHERE `domain_name` = ?
0.052	1	SELECT m.id, m.menutype, m.title, m.alias, m.note, m.path AS route, m.link, m.type, m.level, m.language,m.browserNav, m.access, m.params, m.home, m.img, m.template_style_id, m.component_id, m.parent_id,e.element as component FROM shaba_menu AS m LEFT JOIN shaba_extensions AS e ON m.component_id = e.extension_id WHERE m.published = ? AND m.parent_id > ? AND m.client_id = ? ORDER BY m.lft
0.066	2	select `alias`,`newurl` from `shaba_sh404sef_aliases` where `alias` = ? or `alias` = ? or `alias` = ? order by `alias` desc
0.069	0	SELECT `oldurl`, `newurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `oldurl`=? ORDER BY `rank`;
0.074	1	SELECT id,parent_user FROM shaba_lms_users WHERE user_id = ?
0.116	1	SELECT extension_id AS id, element AS ?, params, enabled FROM shaba_extensions WHERE `type` = ? AND `element` = ?
0.439	1	SELECT count(*) FROM shaba_tests WHERE id=? AND user_id=?
0.44	1	SELECT plan_id FROM shaba_ep_user_plan WHERE user_id=?
0.441	1	SELECT * FROM shaba_ep_acl WHERE group_id=?
0.442	26848	SELECT a.*,b.qtype_name FROM shaba_test_question a,shaba_test_question_type b WHERE a.questions_types_id=b.id and a.id in(select question_id from shaba_tests_to_questions where test_id =?) LIMIT ?, ?
27.291	11	SELECT distinct topics_id FROM shaba_tests_question_topics WHERE testid=?
27.303	0	SELECT distinct topics_id FROM shaba_tests_question_topics WHERE testid=?
27.304	0	SELECT id,objective_name,parent_id FROM shaba_objectives WHERE id = ? OR parent_id IN (?) AND user_id=? ORDER BY parent_id ASC
27.304	1	SELECT id,objective_name,parent_id FROM shaba_objectives WHERE id = ? OR parent_id IN (?) AND user_id=? ORDER BY parent_id ASC
27.305	20250	SELECT count(?) FROM shaba_test_question a,shaba_test_question_type b WHERE a.questions_types_id=b.id and questions_status=? and a.id in(select question_id from shaba_tests_to_questions where test_id =?)
47.555	9	SELECT is_difficult,is_above_average,is_average,is_below_average,is_easy,user_id ,tests_name,questionlimit,random_answers,random_questions,scoring_method_certify,distribution_objective,distribution_difficulty FROM shaba_tests WHERE id=?
47.564	17671	SELECT count(*) FROM shaba_test_question WHERE id IN (SELECT question_id FROM shaba_tests_to_questions where test_id =?)
65.236	36	SELECT tests_name, image_library, tests_image FROM shaba_tests WHERE id =?
65.272	8	SELECT tests_name, image_library, tests_image FROM shaba_tests WHERE id =?
65.28	4	select distinct(m.user_id),u.name FROM shaba_membership_teacher_manager m, shaba_users u WHERE m.invite_userid=? AND u.id = m.user_id AND `type` LIKE ?
65.285	3	select id,tests_name from shaba_tests where in_lms=? AND user_id=? AND id <> ? order by tests_name
65.292	0	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;
65.295	0	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;
65.296	1	select distinct(m.user_id),u.name FROM shaba_membership_teacher_manager m, shaba_users u WHERE m.invite_userid=? AND u.id = m.user_id AND `type` LIKE ?
65.299	0	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;
65.301	0	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;
65.303	0	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;
65.305	0	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;
65.306	2	SELECT tests_name FROM shaba_tests WHERE id = ?
65.31	0	SELECT `oldurl` FROM shaba_sh404sef_urls WHERE `newurl`=?;
65.312	0	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;
65.312	4	SELECT tests_name FROM shaba_tests WHERE id = ?
65.316	4	SELECT questions_detail FROM shaba_test_question WHERE id = ?
65.321	0	SELECT `oldurl` FROM shaba_sh404sef_urls WHERE `newurl`=?;
65.323	0	SELECT `id`, `newurl`, `rank`, `dateadd` FROM shaba_sh404sef_urls WHERE `oldurl`=? ORDER BY `rank`;
65.323	4	INSERT INTO `shaba_sh4?4sef_urls` (`oldurl`, `newurl`, `rank`, `dateadd`) VALUES (?, ?, ?, ?);
65.329	0	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;
65.33	1	SELECT tests_name FROM shaba_tests WHERE id = ?
65.333	0	SELECT `oldurl` FROM shaba_sh404sef_urls WHERE `newurl`=?;
65.334	0	SELECT `id`, `newurl`, `rank`, `dateadd` FROM shaba_sh404sef_urls WHERE `oldurl`=? ORDER BY `rank`;
65.335	3	INSERT INTO `shaba_sh4?4sef_urls` (`oldurl`, `newurl`, `rank`, `dateadd`) VALUES (?, ?, ?, ?);
65.34	0	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;
65.341	3	SELECT tests_name FROM shaba_tests WHERE id = ?
65.346	0	SELECT `oldurl` FROM shaba_sh404sef_urls WHERE `newurl`=?;

Timestamp (Second)	Execution time (ms)	Query	No. of Queries:80
65.347	0	SELECT `id`, `newurl`, `rank`, `dateadd` FROM shaba_sh404sef_urls WHERE `oldurl`=? ORDER BY `rank`;	
65.348	3	INSERT INTO `shaba_sh?4sef_urls` (`oldurl`, `newurl`, `rank`, `dateadd`) VALUES (?, ?, ?, ?);	
65.353	0	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;	
65.353	1	SELECT tests_name FROM shaba_tests WHERE id = ?	
65.356	0	SELECT `oldurl` FROM shaba_sh404sef_urls WHERE `newurl`=?;	
65.357	0	SELECT `id`, `newurl`, `rank`, `dateadd` FROM shaba_sh404sef_urls WHERE `oldurl`=? ORDER BY `rank`;	
65.358	2	INSERT INTO `shaba_sh?4sef_urls` (`oldurl`, `newurl`, `rank`, `dateadd`) VALUES (?, ?, ?, ?);	
65.362	0	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;	
65.362	1	SELECT tests_name FROM shaba_tests WHERE id = ?	
65.365	0	SELECT `oldurl` FROM shaba_sh404sef_urls WHERE `newurl`=?;	
65.366	0	SELECT `id`, `newurl`, `rank`, `dateadd` FROM shaba_sh404sef_urls WHERE `oldurl`=? ORDER BY `rank`;	
65.366	3	INSERT INTO `shaba_sh?4sef_urls` (`oldurl`, `newurl`, `rank`, `dateadd`) VALUES (?, ?, ?, ?);	
65.371	0	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;	
65.372	0	SELECT tests_name FROM shaba_tests WHERE id = ?	
65.373	3	SELECT questions_detail FROM shaba_test_question WHERE id = ?	
65.377	0	SELECT `oldurl` FROM shaba_sh404sef_urls WHERE `newurl`=?;	
65.379	0	SELECT `id`, `newurl`, `rank`, `dateadd` FROM shaba_sh404sef_urls WHERE `oldurl`=? ORDER BY `rank`;	
65.379	3	INSERT INTO `shaba_sh?4sef_urls` (`oldurl`, `newurl`, `rank`, `dateadd`) VALUES (?, ?, ?, ?);	
65.383	1	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;	
65.384	6	SELECT tests_name FROM shaba_tests WHERE id = ?	
65.392	0	SELECT `oldurl` FROM shaba_sh404sef_urls WHERE `newurl`=?;	
65.393	0	SELECT `id`, `newurl`, `rank`, `dateadd` FROM shaba_sh404sef_urls WHERE `oldurl`=? ORDER BY `rank`;	
65.394	2	INSERT INTO `shaba_sh?4sef_urls` (`oldurl`, `newurl`, `rank`, `dateadd`) VALUES (?, ?, ?, ?);	
65.398	0	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;	
65.398	1	SELECT tests_name FROM shaba_tests WHERE id = ?	
65.401	0	SELECT `oldurl` FROM shaba_sh404sef_urls WHERE `newurl`=?;	
65.402	0	SELECT `id`, `newurl`, `rank`, `dateadd` FROM shaba_sh404sef_urls WHERE `oldurl`=? ORDER BY `rank`;	
65.403	2	INSERT INTO `shaba_sh?4sef_urls` (`oldurl`, `newurl`, `rank`, `dateadd`) VALUES (?, ?, ?, ?);	
65.407	0	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;	
65.408	0	SELECT tests_name FROM shaba_tests WHERE id = ?	
65.41	0	SELECT `oldurl` FROM shaba_sh404sef_urls WHERE `newurl`=?;	
65.411	1	SELECT `id`, `newurl`, `rank`, `dateadd` FROM shaba_sh404sef_urls WHERE `oldurl`=? ORDER BY `rank`;	
65.412	2	INSERT INTO `shaba_sh?4sef_urls` (`oldurl`, `newurl`, `rank`, `dateadd`) VALUES (?, ?, ?, ?);	
65.416	0	SELECT `oldurl`, `dateadd` FROM shaba_sh404sef_urls WHERE `newurl`=?;	