PRAVEEN V 241901082

Exercise 6
Enumerate Web Server Information

AIM

To enumerate the services running on an authorized lab machine by performing service detection using Nmap and comparing the detected services with the expected lab configuration.

PROCEDURE

a) Service Detection Using Nmap

1. Open a terminal in Kali Linux.
2. Identify the IP address of the authorized lab machine to be scanned.
3. Run an Nmap service detection scan on the target:
   nmap -sV <target-IP>
4. Note the open ports, service names and version numbers detected.
5. Run a more detailed scan to confirm service and OS details:
   nmap -sV -O <target-IP>

b) Comparing Detected Services with Expected Lab Configuration

1. Refer to the expected lab configuration document/sheet listing the services that should be running on the machine (e.g., FTP, SSH, HTTP, MySQL).
2. Compare each service and port detected by Nmap against the expected list.

3. Note any differences — such as unexpected open ports, missing expected services, or mismatched version numbers.
4. Record all comparisons in the observation table.

OBSERVATION TABLE

S.No	Port	Service Detected (Nmap)	Expected Service (Lab Config)	Match / Mismatch
1	21	FTP (vsftpd 3.0.3)	FTP	Match
2	22	SSH (OpenSSH 8.2)	SSH	Match
3	80	HTTP (Apache 2.4.41)	HTTP	Match
4	3306	MySQL (5.7.33)	MySQL	Match
5	8080	HTTP-Proxy	Not expected	Mismatch

OUTPUT

Nmap -sV output:
PORT STATE SERVICE VERSION
21/tcp open ftp vsftpd 3.0.3
22/tcp open ssh OpenSSH 8.2p1
80/tcp open http Apache httpd 2.4.41
3306/tcp open mysql MySQL 5.7.33
8080/tcp open http nginx 1.18.0 (unexpected)

PRAVEEN V 241901082

RESULT

Thus, the services running on the authorized lab machine were successfully enumerated using Nmap. The detected services were compared with the expected lab configuration, and an unexpected service running on port 8080 was identified as a mismatch.