Where Gap-Adaptive Spectral Regularization Helps, and Where It Does Not: A Characterization and Operating Envelope for Differential Spectral Damping

Praveg Vashishtha[a,b]

[a] *Department of Computer Science and Engineering, Indian Institute of Technology Patna, India*

[b] *Sopra Banking Software India*

Abstract

Differential Spectral Damping (DSD) regularizes an ill-conditioned kernel system matrix by damping each spectral direction according to its local eigengap rather than its eigenvalue magnitude, on the Davis–Kahan principle that small-gap eigenvectors are the ones a perturbation corrupts. An earlier report introduced DSD for least-squares twin support vector machines and showed a sizeable accuracy gain over Tikhonov regularization. Two questions were left open: does the idea extend beyond that one classifier, and what, if anything, can be proved about it. We answer both, and we are deliberate about the negative parts of the answer. On the positive side, DSD improves two further high-dimensional linear discriminants (ridge classification and Fisher discriminant analysis) on real data, and the improvement survives a strengthened baseline set that includes truncated SVD and a tuned spectral filter: on GINA ($d = 970$) and Madelon ($d = 500$), gap-adaptive damping beats the best competing spectral regularizer by 3.3 to 4.9 percentage points across 25 seeds. We then prove a characterization theorem: the DSD inverse is bounded and well-posed, it reduces exactly to Tikhonov when the spectrum carries no gap information, and it is the unique member of its family that imposes a strictly monotone reliability ordering (larger gap, larger weight), something no function of eigenvalue magnitude can do. Finally we map the method's operating envelope. Across four settings we show, with a mechanism in each case, that DSD collapses to ordinary scalar regularization:

Email address: praveg_pa2503mth259@iitp.ac.in (Praveg Vashishtha)

Gaussian process regression, non-linear RBF kernel classifiers, iterative-solver preconditioning, and high-dimensional covariance estimation. The picture that emerges is specific rather than grand. DSD is a structural prior for a particular regime, ill-conditioned linear high-dimensional classification, and we delineate that regime precisely.

Keywords: spectral regularization, eigengap, twin support vector machine, ill-conditioned kernel methods, Davis–Kahan perturbation, operating envelope

---

1. Introduction

Many kernel methods reduce to inverting a symmetric system matrix whose spectrum decays fast. Twin support vector machines, least-squares SVMs, Fisher discriminant analysis and ridge classification all build their decision rule from such an inverse. When the input dimension is large relative to the sample size, these matrices become severely ill-conditioned: a long tail of tiny, tightly clustered eigenvalues sits beneath a few large ones. The standard remedy, Tikhonov regularization, adds a single scalar to every eigenvalue. It stabilizes the inverse, but it treats all directions alike.

Differential Spectral Damping (DSD) [1] was proposed on a different premise. The Davis–Kahan theorem [2] says that the eigenvector attached to an eigenvalue with a small spectral gap is the one a perturbation rotates most; its direction is unreliable. DSD damps each direction by a function of that gap rather than of the eigenvalue magnitude, suppressing small-gap (unreliable) directions and leaving well-separated ones almost untouched. On least-squares twin SVM the reported gain over Tikhonov was large.

That first report left the work in an awkward place. The evidence was confined to one classifier, the comparison was mostly against a single baseline, and the only theory was a motivating inequality with no proof. This paper addresses those gaps, and it does so without inflating the result. We ask three questions and report the answers as we found them, including the ones that are negative.

Does the idea generalize beyond twin SVM? Yes, within a specific regime. DSD improves ridge classification and Fisher discriminant analysis on real high-dimensional data, and the gain holds up against truncated SVD and a tuned spectral filter, not only against Tikhonov (Section 4).

Can anything be proved? Yes, a characterization rather than a performance guarantee. We prove that the DSD inverse is bounded, that it contains Tikhonov as a special case, and that it uniquely imposes a gap-monotone reliability ordering (Section 3). We are careful to attribute the boundedness and Tikhonov-recovery parts to classical regularization theory; the new content is the ordering and the composite statement.

Where does it stop working? In four distinct settings, each for a reason we can name. We report these boundaries as a first-class contribution (Section 5), because a method whose scope is mapped is more useful than one whose scope is merely asserted.

We also correct the record. The original report conjectured that DSD improves algorithmic stability. Our measurements show the opposite, and we retract that conjecture in Section 6.

2. Background and the DSD operator

Let $W = \sum_i \lambda_i u_i u_i^\top$ be a symmetric positive semi-definite system matrix with eigenvalues $\lambda_i > 0$ in ascending order and orthonormal eigenvectors u_i. Define the local eigengap $\delta_i = \min_{j \neq i} |\lambda_i - \lambda_j|$, which for an ordered spectrum is the smaller of the two neighbouring gaps. Tikhonov regularization replaces $1/\lambda_i$ by $1/(\lambda_i + \gamma)$. DSD instead uses

$$\tilde{\lambda}_i^{-1} \;=\; \phi(\lambda_i, \delta_i) \;=\; \frac{\lambda_i}{\lambda_i^2 + \alpha\, e^{-\beta \delta_i}}, \qquad \alpha, \beta > 0, \tag{1}$$

and forms $W^+_{\mathrm{DSD}} = \sum_i \phi(\lambda_i, \delta_i)\, u_i u_i^\top$. Writing $d_i = \alpha e^{-\beta \delta_i}$ for the damping, a small gap produces large d_i and therefore strong suppression of that direction. The parameters are set from the spectrum itself by the initialization rule of [1], so DSD requires no cross-validation.

Two features of (1) matter for what follows. The damping depends on the gap, not on the magnitude; and when the gap is constant across the spectrum the formula is indistinguishable from a scalar ridge. Both observations are made precise in Section 3.

The downstream classifiers invert a matrix of this kind. Ridge classification solves $(X_a^\top X_a)\, w = X_a^\top y$ with X_a the bias-augmented design; Fisher discriminant analysis solves $S_w\, w = (m_+ - m_-)$ with S_w the within-class scatter; twin SVM [3] solves a pair of such systems. In the high-dimensional regime each of these matrices exhibits the clustered tail that makes the gap informative.

2.1. Related work

Four lines of work border ours. Classical regularization of ill-posed inverses, from Tikhonov [4] through the filter-factor theory of Engl, Hanke and Neubauer [5] and the pseudo-inverse analysis in Golub and Van Loan [6], supplies the magnitude-based filters we compare against; a recent construction in this tradition [7] proves boundedness and Moore–Penrose recovery for a structured spectral pseudo-inverse, and a learned variant reweights spectral coefficients by signal-to-noise ratio [8]. All of these key on eigenvalue magnitude, not on the gap. The generalization theory of spectral algorithms [9] analyzes exactly the magnitude-filter class $h(\lambda)$; our operator lies outside it by construction (Theorem 1(c)). The twin-SVM and kernel-machine literature has moved briskly in recent years, with robust loss functions [10] and restricted kernel machine formulations [11], but these target the loss, the data representation, or multi-view structure rather than the conditioning of the system-matrix inverse, so DSD is orthogonal to and composable with them. Doubly regularized discriminant analysis [12] uses two magnitude ridge parameters, again without a gap term. Finally, Nyström approximation [13] produces the kind of kernel submatrix DSD inverts, and the boundary studies of Section 5 touch Gaussian processes [14], covariance shrinkage [15, 16] and algorithmic stability [17].

3. A characterization theorem

We prove what the DSD operator *is*, not that it lowers risk. The attempt to prove a risk guarantee failed for an instructive reason that we discuss in Section 6; what survives is a clean characterization.

Theorem 1 (DSD operator characterization)**.** *Let W_{DSD}^{+} be as above with damping $d_i = \alpha e^{-\beta\delta_i}$, $\alpha, \beta > 0$.*

- *(a)* ***Boundedness.*** *For every i, $0 < \phi(\lambda_i, \delta_i) \le 1/(2\sqrt{d_i})$, with equality iff $\lambda_i = \sqrt{d_i}$. Hence $\|W_{\mathrm{DSD}}^{+}\|_2 \le 1/(2\sqrt{\min_i d_i}) = e^{\beta \max_i \delta_i/2}/(2\sqrt{\alpha})$. In particular $\phi \to 0$ as $\lambda_i \to 0$ with d_i bounded below, so the inverse stays bounded as W approaches singularity.*
- *(b)* ***Tikhonov recovery.*** *If all gaps are equal, or in the limit $\beta \to 0$, then $d_i \equiv \gamma := \alpha e^{-\beta\delta}$ and $\phi(\lambda_i, \delta_i) = \lambda_i/(\lambda_i^2 + \gamma)$. DSD thus contains eigenvalue-domain Tikhonov as a special case.*

(c) ***Monotone reliability ordering.*** *For fixed $\lambda > 0$, $\phi(\lambda, \delta)$ is strictly increasing in δ. Among directions of equal eigenvalue magnitude, DSD assigns strictly larger weight to the larger-gap direction. No filter that is a function of eigenvalue magnitude alone can reproduce this ordering.*

Proof. (a) Fix i and set $p(\lambda) = \lambda/(\lambda^2 + d_i)$. Then $p'(\lambda) = (d_i - \lambda^2)/(\lambda^2 + d_i)^2$, positive for $\lambda < \sqrt{d_i}$ and negative after, so p is maximized at $\lambda = \sqrt{d_i}$ with value $1/(2\sqrt{d_i})$. Positivity is immediate. Since W^{+}_{DSD} is symmetric with eigenvalues $\phi(\lambda_i, \delta_i)$, its spectral norm is $\max_i \phi(\lambda_i, \delta_i) \le \max_i 1/(2\sqrt{d_i}) = 1/(2\sqrt{\min_i d_i})$, and $\min_i d_i = \alpha e^{-\beta \max_i \delta_i}$ gives the stated form. If $\lambda_i \to 0$ with $d_i \ge d_{\min} > 0$ then $p(\lambda_i) \le \lambda_i / d_{\min} \to 0$.

(b) Equal gaps give $d_i \equiv \gamma$, and the formula becomes the eigenvalue-domain Tikhonov inverse. The $\beta \to 0$ limit sends every d_i to α identically.

(c) With $d = \alpha e^{-\beta\delta}$ we have $\partial d/\partial \delta = -\alpha\beta e^{-\beta\delta} < 0$ and $\partial \phi/\partial d = -\lambda/(\lambda^2 + d)^2 < 0$, so by the chain rule $\partial\phi/\partial\delta = \lambda\alpha\beta e^{-\beta\delta}/(\lambda^2 + d)^2 > 0$ for $\lambda > 0$. A magnitude filter $g(\lambda)$ is by definition constant on equal-λ directions, so it cannot realize a strict order between two such directions. □

Parts (a) and (b) are, in spirit, classical facts of regularization theory [5]; a recent construction for structured inverse problems proves the same boundedness and Moore–Penrose recovery for a magnitude-based filter [7]. We restate them here only to situate the operator. The content specific to DSD is part (c): a gap-keyed filter sits outside the magnitude-filter class $h(\lambda)$ studied in the generalization theory of spectral algorithms [9], precisely because it can separate two directions that share an eigenvalue. This is the honest formal statement of what DSD does differently, and it makes no claim about risk.

We verified all three parts numerically. Over 7×10^4 randomized checks the boundedness inequality was never violated and was tight at $\lambda = \sqrt{d}$ to a relative error of 10^{-6}; the $\beta \to 0$ Tikhonov recovery matched to 7×10^{-14}; and ϕ was strictly increasing in the gap on every (λ, δ) grid tested, with zero monotonicity violations across 5×10^4 adversarial parameter draws.

4. Empirical study

4.1. Protocol

We follow the fairness protocol of [1]. DSD uses only its spectral initialization, with no tuning. Every competitor is tuned: Tikhonov over a

Table 1: Test accuracy, DSD (untuned) versus grid-tuned Tikhonov, 25 seeds. All advantages are significant at $p < 10^{-3}$.

Dataset	Classifier	DSD	Tikhonov	Advantage
Synthetic d=200	Ridge	0.761	0.621	+14.0 pp
Synthetic d=200	Fisher	0.766	0.621	+14.5 pp
GINA d=970	Ridge	0.859	0.812	+4.7 pp
GINA d=970	Fisher	0.861	0.812	+4.9 pp
Madelon d=500	Ridge	0.581	0.548	+3.3 pp
Madelon d=500	Fisher	0.586	0.548	+3.8 pp

15-point logarithmic grid for γ; truncated SVD over a grid of ranks; a general spectral filter $\lambda^p/(\lambda^{p+1} + \varepsilon)$ over (p, ε). Selection is on training accuracy, as in the original report. All methods receive identical data and a 0.1-magnitude feature-noise injection; results are over 25 random train/test splits with paired t-tests.

Datasets are the two real high-dimensional benchmarks from the feature-selection literature, GINA ($d = 970$) and Madelon ($d = 500$) [18], plus a synthetic $d = 200$ problem for a controlled check. The classifiers are ridge classification and Fisher discriminant analysis, inverting the matrices of Section 2; twin SVM is the subject of the original report and is cited rather than re-run.

4.2. Gap-adaptive damping improves two further discriminants

Table 1 reports the comparison against Tikhonov. On both real datasets DSD improves ridge and Fisher classification by a clear margin, winning on almost every seed. The advantage tracks the severity of the tail clustering: it is largest on GINA, whose system matrix has the tightest cluster, and smaller on Madelon. The GINA gain of roughly 4.7 points also matches the twin-SVM gain reported in [1], which is the consistency one would hope to see if the mechanism is real.

4.3. The advantage survives stronger baselines

A single baseline is not convincing, so we added the two spectral regularizers a reviewer would reasonably ask for: truncated SVD and a tuned spectral filter. Table 2 gives the outcome. On real data the result is unambiguous. Tikhonov, truncated SVD and the spectral filter all converge to

Table 2: DSD versus the best of {Tikhonov, truncated SVD, spectral filter, naive}, all tuned, 25 seeds. On real data every competitor collapses to the same value.

Dataset	Classifier	DSD	best competitor	gap	p
Synthetic d=200	Ridge	0.761	0.778 (TSVD)	−1.7 pp	0.06
Synthetic d=200	Fisher	0.766	0.751 (TSVD)	+1.5 pp	0.02
GINA d=970	Ridge	0.859	0.812	+4.7 pp	$<10^{-3}$
GINA d=970	Fisher	0.861	0.812	+4.9 pp	$<10^{-3}$
Madelon d=500	Ridge	0.581	0.548	+3.3 pp	$<10^{-3}$
Madelon d=500	Fisher	0.586	0.548	+3.8 pp	$<10^{-3}$

essentially the same accuracy, and DSD stands above the best of them by the same margins as before. On the synthetic problem the story is more nuanced and we report it plainly: there truncated SVD is competitive, beating DSD on ridge by 1.7 points and losing to it on Fisher by 1.5 points. The two methods trade on synthetic spectra; on the real benchmarks DSD is the clear standout. The reading we take from this is that truncated SVD, not Tikhonov, is the baseline that matters, and that on genuine high-dimensional spectra the eigengap carries information a hard rank cutoff does not.

5. Operating envelope: where DSD stops helping

A regularizer that helps everywhere usually helps nowhere in particular. We therefore mapped the boundary of DSD's usefulness across four settings, and in each we can say why it reduces to scalar regularization. We treat these as results, not caveats.

Gaussian process regression.. We built a GP regressor whose posterior inverse $(K + \sigma^2 I)^{-1}$ can be formed by jitter, tuned Tikhonov, truncated SVD or DSD, and measured calibration (negative log predictive density and interval coverage) over ill-conditioned regimes with every competitor tuned on validation. DSD did not improve calibration in any regime. The reason is structural: a GP already carries a principled scalar, the observation noise σ^2, that sets the regularization level for calibration optimally, so there is no reliability gap for DSD to exploit. Its advantage in classification comes precisely from the absence of such a scalar there.

Non-linear RBF kernel classifiers.. On RBF-kernel twin SVM and LS-SVM the gap-adaptive inverse gave no gain. A bandwidth sweep explains it. The RBF Gram matrix is ill-conditioned only at small bandwidth, but at those bandwidths the classifier cannot learn (accuracy near chance); where it learns, the Gram matrix is already well-conditioned and DSD coincides with Tikhonov. The ill-conditioning and the signal occupy different bandwidths, so there is nothing for the gap to protect. This is consistent with the small non-linear gain reported in [1].

Iterative-solver preconditioning.. DSD makes a poor preconditioner. Preconditioned conjugate gradient converged faster with a Tikhonov-shifted preconditioner than with a DSD one, in both truncated and full-spectrum form. The reason is a sign: accelerating a solver requires *amplifying* small eigenvalues to reduce the condition number, whereas DSD *suppresses* small-gap directions. The property that aids generalization in classification is the wrong one for solving a system.

High-dimensional covariance estimation.. Gap-aware eigenvalue shrinkage was statistically indistinguishable from both linear Ledoit–Wolf [15] and nonlinear shrinkage [16] on Stein loss and minimum-variance-portfolio risk ($p = 0.51$ and $p = 0.41$). On a clustered spectrum a small eigenvalue and a small gap nearly coincide, so the gap adds no information a magnitude-based shrinkage does not already use. The gap carries independent signal only when the corruption is of the eigenvector *direction* and that direction enters the objective, as it does in a discriminant but not in a covariance estimate.

Taken together, these four boundaries locate DSD's advantage. It requires a task in which corrupted eigenvector directions, not merely small eigenvalues, harm the objective, and in which suppressing those directions improves generalization. High-dimensional linear classification is such a task; regression calibration, solving, and covariance estimation are not.

6. Limitations and a retraction

We are explicit about what we do not claim, including a correction to the earlier report.

No excess-risk guarantee. We tried to prove that gap-adaptive damping lowers the excess risk of the downstream classifier relative to any magnitude filter. The claim is false in general. Under perturbation the eigenvalues shift

as well as the eigenvectors, so a tuned magnitude filter already absorbs most of the reliability signal that the gap would carry, and in strong noise the gap signal is itself corrupted and gap damping becomes actively harmful. This is why Theorem 1 is a characterization and not a performance bound, and why our positioning against the magnitude-filter generalization framework [9] is one of complementarity, not dominance.

Retraction of the stability conjecture. The original report conjectured that DSD improves algorithmic stability. We measured leave-one-out sensitivity of the solved direction for DSD and for a matched Tikhonov on clustered data, and found DSD to be roughly an order of magnitude *less* stable, with the difference significant. We retract the conjecture. DSD's benefit is not a stability effect.

Scope. The advantage is specific to the ill-conditioned linear high-dimensional regime, and on synthetic spectra truncated SVD can match it. The headline evidence is on two real datasets and two linear discriminants; broader confirmation, and a genuine theoretical account of the real-data advantage that the failed excess-risk argument did not provide, are left to future work.

7. Conclusion

Differential spectral damping is a gap-adaptive regularizer with a precisely drawn scope. It improves high-dimensional linear classification on real data, and the improvement holds against the full standard family of spectral regularizers, not only Tikhonov. It admits a clean characterization: the inverse is bounded, it generalizes Tikhonov, and it alone imposes a gap-monotone reliability ordering. And it reduces to ordinary scalar regularization in four settings we identify with a mechanism in each. What we do not have is a performance theorem, and we have retracted a prior stability claim that the data contradicts. The contribution is an honest, well-bounded account of a specialized tool, which we think is more useful to a practitioner than a broader claim would be.

CRediT authorship contribution statement

Praveg Vashishtha: Conceptualization, Methodology, Software, Validation, Formal analysis, Investigation, Data curation, Visualization, Writing – original draft, Writing – review & editing.

Declaration of competing interest

The author declares that he has no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper. The author is employed by Sopra Banking Software India; this research was carried out independently of that employment, which neither funded nor directed it.

Funding

This research did not receive any specific grant from funding agencies in the public, commercial, or not-for-profit sectors.

Data availability

The real datasets, GINA and Madelon, are publicly available from OpenML (`gina_agnostic` and `madelon`, version 1). Synthetic data are generated by the released scripts. Code, a script for every reported number, and the committed result files are available at `https://github.com/Praveg432/dsd-regularization`; each reported value reproduces deterministically from its script.

Declaration of generative AI and AI-assisted technologies in the research and writing process

During the preparation of this work the author used Kiro, an AI coding and writing assistant, to help write and debug experiment code, check derivations, and draft and edit the manuscript text. After using this tool, the author reviewed and edited the content as needed and takes full responsibility for the content of the published article.

References

[1] P. Vashishtha, Differential spectral damping: Gap-adaptive regularization for ill-conditioned kernel methods, arXiv preprint arXiv:2606.23407 (2026).

[2] C. Davis, W. M. Kahan, The rotation of eigenvectors by a perturbation. III, SIAM Journal on Numerical Analysis 7 (1) (1970) 1–46.

[3] M. A. Kumar, M. Gopal, Least squares twin support vector machines for pattern classification, Expert Systems with Applications 36 (4) (2009) 7535–7543.

[4] A. N. Tikhonov, On the solution of ill-posed problems and the method of regularization, Doklady Akademii Nauk SSSR 151 (3) (1963) 501–504.

[5] H. W. Engl, M. Hanke, A. Neubauer, Regularization of Inverse Problems, Springer, 1996.

[6] G. H. Golub, C. F. Van Loan, Matrix Computations, 4th Edition, Johns Hopkins University Press, 2013.

[7] S. Chen, A spectral-domain pseudo-inverse construction method for unitary diagonalizable linear inverse problems, arXiv preprint arXiv:2607.26951 (2026).

[8] H. Dong, P. Cheng, S. Li, Interpretable operator learning for inverse problems via adaptive spectral filtering: Convergence and discretization invariance, arXiv preprint arXiv:2603.20602 (2026).

[9] M. Velikanov, M. Panov, D. Yarotsky, Generalization error of spectral algorithms, International Conference on Learning Representations (ICLR)ArXiv:2403.11696 (2024).

[10] M. Akhtar, M. Tanveer, M. Arshad, Advancing supervised learning with the wave loss function: A robust and smooth approach, arXiv preprint arXiv:2404.18101 (2024).

[11] A. Quadir, M. Tanveer, TRKM: Twin restricted kernel machines for classification and regression, arXiv preprint arXiv:2502.15759 (2025).

[12] A. Zaib, T. Ballal, S. Khattak, T. Y. Al-Naffouri, A doubly regularized linear discriminant analysis classifier with automatic parameter selection, arXiv preprint arXiv:2004.13335 (2020).

[13] C. K. I. Williams, M. Seeger, Using the Nyström method to speed up kernel machines, in: Advances in Neural Information Processing Systems, Vol. 13, 2001, pp. 682–688.

[14] C. E. Rasmussen, C. K. I. Williams, Gaussian Processes for Machine Learning, MIT Press, 2006.

[15] O. Ledoit, M. Wolf, A well-conditioned estimator for large-dimensional covariance matrices, Journal of Multivariate Analysis 88 (2) (2004) 365–411.

[16] O. Ledoit, M. Wolf, Analytical nonlinear shrinkage of large-dimensional covariance matrices, The Annals of Statistics 48 (5) (2020) 3043–3065.

[17] O. Bousquet, A. Elisseeff, Stability and generalization, Journal of Machine Learning Research 2 (2002) 499–526.

[18] I. Guyon, S. Gunn, A. Ben-Hur, G. Dror, Result analysis of the NIPS 2003 feature selection challenge, Advances in Neural Information Processing Systems (2004).