

SIMATS ENGINEERING

ASSESSMENT TOOL 1

COURSE CODE: ITA 06

COURSE NAME: MACHINE LEARNING

COURSE OUTCOME COVERED

CO2: *Neural Network Representation, Perceptron Model, Multilayer Perceptrons, Backpropagation Algorithm, Deep Neural Networks, Genetic Algorithms, Hypothesis Space Search, Genetic Programming, Models of Evaluation and Learning (BL1, BL2)*

Assessment Tool Weightage: 40%

QUESTIONS: 15

Total Marks:25

Annexure A

Analytical Problem Solving

Code of Conduct:

I Pravin R (192421292) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.

I understand that any violation of academic integrity rules will result in disciplinary action.

Signature of the student:

Annexure A

Short Answer Test

1, A simple perceptron model is used to classify whether a student passes or fails based on two input features, namely study hours and attendance. The weights associated with these inputs are 0.6 and 0.4 respectively, and the bias value is -0.5 . For a given student with study hours equal to 2 and attendance equal to 1, compute the net input to the perceptron and apply the step activation function to determine the final output. Based on the result, conclude whether the student passes or fails. (5 Marks)

2. In a neural network, a single neuron is trained using the backpropagation learning rule. The initial weight is 0.5 and the learning rate is 0.1. For an input value of 2, the actual output produced by the neuron is 0.6, whereas the target output is 1. Calculate the error in the output and determine the weight update using the delta rule. Hence, compute the new updated weight after one iteration of training. (5 Marks)

3. A deep learning model is developed for disease prediction and its performance is evaluated using a confusion matrix. The model yields 180 true positives, 150 true negatives, 20 false positives, and 50 false negatives. Using these values, compute the accuracy, precision, sensitivity (recall), and specificity of the model. Based on the calculated results, discuss whether the model is reliable for medical diagnosis, considering the importance of minimizing diagnostic errors. (5 Marks)

5 .During the training of a deep neural network model, the training and validation accuracies are observed over multiple epochs. The training accuracy increases steadily from 60% to 95%, while the validation accuracy initially increases from 58% to 72% but then decreases to 68% in later epochs. Analyse this trend and identify the issue affecting the model after a certain point in training. Explain why this issue occurs in neural networks and suggest two effective techniques to address it. Also, discuss the significance of validation accuracy in evaluating the performance of a learning model. (5 Marks)

6. A perceptron model is used to classify whether a loan is approved based on two features: income and credit score. The weights are 0.7 and 0.5, and the bias is -0.6 . For an applicant with income = 1.5 and credit score = 2, compute the net input and apply the step activation function. Determine whether the loan is approved or rejected. (5 Marks)

7. In a neural network, a single neuron uses the delta learning rule. The initial weight is 0.4, learning rate is 0.2, and input is 3. The actual output is 0.5, while the target output is 0.9. Calculate the error, determine the weight update, and compute the new weight after one iteration. (5 Marks)

8. A classification model produces the following confusion matrix values: True Positives = 120, True Negatives = 200, False Positives = 30, and False Negatives = 50. Compute accuracy, precision, recall (sensitivity), specificity, and F1-score. Based on these results, evaluate whether the model is suitable for applications where false negatives are critical. (5 Marks)

10. During training of a neural network, the training loss decreases continuously, while validation loss decreases initially and then starts increasing after several epochs. Identify the issue occurring in the model. Explain the reason behind this behavior and suggest two techniques such as regularization or early stopping to improve generalization performance. (5 Marks)

11. A perceptron model is used to classify whether a customer will purchase a product based on two features: advertisement exposure and income level. The weights are 0.5 and 0.3, and the bias is -0.4 . For a customer with advertisement exposure = 2 and income level = 1, compute the net input to the perceptron and apply the step activation function. Determine whether the customer makes a purchase or not. (5 Marks)

12. In a neural network, a neuron is trained using the delta learning rule. The initial weight is 0.6, the learning rate is 0.15, and the input is 2.5. The actual output is 0.7, while the target output is 1. Calculate the error, determine the weight update, and compute the new updated weight after one iteration. (5 Marks)

13. A classification model produces the following confusion matrix values: True Positives = 140, True Negatives = 180, False Positives = 25, and False Negatives = 35. Compute accuracy, precision, recall (sensitivity), specificity, and F1-score. Based on the results, analyze whether the model is suitable for applications such as fraud detection where false positives are costly. (5 Marks)

15. During the training of a deep learning model, the training accuracy increases from 65% to 97%, while validation accuracy increases from 63% to 75% and then fluctuates around 72%. Identify the issue present in the model. Explain why this happens and suggest techniques such as dropout and data augmentation to improve the model's performance. Also, discuss the importance of validation metrics in model evaluation. (5 Marks)

SOLUTIONS:

1. Perceptron Classification

Given:

- Weight $w_1=0.6$, $w_2=0.4$
- Bias $b=-0.5$
- Study hours $x_1= 2$
- Attendance $x_2=1$
- Net Input = $(0.6 \times 2) + (0.4 \times 1) - 0.5 = 1.2 + 0.4 - 0.5 = 1.1$

Step Activation Function:

Since Net Input > 0 , Output = 1

Conclusion: The student passes.

2. Delta Learning Rule

Given:

- Initial weight = 0.5
- Learning rate = 0.1
- Input = 2
- Target output = 1
- Actual output = 0.6

Error:

Error = Target – Actual = $1 - 0.6 = 0.4$

Weight Update:

$\Delta w = \text{Learning Rate} \times \text{Error} \times \text{Input} = 0.1 \times 0.4 \times 2 = 0.08$

Updated Weight:

New Weight = $0.5 + 0.08 = 0.58$

Answer: Error = 0.4, Weight Update = 0.08, New Weight = 0.58

3. Confusion Matrix Evaluation

Given:

TP = 180, TN = 150, FP = 20, FN = 50

Accuracy:

Accuracy = $(TP + TN) / (TP + TN + FP + FN) = (180 + 150) / 400 = 330 / 400 = 82.5\%$

Precision:

Precision = $TP / (TP + FP) = 180 / 200 = 90\%$

Recall (Sensitivity):

$$\text{Recall} = \text{TP} / (\text{TP} + \text{FN}) = 180 / 230 = 78.26\%$$

Specificity:

$$\text{Specificity} = \text{TN} / (\text{TN} + \text{FP}) = 150 / 170 = 88.24\%$$

Conclusion: The model has good accuracy and precision but lower recall. For medical diagnosis, recall should be improved to reduce false negatives.

5. Training vs Validation Accuracy

Training accuracy increases from 60% to 95%, while validation accuracy increases to 72% and then decreases to 68%.

Issue: Overfitting.

Reason: The model memorizes the training data instead of learning general patterns, reducing performance on unseen data.

Techniques to overcome:

1. Dropout
2. Early Stopping

Importance of Validation Accuracy: Validation accuracy measures the model's performance on unseen data and helps detect overfitting.

6. Perceptron Loan Classification

Given:

- Weight $w_1=0.7$, $w_2=0.5$
- Bias = -0.6
- Income = 1.5
- Credit Score = 2

$$\text{Net Input} = (0.7 \times 1.5) + (0.5 \times 2) - 0.6 = 1.05 + 1 - 0.6 = 1.45$$

Step Activation Function:

Since Net Input > 0, Output = 1

Conclusion: Loan is approved.

7. Delta Learning Rule

Given:

- Initial weight = 0.4
- Learning rate = 0.2
- Input = 3
- Target output = 0.9

- Actual output = 0.5

$$\text{Error} = 0.9 - 0.5 = 0.4$$

Weight Update:

$$\Delta w = 0.2 \times 0.4 \times 3 = 0.24$$

Updated Weight:

$$\text{New Weight} = 0.4 + 0.24 = 0.64$$

Answer: Error = 0.4, Weight Update = 0.24, New Weight = 0.64

8. Confusion Matrix Evaluation

Given:

$$TP = 120, TN = 200, FP = 30, FN = 50$$

Accuracy:

$$\text{Accuracy} = (120 + 200) / 400 = 80\%$$

Precision:

$$\text{Precision} = 120 / 150 = 80\%$$

Recall (Sensitivity):

$$\text{Recall} = 120 / 170 = 70.59\%$$

Specificity:

$$\text{Specificity} = 200 / 230 = 86.96\%$$

F1-Score:

$$F1 = 2 \times (0.80 \times 0.7059) / (0.80 + 0.7059) = 75\%$$

Conclusion: Since recall is only 70.59%, the model is not suitable for applications where false negatives are critical.

10. Training Loss vs Validation Loss

Training loss decreases continuously, while validation loss decreases initially and then increases.

Issue: Overfitting.

Reason: The model learns the training data too closely and cannot generalize well to unseen data.

Techniques to improve performance:

1. Regularization (L1/L2)
2. Early Stopping

Conclusion: These techniques improve the model's generalization performance.

11. Perceptron Customer Purchase

Given:

- Weight $w_1=0.5$
- Bias = -0.4
- Advertisement Exposure = 2
- Income Level = 1

Net Input:

$$\text{Net Input} = (0.5 \times 2) + (0.3 \times 1) - 0.4 = 1 + 0.3 - 0.4 = 0.9$$

Step Activation Function:

Since Net Input > 0 , Output = 1

Conclusion: The customer purchases the product.

12. Delta Learning Rule

Given:

- Initial weight = 0.6
 - Learning rate = 0.15
 - Input = 2.5
 - Target output = 1
 - Actual output = 0.7
- $$\text{Error} = 1 - 0.7 = 0.3$$

Weight Update:

$$\Delta w = 0.15 \times 0.3 \times 2.5 = 0.1125$$

Updated Weight:

$$\text{New Weight} = 0.6 + 0.1125 = 0.7125$$

Answer: Error = 0.3, Weight Update = 0.1125, New Weight = 0.7125

13. Confusion Matrix Evaluation

Given:

TP = 140, TN = 180, FP = 25, FN = 35

Accuracy:

$$\text{Accuracy} = (140 + 180) / 380 = 84.21\%$$

Precision:

$$\text{Precision} = 140 / 165 = 84.85\%$$

Recall (Sensitivity):

$$\text{Recall} = 140 / 175 = 80\%$$

Specificity:

$$\text{Specificity} = 180 / 205 = 87.80\%$$

$$F1 = 2 \times (0.8485 \times 0.80) / (0.8485 + 0.80) = 82.4\%$$

Conclusion: The model has good precision and is reasonably suitable for fraud detection, where false positives are costly.

15. Training vs Validation Accuracy

Training accuracy increases from 65% to 97%, while validation accuracy increases from 63% to 75% and then fluctuates around 72%.

Issue: Overfitting.

Reason: The model memorizes the training data instead of learning generalized patterns, causing reduced performance on unseen data.

Techniques to improve performance:

1. Dropout
2. Data Augmentation

Importance of Validation Metrics: Validation metrics evaluate the model's ability to generalize to unseen data, help detect overfitting, and assist in selecting the best-performing model.

RUBRICS FOR CALCULATION

Criteria	Weightage	Level 4 – Exemplary (5 Marks)	Level 3 – Proficient (4 Marks)	Level 2 – Developing (2–3 Marks)	Level 1 – Beginning (0–1 Mark)
Conceptual Understanding	25	Demonstrates clear and complete understanding of the concept	Good understanding with minor gaps	Basic understanding with some misconceptions	Poor or incorrect understanding
Accuracy of Answer	25	Completely correct answer with no errors	Mostly correct with minor errors	Partially correct with noticeable errors	Incorrect or irrelevant answer
Application of Knowledge	20	Correctly applies concepts to solve the question/problem	Applies concepts with minor mistakes	Limited or partially correct application	No or incorrect application
Completeness of Response	15	Covers all required parts of the question	Covers most parts with minor omissions	Covers only some parts	Incomplete or missing response
Clarity & Presentation	15	Clear, concise, and well-organized answer	Understandable with minor issues	Somewhat unclear or poorly structured	Difficult to understand

