Ather 450X specifications.

—

	Ather 450X	Ather 450 Plus
Performance		
Power (continuous / peak)	3.3 kW / 6 kW	3.3 kW / 5.4 kW
Max torque	26 Nm	22 Nm
Top speed	80 km/h	80 km/h
Acceleration (0-40 km/h)	3.3 s	3.9 s
Gradeability	20 degrees	18 degrees
Riding modes	Warp | Sport | Ride | Eco	Sport | Ride | Eco
Motor type	PMSM	PMSM
Ingress protection (motor)	IP66	IP66
Ingress protection (controller)	IP65	IP65
Range		
TrueRange™ (Ride)	70 km	60 km
TrueRange™ (Eco)	85 km	70 km
Range (Indian Drive Cycle)	116 km	100 km
Charging		
Charging unit	Ather Dot (or) Portable charger	Ather Dot (or) Portable charger
0-80% (home charging)	3 h 35 min	3 h 35 min
0-100% (home charging)	5 h 45 min	5 h 45 min
Fast charging rate (0-50% SOC)	1.5 km/min	1 km/min
Fast charging rate (50-80% SOC)	1 km/min	1 km/min
Battery		
Installed capacity	2.9 kWh	2.9 kWh
Usable capacity	2.6 kWh	2.23 kWh
Battery type	Lithium-ion, 21700 cell	Lithium-ion, 21700 cell
Water & dust resistance	IP67	IP67
Pack casing	Aluminium alloy	Aluminium alloy

	Ather 450X	Ather 450 Plus
Transmission		
Type	Belt drive	
Transmission ratio	7:8:1	
Tyres & wheels		
Wheel type	Alloy wheels	
Wheel size (front)	30.48 cm x 5.46 cm (12” x 2.15”)	
Wheel size (rear)	30.48 cm x 6.35 cm (12” x 2.5”)	
Tyre size (front)	90/90-12 tubeless	
Tyre size (rear)	90/90-12 tubeless	
Brakes		
Braking system	Combined braking system & regenerative braking	
Brake type (front)	Hydraulically actuated triple-piston calliper disc	
Brake type (rear)	Hydraulically actuated single-piston calliper disc	
Disc size (front)	200 mm	
Disc size (rear)	190 mm	
Braking distance (60-0 km/h)	28.6 m	
Suspension		
Front suspension	Telescopic forks	
Rear suspension	Symmetrically mounted progressive mono-schock	
Peripherals		
Headlights	LED	
Taillights	LED	
Indicators	LED with auto turn-off feature	
Parking assist	Reverse Assist	
Colours	White Space Grey Mint Green	

	Ather 450X	Ather 450 Plus
Dimensions & storage		
Kerb weight	108 kg	
F:R weight ratio	48 : 52	
Seat height	780 mm	
Boot capacity	22 l	
Display + touchscreen dashboard		
Processor	Snapdragon 212 Quadcore 1.3Ghz, 1GB RAM, 8GB storage	
Operating system	Android Open Source OS (AOSP)	
Screen size & type	17.78 cm (7”) TFT, LED-backlit, capacitive touch	
Water & dust resistance	IP65	
Smart features		
Positioning system	GNSS with AGPS	GNSS with AGPS
Connectivity	4G LTE Cat-4 / WCDMA / EDGE	4G LTE Cat-4 / WCDMA / EDGE
Bluetooth	Bluetooth 4.2, BLE 5.0	-
Dashboard	Over-the-air-updates Onboard navigation Auto indicator off Side stand sensor Guide-me-home lights Connected mobile app Time based adaptive screen brightness & themes	
App based smart features		
Mobile app	Ride Stats Push navigation Live location & vehicle state tracking Music & call control * Welcome lights	Ride Stats Push navigation Live location & vehicle state tracking - -
Smart accessories support	Tyre Pressure Monitoring System (TPMS)	-

*Will be implemented soon through over-the-air updates.

www.atherenergy.com

*All trademarks are the property of their respective owners.
*Ather reserves the right to alter specifications, designs or add / delete features without prior notice and without liability.
*All internet / connected features will be available only if one has subscribed to the Ather Connect subscription plan.
*Please refer to the website for detailed Terms and Conditions.