



ALLIANCE
UNIVERSITY
Private University established in Karnataka State by Act No.34 of year 2010
Recognized by the University Grants Commission (UGC), New Delhi

NAAC
GRADE A+
ACCREDITED UNIVERSITY

Comparing of Deep Learning Architecture

Bachelor of Computer Application
Semester – V

Sub: Deep Learning

Topic: Comparing of Deep Learning Architecture

By

Name: Prem Panchal
Reg no.: 2411021240011

Faculty Name: Nagasri. P

Faculty Signature: _____

Department of Computer Application
Alliance University
Chandapura - Anekal Main Road, Anekal
Bengaluru - 562 106

1. Introduction

Deep Learning is a branch of Artificial Intelligence and Machine Learning that uses neural networks with multiple processing layers to learn patterns from data. Different deep learning architectures are designed for different types of input and tasks. Feedforward Neural Networks are suitable for relatively static, structured data, CNNs are especially effective for spatial data such as images, and RNNs are designed to handle sequential or time-dependent data. Understanding these architectures helps us choose an appropriate model for a particular real-world problem.

2. Objectives of the Project

- Study the basic architecture of Feedforward Neural Networks, CNNs, and RNNs.
- Understand how information flows through each architecture.
- Identify suitable applications for each architecture.
- Compare the architectures based on structure, input data, strengths, limitations, and applications.
- Understand why a particular architecture is preferred for a particular type of problem.

3. Task 1 – Basic Architecture of Deep Learning Models

3.1 Feedforward Neural Network (FNN)

A Feedforward Neural Network is the basic form of an artificial neural network in which information moves in one direction: from the input layer through one or more hidden layers to the output layer. There are no feedback loops or recurrent connections. A Multi-Layer Perceptron (MLP) is a common example of a feedforward network.

Input Layer → Hidden Layer(s) → Output Layer

- Input Layer: Receives the features or variables of the dataset.
- Hidden Layer(s): Process the input using weights, biases, and activation functions.
- Output Layer: Produces the final prediction or classification.
- Data flows only forward; the network does not maintain memory of previous inputs.

3.2 Convolutional Neural Network (CNN)

A Convolutional Neural Network is a deep learning architecture particularly effective for data with spatial structure, especially images. CNNs automatically learn important features such as edges, shapes, textures, and objects using convolutional filters.

Input Image → Convolution → ReLU → Pooling → Fully Connected → Output

- Convolutional Layer: Uses filters/kernels to detect local features in the input.
- Activation Function (commonly ReLU): Adds non-linearity so the network can learn complex patterns.
- Pooling Layer: Reduces the spatial size of feature maps and helps reduce computation.
- Fully Connected Layer: Uses learned features to perform classification or prediction.
- CNNs use shared filters and local connections, making them efficient for spatial patterns.

3.3 Recurrent Neural Network (RNN)

A Recurrent Neural Network is designed for sequential data. Unlike a basic feedforward network, an RNN uses information from previous time steps through a hidden state. This allows the model to consider context when processing a sequence.

$$\mathbf{x}_1 \rightarrow [\text{RNN}] \rightarrow \mathbf{h}_1 \rightarrow [\text{RNN}] \rightarrow \mathbf{h}_2 \rightarrow [\text{RNN}] \rightarrow \mathbf{h}_3 \rightarrow \text{Output}$$

- Input Sequence: Data arrives in an ordered sequence, such as words or time-series values.
- Hidden State: Carries information from earlier time steps to later steps.
- Output: Produces a prediction for the whole sequence or for individual time steps.
- RNNs are useful when the order of the data matters.
- LSTM and GRU are improved recurrent architectures commonly used to handle longer dependencies.

4. Task 2 – Suitable Applications

Architecture	Suitable Input	Common Applications	Example
FNN	Structured/tabular data	Classification, regression, prediction, risk scoring	Customer churn prediction
CNN	Images, video frames, spatial data	Image classification, object detection, face recognition, medical image analysis	Detecting objects in an image
RNN	Sequential/time-series data	Speech recognition, language modeling, sentiment analysis, forecasting	Predicting the next word in a sentence

The choice of architecture depends mainly on the structure of the input data. For example, a table of customer information can often be handled by an FNN, an X-ray or photograph is naturally suited to a CNN, and a sequence such as a sentence, stock-price series, or speech signal can be modeled using an RNN.

5. Task 3 – Comparison of FNN, CNN, and RNN

Basis	FNN	CNN	RNN
Basic structure	Input → hidden layers → output	Convolution + activation + pooling + dense layers	Recurrent units with hidden state
Information flow	Forward only	Forward through convolutional hierarchy	Sequential with recurrent connections
Best suited for	Static/structured data	Spatial data such as images	Sequential/time-series data
Memory of previous input	No	No inherent temporal memory	Yes, through hidden state
Feature extraction	Usually learned through dense layers	Automatically learns spatial features	Learns sequence/context features
Typical input	Numerical/tabular features	Image/video/spatial arrays	Text, speech, time series
Main strength	Simple and effective for structured problems	Excellent spatial feature extraction	Captures order and temporal dependencies
Main limitation	Not ideal for spatial/sequence relationships	Can require high computation and large datasets	Traditional RNNs can struggle with long-term dependencies
Examples	Classification and regression	Image recognition and object detection	Language and time-series modeling

6. Advantages and Limitations

6.1 Feedforward Neural Network

Advantages:

- Simple architecture and relatively easy to understand.
- Works well with structured numerical data.
- Can be used for both classification and regression.

Limitations:

- Does not naturally capture spatial relationships like CNNs.
- Does not remember previous time steps like RNNs.
- Fully connected layers can contain many parameters for high-dimensional inputs.

6.2 Convolutional Neural Network

Advantages:

- Automatically learns useful spatial features.
- Very effective for image and visual recognition tasks.
- Parameter sharing reduces the number of weights compared with a fully connected approach to images.

Limitations:

- Training can require substantial computational resources.
- High-quality labeled data may be needed for many applications.
- A CNN is not naturally designed to model long temporal dependencies.

6.3 Recurrent Neural Network

Advantages:

- Designed for sequential and time-dependent data.
- Uses previous information to provide context for current predictions.
- Can process sequences of varying length.

Limitations:

- Traditional RNNs may suffer from vanishing or exploding gradients.
- Long-term dependencies can be difficult to learn.
- LSTM and GRU variants are often preferred when longer context is important.

7. Real-World Examples

FNN: A bank can use an FNN to predict whether a customer is likely to default on a loan using features such as income, age, credit history, and loan amount.

CNN: A healthcare system can use a CNN to analyze medical images and assist in identifying patterns associated with diseases.

RNN: A language application can use an RNN-based model to process a sequence of words and predict or classify the next part of the sequence.

8. Conclusion

Feedforward Neural Networks, Convolutional Neural Networks, and Recurrent Neural Networks are important deep learning architectures, but they are designed for different types of problems. FNNs are a good choice for structured and relatively independent input features. CNNs are highly effective for spatial data because they learn local and hierarchical features automatically. RNNs are designed for sequential data because they use information from previous time steps. Therefore, the most appropriate architecture should be selected according to the structure of the input data and the requirements of the application.

9. Quick Selection Guide

If your data/problem is...	Consider...
Mainly tabular or structured numerical data	FNN / MLP
Images or spatial patterns	CNN
Text, speech, or time-series sequence	RNN / LSTM / GRU

10. References

- Gheisari, M. et al. (2023). Deep learning: Applications, architectures, models, tools, and frameworks: A comprehensive survey. CAAI Transactions on Intelligence Technology.
- Review of deep learning: concepts, CNN architectures, challenges, applications, future directions. Journal of Big Data / PMC.
- Frontiers in Artificial Intelligence. An Introductory Review of Deep Learning for Prediction Models With Big Data.
- Shiri, F. M. et al. (2023). A Comprehensive Overview and Comparative Analysis on Deep Learning Models: CNN, RNN, LSTM, GRU.