Bootstrap Framework -

- 1) What is Bootstrap Framework?
 - It is a free front-end framework for faster and easier web development.
- It includes HTML and CSS based design templates for typography, forms, buttons, tables, navigation, modals, image carousels and many other, as well as optional JavaScript plugins.
 - It also gives you the ability to easily create responsive designs.
- 2) Bootstrap History?
 - It was developed by Mark Otto and Jacob Thornton at Twitter.
 - It was released as an open source product in August 2011 on GitHub.
- 3) Why Use Bootstrap?
- a) Easy to use: Anybody with just basic knowledge of HTML and CSS can start using Bootstrap
- b) Responsive features: Bootstrap's responsive CSS adjusts to phones, tablets, and desktops
- c) Mobile-first approach: In Bootstrap 3, mobile-first styles are part of the core framework
- d) Browser compatibility: Bootstrap is compatible with all modern browsers (Chrome, Firefox, Internet Explorer, Edge, Safari, and Opera)
- 4) Bootstrap Versions?
 - Bootstrap 3, which was released in 2013.
 - Bootstrap 4, which was released in 2018.
 - Bootstrap 5, which was released in 2021
- 5) Where to Get Bootstrap?
 - There are two ways to use Bootstrap
 - a) Download Bootstrap from getbootstrap.com
 - b) Include Bootstrap from a CDN (Content Delivery Network)
- 6) Getting Started with Bootstrap 5 Version -
 - Containers There are two container classes
 - a) The .container class provides a responsive fixed width container.
 - b) The .container-fluid class provides a full width container.

- 7) Introduction with Bootstrap Grid Layout -
 - Bootstrap's grid system allows up to 12 columns across the page for a single row.
- Bootstrap's grid system is responsive, and the columns will re-arrange automatically depending on the screen size.
 - Grid Classes for Bootstrap 3
 - The Bootstrap 3 grid system has four classes:
 - a) xs (for phones screens less than 768px wide)
 - b) sm (for tablets screens equal to or greater than 768px wide)
 - c) md (for small laptops screens equal to or greater than 992px wide)
 - d) lg (for laptops and desktops screens equal to or greater than

1200px wide)

- Grid Classes for Bootstrap 4
 - The Bootstrap 4 grid system has five classes:
 - a) .col- (extra small devices screen width less than 576px)
 - b) .col-sm- (small devices screen width equal to or greater than

576px)

c) .col-md- (medium devices - screen width equal to or greater than

768px)

- d) .col-lg- (large devices screen width equal to or greater than 992px)
- e) .col-xl- (xlarge devices screen width equal to or greater than

1200px)

- The Bootstrap 5 grid system has six classes:
 - a) .col- (extra small devices screen width less than 576px)
 - b) .col-sm- (small devices screen width equal to or greater than

576px)

c) .col-md- (medium devices - screen width equal to or greater than

768px)

- d) .col-lg- (large devices screen width equal to or greater than 992px)
- e) .col-xl- (xlarge devices screen width equal to or greater than

1200px)

f) .col-xxl- (xxlarge devices - screen width equal to or greater than

1400px)

8) Text/Typography -

```
1) <h1> to <h6> -
              Elements & Classes (.h1 to .h6)
       2) Display Headings-
                      .display-1 to .display-6 classes - Bigger Headings
       3) <small> or .small class
       4) <mark> or .mark class
       5)  element only no bootstrap class
       6) Other Text/Typography classes -
                      .text-start - left aligned text
                      .text-center - center aligned text
                      .text-end - right alingned text
                      .text-decoration-none - Removes the underline from a link
                      .text-lowercase -Indicates lowercased
                      .text-uppercase - Indicates uppercased text
                      .text-capitalize - Indicates capitalized text
                      .list-unstyled - Removes the default list-style and left margin on list
items (works on both  and ).
9) Bootstrap 5 Colors Classes-
       1) Text Color Classes -
               .text-muted
              .text-primary
               .text-success
              .text-info
              .text-warning
              .text-danger
              .text-secondary
              .text-white
               .text-dark
               .text-body
               .text-light
```

2) Background Colors Classes-.bg-primary .bg-success .bg-info .bg-warning .bg-danger .bg-secondary .bg-dark .bg-light 10) Bootstrap Table -1) Basic Table - .table class 2) Striped Rows - .table-striped class 3) Bordered Table - .table-bordered class 4) Hover Rows - .table-hover class 5) Black/Dark Table - .table-dark class 6) Dark Striped Table - .table-dark .table-striped class 7) Hoverable Dark Table - .table-dark .table-hover class 8) Borderless Table - .table-borderless class 9) Contextual Classes (Tables color classes) .table-primary .table-success .table-danger .table-info .table-warning .table-active .table-secondary .table-light .table-dark

10) Responsive Tables - .table-responsive class

11) Images -1) Shapes a) Rounded Corners - .rounded class b) Circle - .rounded-circle class c) Thumbnail - .img-thumbnail class 2) Aligning Images a) .float-start - left aligned b) .float-end - right aligned 3) Centered Image a) .mx-auto (margin:auto) b) .d-block (display:block) 4) Responsive Images a) .img-fluid class (max-width: 100%; height: auto;) 12) Alerts -1) .alert class - Main Class / Parent Class 2) Contextual classes -.alert-success .alert-info .alert-warning .alert-danger .alert-primary .alert-secondary .alert-light .alert-dark 3) Alert Links -

.alert-link

```
4) Closing Alerts -
               .alert-dismissible - for positioned close button to right side
               - data-bs-dismiss="alert" - JavaScript Attribute for Closing alert
       5) Animated Alerts -
               .fade and .show class
13) Bootstrap 5 Buttons-
       1) Button Styles-
               a).btn class - Main / Parent Class
               b) Contextual Color Class-
                       .btn-primary
                       .btn-secondary
                       .btn-success
                       .btn-info
                       .btn-warning
                       .btn-danger
                       .btn-dark
                       .btn-light
                       .btn-link
               The button classes can be used on <a>, <button>, or <input> elements:
       2)Button Outline-
               a).btn class - Main / Parent Class
               b) Contextual Color Class-
                       .btn-outline-primary
                       .btn-outline-secondary
                       .btn-outline-success
                       .btn-outline-info
                       .btn-outline-warning
                       .btn-outline-danger
                       .btn-outline-dark
                       .btn-outline-light
```


- 3) Button Sizes
 - a) .btn-lg large size button
 - b) .btn-sm small size button
- 4) Block Level Buttons-
- To create a block level button that spans the entire width of the parent element,

use the .d-grid "helper" class on the parent element:

- If you have many block-level buttons, you can control the space between them with the .gap-* class
 - 5) Active/Disabled Buttons
 - a) .active class The class .active makes a button appear pressed
 - b) disabled attribute attribute makes a button unclickable
 - 6) Bootstrap 5 Button Groups-
- a) .btn-group class group a series of buttons together (on a single line) in a button group
 - b) Button group Sizes-
 - .btn-group-lg for a large button group
 - .btn-group-sm for a small button group
 - c) Vertical Button Groups -

Use the class

- .btn-group-vertical to create a vertical button group
- d) Button Groups Side by Side-
- Button groups are "inline" by default, which makes them appear side by side when you have multiple groups
- 14) Badges -
 - Badges are used to add additional information to any content
 - a) .badge class used with contextual classes like bg-secondary etc.
 - b) Contextual Badges class -
 - .bg-primary
 - .bg-success



.progress-bar-striped class to add stripes to the progress bars

```
- Animated Progress Bar -
              .progress-bar-animated class to animate the progress bar
       - Multiple Progress Bars -
16) Bootstrap 5 Spinners -
              a) .spinner-border class
              b) Colored Spinners -
                      .text-muted
                      .text-primary
                      .text-success
                      .text-info
                      .text-warning
                      .text-danger
                      .text-secondary
                      .text-white
                      .text-dark
                      .text-body
                      .text-light
              c) Spinner Size -
                      .spinner-border-sm class
              d) Growing Spinners -
                      .spinner-grow class
              e) Spinner Size -
                      .spinner-grow-sm class
              f) Spinner Buttons -
17) Bootstrap 5 Pagination-
       a) Basic Pagination-
              .pagination class to an  element
              .page-item to each  element
              .page-link class to each link inside
```

```
b) Active State-
               .active class is used to "highlight" the current page
       c) Disabled State -
               .disabled class is used for un-clickable links
       d) Pagination Sizing-
               .pagination-lg for larger blocks
               .pagination-sm for smaller blocks
       e) Pagination Alignment -
               .justify-content-start
               .justify-content-center
               .justify-content-end
18) Bootstrap 5 List Groups -
       a) Basic List Groups -
               .list-group class with  element
               .list-group-item class with  element
       b) Active State-
               .active class
       c) List Group With Linked Items -
               - use <div> instead of 
               - <a> instead of  -
                      .list-group-item-action class if you want a grey background color on
hover
       d) Disabled Item -
               .disabled class adds a lighter text color to the disabled item
       e) Flush / Remove Borders -
               .list-group-flush class to remove some borders and rounded corners
       f) Numbered List Groups -
               .list-group-numbered class to create list items with numbers in front of them
       g) Horizontal List Groups-
               .list-group-horizontal
```

```
h) Contextual Classes -
               .list-group-item-success
              .list-group-item-secondary
               .list-group-item-info
              .list-group-item-warning
              .list-group-item-danger
              .list-group-item-primary
               .list-group-item-dark
              .list-group-item-light
       i) List Group with Badges-
19) Bootstrap 5 Cards -
       a) Cards-
              - bordered box with some padding around its content.
              - It includes options for headers, footers, content, colors, etc.
       b) Basic Card -
               .card class - bordered box
               .card-header - class adds a heading to the card
              .card-body class - some padding
              .card-footer class adds a footer to the card
       c) Contextual Cards -
              .bg-primary
              .bg-success
              .bg-info
              .bg-warning
              .bg-danger
              .bg-secondary
              .bg-dark
              .bg-light
       d) Titles, text, and links
               .card-title to add card titles to any heading element
```

.card-text class is used to remove bottom margins for a <p> element if it is the last child

.card-link class adds a blue color to any link, and a hover effect

e) Card Images-

```
.card-img-top -
```

.card-img-bottom -

f) Card Image Overlays -

.card-img-overlay to add text on top of the image:

- 20) Bootstrap 5 Collapse
 - a) Basic Collapsible -
 - .collapse class indicates a collapsible element
 - data-bs-toggle="collapse"
 - data-bs-target="#id"
 - b) Accordion -

data-bs-parent attribute to make sure that all collapsible elements under the specified parent will be closed when one of the collapsible item is shown.

- 21) Bootstrap 5 Dropdowns
 - a) Basic Dropdown -
 - .dropdown class indicates a dropdown menu
 - .dropdown-toggle Set dropdown icon to button or link
 - .dropdown-menu class or <div> element
 - .dropdown-item class <a> element
 - data-bs-toggle="dropdown" attribute
 - b) Dropdown Divider-

.dropdown-divider class is used to separate links inside the dropdown menu with a thin horizontal border

c) Dropdown Header -

.dropdown-header class is used to add headers inside the dropdown menu

- d) Disable and Active items -
 - .active class <a> element
 - .disabled class <a> element

```
e) Dropdown Position -
              .dropend
              .dropstart
       f) Dropdown Menu Right-
              .dropdown-menu-end class to the element with .dropdown-menu
       g) Dropup -
              .dropup class
       h) Dropdown Text-
              .dropdown-item-text class
       i) Grouped Buttons with a Dropdown -
       j) Vertical Button Group with Dropdown-
22) Bootstrap 5 Navs -
       a) Nav Menus -
              .nav class to a  element
              .nav-item for each  element
              .nav-link class to <a> element
       b) Aligned Nav -
              .justify-content-center class to center the nav
              .justify-content-end class to right-align the nav.
       c) Vertical Nav -
              .flex-column class to create a vertical nav
       d) Tabs -
              .nav-tabs class for  element
              .active class to the active/current link.
       e) Pills -
              .nav-pills class for  element
              .active class to the active/current link.
       f) Justified Tabs/pills -
              .nav-justified class for (equal width)
```

```
g) Pills with Dropdown -
       h) Tabs with Dropdown -
       i) Toggleable / Dynamic Tabs -
              .tab-content - for <div> element as a parent
              .tab-pane class - for hiding
              - data-bs-toggle="tab" attribute to <a> element
              .fade - animated effect
       j) Toggleable / Dynamic Pills -
              .tab-content - for <div> element as a parent
              .tab-pane class - for hiding
              - data-bs-toggle="pill" attribute to <a> element
              .fade - animated effect
23) Bootstrap 5 Navbars -
       a) Basic Navbar -
              .navbar class
              .navbar-expand-xxl|xl|lg|md|sm - for responsive collapsing class
              .navbar-nav class to  or <div>
              .nav-item class for 
              .nav-link class for <a>
       b) Centered Navbar -
              .justify-content-center class to center the navigation bar
       c) Colored Navbar -
                      .bg-primary
                      .bg-success
                      .bg-info
                      .bg-warning
                      .bg-danger
                      .bg-secondary
                      .bg-dark
                      .bg-light
```


d) Brand / Logo -.navbar-brand class is used to highlight the brand/logo/project name of your page 24) Bootstrap 5 Carousel a) Slides only carousels -.carousel class - main parent class .slide class - for sliding images .carousel-inner class - child class for carousel .carousel-item class - for each images .active class - for displaying 1st image - data-bs-ride="carousel" attribute to run carousel b) With controls carousel -- id - for identity .carousel class - main parent class .slide class - for sliding images .carousel-inner class - child class for carousel .carousel-item class - for each images .active class - for displaying 1st image - data-bs-ride="carousel" attribute to run carousel .carousel-control-prev class - for <button> element .carousel-control-prev-icon class - for previous button icon .carousel-control-next class - for <button> element .carousel-control-next-icon class - for Next button icon - data-bs-target="#id" - carousel id for <button> element c) With indicators carousel -- id - for identity .carousel class - main parent class .slide class - for sliding images .carousel-inner class - child class for carousel .carousel-item class - for each images

.active class - for displaying 1st image

```
- data-bs-ride="carousel" attribute to run carousel
               .carousel-control-prev class - for <button> element
               .carousel-control-prev-icon class - for previous button icon
               .carousel-control-next class - for <button> element
               .carousel-control-next-icon class - for Next button icon
              - data-bs-target="#id" - carousel id for <button> element
               .carousel-indicators class - for indexing <button> element
              - data-bs-slide-to="index" attribute - for indicators <button> element
       d) With captions carousel -
               .carousel-caption class
               .d-none & .d-md-block class
       e) Crossfade effect -
               .carousel-fade
       f) Individual .carousel-item interval -
              - data-bs-interval="1000" attribute to each .carousel-item to change slide time
25) Bootstrap 5 Modal -
       a) Modals -
              The Modal component is a dialog box/popup window that is displayed on top
of the current page
               .modal class - main parent class
               .modal-dialog class
               .modal-content class
               .modal-header class
               .modal-body class
               .modal-footer class
              - data-bs-dismiss="modal" attribute - for closing modal
              - data-bs-toggle="modal" attribute
              - data-bs-target="#id"
       b) Add animation to modal -
               .fade class - to parent element
```

```
c) Modal Size -
               .modal-sm class - small modal
               .modal-lg class - large modal
               .modal-fullscreen class - full screen modal
       d) Centered aligned Modal -
               .modal-dialog-centered class
       e) Scrolling Modal -
               .modal-dialog-scrollable to .modal-dialog class
26) Bootstrap 5 Utilities -
       a) Borders -
               .border class - all side solid style default border
               - To removing each side boders -
                       .border-0 class - remove all side borders
                       .border-top-0 class - remove top side border only
                       .border-end-0 class - remove right side border only
                       .border-bottom-0 class - remove bottom side border only
                       .border-start-0 class - remove left side border only
               - To adding each side border separately -
                       .border-top class - Only add top side border
                       .border-end class - Only add right side border
                       .border-bottom class - Only add bottom side border
                      .border-start class - Only add left side border
       b) Border Width -
               Use .border-1 to .border-5 to change the width of the border
       c) Border Color -
                       .border-primary
                       .border-success
                       .border-info
                       .border-warning
                       .border-danger
```

```
.border-secondary
               .border-dark
               .border-light
               .border-white
d) Border Radius -
       .rounded class
e) Float and Clearfix
       .float-end class - for right alignment
       .float-start class - for left alignment
       .clearfix class - for removing overflow to parent
f) Center Align -
       .mx-auto class (adds margin-left and margin-right: auto)
g) Width -
       .w-25 class - 25% Width
       .w-50 class - 50% Width
       .w-75 class - 75% Width
       .w-100 class - 100% Width
       .w-auto class - Auto Width
       .mw-100 class - Max Width 100%
h) Height -
       .h-25 class - 25% Height
       .h-50 class - 50% Height
       .h-75 class - 75% Height
       .h-100 class - 100% Height
       .h-auto class - Auto Height
       .h-100 class - Max Height 100%
i) Spacing -
       - m - margin
       - p - padding
```



```
.text-body
               .text-light
       m) Background Colors Classes-
               .bg-primary
               .bg-success
               .bg-info
               .bg-warning
               .bg-danger
               .bg-secondary
               .bg-dark
               .bg-light
27) Bootstrap 5 Flex
       a) Flexbox -
               .d-flex class: - to parent element for Block flexbox Container
               .d-inline-flex class - to parent element for inline flexbox container
       b) Horizontal Direction -
               .flex-row to display the flex items horizontally
               .flex-row-reverse to right-align the horizontal direction
       c) Vertical Direction -
               .flex-column to display the flex items vertically
               .flex-column-reverse to reverse the vertical direction
       d) Justify Content -
               .justify-content-start class - for left side aligned - default
               .justify-content-end class - for right side aligned
               .justify-content-center class - for center aligned
               .justify-content-between class - for space between
               .justify-content-around class - for left & right side equal margin
       e) Fill / Equal Widths -
               .flex-fill on flex items to force them into equal widths
```

```
f) Order -
       .order classes.
g) Auto Margins -
       .ms-auto (push items to the right)
       .me-auto (push items to the left)
h) Wrap -
       .flex-nowrap class - default
       .flex-wrap class -
       .flex-wrap-reverse class
i) Align Content - for multiple child in row
        .align-content-start class - default - vertical align top
        .align-content-end class - vertical align bottom
       .align-content-center class - vertical center
       .align-content-between class - vertical justify
       .align-content-around class - top Bottom equal margin
        .align-content-stretch - child stretch as per parent height
j) Align Items - for single row child
       .align-items-start class - vertical top
       .align-items-end class - vertical bottom
       .align-items-center - vertical center
       .align-items-stretch - default
       .align-items-baseline - vertical top
k) Align Self - for single child vertical align
        .align-self-start class - vertical top
       .align-self-end class - vertical bottom
       .align-self-center class - vertical center
       .align-self-baseline class - vertical top
       .align-self-stretch -default
```

28) Bootstrap 5 Forms a) Stacked Form -.form-control get proper form styling - use to <input>, <textarea> element .form-label class to each label element to ensure correct padding. b) Form Row/Grid (Inline Forms) use grid classes with form classes c) Form Control Size -.form-control-lg class .form-control-sm class d) Disabled and Readonly -- disabled attribute - readonly attribute e) Plain text Inputs -.form-control-plaintext class to style an input field without borders, but keep proper marigins and padding f) Color Picker -.form-control-color class g) Select Menu -.form-select class to the <select> element h) Select Menu Size -.form-select-lg class .form-select-sm class i) Disabled Select Menu -- disabled attribute to disable the select menu. i) Checkboxes & Radio Buttons -.form-check-input to style checkboxes & Radio button .form-check-label class to label elements k) Toggle Switches -.form-switch class together with container 1) Custom Range -

.form-range class

m) Input Groups -

.input-group class is a container to enhance an input by adding an icon, text or a button in front or behind the input field as a "help text"

.input-group-text class

n) Input Group Size -

.input-group-sm class for small input

.input-group-lg for large inputs groups

o) Floating Labels / Animated Labels -

.form-floating class to container

- placeholder attribute is required for each <input> element