

---

***Title* : Natural Language Processing (Almost)  
from Scratch**

***Writer* : COLLOBERT, WESTON, BOTTOU,  
KARLEN, KAVUKCUOGLU AND KUKSA**

***Citations* : 5359**

---

Mohammad Sabik Irbaz (160041004)

**January 22, 2020**

## **Types of NLP task :**

Four standard NLP tasks are described : Part-Of-Speech tagging (POS), chunking (CHUNK), Named Entity Recognition (NER) and Semantic Role Labeling (SRL).

### **Part-Of-Speech Tagging :**

POS aims at labeling each word with a unique tag that indicates its syntactic role, for example, plural noun, adverb, . . .

### **Chunking or Shallow Parsing :**

Aims at labeling segments of a sentence with syntactic constituents such as noun or verb phrases (NP or VP). Each word is assigned only one unique tag, often encoded as a begin-chunk (e.g., B-NP) or inside-chunk tag (e.g., I-NP). Validation is achieved by splitting the training set.

### **Named Entity Recognition :**

NER labels atomic elements in the sentence into categories such as 'PERSON' or 'LOCATION'. As in the chunking task, each word is assigned a tag prefixed by an indicator of the beginning or the inside of an entity.

### **Semantic Role Labeling :**

SRL aims at giving a semantic role to a syntactic constituent of a sentence. Feature categories commonly used by these system include (Gildea and Jurafsky, 2002; Pradhan et al., 2004):

- the parts of speech and syntactic labels of words and nodes in the tree;
- the node's position (left or right) in relation to the verb;
- the syntactic path to the verb in the parse tree;
- whether a node in the parse tree is part of a noun or verb phrase;
- the voice of the sentence: active or passive;
- the node's head word; and
- the verb sub-categorization.

## Steps :

(Using Neural Network)

### **Transforming Words into Feature Vectors :**

the first layer of their network maps each word indices into a feature vector, by a lookup table operation. Given a task of interest, a relevant representation of each word is then given by the corresponding lookup table feature vector, which is trained by backpropagation, starting from a random initialization.

### **Extracting Higher Level Features from Word Feature Vectors:**

Feature vectors produced by the lookup table layer need to be combined in subsequent layers of the neural network to produce a tag decision for each word in the sentence. Producing tags for each element in variable length sequences is a standard problem in machine-learning. They considered two common approaches which tag one word at the time: a window approach, and a (convolutional) sentence approach.

**Window Approach :** A window approach assumes the tag of a word depends mainly on its neighboring words.

**Sentence Approach :** Window approach performs well for most natural language processing tasks we are interested in but this approach fails with SRL. In this case, tagging a word requires the consideration of the whole sentence. When using neural networks, the natural choice to tackle this problem becomes a convolutional approach. In the semantic role labeling case, this operation is performed for each word in the sentence, and for each verb in the sentence.

**Tagging Schemes :**