

ZOOM ® View™		Report Created 03 May 2021		
Device Settings Report				
Hucík, Stepán		Last Office Interrogation		
Date of Birth	7 Jan 1944	08 Jun 2020		
Device	INCEPTA CRT-D P162/119874	Implant Date		

12 Mar 2013

Programming

Last Programmed 02 May 2019

Ventricular Tachy Mode 02 May 2019 Changed to Monitor + Therapy

Tachy Mode

02 May 2019 Changed to Off

02 May 2019 Changed to Monitor Only 12 Mar 2013 Changed to Monitor + Therapy

Therapy

Monitor + Therapy

Ventricular Tachy	
VF 230 min⁻¹ (261 ms)	
Detection/Redetection	
Initial Duration	1.0 s
Redetection Dur	1.0 s
Post-shock Dur	1.0 s
VT 205 min ⁻¹ (293 ms)	
Detection/Redetection	
Initial Duration	7.0 s
Redetection Dur	1.0 s
Post-shock Dur	1.0 s
Enhancements	Onset/Stability
VT Detection	On
Polymorphic VT Discrimination	on
Initial Detection	
Shock if Unstable	30 ms

QUICK CONVERT™ ATP	On
Shock 1	31 J
Shock 2	41 J
Additional 41 J Shocks	6
ATP1	Scan
Number of Bursts	2
Pulses per Burst	
Initial	8
Increment	2
Maximum	10
Coupling Interval	88 %
Decrement	10 ms
Burst Cycle Length	88 %
Ramp Decrement	0 ms
Scan Decrement	10 ms
Minimum Interval	220 ms
ATP2	Ramp
Number of Bursts	2
Pulses per Burst	
Initial	8
Increment	2
Maximum	10
Coupling Interval	84 %
Decrement	0 ms
Burst Cycle Length	84 %
Ramp Decrement	10 ms
Scan Decrement	0 ms
Minimum Interval	220 ms
ATP Time-out	Off mm:ss
Shocks	
Shock 1	31 J
Shock 2	41 J
Shock 3 -6	41 J

2868 Software Version: 4.08 P162 Firmware Version: B_v1.02.00(4.01) © 2016

Boston Scientific Corporation
or its affiliates. All rights reserved.

Page 1 of 4

Clinician Signature:

Ventricular Tachy (Continued)			
VT-1 160 min ⁻¹ (375 ms)			
Detection/Redetection		ATP1	Scan
Initial Duration	10.0 s	Number of Bursts	4
Redetection Dur	1.0 s	Pulses per Burst	
Post-shock Dur	1.0 s	Initial	6
Enhancements	Onset/Stability	Increment	0
VT-1 Detection	On	Coupling Interval	75 %
Atrial Tachy Discrimination		Decrement	10 ms
Sinus Tachycardia Discrimina	ation	Burst Cycle Length	75 %
Initial Detection		Ramp Decrement	0 ms
V Rate > A Rate	Off	Scan Decrement	10 ms
AFib Rate Threshold	150 min ^{−1}	Minimum Interval	210 ms
Stability	10 ms	ATP2	Ramp
	And	Number of Bursts	4
Onset	16 %	Pulses per Burst	
Sustained Rate Duration	Off mm:ss	Initial	6
Post-Shock Detection		Increment	0
V Rate > A Rate	Off	Coupling Interval	72 %
AFib Rate Threshold	150 min ^{−1}	Decrement	0 ms
Stability	20 ms	Burst Cycle Length	72 %
Sustained Rate Duration	00:15 mm:ss	Ramp Decrement	10 ms
		Scan Decrement	0 ms
		Minimum Interval	210 ms
		ATP Time-out	Off mm:ss
		Shocks	
		Shock 1	41 J
		Shock 2	41 J
		Shock 3 -5	41 J
Ventricular Tachy Therapy Setu	ıp		
ATP		Shock (All Shocks)	
RV ATP Amplitude	5.0 V	Waveform	Biphasic
RV ATP Pulse Width	1.0 ms	Committed Shock	Off
LV ATP Amplitude	5.0 V	Lead Polarity	Initial
LV ATP Pulse Width	1.0 ms	Shock Lead Vector	RV Coil to RA Coil
Magnet and Beeper			and Can
Magnet Response	Inhibit Therapy		
Beep During Capacitor Char	ge Off		
Atrial Tachy			
Therapy		Vantaioulas Bassalatias	
ATR Mode Switch Details	7 0:1	Ventricular Regulation	Max
ATR/VTR Fallback LRL	70 min ⁻¹	Vent Rate Regulation	Max
		BiV Trigger Maximum Pacing Rate	On 130 min ⁻¹
		iviaximum Pacing Rate	130 111111 '

2868 Software Version: 4.08 P162 Firmware Version: B_v1.02.00(4.01)

© 2016 Boston Scientific Corporation or its affiliates. All rights reserved.
Page 2 of 4

Clinician Signature:

Brady/CF						
	l Settings			.		
Mode			VVIR	Output		
Lower Rate Limit		65 m			2.5 V @ 0.4 ms	
Maximum Sensor Rate		130 m			3.0 V @ 0.4 ms	
RV-Refractory (RVRP)		230 - 250 m	•	/		
LV-Refractory (LVRP)			250 m			AGC 0.25 mV
	icular Pacing Ch	namber	BiV	■RV		AGC 0.6 mV
	LV Offset		0 m			AGC 1.0 mV
	otection Period		400 m			
Blank			2 .	•A		D: 1
	Blank after V-Pac	_	Smart m			Bipolar
	Blank after RV-Se	ense	Smart m			Off
	Response		VOO	■RV		5: 1
	Enhancements	5		Pace		Bipolar
	e Smoothing		011.01	Sense		Bipolar
	lp .		Off %	•	0 " "	5 .
D	own		Off %		e Configuration	Dual
				Pace		LVring>>RV
				Sense		LVtip>>LVring
				Sensor		0.5
				Accelero		On
					nse Factor	8 Maralinasa
				-	/ Threshold	Medium
					on Time	30 s
					ery Time	2 min
Brady/CE	RT (Post-Thera	ov)		Respirat	ory Sensor	On
	CRT Settings	ру)		Post Thera	anv	
•	r Rate Limit		75 m		rapy Period	00:30 mm:ss
			75 111	iii Fost Inc	rapy renou	00.50 11111.85
Output ■RV		5.0 V @ 1.0 m	6			
● L\	=		5.0 V @ 1.0 m			
Setup	V		3.0 V @ 1.0 III	.		
Beeper	•					
•	when Explant is	s Indicated			On	
Telemetry				•		
Enable use of ZIP™ telemetry				On		
Trending Setup		•				
Recording Method			30 Second Ave	rage		
Durat	ion			25 h	ours	
Data Storage Sleep Schedule Sleep Start Time Sleep Duration			Continu	ious		
				23:00 hh	:mm	
		07 hours				
Leads	Status Setup					
		Daily	Daily	Impedance Limits	Beep When	
		Intrinsic	Impedance	Low High	Out-of-Range	
		Amplitude				
●A	Pace/Sense	On	On	200 - 2000 Ω	Off	
■RV	Pace/Sense	On	On	200 - 2000 Ω	Off	
♦ LV	Pace/Sense	On	On	200 - 2000 Ω	Off	
2868 Software Version: 4.08			© 2016	Clinician Sig	gnature:	
P162 Firmwa	are Version: B_v1.02	2.00(4.01)		Scientific Corporation		,
		or its affi	liates. All rights reserved. Page 3 of 4			
				1 aye 3 01 4		

Setup (Continued) Leads Status Setup

Daily Daily Impedance Limits Beep When Intrinsic Impedance Low High Out-of-Range

2868 Software Version: 4.08 P162 Firmware Version: B_v1.02.00(4.01) © 2016

Boston Scientific Corporation
or its affiliates. All rights reserved.

Page 4 of 4

Clinician Signature: