

UNIT 4 – SEARCHING AND SORTING

(Questions 1–20)

Q1. Which of the following algorithms is NOT a searching algorithm?

- a) Linear search
- b) Binary search
- c) Selection sort
- d) Interpolation search

Q2. The time complexity of linear search in the worst case is _____.

- a) $O(1)$
- b) $O(\log n)$
- c) $O(n)$
- d) $O(n^2)$

Q3. Fill in the blank: Binary search can only be applied on _____ data.

- a) Random
- b) Unsorted
- c) Sorted
- d) Partially sorted

Q4. The best case time complexity of binary search is _____.

- a) $O(1)$
- b) $O(n)$
- c) $O(\log n)$
- d) $O(n \log n)$

Q5. Which of the following searching techniques works based on the position formula:

$\text{pos} = \text{low} + [(\text{key} - \text{arr}[\text{low}]) * (\text{high} - \text{low}) / (\text{arr}[\text{high}] - \text{arr}[\text{low}])]$?

- a) Linear search
- b) Binary search
- c) Interpolation search

d) Fibonacci search

Q6. What is the space complexity of binary search (recursive version)?

- a) $O(1)$
- b) $O(n)$
- c) $O(\log n)$
- d) $O(n \log n)$

Q7. Which sorting algorithm repeatedly compares adjacent elements and swaps them if they are in wrong order?

- a) Bubble sort
- b) Insertion sort
- c) Selection sort
- d) Merge sort

Q8. Fill in the blank: In selection sort, the smallest element is placed at the _____ of the list in each pass.

- a) Beginning
- b) End
- c) Middle
- d) Random position

Q9. What is the time complexity of bubble sort in the best case (already sorted)?

- a) $O(n^2)$
- b) $O(n \log n)$
- c) $O(n)$
- d) $O(1)$

Q10. Which sorting algorithm works by inserting each element into its correct position among previously sorted elements?

- a) Bubble sort
- b) Insertion sort
- c) Selection sort
- d) Merge sort

Q11. Fill in the blank: The merge sort algorithm is based on the _____ principle.

- a) Divide and conquer
- b) Decrease and conquer
- c) Greedy method
- d) Dynamic programming

Q12. Which of the following has the best average case time complexity?

- a) Bubble sort
- b) Selection sort
- c) Insertion sort
- d) Quick sort

Q13. What is the worst-case time complexity of quick sort?

- a) $O(n \log n)$
- b) $O(n^2)$
- c) $O(\log n)$
- d) $O(1)$

Q14. Fill in the blank: In quick sort, the element used to divide the array is called _____.

- a) Pivot
- b) Splitter
- c) Divider
- d) Marker

Q15. Which sorting algorithm is considered stable?

- a) Quick sort
- b) Merge sort
- c) Selection sort
- d) Heap sort

Q16. What is the time complexity of merge sort in the worst case?

- a) $O(n)$
- b) $O(\log n)$
- c) $O(n^2)$

d) $O(n \log n)$

Q17. Fill in the blank: The number of passes required to sort n elements using bubble sort is _____.

- a) n
- b) $n - 1$
- c) $\log n$
- d) n^2

Q18. In insertion sort, if the input is already sorted, the number of swaps performed is _____.

- a) $n - 1$
- b) 0
- c) n
- d) $\log n$

Q19. Which sorting algorithm is **non-comparative**?

- a) Merge sort
- b) Quick sort
- c) Radix sort
- d) Selection sort

Q20. What is the time complexity of radix sort if there are n elements and d digits per element?

- a) $O(n)$
- b) $O(n \log n)$
- c) $O(dn)$
- d) $O(n^2)$

ANSWER KEY – UNIT 4 (Q1–Q20)

1. c – Selection sort is a sorting algorithm, not searching.
2. c – Linear search checks all n elements $\Rightarrow O(n)$.
3. c – Binary search requires sorted input.

4. a – Best case: middle element found at first step.
5. c – Interpolation search uses position formula.
6. c – Recursive version adds $O(\log n)$ stack space.
7. a – Bubble sort compares adjacent elements.
8. a – Selection sort places smallest at beginning.
9. c – Optimized bubble sort $\approx O(n)$ if sorted.
10. b – Insertion sort inserts in correct order.
11. a – Merge sort uses divide and conquer.
12. d – Quick sort usually fastest ($O(n \log n)$ avg).
13. b – Worst case when pivot always smallest/largest $\approx O(n^2)$.
14. a – Pivot divides array into subarrays.
15. b – Merge sort maintains order \approx stable.
16. d – Merge sort always $O(n \log n)$.
17. b – Bubble sort requires $n-1$ passes.
18. b – No swaps if already sorted.
19. c – Radix sort works on digits, not comparisons.
20. c – Radix sort = $O(dn)$.

✖ END OF SET 1 (UNIT 4: QUESTIONS 1–20)

✖ UNIT 4 – SEARCHING AND SORTING

(Questions 21–40)

Q21. What will be the output of the following code?

```
int arr[] = {5, 2, 8, 3};  
for (int i = 0; i < 3; i++) {  
    for (int j = 0; j < 3 - i; j++) {  
        if (arr[j] > arr[j + 1]) {
```

```
swap(arr[j], arr[j + 1]);  
}  
}  
}  
for (int i = 0; i < 4; i++) cout << arr[i] << " ";
```

- a) 8 5 3 2
- b) 2 3 5 8
- c) 5 2 3 8
- d) 3 2 5 8

Q22. The number of comparisons in the best case for binary search on an array of 16 elements is _____.

- a) 1
- b) 2
- c) 4
- d) $\log_2 16$

Q23. Fill in the blank: The key characteristic of selection sort is that it performs _____ swaps in total.

- a) n
- b) n-1
- c) $\log n$
- d) n^2

Q24. What will be the output of linear search for value 7 in the array [3, 5, 7, 9, 11]?

- a) Index 2
- b) Index 3
- c) Index 4
- d) Not found

Q25. Which searching algorithm is preferred when data is continuously changing?

- a) Linear search
- b) Binary search
- c) Interpolation search

d) Fibonacci search

Q26. Fill in the blank: In bubble sort, after k passes, the last k elements are guaranteed to be _____.

- a) Unsorted
- b) In their correct positions
- c) Randomly placed
- d) Duplicated

Q27. The best case time complexity of insertion sort occurs when _____.

- a) Array is in reverse order
- b) Array is already sorted
- c) All elements are same
- d) Pivot chosen at random

Q28. What is the auxiliary space of merge sort?

- a) $O(1)$
- b) $O(n)$
- c) $O(\log n)$
- d) $O(n^2)$

Q29. Which sorting algorithm can be easily implemented using recursion?

- a) Bubble sort
- b) Quick sort
- c) Insertion sort
- d) Selection sort

Q30. Fill in the blank: The number of comparisons in selection sort for n elements is _____.

- a) $(n - 1)$
- b) $n(n - 1)/2$
- c) $n \log n$
- d) n^2

Q31. Which sorting algorithm is considered the fastest for large datasets (average case)?

- a) Quick sort
- b) Bubble sort
- c) Selection sort
- d) Insertion sort

Q32. What is the time complexity of searching in a hash table (on average)?

- a) $O(1)$
- b) $O(n)$
- c) $O(\log n)$
- d) $O(n^2)$

Q33. Fill in the blank: In binary search, if the key is greater than mid element, the search continues in the _____ half.

- a) Left
- b) Right
- c) Middle
- d) Random

Q34. Which sorting algorithm divides the list into two halves and merges them after sorting?

- a) Merge sort
- b) Quick sort
- c) Heap sort
- d) Selection sort

Q35. What is the output of this pseudo-code?

```
arr = [4, 1, 3, 9];  
selectionSort(arr);
```

Output: _____

- a) 1 3 4 9
- b) 4 3 1 9
- c) 1 4 3 9

d) 3 1 4 9

Q36. Which sorting technique is called ****in-place**** because it requires no extra memory?

- a) Merge sort
- b) Quick sort
- c) Counting sort
- d) Bucket sort

Q37. Fill in the blank: The maximum number of comparisons in a binary search for n elements is _____.

- a) $\log_2 n$
- b) n
- c) $n \log n$
- d) n^2

Q38. The partition step in quick sort divides the array into _____.

- a) Two sorted halves
- b) Two unsorted halves
- c) Sorted and unsorted halves
- d) Random halves

Q39. What is the average case time complexity of linear search?

- a) $O(1)$
- b) $O(n)$
- c) $O(\log n)$
- d) $O(n^2)$

Q40. Which of the following sorting algorithms is NOT stable?

- a) Bubble sort
- b) Insertion sort
- c) Quick sort
- d) Merge sort

ANSWER KEY – UNIT 4 (Q21–Q40)

- 21. b – After bubble sort 2 3 5 8.
- 22. d – $\log_2 16 = 4$ comparisons (best case 1).
- 23. b – Selection sort performs $n-1$ swaps.
- 24. a – Value 7 found at index 2 (0-based).
- 25. a – Linear search works for changing data.
- 26. b – Each pass places largest at end.
- 27. b – Best when array already sorted – $O(n)$.
- 28. b – Merge sort uses $O(n)$ auxiliary space.
- 29. b – Quick sort naturally recursive.
- 30. b – Selection sort makes $n(n-1)/2$ comparisons.
- 31. a – Quick sort average $O(n \log n)$.
- 32. a – Hashing average search = $O(1)$.
- 33. b – If key > mid, search right half.
- 34. a – Merge sort divides and merges.
- 35. a – Selection sort output 1 3 4 9.
- 36. b – Quick sort modifies array in-place.
- 37. a – At most $\log_2 n$ comparisons.
- 38. b – Quick sort partitions into two unsorted subarrays.
- 39. b – Linear search scans half on average – $O(n)$.
- 40. c – Quick sort not stable by default.

END OF SET 2 (UNIT 4: QUESTIONS 21–40)

UNIT 4 – SEARCHING AND SORTING

(Questions 41–60)

Q41. What will be the array after the first pass of bubble sort on [5, 3, 8, 4, 2]?

- a) [3, 5, 8, 4, 2]
- b) [3, 5, 4, 2, 8]
- c) [5, 3, 4, 2, 8]
- d) [2, 3, 4, 5, 8]

Q42. Fill in the blank: Binary search reduces the search interval by a factor of _____ in each step.

- a) $1/2$
- b) $1/3$
- c) 2
- d) n

Q43. The number of comparisons required for linear search in the best case is _____.

- a) n
- b) 1
- c) $\log n$
- d) $n - 1$

Q44. What is the time complexity of insertion sort in the worst case?

- a) $O(n)$
- b) $O(n \log n)$
- c) $O(n^2)$
- d) $O(1)$

Q45. Which sorting algorithm divides the array into partitions based on a pivot element?

- a) Merge sort
- b) Quick sort
- c) Insertion sort
- d) Selection sort

Q46. Fill in the blank: The time complexity of bubble sort and selection sort in the worst case is _____.

- a) $O(n)$
- b) $O(n^2)$

- c) $O(\log n)$
- d) $O(n \log n)$

Q47. What will be the sorted output of insertion sort for the list [9, 5, 1, 4, 3]?

- a) [1, 3, 4, 5, 9]
- b) [9, 5, 1, 3, 4]
- c) [5, 9, 1, 4, 3]
- d) [1, 4, 3, 5, 9]

Q48. The stability of a sorting algorithm means _____.

- a) Equal elements remain in same relative order
- b) It uses no extra space
- c) It runs in $O(n \log n)$
- d) It cannot handle duplicates

Q49. Which sorting algorithm does not perform well on linked lists?

- a) Merge sort
- b) Quick sort
- c) Insertion sort
- d) Bubble sort

Q50. Fill in the blank: In merge sort, the number of comparisons in merging two sorted lists of sizes m and n is at most _____.

- a) $m \times n$
- b) $m + n - 1$
- c) $\log(m + n)$
- d) $(m + n)^2$

Q51. What will be the array after the second pass of selection sort on [6, 3, 8, 5]?

- a) [3, 6, 5, 8]
- b) [3, 5, 6, 8]
- c) [3, 8, 6, 5]
- d) [3, 6, 8, 5]

Q52. Which searching algorithm does NOT require sequential access?

- a) Linear search
- b) Binary search
- c) Sequential search
- d) Sentinel search

Q53. Fill in the blank: The total number of comparisons in bubble sort for n elements is approximately _____.

- a) $n^2 / 2$
- b) $n \log n$
- c) n
- d) n^2

Q54. What is the auxiliary space used in quick sort (iterative implementation)?

- a) $O(1)$
- b) $O(n)$
- c) $O(\log n)$
- d) $O(n^2)$

Q55. Which sorting algorithm is based on counting the occurrences of each element?

- a) Bucket sort
- b) Counting sort
- c) Quick sort
- d) Radix sort

Q56. Fill in the blank: In linear search, if the element is not found, the number of comparisons is _____.

- a) $n - 1$
- b) n
- c) $\log n$
- d) $2n$

Q57. Which of the following has the same time complexity for best, average, and worst cases?

- a) Merge sort
- b) Quick sort

- c) Insertion sort
- d) Selection sort

Q58. What is the time complexity of sorting an array using quick sort when all elements are identical?

- a) $O(1)$
- b) $O(n)$
- c) $O(n \log n)$
- d) $O(n^2)$

Q59. Fill in the blank: The minimum number of passes required to sort 6 elements using bubble sort is _____.

- a) 6
- b) 5
- c) $\log n$
- d) 4

Q60. Which sorting algorithm is the most suitable for small datasets and nearly sorted data?

- a) Merge sort
- b) Quick sort
- c) Insertion sort
- d) Heap sort

ANSWER KEY – UNIT 4 (Q41–Q60)

- 41. a – First pass moves largest to end [3,5,8,4,2].
- 42. a – Binary search halves the interval each step.
- 43. b – Best case: found at first position 1.
- 44. c – In reverse order $O(n^2)$.
- 45. b – Quick sort uses pivot-based partitioning.
- 46. b – Both have $O(n^2)$ worst case.
- 47. a – Sorted list after insertion sort: [1,3,4,5,9].
- 48. a – Stable = equal elements maintain order.

- 49. b – Quick sort not efficient for linked lists.
- 50. b – Merging takes $\leq m + n - 1$ comparisons.
- 51. a – After 2 passes: [3,6,5,8].
- 52. b – Binary search can directly access mid element.
- 53. a – $(n^2 - n)/2 \approx n^2 / 2$.
- 54. c – Stack depth = $O(\log n)$.
- 55. b – Counting sort counts frequency of elements.
- 56. b – Must check all n elements if not found.
- 57. a – Merge sort = $O(n \log n)$ in all cases.
- 58. d – Identical elements \nrightarrow worst partitioning $\nrightarrow O(n^2)$.
- 59. b – Bubble sort $\nrightarrow n - 1$ passes = 5.
- 60. c – Insertion sort good for small/nearly sorted data.

☐ END OF SET 3 (UNIT 4: QUESTIONS 41–60)

☐ UNIT 4 – SEARCHING AND SORTING

(Questions 61–80)

Q61. Which of the following algorithms is a ****Divide and Conquer**** algorithm?

- a) Merge sort
- b) Bubble sort
- c) Selection sort
- d) Insertion sort

Q62. Fill in the blank: Binary search is efficient because it eliminates _____ of elements in each step.

- a) 1
- b) 2
- c) Half
- d) All

Q63. Which sorting algorithm uses the concept of "minimum selection" in each pass?

- a) Bubble sort
- b) Selection sort
- c) Merge sort
- d) Insertion sort

Q64. What will be the array after the first partition step of quick sort with pivot = 6 for [8, 4, 7, 2, 6, 5]?

- a) [4, 2, 5, 6, 8, 7]
- b) [6, 4, 2, 5, 8, 7]
- c) [2, 4, 5, 6, 7, 8]
- d) [4, 2, 6, 8, 5, 7]

Q65. Fill in the blank: The time complexity of merge sort and quick sort (average case) is _____.

- a) $O(n^2)$
- b) $O(n \log n)$
- c) $O(\log n)$
- d) $O(n)$

Q66. Which sorting algorithm works by comparing and inserting elements into a partially sorted list?

- a) Selection sort
- b) Insertion sort
- c) Bubble sort
- d) Quick sort

Q67. The number of comparisons made in binary search for an array of 128 elements (worst case) is _____.

- a) 7
- b) 8
- c) $\log_2 128$
- d) Both b and c

Q68. Fill in the blank: In bubble sort, if no swapping occurs in a pass, the array is _____.

- a) Partially sorted

- b) Fully sorted
- c) Reversed
- d) Random

Q69. Which searching algorithm has an average time complexity of $O(\log \log n)$?

- a) Binary search
- b) Linear search
- c) Interpolation search
- d) Fibonacci search

Q70. What is the main disadvantage of bubble sort?

- a) Complex to implement
- b) Requires extra memory
- c) Slow for large data
- d) Unstable algorithm

Q71. Fill in the blank: Quick sort performs poorly when pivot element is always the _____.

- a) Middle element
- b) Random element
- c) Smallest or largest element
- d) None

Q72. Which sorting algorithm can be easily adapted for singly linked lists?

- a) Bubble sort
- b) Merge sort
- c) Quick sort
- d) Selection sort

Q73. Which of the following is TRUE about the stability of sorting algorithms?

- a) Merge sort is stable
- b) Quick sort is stable
- c) Selection sort is stable
- d) Heap sort is stable

Q74. Fill in the blank: Counting sort and radix sort are examples of _____ sorting algorithms.

- a) Comparison-based
- b) Non-comparison-based
- c) Recursive
- d) Divide-and-conquer

Q75. What is the auxiliary space required for counting sort?

- a) $O(1)$
- b) $O(n)$
- c) $O(k)$ where k = range of input
- d) $O(n \log n)$

Q76. Which of the following best describes the working of radix sort?

- a) Sorts elements based on digits or bits
- b) Uses comparison of elements
- c) Requires recursion
- d) Works only on floats

Q77. Fill in the blank: The best case time complexity of quick sort occurs when the pivot divides the array into _____.

- a) Unequal parts
- b) Two equal halves
- c) Random halves
- d) Single elements

Q78. Which searching technique can be used efficiently on linked lists?

- a) Binary search
- b) Linear search
- c) Interpolation search
- d) Jump search

Q79. The number of swaps in selection sort for n elements is always _____.

- a) n

- b) $n - 1$
- c) $n \log n$
- d) n^2

Q80. Fill in the blank: Merge sort is preferred for large datasets because it has _____ time complexity in all cases.

- a) $O(n)$
- b) $O(\log n)$
- c) $O(n^2)$
- d) $O(n \log n)$

ANSWER KEY – UNIT 4 (Q61–Q80)

- 61. a – Merge sort follows Divide and Conquer.
- 62. c – Binary search removes half of remaining elements per step.
- 63. b – Selection sort picks minimum each pass.
- 64. a – First partition with pivot=6 → [4,2,5,6,8,7].
- 65. b – Both merge and quick sort average at $O(n \log n)$.
- 66. b – Insertion sort inserts into partially sorted section.
- 67. d – $\log_2 128 = 7$ → about 7-8 comparisons.
- 68. b – No swaps = already sorted.
- 69. c – Interpolation search has $O(\log \log n)$ average time.
- 70. c – Bubble sort is inefficient for large datasets.
- 71. c – Poor pivot choice (min/max) → worst $O(n^2)$.
- 72. b – Merge sort ideal for linked lists.
- 73. a – Merge sort is stable; others are not by default.
- 74. b – Counting & radix are non-comparison sorts.
- 75. c – Counting sort requires auxiliary array of size k.
- 76. a – Radix sort sorts digits one by one.
- 77. b – Best case = pivot divides array equally.
- 78. b – Linear search only practical for linked lists.
- 79. b – Selection sort always swaps $n-1$ times.

80. d – Merge sort consistently $O(n \log n)$.

☒ END OF SET 4 (UNIT 4: QUESTIONS 61–80)

☒ UNIT 4 – SEARCHING AND SORTING

(Questions 81–100)

Q81. Which sorting algorithm is the best choice for **large datasets with random order**?

- a) Insertion sort
- b) Merge sort
- c) Quick sort
- d) Bubble sort

Q82. Fill in the blank: Linear search is also called _____.

- a) Sequential search
- b) Indexed search
- c) Hash search
- d) Binary search

Q83. Which of the following sorting algorithms does **not** require comparisons between elements?

- a) Counting sort
- b) Selection sort
- c) Quick sort
- d) Merge sort

Q84. The space complexity of quick sort (recursive version) is _____.

- a) $O(1)$
- b) $O(n)$
- c) $O(\log n)$

d) $O(n^2)$

Q85. What is the maximum number of comparisons required in binary search on a sorted list of 1000 elements?

a) 10

b) 11

c) $\log_2(1000) \approx 10$

d) Both b and c

Q86. Fill in the blank: The main advantage of merge sort is its _____ performance on large datasets.

a) Inconsistent

b) Predictable

c) Slow

d) Unstable

Q87. Which of the following algorithms is **unstable** but **in-place**?

a) Merge sort

b) Quick sort

c) Bubble sort

d) Insertion sort

Q88. What will be the array after one pass of insertion sort on [5, 3, 4, 1, 2]?

a) [3, 5, 4, 1, 2]

b) [4, 5, 3, 1, 2]

c) [1, 3, 4, 5, 2]

d) [5, 4, 3, 2, 1]

Q89. Which searching technique is efficient for data stored in **linked lists**?

a) Linear search

b) Binary search

c) Jump search

d) Hashing

Q90. Fill in the blank: The process of arranging data items in logical order is called _____.

- a) Searching
- b) Sorting
- c) Insertion
- d) Deletion

Q91. The best case time complexity of bubble sort occurs when the array is _____.

- a) Randomly ordered
- b) Reverse ordered
- c) Already sorted
- d) Containing duplicates

Q92. Which algorithm is ****recursive and non-stable****, but usually faster than merge sort for practical cases?

- a) Bubble sort
- b) Quick sort
- c) Insertion sort
- d) Selection sort

Q93. Fill in the blank: The time complexity of linear search in average case is _____.

- a) $O(1)$
- b) $O(n)$
- c) $O(\log n)$
- d) $O(n^2)$

Q94. What is the primary advantage of counting sort over comparison-based algorithms?

- a) Handles any type of data
- b) Linear time for limited range inputs
- c) Uses less memory
- d) Simple recursive structure

Q95. Which of the following algorithms would be most efficient for sorting ****student roll numbers (0–999)****?

- a) Bubble sort
- b) Radix sort
- c) Quick sort

d) Selection sort

Q96. Fill in the blank: The number of levels in a binary search on n elements is approximately _____.

- a) n
- b) $\log n$
- c) \sqrt{n}
- d) $n \log n$

Q97. Which of the following statements about quick sort and merge sort is TRUE?

- a) Quick sort uses extra space; merge sort is in-place
- b) Merge sort uses extra space; quick sort is in-place
- c) Both are in-place
- d) Both require extra space

Q98. The average time complexity of bubble sort and selection sort are both _____.

- a) $O(n^2)$
- b) $O(n \log n)$
- c) $O(n)$
- d) $O(\log n)$

Q99. Which of the following is a real-life application of sorting algorithms?

- a) Ranking students by marks
- b) Searching files alphabetically
- c) Database indexing
- d) All of the above

Q100. Fill in the blank: The most suitable sorting algorithm for **external sorting (large files)** is _____.

- a) Merge sort
- b) Bubble sort
- c) Insertion sort
- d) Selection sort

☒ ANSWER KEY – UNIT 4 (Q81–Q100)

- 81. c – Quick sort performs best on large, random data.
- 82. a – Linear search = sequential search.
- 83. a – Counting sort compares no elements, uses counting logic.
- 84. c – Recursive quick sort uses $O(\log n)$ stack space.
- 85. d – $\log_2 1000 \approx 10$, so about 10–11 comparisons.
- 86. b – Merge sort gives consistent $O(n \log n)$ performance.
- 87. b – Quick sort is in-place but not stable.
- 88. a – After one pass ☒ [3, 5, 4, 1, 2].
- 89. a – Linked lists allow only sequential access ☒ linear search.
- 90. b – Sorting arranges data in order.
- 91. c – Already sorted array = best case for bubble sort.
- 92. b – Quick sort faster in practice but non-stable.
- 93. b – Average $O(n)$ for linear search.
- 94. b – Counting sort = $O(n + k)$ for small range values.
- 95. b – Radix sort ideal for fixed-digit integers.
- 96. b – Binary search depth $\approx \log_2 n$.
- 97. b – Merge sort needs extra arrays; quick sort is in-place.
- 98. a – Both bubble & selection sort take $O(n^2)$.
- 99. d – Sorting used in all ranking and search systems.
- 100. a – Merge sort handles large external data efficiently.

☒ END OF SET 5 (UNIT 4: QUESTIONS 81–100)

☒ UNIT 4 COMPLETE – SEARCHING AND SORTING (100 QUESTIONS)

Topics Covered:

- Searching: Linear, Binary, Interpolation
- Sorting: Bubble, Selection, Insertion, Quick, Merge, Radix, Counting

- Complexity (Best, Average, Worst)
- Stability & Space trade-offs
- Real-world & Implementation-based questions