

Nexus Static-Credential Providers — Validation Status (staging `oauth_broker`)

Generated 2026-07-09. Source: `provider_profiles` where `auth_type` IN ('`api_key`', '`basic_auth`') and `deleted_at` IS NULL .

After the "fail-closed" broker change, a static-credential (`api_key` / `basic_auth`) provider can only connect if it has **both** `api_base_url` and `user_info_endpoint` set, and that endpoint returns **401/403 for a bad key**.

Totals: 75 providers — Group A  14 working, Group B  35 not working, Group C  26 self-hosted.

Group A — Working (configured & verified) — 14

Each endpoint was live-tested with a bad key and returned `401` . `api_key` rows use `Authorization: Bearer <key>` unless noted; `basic_auth` rows use HTTP Basic with the fields shown.

Provider	auth_type	api_base_url	user_info_end
airtable-api	api_key	<code>https://api.airtable.com</code>	<code>/v0/meta/whoami</code>
close	basic_auth	<code>https://api.close.com</code>	<code>/api/v1/me/</code>
coda	api_key	<code>https://coda.io</code>	<code>/apis/v1/whoami</code>
drift	api_key	<code>https://driftapi.com</code>	<code>/contacts</code>
folk	api_key	<code>https://api.folk.app</code>	<code>/v1/users/me</code>
hubspot-api	api_key	<code>https://api.hubapi.com</code>	<code>/crm/v3/objects/limit=1</code>
insightly	basic_auth	<code>https://api.insightly.com</code>	<code>/v3.1/Users/GetU</code>
liquidplanner	api_key	<code>https://app.liquidplanner.com/api</code>	<code>/v1/account</code>
nifty	api_key	<code>https://openapi.niftypm.com</code>	<code>/api/v1.0/projec</code>
paystack	api_key	<code>https://api.paystack.co</code>	<code>/balance</code>
sendgrid	api_key	<code>https://api.sendgrid.com</code>	<code>/v3/user/profile</code>

shortcut	api_key	https://api.app.shortcut.com	/api/v3/member
streak	basic_auth	https://api.streak.com	/api/v1/users/me
twilio	basic_auth	https://api.twilio.com	/2010-04-01/Accounts.json

⚠ **Re-connect note:** `close`, `insightly`, `twilio` each had 1 active connection from before the fix. Because the credential fields changed (now `username / password`), those connections must be **re-connected** through the new form. `streak` had none active.

✗ Group B — Not working (with reason) — 35

The validator injects the key as an HTTP **header** (`Authorization: Bearer <key>`, or a raw value in a named header) or as **Basic** (`username / password`), and only treats `401 / 403` as failure. These don't fit that, have no verifiable endpoint, or still need verification.

Provider	auth_type	Reason	Action needed
telegram	api_key	Token goes in the URL path (<code>/bot<token>/getMe</code>)	<code>path</code> auth-strategy feature
amazon-s3	api_key	AWS SigV4 signing	SigV4 validation support
whatsapp-business	api_key	Bearer but path embeds phone-number-id (graph.facebook.com)	Path/templated endpoint support
trello	api_key	Key + token in query params	<code>query_param</code> validation support
what3words	api_key	Key in query param	<code>query_param</code> validation support
klaviyo	api_key	<code>Authorization: Klaviyo-API-Key <key></code> (custom prefix)	Custom value-prefix support
salesflare	api_key	<code>Authorization: <key></code> raw (no	Raw-Authorization

salesforce	api_key	Bearer)	support
travis-ci	api_key	Authorization: token <key> (custom prefix)	Custom value-prefix support
africas-talking	api_key	Custom apiKey header + username; sandbox vs prod hosts	Custom header/host handling
slack-bot	api_key	⚠ auth.test returns HTTP 200 with {"ok":false} for a bad token	Body-aware validation
amplitude	api_key	Pre-encoded single-field Basic (Authorization: Basic {{api_key}}); returns 403	Split into user/secret Basic, or header-template support
mixpanel	api_key	api_secret Basic (being deprecated); no clean 401 endpoint	Migrate to service-account Basic, verify
segment	api_key	Write key — tracking API has no authenticated 401 endpoint	Confirm nothing to validate
crisp	api_key	Basic (identifier:key) plus required X-Crisp-Tier header	Extra-header support (validator can't send it)
backblaze-b2	basic_auth	b2_authorize_account (Basic)	Set base + endpoint, verify
less-annoying-crm	basic_auth	Custom auth scheme	Verify scheme
heap	api_key	Ingestion/write key — no authenticated 401 endpoint	Confirm nothing to validate
kissmetrics	api_key	Ingestion/write key — no 401 endpoint	Confirm nothing to validate
logrocket	api_key	Ingestion/write key — no 401 endpoint	Confirm nothing to validate
fullstory	api_key	Ingestion/write key — no 401 endpoint	Confirm nothing to validate
pendo	api_key	Ingestion/write key — no 401 endpoint	Confirm nothing to validate
		Ingestion/write key — region-	Confirm nothing to

posthog	api_key	ingestion/write key — region specific, no 401 endpoint	Confirm nothing to validate
plausible	api_key	Analytics key — limited authenticated surface	Confirm nothing to validate
clay	api_key	Endpoint unknown (/v1/workspaces → 404)	Find correct endpoint, verify
pivotal-tracker	api_key	X-TrackerToken header; test host unreachable	Retry verify (raw header)
height	api_key	Base host api.height.app unreachable	Confirm correct base URL
nutshell	api_key	JSON-RPC + Basic	Verify / re-register
nimble	api_key	OAuth-ish auth	Verify scheme
freedcamp	api_key	API key + secret hashing	Verify scheme
simplepay	api_key	Region-specific (ZA/AU)	Confirm region base, verify
sourceforge	api_key	Mostly public REST	Verify endpoint
olark	api_key	Limited API	Verify endpoint
tawktot	api_key	Endpoint unknown	Verify endpoint
prembly	api_key	Base/endpoint unknown	Verify base + endpoint
dummy	api_key	Test provider — no real API	N/A (test only)

Group C — Self-hosted / instance-specific base URL — 26

Base URL depends on the customer's deployment (self-hosted or per-account subdomain), so it can't be guessed. Fill in per environment, then verify the check endpoint returns 401.

Provider	auth_type	Current base_url	Note
jenkins	basic_auth	(blank)	self-hosted CI URL
svn	basic_auth	(blank)	self-hosted repo URL
teamcity	api_key	(blank)	self-hosted CI URL
mattermost	api_key	(blank)	self-hosted chat URL

rocket-chat	api_key	(blank)	self-hosted chat URL
matomo	api_key	(blank)	self-hosted analytics URL
phabricator	api_key	(blank)	self-hosted URL
sourcegraph	api_key	(blank)	self-hosted / cloud URL
odoo	api_key	https://dromos-llc.odoo.com	per-tenant; JSON-RPC auth verify endpoint
openmrs	basic_auth	https://o2.openmrs.org	per-tenant; verify endpoint
woocommerce	basic_auth	(blank)	per-store URL (WP site)
prestashop	api_key	(blank)	per-store URL
opencart	api_key	(blank)	per-store URL
volusion	api_key	(blank)	per-store URL
corecommerce	api_key	(blank)	per-store URL
gorgias	api_key	(blank)	<account>.gorgias.com
zendesk-chat	api_key	(blank)	<subdomain>.zendesk.com
perforce	api_key	(blank)	self-hosted server
beanstalk	api_key	(blank)	<account>.beanstalkapp.cc
workfront	api_key	(blank)	per-tenant host
targetprocess	api_key	(blank)	per-tenant host
activecampaign	api_key	(blank)	<account>.api-us1.com per account
agilecrm	api_key	(blank)	<domain>.agilecrm.com
infobip	api_key	(blank)	<base>.api.infobip.com per-account
proofhub	api_key	(blank)	<company>.proofhub.com
freshchat	api_key	(blank)	region-specific base host