PRESTIGE
IRON DOORS

Door Order Process

DESIGN

Our design process is simple, collaborative, and tailored to your project.

⇒ **Step 1: Choose your preferred style.**
Browse our website, design publications, or other sources for inspiration. Reference photos, sketches, and hand-drawn concepts are all welcome and help us better understand your vision.

⇒ **Step 2: Provide a photo and preliminary measurements.**
For replacement projects, we recommend having a qualified door installer verify the opening dimensions. For new construction, please provide the door-opening specifications from your plans or contractor.

⇒ **Step 3: Select your glass and finish.**
Review the available glass and finish options on our website. You are also welcome to visit our Central Florida showroom to view samples and experience the quality and craftsmanship in person.

⇒ **Step 4: Review and approve the CAD drawings.**
We will prepare detailed drawings for your review before production begins. Revisions may be requested as needed. Simply mark your requested changes and return the drawings to us for updating.

A 50% deposit is required to begin production.
Major credit and debit cards, checks, and cash are accepted. Financing options may also be available.

PRODUCTION

Production begins once the final CAD drawings have been approved and the required deposit has been received.

⇒ We'll do our best to provide progress photos throughout production and accommodate minor revisions when possible. Please feel free to contact us at any time for a general update.
⇒ Once production is complete, we'll send final photos of your order for approval. After approval and receipt of the remaining 50% balance, your order will be secured in a custom iron-framed pallet and prepared for shipment.

The remaining 50% is required to release the unit for shipping.
*Installation **remains unpaid** until the door has been installed and approved. A deposit may be required for multi-day installations.*

SHIPPING & DELIVERY

Once final production photos have been approved and the remaining balance has been paid, your order will be released for shipment to your home, jobsite, or designated storage facility.

⇒ Custom orders typically take approximately 3–4 months from the date of order to delivery. All production and delivery timeframes are estimates and are not guaranteed.
⇒ Because every product is custom-made, manufacturing or freight delays may occasionally occur. We will provide updates as they become available and work to deliver your order as promptly as possible.
⇒ Orders are generally shipped to the nearest bonded warehouse. In many areas, direct delivery to your home or jobsite can be arranged for an additional charge. Most installers and contractors elect to pick up the order directly from the warehouse. Please confirm the preferred delivery method with your installer in advance.
⇒ Orders must be picked up within two business days of arrival. Pickup instructions and advance notice will be provided. Warehouses may begin charging storage fees after the third day, and any storage charges are the customer's responsibility. We can assist with locating a storage facility when needed.
⇒ Prestige will cover standard warehouse in-and-out handling charges, when applicable. Storage, delivery, special handling, and other additional charges are the customer's responsibility.
⇒ Home and jobsite deliveries require coordination with the freight carrier. The customer or installer must be available to receive the shipment and assist the driver as needed. These are large, heavy products and are not delivered like standard residential packages. Oversized units may require special equipment and two or more people to unload safely.

PRESTIGE IRON DOORS

Limited Product Warranty

Prestige Iron Doors *(hereinafter referred to as "the Company") extends the following Limited Product Warranty to the original purchaser of a* ***Prestige Iron Doors*** *Iron Door (hereinafter referred to as "the Product"), provided the Product is installed in the United States or Canada.*

I. Warranty Coverage and Period

The Company warrants that the Product will be free from defects in materials and workmanship for the periods specified below, subject to the conditions and exclusions outlined in this document.

Component	Warranty Period[1]	Coverage Details
Structural Integrity (Frame, Hinges, Door Slab)	**10 Years**	Covers welding failures and structural issues that impair the operation of the door.
Exterior Finish/Paint[2]	**Standard: 5 Years** **Marine Grade: 8 Years** **High-Salinity Area: 3 Years**	Covers peeling, flaking, blistering, or loss of adhesion caused by defects in the factory-applied finish.
Glass/Insulated Units	**3 Years**	Covers seal failure resulting in permanent obstruction of vision from dust or moisture between the glass panes. *Excludes breakage.*
Hardware (Locks, Handles, Hinges, etc.)	**1 Year**	Covers defects in materials and workmanship of supplied hardware components.

1. *Warranty periods begin on the date of delivery.*
2. *A High-Salinity Area means a property within one (1) mile of a coastline, tidal waterway, or other saltwater source, or otherwise subject to direct or frequent salt spray or salt-laden air. Marine Grade Finish is required in High-Salinity Environments.*

II. Remedy

If a defect covered by this warranty is discovered within the applicable warranty period, the Company's sole and exclusive obligation will be, at its option, to:

a. Repair the defective component of the Product.
b. Replace the defective component or the entire Product with a comparable product.
c. Refund the original purchase price of the Product.

The Company will not be responsible for any costs associated with the removal, installation, or re-installation of the Product, or for any freight or transportation costs associated with the remedy.

III. Conditions and Purchaser Responsibilities

This warranty is valid only if:

a. The Product is installed according to the Company's written instructions and all applicable building codes.
b. The Product is used for its intended purpose (as an exterior door).
c. The Product is properly maintained, including regular cleaning and, where applicable, touch-up of the finish using Company-approved methods and materials.
d. The Company is notified in writing of any alleged defect within thirty (30) days of its discovery and the original proof of purchase is provided.

IV. Exclusions

This warranty does not cover:

a. Damage due to improper installation, handling, storage, or modifications made after the Product leaves the Company's facility.
b. Damage caused by acts of nature (e.g., storms, hurricanes, floods, fires, earthquakes) or other factors beyond the Company's control.
c. Damage resulting from misuse, abuse, vandalism, or accident.
d. Normal wear and tear, including:
e. Fading, chalking, or weathering of the finish due to exposure to the elements, harsh chemicals, or pollutants.
f. Minor surface rust (flash rusting) on unexposed or internal components (e.g., within the hinges) or rust resulting from deep scratches in the finish that were not promptly treated. Surface rust on the main exposed components is covered for the finish warranty period.
g. Corrosion or failure caused by exposure to chemicals, salt spray, or other corrosive environments, or failure to perform recommended maintenance in coastal or high-humidity areas.
h. Minor variations in glass appearance, color, or minor imperfections (e.g., air bubbles) inherent to the manufacturing process of hand-forged iron doors or art glass.
i. Condensation, frost, or ice on the glass or door unit, which may be a result of high interior humidity and is not considered a defect.
j. Labor costs for replacement or re-installation.
k. Any door where the original factory finish has been altered, painted over, or removed without prior written approval from the Company.
l. Hardware: Locksets, hardware, and other components not supplied by Prestige Iron Doors are covered solely by their respective manufacturers' warranties
m. Lack of Overhang Protection: Damage due to insufficient overhang protection from the elements. The minimum recommended overhang should be at least one-half the distance between the bottom of the door and the bottom of the overhang.
n. Products that are not paid for in full.

V. Transferability

This warranty is non-transferable and applies only to the original purchaser of the Product.

VI. Limitation of Liability and Legal Provisions

a. Limitation of Damages. In no event shall Prestige Iron Doors LLC be liable for incidental, consequential, special, or indirect damages. Our total liability under this warranty is limited to the cost of repairing or replacing the defective product.
b. No Other Warranties: This is the sole and exclusive warranty offered by Prestige Iron Doors LLC. No employee, agent, dealer, or other person is authorized to alter this warranty or make any other warranty on our behalf.
c. Legal Compliance: This warranty gives you specific legal rights, and you may also have other rights that vary from state to state.

VII. Disclaimer

THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THE COMPANY SHALL NOT BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES ARISING OUT OF THE PURCHASE, USE, OR INABILITY TO USE THE PRODUCT.

PRESTIGE IRON DOORS

Product Care Instructions

Following these care and maintenance requirements is necessary to maintain coverage under Prestige Iron Doors' Limited Warranty. Regular cleaning and prompt attention to finish damage are especially important in coastal, high-humidity, and salt-air environments.

I. Maintenance Schedule at-a-Glance

Task	Frequency	Care Requirements
Regular cleaning	Monthly	Remove dirt and residue; rinse with a damp cloth and dry thoroughly. Clean at least twice monthly in coastal or high-humidity areas.
Hinges and flush bolts	Annually / as needed	Lubricate moving parts, check operation, and wipe away excess lubricant.
Finish inspection / repair	Quarterly / as needed	Check for chips, scratches, and rust. Address damage promptly.
Protective sealant / wax	Every 6 months	Apply a compatible exterior sealant or wax to a clean, dry surface.
Finish renewal	Every 3–5 years / as needed	Assess dull or faded finishes for approved re-sealing or repainting.

II. Regular Cleaning (Monthly)

Regular cleaning removes dirt, dust, and corrosive residue. Use warm water, a few drops of mild soap (such as Castile soap or mild dish detergent), soft cloths or sponges, and clean, dry towels. Microfiber is ideal. Use glass cleaner on glass panels only.

a. Remove loose debris. Gently wipe the door with a soft, dry cloth to remove dirt, dust, and cobwebs, including debris in scrollwork and corners.

b. Wash the iron. Dampen a soft cloth or sponge with the soap-and-water solution. Wipe the iron surfaces gently, working from top to bottom. Do not use harsh or abrasive cleaners, ammonia, bleach, or acidic products; these can damage the finish.

c. Rinse and dry. Remove soap residue with a clean cloth dampened with water. Avoid hosing down the door, which can cause excessive moisture buildup. Immediately dry all surfaces, crevices, and corners thoroughly with a clean towel.

d. Clean the glass. Apply glass cleaner to a cloth and clean the glass panels only. Keep the cleaner off the iron frame and finish.

III. Lubrication (Annually or as Needed)

Lubricate hinges and moving parts to support smooth operation and prevent squeaks. Use a lubricant suitable for the installed hardware, such as silicone spray, white lithium grease, or 3-in-One oil, and keep clean rags on hand. Follow the hardware manufacturer's instructions.

a. Access the hinges. Apply lubricant at accessible hinge joints or pins. Do not lift the door or remove hinge pins unless the work is performed by a qualified installer.

b. Apply sparingly. Use a small amount of lubricant. For sealed hinges, use the spray's straw attachment to direct lubricant into the accessible joint or gap.

c. Distribute and wipe. Open and close the door several times, then wipe away excess oil or grease to prevent dirt and dust buildup.

d. Lubricate flush bolts. On double doors, lubricate the top and bottom flush bolts on the inactive slab. Use the straw attachment to reach the moving mechanism, then gently operate the latch until it moves smoothly. Do not force a stuck latch.

IV. Finish Repair and Rust Prevention (Inspect Quarterly; Repair as Needed)

Inspect the finish quarterly for chips, scratches, and rust, and address damage promptly. Use Company-approved methods and compatible materials: fine-grit sandpaper (120–220 grit) or a suitable rust-removal tool, exterior-metal rust-inhibiting primer, matching touch-up paint, a small applicator, and clean cloths.

a. Prepare the area. For small rust spots or deep scratches, gently remove surface rust and loose or flaking paint. Keep sanding or brushing confined to the damaged area, then wipe away dust and debris.

b. Prime exposed metal. Apply a thin, even coat of compatible rust-inhibiting primer to bare metal. Allow it to dry fully according to the product instructions.

c. Touch up the finish. Apply matching paint in several thin coats, allowing the required drying time between coats. Feather the edges lightly to blend with the existing finish.

d. Assess finish renewal. Every 3–5 years, or sooner if the finish is dull or faded, assess whether re-sealing or repainting is needed. Obtain Prestige Iron Doors' written approval before altering or repainting the factory finish, and follow the approved preparation, priming, and coating instructions.

V. Long-Term Protection (Every 6 Months)

A compatible protective sealant or wax can provide added protection, particularly in challenging climates. Confirm compatibility with the door's finish before application.

a. Clean and dry. Clean the door thoroughly and allow all surfaces to dry completely.

b. Apply protection. Use a soft cloth to apply a compatible, high-quality automotive or wax-based exterior sealant according to its instructions.

c. Buff as directed. If the product requires it, allow a light haze to form, then buff gently with a clean microfiber cloth. Follow the product's drying and application directions.

VI. Seasonal and Climate-Specific Care

a. Coastal or high humidity. Clean at least twice monthly to remove salt residue, and inspect frequently for rust. Increase cleaning as exposure or buildup requires.

b. High pollen. Clean more often during high-pollen seasons to remove buildup, especially in spring and summer.

c. Winter, snow, or ice. Remove residual moisture after snow or ice exposure. Avoid de-icing salt near the door, as it can accelerate corrosion.