CS 470/547: Assignment 02

Programming Assignments

Your program MUST be written in **Python**. Your code file should be named **Assign02.py.** The principal goal of this assignment is to perform convolution using various approaches.

CS 547 only: You will also try to come up with an "optimal" convolution function that switches between approaches based on the circumstances.

Restrictions

You CANNOT use the following functions:

- **cv2.filter2D (or any other convolution/filtering functions in OpenCV)**
- **np.convolve**
- **scipy.signal.convolve2d**

The following are permitted in all functions:

- **cv2.copyMakeBorder()**
- **np.pad()**
- **cv2.flip()**
- **cv2.convertScaleAbs()**

If you are not sure whether a library function is permitted, ASK ME!

EXCEPT for do_convolution_slow(), while and for loops must be avoided. Everything can be implemented by taking advantage of numpy's indexing and broadcasting functionality.

Assign02.py

Both CS 470 and 547

The following general guidelines apply:

- All input images are grayscale images of shape (height, width) and with dtype "uint8".
- Input images and kernels should be converted to **"float64" before calculations**.
- All padding (actual or implicit) is assumed to be **zero-padding**.
- Output images are expected to have the same shape, but type will either be "uint8" or "float64". If convert_uint8 is True, ***use cv2.convertScaleAbs() with the provided alpha and beta to convert (as opposed to the numpy variant):***
    - **output = cv2.convertScaleAbs(output, alpha=alpha, beta=beta)**
    - **WARNING: Use the keyword arguments for alpha and beta as shown above!**

- All convolution functions take the same parameters and should return the same output given the same parameter values (they only differ in approach).

You are welcome and in fact encouraged to write helper functions for this assignment, BUT the below functions should be written as specified:

- **def read_kernel_file(filepath)**
  - Open a file for reading and grab the first line
  - The kernel files have the format:
    - (row count) (column count) (value 0,0) (value 0,1) … (value r,c)
  - For example:
    - 3 3 1 2 1 0 0 0 -1 -2 -1
  - …will ultimately become:
    - 1 2 1
0 0 0
-1 -2 -1
  - Split the line into tokens by spaces
    - Use the string split method
  - Grab the first and second tokens, convert them to ints, and store them as the row and column counts:
    - rowCnt = int(tokens[0])
    - colCnt = int(tokens[1])
  - Starting at index = 2, convert the remaining tokens into a kernel array with type "float64" and shape (rowCnt, colCnt)
    - ***HINT***: You CAN do this without a loop, as numpy CAN store string types (dtype=np.str_). You can then convert to float.
  - Return your kernel

- **def do_convolution_slow(image, kernel, alpha=1.0, beta=0.0, convert_uint8=True)**
  - Implement convolution ***using pure Python code and loops***.
  - **Avoid library functionality (OpenCV, Numpy, etc.) EXCEPT for:**
    - Numpy arrays (creation, indexing, slicing, shape)
    - The "always permitted" functions above
  - ***This is the ONLY function where loops are not only allowed but required.***

- **def do_convolution_fast(image, kernel, alpha=1.0, beta=0.0, convert_uint8=True)**
  - Implement convolution using numpy (this time avoiding loops).

- **def do_convolution_fourier(image, kernel, alpha=1.0, beta=0.0, convert_uint8=True)**
  - Implement convolution using the Fourier transform.
  - Make sure to use **cv2.getOptimalDFTSize()** for efficiency.

CS 547 only

The following additional functions must be written:

- **def check_if_separable(kernel)**
  - Given a kernel, determine if it is separable.
  - Use > 1e-5 to determine non-zero.
  - If the kernel is separable, return True, the vertical filter, and the horizontal filter.
  - Otherwise, return False, None, and None.
- **def do_convolution_separable(image, kernel, alpha=1.0, beta=0.0, convert_uint8=True, conv_func=do_convolution_fast)**
  - Check if the kernel is separable.
  - If not, return None.
  - Otherwise, perform convolution using the provided conv_func() with the vertical and then horizontal filters.
- **def do_convolution_optimal(image, kernel, alpha=1.0, beta=0.0, convert_uint8=True)**
  - For this function, you will decide how to most optimally choose between the following for convolution:
    - **do_convolution_fast()**
    - **do_convolution_separable()**
    - **do_convolution_fourier()**
  - Generally speaking, a correct implementation of this will NOT always pick one.
  - To justify your implementation, you will use ***Eval_Assign02_Grad.py*** (discussed later).

Testing Screenshot

I have provided several new files for testing:

- **General_Assign02.py** – helper functions and constants
- **Test_Assign02.py** – the test program run by CS 470 students
- **Test_Assign02_Grad.py** – the test program run by CS 547 students
- **Eval_Assign02_Grad.py** – the evaluation/timing program for do_convolution_optimal()
- **assign02/**
  - **images/**
    - Input images for testing
  - **filters/**
    - Filter files

Once you have merged from my repo into yours, these files/folders should reside in your main project directory. Your source file (Assign02.py) should reside in the main project directory as well (NOT the assign02 folder). You can either run the testing programs directly OR you can use the testing section of Visual Code.

You MUST run the appropriate test program and send a screenshot of the test results! Even if your program(s) do not pass all the tests, you MUST send this screenshot!

You may have to do "Command Palette" → "Python: Configure Tests" → unitttest → root directory → "test_*.py", and then modify .vscode/settings.json to use "Test_*.py"

This screenshot should show clearly:

- The final result of the test run on the command line ("OK" for all passing, "FAILED (failures=N)" for some or all failing).
- OR
- The testing view in Visual Code

The screenshot should be copied to the screenshots/ folder.

CS 470 only

For the screenshot, you should run Test_Assign02.py.

CS 547 only

For the screenshot, you should run Test_Assign02_Grad.py.

While you will need to run Eval_Assign02_Grad.py, you do NOT need a screenshot of it.

Eval_Assign02_Grad.py (CS 547 only)

This script runs multiple random trials to get the minimum execution time for running the different convolution functions (including do_convolution_optimal()) in different situations, to wit:

- Non-separable filters from size 3 to MAX_ODD_SIZE (default: 43) in increments of 2.
- Gaussian filters from size 3 to MAX_GAUSS_SIZE (default: 65) in increments of 2.

It will then chart the timings vs. filter size as well as give a bar chart of the total filter times per experiment. These charts are both displayed as well as saved to disk under "assign02/output". The charts default to a log scale for the timing axis (i.e., y axis).

For obvious reasons, do_convolution_separable() is NOT run against the "odd" filters.

A reasonably-sized image is used in all cases. **Barring extenuating circumstances, MAX_ODD_SIZE, MAX_GAUSS_SIZE, and TEST_IMAGE_PATH should NOT be modified.**

However, the rest of the parameters may be modified as you see fit. In particular, MAX_TRIAL_CNT may have to be adjusted. If it is too low, your timing numbers will be more erratic. However, a higher number of trials increases the amount of time your experiments will take. That said, **for any final results, MAX_TRIAL_CNT should at LEAST be 10.**

Please note that your results WILL vary depending on your hardware. In other words, your "optimal" convolution function may not be optimal on my machine. That is expected, which is why in the README you will add charts and text that justifies your choices in implementing do_convolution_optimal().

README.md

Update the README.md of your repository with the following:

- Add a new entry under "Runnable Python Scripts" for "Assign02.py".
- ***CS 470 only:***
    - Very briefly describe what functionality is available. I am only looking for a few sentences.
- ***CS 547 only:***
    - Have a first subsection under it for "**General Functionality**". Very briefly describe what functionality is available. I am only looking for a few sentences.
    - Have a second subsection "**Optimal Convolution**". Here you will justify your implementation choice by providing timing charts from running the evaluation script and your own explanation/analysis text.
        - All final images should be stored in folder **assign02/charts**.
        - You can add an image to markdown document like so:
            - **![Chart for timings](assign02/charts/AllTimingsGraph.png)**
        - Ensure you include alt-text like shown above.
        - **I am expecting text AND images.**

Grading

Your OVERALL assignment grade is weighted as follows:

CS 470:

- 5% - Testing results screenshot
- 5% - README update
- 90% - Programming assignments

CS 547:

- 5% - Testing results screenshot
- 20% - README update
- 75% - Programming assignments

I reserve the right to take points off for not meeting the specifications in this assignment description.

The following specific penalties (applied to the WHOLE assignment) can be expected:

Problem	**Maximum Penalty**
Code that is not syntactically correct	60
Usage of forbidden function(s)	60
One GIGANTIC commit for whole assignment	30
Incorrect implementation of filter functions (including trivial implementation of do_convolution_optimal())	50
Usage of for/while loops **per function** (or lack of it in do_convolution_slow())	10
Incorrect implementation of check_if_separable()	10
Incorrect implementation of read_kernel_file()	5
Failing to either flip kernel (actual or conceptual)	5
Incorrect conversion to uint8	5
Incorrect padding for optimal DFT size	5
Technically correct code, but poor code design	5
Missing assignment Git branch	5
Missing testing screenshot	5
Wrong names for branch, files, etc.	2 for each
Bad commit messages	2 for each

In general, these are things that will be penalized:

- **Code that is not syntactically correct (up to 60 points off!)**
- Sloppy or poor coding style
- Bad coding design principles
- Code that crashes, does not run, or takes a VERY long time to complete
- Using code from ANY source other than the course materials
- Collaboration on code of ANY kind; this is an INDIVIDUAL PROJECT
- Sharing code with other people in this class or using code from this or any other related class
- Output that is incorrect
- Algorithms/implementations that are incorrect
- Submitting improper files
- Failing to submit ALL required files