

Lab Exercise 10- Creating and Managing a ReplicaSet in Kubernetes

Objective:

A ReplicaSet in Kubernetes ensures a specified number of Pod replicas are running at any given time. This exercise will guide you through creating a ReplicaSet to maintain the desired state of your application.

- Understand the syntax and structure of a Kubernetes ReplicaSet definition file (YAML).
- Learn how to create and manage a ReplicaSet to ensure application availability.
- Understand how a ReplicaSet helps in scaling applications and maintaining desired states.

Prerequisites

- Kubernetes Cluster: Have a running Kubernetes cluster (locally using Minikube or kind, or a cloud-based service).
- kubectl: Install and configure kubectl to interact with your Kubernetes cluster.
- Basic Knowledge of YAML: Familiarity with YAML format will be helpful for understanding Kubernetes resource definitions.

Step-by-Step Guide

Step 1: Understanding ReplicaSet

A ReplicaSet ensures a specified number of Pod replicas are running at any given time. If a Pod crashes or is deleted, the ReplicaSet creates a new one to meet the defined number of replicas. This helps maintain application availability and ensures that your application can handle increased load by distributing traffic among multiple Pods.

Step 2: Create a ReplicaSet

We'll define a ReplicaSet to maintain three replicas of a simple Nginx web server Pod.

Create a YAML file named nginx-replicaset.yaml with the following content:

```
apiVersion: apps/v1
kind: ReplicaSet
metadata:
  name: nginx-replicaset
spec:
  replicas: 3
  selector:
    matchLabels:
      app: nginx
  template:
    metadata:
      labels:
        app: nginx
    spec:
      containers:
        - name: nginx
          image: nginx:latest
          ports:
            - containerPort: 80
```

```
nginx-replicaset.yaml ×
lab > nginx-replicaset.yaml > {} spec > {} t
io.k8s.api.apps.v1.ReplicaSet (v1@replicaset.json)
1  apiVersion: apps/v1
2  kind: ReplicaSet
3  metadata:
4    name: nginx-replicaset
5  spec:
6    replicas: 3
7    selector:
8      matchLabels:
9        app: nginx
10   template:
11     metadata:
12       labels:
13         app: nginx
14     spec:
15       containers:
16       - name: nginx
17         image: nginx:latest
18         ports:
19       - containerPort: 80
```

Explanation:

- **apiVersion:** Defines the API version (apps/v1) used for the ReplicaSet resource.
- **kind:** Specifies that this resource is a ReplicaSet.
- **metadata:** Contains metadata about the ReplicaSet, including name.
 - **name:** The unique name for the ReplicaSet.
- **spec:** Provides the specification for the ReplicaSet.
 - **replicas:** Defines the desired number of Pod replicas.
 - **selector:** Criteria for selecting Pods managed by this ReplicaSet.
 - **matchLabels:** Labels that Pods must have to be managed by this ReplicaSet.

- template: Defines the Pod template used for creating new Pods.
 - metadata: Contains metadata for the Pods, including labels.
 - labels: Labels applied to Pods created by this ReplicaSet.
- spec: Specification for the Pods.
 - containers: Lists the containers that will run in the Pod.
 - name: The unique name of the container within the Pod.
 - image: The Docker image used for the container.
 - ports: Ports exposed by the container.

Step 3: Apply the YAML to Create the ReplicaSet

Use the `kubectl apply` command to create the ReplicaSet based on the YAML file.

```
kubectl apply -f nginx-replicaset.yaml
```

Verify the ReplicaSet is running and maintaining the desired number of replicas:

```
kubectl get replicaset
```

This command lists all ReplicaSets in the current namespace.

To check the Pods created by the ReplicaSet:

```
kubectl get pods -l app=nginx
```

This command lists all Pods with the label `app=nginx`.

NAME	DESIRED	CURRENT	READY	AGE
nginx-replicaset	3	3	0	5s

NAME	DESIRED	CURRENT	READY	AGE
nginx-replicaset	3	3	3	42s

NAME	READY	STATUS	RESTARTS	AGE
nginx-replicaset-7c77d	1/1	Running	0	49s
nginx-replicaset-pwdkk	1/1	Running	0	49s
nginx-replicaset-vhfmg	1/1	Running	0	49s

Step 4: Managing the ReplicaSet

1. Scaling the ReplicaSet

You can scale the number of replicas managed by the ReplicaSet using the `kubectl scale` command.

```
kubectl scale --replicas=5 replicaset/nginx-replicaset
```

This command scales the ReplicaSet to maintain 5 replicas. Verify the scaling operation:

```
kubectl get pods -l app=nginx
```

You should see that the number of Pods has increased to 5.

NAME	READY	STATUS	RESTARTS	AGE
nginx-replicaset-7c77d	1/1	Running	0	82s
nginx-replicaset-bqr57	1/1	Running	0	16s
nginx-replicaset-pwdkk	1/1	Running	0	82s
nginx-replicaset-vhfmg	1/1	Running	0	82s
nginx-replicaset-vmsvj	1/1	Running	0	16s

2. Updating the ReplicaSet

If you need to update the Pod template (e.g., to use a different Docker image version), modify the YAML file and apply it again. For instance, change the image to a specific version of Nginx:

```
spec:
  template:
    spec:
      containers:
      - name: nginx
```

```
image: nginx:1.19.3 # Change to a specific version
```

```
nginx-replicaset.yaml x
lab > nginx-replicaset.yaml > {} spec > {} template > {} spec > [ ] containers > {} 0
2  kind: ReplicaSet
3  metadata:
4    name: nginx-replicaset
5  spec:
6    replicas: 3
7    selector:
8      matchLabels:
9        app: nginx
10   template:
11     metadata:
12       labels:
13         app: nginx
14     spec:
15       containers:
16       - name: nginx
17         image: nginx:1.19.3 # Change to a specific version
18         ports:
19         - containerPort: 80
```

Apply the changes:

```
kubectl apply -f nginx-replicaset.yaml
```

Check the status to ensure the Pods are updated:

```
kubectl get pods -l app=nginx
```

Note: Updating a ReplicaSet doesn't automatically replace existing Pods with new ones. In practice, you often create a new ReplicaSet or Deployment for updates.

NAME	READY	STATUS	RESTARTS	AGE
nginx-replicaset-7c77d	1/1	Running	0	2m56s
nginx-replicaset-pwdkk	1/1	Running	0	2m56s
nginx-replicaset-vhfmg	1/1	Running	0	2m56s

3. Deleting the ReplicaSet

To clean up the ReplicaSet and its Pods, use the `kubectl delete` command:

```
kubectl delete -f nginx-replicaset.yaml
```

This command deletes the ReplicaSet and all the Pods managed by it.

```
replicaset.apps "nginx-replicaset" deleted from default namespace
```