				3.2.1.1 - functional requirements	What happens to the dashboard when the microcontrollers stop sending? Your use case narrative mentions it as an exception - which requirement covers it?	

				3.1.4 - communication interface	SET-UP: Section 3.1.4 is one paragraph. It says the web application uses HTTP, and that communication between the microcontrollers and the software will be implemented through 'an appropriate network interface'. QUESTION: What protocol do your microcontrollers use to send a reading, what does one message contain, how often is it sent - and where in this entire document is anything encrypted?	Concedes that 'an appropriate network interface' specifies nothing at all. Chooses a real option with a reason - an HTTP POST to a REST endpoint, MQTT to a broker, or a WebSocket - and justifies it for a constrained microcontroller. Defines the message: battery identifier, voltage, temperature, state of charge, charge or discharge flag, timestamp, in a stated format such as JSON. States a transmission interval and says what happens to readings taken while the link is down. On the last part, notices that the document names HTTP rather than HTTPS and never mentions TLS, encryption or how passwords are stored. Strong answers add device authentication - what stops anything on the network posting fabricated readings.

				3.1.2 - hardware interface	Section 2.4.1.1 is headed 'Functional Constraints' and lists things like 'the system must display battery data in a clear format'. Is that a constraint or a requirement, and what is the difference?	

				Section 4 diagram vs 1.2, 2.2, 2.3 and 3.2	SET-UP: Your use case diagram is the only properly drawn UML diagram produced by any group this year - boundary, actors, include and extend relationships, a legend, and six use-case descriptions. But it shows an Administrator role, Manage Users, Add/Edit/Delete User, Generate Reports, Export Report and Backup Data, and section 2.3 defines only one user class while none of those functions appears in your scope, product functions or requirements. QUESTION: Are user management, reporting and export part of this system or not - and which is authoritati	Takes the credit for the diagram but recognises that it specifies a bigger system than the rest of the document, and that a reader cannot tell which to build from. Picks a position and carries it through consistently: either add the Administrator to 2.3, the capabilities to 1.2 and 2.2, and the requirements to 3.2 - or remove them from the diagram. States the principle that the diagram and the text are one model. Strong answers also pick up the modelling detail: Generate Reports to Export Report should be an extend, because exporting is optional, and Manage Users to Add/Edit/Delete User is decomposition rather than inclusion.

				3.3 - performance requirements	SET-UP: Section 3.3 says the system should respond 'with minimal delay' and recover from interruptions 'within a reasonable time'. The only numbers in the whole section are four batteries and one week of storage. QUESTION: How old is the reading on your live dashboard allowed to be before it is misleading - and how much data does one week of logging actually come to?	Turns 'minimal delay' into something testable by tying it to the sampling rate: a reading appears on the dashboard within so many seconds of being taken, and the dashboard refreshes at least that often, with a percentile attached. Replaces 'a reasonable time' with a recovery figure. On the second half, does the arithmetic out loud - readings per battery per interval, times four batteries, times seven days - to get a row count and a storage estimate, which is how a database is sized and which nothing in the document does. Strong answers note that no sampling rate appears anywhere in the document, so neither number can currently be derived at all.

				Scope, 2.2 and 3.2 - alarms and thresholds	SET-UP: Your system measures the voltage and temperature of four solar batteries and draws graphs of both. Nowhere in this document does the system do anything when a value goes out of range - there is no threshold, no alarm, no alert and no notification in your scope, your product functions or your requirements. QUESTION: A battery reaches an unsafe temperature at two in the morning and nobody is looking at the dashboard. What does your system do - and should a battery management system be purely passive?	Concedes that the system as specified does nothing, and treats that as a gap rather than defending it as a scoping decision. Proposes configurable upper and lower thresholds per battery for voltage and temperature, severity levels, a visible alarm state on the dashboard, a notification route to a named person, and logging of every alarm event so it can be reviewed afterwards. Recognises the safety dimension of over-temperature and over- or under-voltage on a battery bank. Strong answers observe that graphs help you diagnose after the event but do not protect anything during it, and that the word 'management' in Battery Management System implies more than logging - then say the client should be asked whether alarms are

				2.2.6, 2.4.3 and 3.6 - retention versus backup	SET-UP: Sections 2.2.6, 2.4.3 and 3.3 all agree that data is kept for a maximum of one week and anything older is cleared. Section 3.6 then requires a backup mechanism to prevent the loss of important battery records. QUESTION: If everything is deleted after seven days, what is the backup actually protecting - and can you tell how a battery is degrading with only one week of history?	Sees the tension: either the backups are purged on the same schedule, in which case they protect against hardware failure but not against the purge, or they hold data beyond a week, which contradicts the retention rule and must be stated. On the second half, recognises that battery health is a long-term trend - capacity fade and gradual temperature drift take months to show - so a seven-day window cannot support the analysis the client probably wants. Proposes the standard answer: keep raw samples for a week and retain daily or hourly aggregates far longer, since summaries cost very little storage. Strong answers say the retention period should be confirmed with the client rather than assumed.

				3.1.3, 2.4.4, 3.4 and document control	Your system monitors four batteries. The client installs forty. What has to change, and which requirement in this document tells you?	