

```
In [18]: # importing libraries
import numpy as nm
import matplotlib.pyplot as mtp
import pandas as pd
from sklearn import metrics

# importing datasets
data_set= pd.read_csv('user_data.csv')

#Extracting Independent and dependent Variable
x= data_set.iloc[:, [2,3]].values
y= data_set.iloc[:, 4].values

# Splitting the dataset into training and test set.
from sklearn.model_selection import train_test_split
x_train, x_test, y_train, y_test= train_test_split(x, y, test_size= 0.25, random_state=0)

#feature Scaling
from sklearn.preprocessing import StandardScaler
st_x= StandardScaler()
x_train= st_x.fit_transform(x_train)
x_test= st_x.transform(x_test)
```

```
In [19]: data set
```

Out[19]:	User ID	Gender	Age	EstimatedSalary	Purchased	
	0	15624510	Male	19	19000	0
	1	15810944	Male	35	20000	0
	2	15668575	Female	26	43000	0
	3	15603246	Female	27	57000	0
	4	15804002	Male	19	76000	0

	395	15691863	Female	46	41000	1
	396	15706071	Male	51	23000	1
	397	15654296	Female	50	20000	1
	398	15755018	Male	36	33000	0
	399	15594041	Female	49	36000	1

400 rows × 5 columns

```
In [20]: #Fitting Decision Tree classifier to the training set random forest
from sklearn.ensemble import RandomForestClassifier
classifier=RandomForestClassifier(n_estimators=10, criterion="entropy")
classifier.fit(x_train, y_train)
```

```
Out[20]: RandomForestClassifier(criterion='entropy', n_estimators=10)
```

```
In [21]: #Predicting the test set result
y_pred= classifier.predict(x_test)
```

```
In [22]: y_pred
```

[illegible]

```
In [23]: #Now we will create the confusion matrix to determine the correct and incorrect predictions.
```

```
#Creating the Confusion matrix
from sklearn.metrics import confusion_matrix
cm= confusion_matrix(y_test, y_pred)
```


In [24]: cm

```
Out[24]: array([[65, 3],
                [ 4, 28]], dtype=int64)
```

```
In [25]: #Visualizing the training Set result
from matplotlib.colors import ListedColormap
x_set, y_set = x_train, y_train
x1, x2 = nm.meshgrid(nm.arange(start = x_set[:, 0].min() - 1, stop = x_set[:, 0].max() + 1, step = 0.01),
nm.arange(start = x_set[:, 1].min() - 1, stop = x_set[:, 1].max() + 1, step = 0.01))
mtp.contourf(x1, x2, classifier.predict(nm.array([x1.ravel(), x2.ravel()]).T).reshape(x1.shape),
alpha = 0.75, cmap = ListedColormap(('purple', 'green' )))
mtp.xlim(x1.min(), x1.max())
mtp.ylim(x2.min(), x2.max())
for i, j in enumerate(nm.unique(y_set)):
    mtp.scatter(x_set[y_set == j, 0], x_set[y_set == j, 1],
c = ListedColormap(('purple', 'green'))(i), label = j)
mtp.title('Random Forest Algorithm (Training set)')
mtp.xlabel('Age')
mtp.ylabel('Estimated Salary')
mtp.legend()
mtp.show()
```

c argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with *x* & *y*. Please use the *color* keyword-argument or provide a 2-D array with a single row if you intend to specify the same RGB or RGBA value for all points.


c argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with *x* & *y*. Please use the *color* keyword-argument or provide a 2-D array with a single row if you intend to specify the same RGB or RGBA value for all points.



```
In [26]: #Visualizing the test set result
from matplotlib.colors import ListedColormap
x_set, y_set = x_test, y_test
x1, x2 = nm.meshgrid(nm.arange(start = x_set[:, 0].min() - 1, stop = x_set[:, 0].max() + 1, step = 0.01),
nm.arange(start = x_set[:, 1].min() - 1, stop = x_set[:, 1].max() + 1, step = 0.01))
mtp.contourf(x1, x2, classifier.predict(nm.array([x1.ravel(), x2.ravel()]).T).reshape(x1.shape),
alpha = 0.75, cmap = ListedColormap(('purple', 'green' )))
mtp.xlim(x1.min(), x1.max())
mtp.ylim(x2.min(), x2.max())
for i, j in enumerate(nm.unique(y_set)):
    mtp.scatter(x_set[y_set == j, 0], x_set[y_set == j, 1],
c = ListedColormap(('purple', 'green'))(i), label = j)
mtp.title('Random Forest Algorithm(Test set)')
mtp.xlabel('Age')
mtp.ylabel('Estimated Salary')
mtp.legend()
mtp.show()
```

c argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with *x* & *y*. Please use the *color* keyword-argument or provide a 2-D array with a single row if you intend to specify the same RGB or RGBA value for all points.

c argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with *x* & *y*. Please use the *color* keyword-argument or provide a 2-D array with a single row if you intend to specify the same RGB or RGBA value for all points.



```
In [30]: accuracy = metrics.accuracy_score(y_test,y_pred)
report = metrics.classification_report(y_test,y_pred)
cm = metrics.confusion_matrix(y_test,y_pred)
```

```
print("Classification report:")
print("Accuracy: ", accuracy)
print(report)
print("Confusion matrix:")
print(cm)
```

Classification report:				
Accuracy:	0.93			
	precision	recall	f1-score	support
0	0.94	0.96	0.95	68
1	0.90	0.88	0.89	32
accuracy			0.93	100
macro avg	0.92	0.92	0.92	100
weighted avg	0.93	0.93	0.93	100

```
Confusion matrix:
[[65  3]
 [ 4 28]]
```

In []:

In []: