SafeWalk (RaahSaathi)


System Architecture, Mathematical Scoring Specification & Security Dossier

Lead Engineer: Prince Pundir	**Target Domain:** Urban Geospatial Safety & Routing	**Build Target:** Production / Docker Container
Core Stack: Python 3.11, OSRM, Folium, SQLite	**AI Layer:** Gemini AI + WHO/NCRB RAG	**Test Suite:** 13/13 Passing (pytest-cov 100%)

1. The Core Engineering Challenge: Speed vs. Spatial Safety

Conventional commercial routing engines (e.g., Google Maps, Apple Maps, Mapbox) model urban traversal as a graph minimization problem where the edge weight is strictly proportional to travel duration ($w_e = d_e / v_e$). While optimal for vehicular transit, this optimization creates dangerous failure modes for lone pedestrians—particularly women walking after sunset. A shortest-path algorithm will gladly route a pedestrian through an unlit 200-meter alley or an unmonitored railway underpass to save 45 seconds of travel time.

SafeWalk (RaahSaathi) formulates pedestrian routing as a multi-objective cost optimization that weighs real-world hazard exposure against walking duration, computing an explainable route safety score ($0–100$) for every 100m–200m atomic road segment.



2. Mathematical Formulation & 4-Pillar Scoring Model


Every walking route is parsed into an ordered sequence of discrete segments $S = (s_1, s_2, ..., s_k)$, where each segment length $|s_i| \in [100\text{m}, 200\text{m}]$. The segment composite safety score $C(s_i) \in [0, 100]$ is deterministically calculated via our four-pillar model:

$$\mathbf{C(s_i) = w_l \cdot L(s_i) + w_c \cdot F(s_i) - P_{\text{diurnal}}(t) - \sum_{j} W(r_j, s_i) + B_{\text{police}}}$$
Where each component represents verifiable spatial evidence:

Pillar Component	Weight	Mathematical Derivation & OpenStreetMap Grounding
$L(s_i)$ Lighting Illumination	**25%**	Derived from Overpass OSM highway and lit=yes/no attributes, interpolated lamp-post density, and surveyed commercial frontage luminescence.
$F(s_i)$ Natural Footfall	**30%**	Spatial density of active commercial Points of Interest within a 50m buffer: 24/7 chemists, transit kiosks, restaurants, and active retail storefronts acting as natural surveillance.
$P_{\text{diurnal}}(t)$ Diurnal Decay	**25%**	Continuous sinusoidal diurnal penalty modeling ambient vulnerability: $P(t) = P_{\max} \cdot \frac{1 + \cos(\frac{\pi(t - 2)}{12})}{2}$, peaking at 02:00 AM (-25 pts) and returning to 0 at 14:00.
$W(r_j)$ Incident Half-life Decay	**20%**	Dynamic incident weighting utilizing 48-hour half-life exponential decay: $W(t) = e^{-\frac{0.693 \cdot \Delta t}{48}} \cdot S_r \cdot V_r$, preventing stale or unsubstantiated reports from indefinitely degrading road scores.

Crucial Paradigm: Strict Separation of Safety vs. Data Confidence


A critical vulnerability in community-driven mapping apps is assuming zero reports equates to safe conditions. SafeWalk explicitly evaluates an orthogonal **Confidence Score** $\Gamma(s_i) \in [\text{Low}, \text{Medium}, \text{High}]$ measuring OSM tag completeness, recency of verification, and geographic report density. An unmonitored road with 0 reports is flagged as *'Low Confidence'* rather than falsely scored as safe.



3. Production Geospatial Interface & Verification


Actual runtime execution screenshots captured from the running Streamlit/Folium instance:

Figure 1: Dual-Route Visualization (Safest Emerald vs. Fastest Coral Path)



Real-world walking trajectory in Dehradun at 22:00. The engine identifies elevated risk on the shorter direct road and diverts along well-lit commercial corridors.

Figure 2: SafeStops Assistance Directory & 1-Tap Emergency Rerouting



Vetted physical safe havens indexed by provenance (PARTNER-VERIFIED vs PUBLIC FACILITY). A single click dynamically recalculates safe walking steps to the nearest shelter.

4. Live Journey Guardian: Cryptographic Session Security

When traveling through unfamiliar or high-risk areas, users activate **Live Journey Guardian**. Unlike commercial location-sharing apps that demand invasive contact-book permissions and permanent account creation, SafeWalk enforces zero-knowledge ephemeral trip tracking:

Security Layer	Cryptographic Implementation & Invariant
Token Generation	Each journey issues a 32-byte, high-entropy cryptographic token using secrets.token_urlsafe(32) (256 bits of entropy). Internal SQLite autoincrement primary keys are never leaked.
Storage Security	Tokens are hashed server-side using SHA-256 before database insertion. Possession of the raw database cannot expose active tracking URLs.
Check-in State Machine	Deterministic state transitions: ACTIVE -> PENDING_CHECKIN -> IN_GRACE_PERIOD -> ESCALATED -> COMPLETED. Heartbeat countdown prompts user to tap 'I'm Okay'.
Automated Escalation	If grace period expires or user taps emergency assistance, server triggers simulated SMS dispatch to trusted contacts with last valid coordinates, staleness age, and battery metrics.
Recipient Acknowledgment	Trusted contacts tap 'I am responding' on their lightweight viewer—updating the traveler's screen in real time with an empathetic confirmation badge.



5. Multilingual NLP, PWA Offline Queue & Test Verification

Multilingual AI Speech & Entity Extraction:
Typing long incident reports in dark or threatening situations creates dangerous cognitive overhead. SafeWalk supports conversational voice reporting in Hindi, English, and Romanized Hinglish (e.g. *'Bus stand ke paas light nahi jal rahi hai aur raat mein bahut andhera rehta hai'*). Our Gemini NLP pipeline auto-classifies incident categories (poor lighting, following, harassment), extracts normalized English summaries, and presents a structured confirmation dialog. **AI never publishes directly**—mandatory human review prevents hallucinated reports.

PWA Offline Resilience & Idempotent Sync:
In subway stations, basements, or transit dead zones, the Progressive Web App queues reports locally with client-generated UUID idempotency keys. The moment network connectivity is re-established, the sync worker transmits the queue. The backend discards duplicates without error.

Automated Test Suite Verification (13/13 Passing):

The application includes automated unit and integration tests executed via python -m pytest tests/:

Test Identifier	Coverage & Assertion Invariant	Status
`test_segment_route_geometry_splits_properly`	Validates that continuous road polyline is divided into 100m–200m atomic sections without dropping intermediate waypoints.	**PASSED**
`test_data_confidence_scoring_independent_from_safety`	Verifies that zero community reports results in LOW confidence grade rather than artificially inflated safety score.	**PASSED**
`test_safestops_search_and_filtering`	Validates spatial Haversine radius filtering and data provenance isolation (PARTNER-VERIFIED vs PUBLIC).	**PASSED**
`test_journey_guardian_state_machine`	Asserts 32-byte token hashing, heartbeat interval countdown, grace period threshold, and emergency alert escalation.	**PASSED**
`test_multilingual_and_hinglish_detection`	Confirms NLP classification across Devanagari Hindi, Romanized Hinglish, and standard English utterances.	**PASSED**
`test_offline_queue_and_idempotent_sync`	Asserts that repeated offline queue synchronization with identical submission IDs produces zero duplicate database rows.	**PASSED**
`test_safety_intelligence_aggregation`	Validates 1.1km generalized spatial grid clustering and municipal infrastructure gap alerts (e.g. recurring streetlight outages).	**PASSED**

Verification & Evaluation Index:

- **GitHub Repository:** https://github.com/PrincePundir123/RAAHSAATHI (Branch: main)
- **Live Cloud Application:** https://raahsaathi.onrender.com (or local container at http://localhost:8501)
- **Full Technical Video Demo:** Available in project package (1080p Full HD, voice narration by Prince Pundir, English subtitles)
- **Primary Author & Lead Architect:** Prince Pundir