

ASSIGNMENT — 20 QUESTIONS

20
Total Marks**30 min**
Time**MCQ**
Type**7 — Promises**
Day

Instructions

Har question ke liye sabse sahi answer choose karo. Sab 1 mark ke hain.

★ questions promise chaining ke tricky parts cover karte hain — dhyan se trace karo.

Answer key aakhiri page pe hai.

Q1. [Promise States] Promise ke teen states kaunse hain?

- (A) Loading, Loaded, Error
- (B) Pending, Fulfilled, Rejected
- (C) Start, Running, Done
- (D) Open, Closed, Failed

Q2. [Promise States] ★ Promise ka executor function kab run hota hai?

- (A) Pehle .then() call hone par
- (B) Synchronously — new Promise() call hote hi immediately
- (C) Microtask queue mein asynchronously
- (D) setTimeout ke baad

Q3. [Promise States] resolve() ke baad reject() call karne par kya hoga?

- (A) Both fire hote hain
- (B) reject() bhi fire hoga — dono run hote hain
- (C) reject() completely ignored hota hai — state already settled
- (D) Error throw hogi

Q4. [Chaining] ★ Promise.resolve(5).then(v => v*2).then(v => v+1) — final value?

- (A) 5
- (B) 10
- (C) 11
- (D) undefined

Q5. `[.catch()]` `.catch(fn)` kab trigger hota hai?

- (A) Sirf `Promise.reject()` se
- (B) Sirf throw statement se
- (C) `reject()` ya `.then()` mein throw se — chain mein kisi bhi jagah error
- (D) Sirf network errors se

Q6. `[.finally()]` ★ `.finally()` ke baare mein kaunsa statement SAHI hai?

- (A) Return value next `.then()` ko pass hoti hai
- (B) Sirf success pe chalta hai
- (C) Hamesha chalta hai — chahe resolve ho ya reject, return value ignored
- (D) Error handling ke liye use hota hai

Q7. `[.then()]` `.then(onFulfilled, onRejected)` vs `.then(onFulfilled).catch(onRejected)` — difference?

- (A) Same hai bilkul
- (B) `.then(fn, fn)` mein `onRejected` sirf current promise ka error pakadta hai, `onFulfilled` ka nahi. `.catch()` dono pakadta hai
- (C) `.catch()` slow hota hai
- (D) No difference in behavior

Q8. [Chaining] ★ `.then()` mein return karna bhool gaye to next `.then()` ko kya milega?

- (A) Previous value
- (B) null
- (C) undefined
- (D) Error throw hogi

Q9. [Chaining] Promise chain mein error throw karne ke baad kya hota hai?

- (A) Chain rok jaati hai permanently
- (B) Nearest `.catch()` tak jump karta hai, uske baad chain continue
- (C) Process crash hota hai
- (D) Error silently ignore hoti hai

Q10. [Chaining] ★ `Promise.resolve('a').then(v => Promise.resolve('b')).then(v => console.log(v))` — output?

- (A) 'a'
- (B) 'b'
- (C) Promise object
- (D) undefined

Q11. [Promise.all] ★ `Promise.all([p1, p2, p3])` mein `p2` reject ho jaaye to kya hoga?

- (A) Sirf p2 ka error aayega, p1 aur p3 ka result milega
- (B) Turant reject hoga p2 ke error ke saath — p1, p3 ke results ignored
- (C) p2 dobara try hoga
- (D) undefined return hoga

Q12. [Promise.allSettled] Promise.allSettled() aur Promise.all() mein main difference?

- (A) allSettled faster hai
- (B) allSettled sab promises ke settle hone ka wait karta hai — kisi failure se stop nahi hota
- (C) all() zyada results deta hai
- (D) Koi farq nahi

Q13. [Promise.race] Promise.race([p1, p2, p3]) kya return karta hai?

- (A) Sabse pehle resolve hone wali promise ka result
- (B) Pehle SETTLE (resolve ya reject) hone wali promise ka result
- (C) Sab promises ka array
- (D) Sabse pehle reject hone wali ka result

Q14. [Promise.any] ★ Promise.any() aur Promise.race() mein difference?

- (A) Same hai dono
- (B) any() pehla FULFILLMENT return karta hai (rejections ignore), race() pehla SETTLEMENT
- (C) race() faster hai
- (D) any() sirf 2 promises accept karta hai

Q15. [Promise.all] Promise.all([]) — empty array pass karne par?

- (A) Pending rehta hai hamesha
- (B) Error throw hoti hai
- (C) Immediately resolve hota hai empty array [] ke saath
- (D) undefined return karta hai

Q16. [Promisification] ★ Promisification kya hai?

- (A) Promise ko callback mein convert karna
- (B) Callback-based function ko Promise-based function mein convert karna
- (C) Multiple promises ko combine karna
- (D) Async function banana

Q17. [Promisification] Node.js util.promisify() kis convention ke callbacks ko convert karta hai?

- (A) Success-first callbacks
- (B) Error-first (Node-style) callbacks: (err, result) => {}

- (C) Value-only callbacks
- (D) Event-based callbacks

Q18. [Promisification] ★ `const delay = ms => new Promise(res => setTimeout(res, ms))` — ye kya karta hai?

- (A) Error throw karta hai after ms
- (B) ms milliseconds baad resolve hone wali Promise return karta hai — async sleep!
- (C) ms milliseconds block karta hai
- (D) Timer create karta hai jo cancel ho sakta hai

Q19. [Error Handling] Unhandled Promise rejection kab hoti hai?

- (A) Hamesha jab `reject()` call ho
- (B) Jab rejected promise pe `.catch()` ya rejection handler na ho
- (C) Sirf browser mein hoti hai
- (D) `setTimeout` ke andar `reject()` call hone par

Q20. [Promise.allSettled] ★ `Promise.allSettled()` ka result kya format hota hai?

- (A) Values ka simple array
- (B) `{ status: 'fulfilled'|'rejected', value/reason }` objects ka array
- (C) Errors ka array
- (D) Promises ka array

Answer Key

Q1: (B)	Q2: (B)	Q3: (C)	Q4: (C)	Q5: (C)
Q6: (C)	Q7: (B)	Q8: (C)	Q9: (B)	Q10: (B)
Q11: (B)	Q12: (B)	Q13: (B)	Q14: (B)	Q15: (C)
Q16: (B)	Q17: (B)	Q18: (B)	Q19: (B)	Q20: (B)

Scoring Guide

20/20 (100%) — Excellent! Promises ke har corner clear hain. Day 8 (async/await) ready.

15-19 (75-95%) — Good! Chaining aur error flow wale questions dubara practice karo.

10-14 (50-70%) — .then()/catch() chaining dubara padhein + exercises run karo.

Below 10 (<50%) — Day 6 + Day 7 ek baar aur revise karo — async/await iske upar build hota hai.