

Rajalakshmi Engineering College

Name: Prince Rohith
Email: 240701399@rajalakshmi.edu.in
Roll no: 240701399
Phone: 6369941431
Branch: REC
Department: CSE - Section 5
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 7_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

John is developing a car loan calculator and has structured his program using two interfaces, Principal and InterestRate, defining methods for principal and interest rate retrieval.

The Loan class implements these interfaces, taking principal and annual interest rates as parameters. User input is solicited for these values, and the program ensures their validity before performing calculations. If input values are invalid (less than or equal to zero), an error message is displayed.

Note: Total interest = principal * interest rate * years

Input Format

The first line of input consists of a double value P, representing the principal.

The second line consists of a double value R, representing the annual interest rate.

The third line consists of an integer value N, representing the loan duration in years.

Output Format

If the input values are valid, print "Total interest paid: Rs. " followed by a double value, representing the total interest paid, rounded off to two decimal places.

If the input values are invalid (negative or zero values for principal, annual interest rate, or loan duration), print "Invalid input values!".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 20000.00

0.05

5

Output: Total interest paid: Rs.5000.00

Answer

```
import java.util.Scanner;
```

```
interface Principal {  
    double getPrincipal();  
}
```

```
interface InterestRate {  
    double getInterestRate();  
}
```

```
class Loan implements Principal, InterestRate {  
    private double principal;  
    private double interestRate;  
    public Loan(double principal, double interestRate) {  
        this.principal = principal;  
    }  
}
```

```

        this.interestRate = interestRate;
    }
    public double getPrincipal() {
        return principal;
    }

    public double getInterestRate() {
        return interestRate;
    }
    public double calculateTotalInterest(int years) {
        return principal * interestRate * years;
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        double carPrice = scanner.nextDouble();

        double annualInterestRate = scanner.nextDouble();

        int loanDuration = scanner.nextInt();

        if (carPrice <= 0 || annualInterestRate <= 0 || loanDuration <= 0) {
            System.out.println("Invalid input values!");
            return;
        }

        Loan carLoan = new Loan(carPrice, annualInterestRate);
        double totalInterest = carLoan.calculateTotalInterest(loanDuration);

        System.out.printf("Total interest paid: Rs.%.2f%n", totalInterest);
    }
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

Alex and Bob are designing a control system for household appliances,

and one of the appliances is a washing machine. You want to create a program to help them that models the washing machine as a motor and calculates its electricity consumption based on its capacity.

Define an interface named Motor with the following methods:

`void run()` `double consume(double capacity)`

Create a class called WashingMachine that implements the Motor interface.

In the WashingMachine class:

Implement the `run()` method to print "Washing machine is running." Implement a `consume()` method to print "Washing machine is consuming electricity." Implement the `consume(double capacity)` method to calculate the electricity consumption (in kWh) of the washing machine based on its capacity. The formula for electricity consumption is (capacity * 0.05).

Input Format

The input consists of a double value representing the capacity of the washing machine in kW.

Output Format

The first line of output prints "Washing machine is running."

The second line prints "Washing machine is consuming electricity."

The third line prints "Electricity consumption: X kWh" where X is a double value, rounded off to two decimal places, representing the electricity consumption.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 2.5

Output: Washing machine is running.

Washing machine is consuming electricity.

Electricity consumption: 0.13 kWh

Answer

```
import java.util.Scanner;

interface Motor {
    void run();
    double consume(double capacity);
}

class WashingMachine implements Motor {

    public void run() {
        System.out.println("Washing machine is running.");
    }

    public void consume() {
        System.out.println("Washing machine is consuming electricity.");
    }

    public double consume(double capacity) {
        return capacity * 0.05;
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        WashingMachine washingMachine = new WashingMachine();

        double capacity = scanner.nextDouble();

        washingMachine.run();
        washingMachine.consume();

        double consumption = washingMachine.consume(capacity);
        System.out.printf("Electricity consumption: %.2f kWh", consumption);

        scanner.close();
    }
}
```

Status : Correct

Marks : 10/10

3. Problem Statement:

Rathish is planning a road trip and needs a program to convert speeds between miles per hour (MPH) and kilometers per hour (KPH).

Create an interface, SpeedConverter, with a method convertSpeed(double mph). Implement the interface with MPHtoKPHConverter class, allowing Rathish to input MPH and receive the converted speed in KPH, rounded to two decimal points.

Formula: Speed in KPH = 1.60934 * Speed in MPH.

Input Format

The input consists of a single double-point number representing the speed in miles per hour (MPH).

Output Format

The output displays the converted speed (double-point number) in kilometers per hour (KPH) rounded off to two decimal points in the following format:

"Speed in KPH: <<converted speed>>".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1.0

Output: Speed in KPH: 1.61

Answer

```
import java.util.Scanner;

interface SpeedConverter {
    double convertSpeed(double mph);
}
```

```
class MPHtoKPHConverter implements SpeedConverter {
    public double convertSpeed(double mph) {
        return 1.60934 * mph;
    }
}
```

```

    }
}
class SpeedConversionApp {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        double speedInMPH = scanner.nextDouble();

        SpeedConverter converter = new MPHtoKPHConverter();

        double speedInKPH = converter.convertSpeed(speedInMPH);

        System.out.printf("Speed in KPH: %.2f\n", speedInKPH);

        scanner.close();
    }
}

```

Status : Correct

Marks : 10/10

4. Problem Statement:

Ray is developing a tax calculation program in Java. The program includes an interface named TaxCalculator with a method to calculate tax based on salary. The SimpleTaxCalculator class implements this interface and determines the tax to be paid based on the salary amount using progressive tax slabs.

Your task is to implement this system. The program first takes an integer T representing the number of test cases, followed by T salary values. For each salary, calculate the total tax to be paid based on the following progressive tax rules:

For the first 50,000 of salary, the tax rate is 5%. For the next 50,000 (i.e., from 50,001 to 1,00,000), the tax rate is 10%. For any amount above 1,00,000, the tax rate is 20%. (That is, only the amount above 1,00,000 is taxed at 20%.)

Example

Input

3

78000

110000

23000

Output

5300

9500

1150

Explanation

For Salary Rs. 78,000

Tax = $0.1 * (78,000 - 50,000) + 0.05 * 50,000 = 5,300$

For Salary Rs. 1,10,000

Tax = $0.2 * (110000 - 100000) + 0.1 * 50,000 + 0.05 * 50,000 = 9,500$

For Salary Rs. 23,000

Tax = $0.05 * 23,000 = 1,150$

Input Format

The first line of the input consists of an integer, T, representing the number of test cases.

The next T lines of the input consist of a single integer, representing the annual salary of an individual, separated by a line.

Output Format

The output displays the calculated tax as an integer for each test case, separated by a line.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 2

100

300

Output: 5

15

Answer

```
import java.util.Scanner;
```

```
interface TaxCalculator {  
    int calculateTax(int salary);  
}
```

```
class SimpleTaxCalculator implements TaxCalculator {  
    public int calculateTax(int salary) {  
        int tax = 0;  
  
        if (salary <= 50000) {  
            tax = (int)(salary * 0.05);  
        } else if (salary <= 100000) {  
            tax = (int)(50000 * 0.05 + (salary - 50000) * 0.10);  
        } else {  
            tax = (int)(50000 * 0.05 + 50000 * 0.10 + (salary - 100000) * 0.20);  
        }  
  
        return tax;  
    }  
}
```

```
class Main {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
        int T = scanner.nextInt();  
  
        TaxCalculator taxCalculator = new SimpleTaxCalculator();  
  
        for (int i = 0; i < T; i++) {  
            int salary = scanner.nextInt();  
            int tax = taxCalculator.calculateTax(salary);  
        }  
    }  
}
```

```
        System.out.println(tax);  
    }  
    scanner.close();  
}  
}
```

Status : Correct

Marks : 10/10