

Ss  
State-space  
Search

## Adversarial Search II: Alpha-Beta Pruning

CSE 415: Introduction to Artificial Intelligence  
University of Washington  
Spring, 2019

© S. Tanimoto and University of Washington, 2019

Ss  
State-space  
Search

## Alpha-Beta Pruning

Enhance minimax search with two extra values at each tree node that represent the interval in which the "solution" value must lie.

$$[\alpha, \beta]$$

Initialize the root's to  $[-\infty, \infty]$ .

Update these at the current node, when possible.

If any node gets  $\alpha \geq \beta$ , then it is "finished", so "prune off" any of its children that remain.

Univ. of Wash.

Adversarial Search II

2

Ss  
State-space  
Search

## Alpha-Beta Cutoffs

An **alpha** (beta) **cutoff** occurs at a Maximizing (minimizing) node when it is known that the maximizing (minimizing) player has a move that results in a value **alpha** (beta) and, subsequently, when an alternative to that move is explored, it is found that the alternative gives the opponent the option of moving to a lower (higher) valued position.

Any further exploration of the alternative can be canceled.


Univ. of Wash.

Adversarial Search II

3

Ss  
State-space  
Search

## Alpha-Beta Pruning




Univ. of Wash.

Adversarial Search II

4

Ss  
State-space  
Search

## Alpha-Beta Pruning




Univ. of Wash.

Adversarial Search II

5

Ss  
State-space  
Search







## Alpha-Beta Pruning















Univ. of Wash.

Adversarial Search II







6


















**Strategy to Increase the Number of Cutoffs**

At each non-leaf level, perform a static evaluation of all successors of a node and order them best-first before doing the recursive calls. If the best move was first, the tendency should be to get cutoffs when exploring the remaining ones.

Or, use **Iterative Deepening**, with ply limits increasing from, say 1 to 15. Use results of the last iteration to order moves in the next iteration.

In games like chess,  $\alpha$ - $\beta$  pruning typically allows searching ahead 2 times as deep. It tends to reduce the effective branching factor from  $d$  to approx.  $\sqrt{d}$ .

Univ. of Wash. Adversarial Search II 42

55  
State-space  
Search

### Strategy to Increase the Number of Cutoffs

At each non-leaf level, perform a static evaluation of all successors of a node and order them best-first before doing the recursive calls. If the best move was first, the tendency should be to get cutoffs when exploring the remaining ones.

Or, use **Iterative Deepening**, with ply limits increasing from, say 1 to 15. Use results of the last iteration to order moves in the next iteration.