

UML Class Diagram - Data Processor Pipeline

```
+-----+
| Processor |
+-----+
| - mode: ProcessingMode |
| - database: Database |
+-----+
| + configure(mode: ModeIdentifier,
|               db: DatabaseIdentifier): void |
| + process(data: Datapoint): void |
+-----+
```

↓ uses
v

```
+-----+
| <<interface>> |
| ProcessingMode |
+-----+
| + process(data: Datapoint,
|               db: Database): void |
+-----+
```

```
      ^      ^      ^
      |      |      |
+-----+ +-----+ +-----+
| DumpMode | | PassThrough | | ValidateMode |
+-----+ +-----+ +-----+
| +process() | | +process() | | +process() |
+-----+ +-----+ +-----+
```

Processor -----> Database

```
+-----+
| <<interface>> |
| Database |
+-----+
| + connect(): void |
| + insert(data: Datapoint): void |
| + validate(data: Datapoint): bool |
+-----+
```

```
      ^      ^      ^
      |      |      |
+-----+ +-----+ +-----+
| PostgresDB | | RedisDB | | ElasticDB |
+-----+ +-----+ +-----+
| +connect() | | +connect() | | +connect() |
| +insert() | | +insert() | | +insert() |
| +validate() | | +validate() | | +validate() |
+-----+ +-----+ +-----+
```

Existing Types:

- Datapoint
- ModeIdentifier (enum)
- DatabaseIdentifier (enum)