

Parallel Molecular Dynamics with a Time-Reversible Nose-Hoover Thermostat  
on CPUs and GPUs

1.0

Generated by Doxygen 1.8.2

Sat Jan 4 2014 19:08:05



# Contents

<b>1</b>	<b>CBEMDGPU</b>	<b>1</b>
<b>2</b>	<b>Hierarchical Index</b>	<b>3</b>
2.1	Class Hierarchy	3
<b>3</b>	<b>Class Index</b>	<b>5</b>
3.1	Class List	5
<b>4</b>	<b>Class Documentation</b>	<b>7</b>
4.1	atom Struct Reference	7
4.1.1	Detailed Description	7
4.2	cellList_cpu Class Reference	7
4.2.1	Detailed Description	8
4.2.2	Constructor & Destructor Documentation	8
4.2.2.1	cellList_cpu	8
4.2.3	Member Function Documentation	10
4.2.3.1	cell	10
4.2.3.2	checkUpdate	10
4.3	customException Class Reference	11
4.3.1	Detailed Description	12
4.4	float3 Struct Reference	12
4.4.1	Detailed Description	12
4.5	int3 Struct Reference	12
4.5.1	Detailed Description	13
4.6	integrator Class Reference	13
4.6.1	Detailed Description	13
4.6.2	Member Function Documentation	14
4.6.2.1	calcForce	14
4.7	nve Class Reference	15
4.7.1	Detailed Description	15
4.7.2	Member Function Documentation	16
4.7.2.1	calcForce	16

4.7.2.2	step	17
4.8	nvt_NH Class Reference	18
4.8.1	Detailed Description	19
4.8.2	Constructor & Destructor Documentation	19
4.8.2.1	nvt_NH	19
4.8.3	Member Function Documentation	20
4.8.3.1	calcForce	20
4.8.3.2	step	21
4.9	systemDefinition Class Reference	22
4.9.1	Detailed Description	24
4.9.2	Member Function Documentation	24
4.9.2.1	initRandom	24
4.9.2.2	initThermal	24
4.9.2.3	setPotential	26
4.9.2.4	writeSnapshot	26
4.10	systemProps Class Reference	26
4.10.1	Detailed Description	27
4.11	SystemTest Class Reference	27
4.11.1	Detailed Description	28

## Index

28

# Chapter 1

## CBEMDGPU

CBE MD on GPUs

by Nathan A. Mahynski, George A. Khoury, and Carmeline J. Dsilva

See [main.cpp](#) to set parameters which are documented by example in this file.

To compile the CPU version, type `$ make MD`

To compile the GPU version, type `$ make -f Makefile_cuda`

To compile tests, etc., type `$ make ${var}` where var is the suffix desired (see Makefile for details)



## Chapter 2

# Hierarchical Index

### 2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

atom . . . . .	7
cellList_cpu . . . . .	7
exception	
customException . . . . .	11
float3 . . . . .	12
int3 . . . . .	12
integrator . . . . .	13
nve . . . . .	15
nvt_NH . . . . .	18
systemDefinition . . . . .	22
systemProps . . . . .	26
Test	
SystemTest . . . . .	27





## Chapter 3

# Class Index

### 3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<a href="#">atom</a>	Structure of an atom . . . . .	7
<a href="#">cellList_cpu</a>	. . . . .	7
<a href="#">customException</a>	Error reporting . . . . .	11
<a href="#">float3</a>	3 floating point numbers, same as defined for GPUs . . . . .	12
<a href="#">int3</a>	3 integers, same as defined for GPUs . . . . .	12
<a href="#">integrator</a>	Base class for integrators such as NVT (Nose-Hoover) or NVE ensembles . . . . .	13
<a href="#">nve</a>	Integration scheme that preserves total energy of the system . . . . .	15
<a href="#">nvt_NH</a>	Uses Nose-Hoover integration method to thermostat a system (constant T rather than E) . . . . .	18
<a href="#">systemDefinition</a>	Contains all information pertaining to a system being simulated . . . . .	22
<a href="#">systemProps</a>	Holds all information about the CPU and GPU the simulation is being performed on . . . . .	26
<a href="#">SystemTest</a>	. . . . .	27



## Chapter 4

# Class Documentation

### 4.1 atom Struct Reference

Structure of an atom.

```
#include <dataTypes.h>
```

#### Public Attributes

- [float3 pos](#)  
*Position.*
- [float3 vel](#)  
*Velocity.*
- [float3 acc](#)  
*Acceleration.*

#### 4.1.1 Detailed Description

Structure of an atom.

Definition at line 28 of file `dataTypes.h`.

The documentation for this struct was generated from the following file:

- `/Users/nathanmahynski/Desktop/CBEMDGPU/dataTypes.h`

### 4.2 cellList\_cpu Class Reference

```
#include <cellList.h>
```

#### Public Member Functions

- [cellList\\_cpu](#) (const [float3](#) &box, const float rc, const float rs)
- void [checkUpdate](#) (const [systemDefinition](#) &sys)  
*Check if the neighbor list requires updating.*
- int [cell](#) (const [float3](#) &pos)  
*Calculate the cell in which a given coordinate is located.*
- int [head](#) (const int [cell](#)) const

- Return the first atom (aka 'head') of each cell.*
- `int list` (`const int index`) `const`  
*Iterates through a linked list of particles, returns the index of the next atom in line.*
- `std::vector< int > neighbors` (`const int cellID`) `const`  
*Returns the indices of a cell's neighboring cells.*

## Public Attributes

- `int3 nCells`  
*Number of cells in each direction.*

### 4.2.1 Detailed Description

Cell Lists

Date

11/19/13

Maintains a linked list to track cells on the CPU

Definition at line 38 of file `cellList.h`.

### 4.2.2 Constructor & Destructor Documentation

#### 4.2.2.1 `cellList_cpu::cellList_cpu ( const float3 & box, const float rc, const float rs )`

Cell Lists

Date

11/19/13

Initialize a cell list on the CPUs.

Parameters

<code>in</code>	<code>box</code>	Box size
<code>in</code>	<code>rc</code>	Cutoff radius
<code>in</code>	<code>rs</code>	Skin Radius

Definition at line 154 of file `cellList.cpp`.

References `nCells`.

```

{
    if (rc < 0.0) {
        throw customException("Cutoff radius must be > 0");
        return;
    }
    rc_ = rc;
    if (rs < 0.0) {
        throw customException("Skin radius must be > 0");
        return;
    }
    rs_ = rs;

    box_ = box;

    start_ = 1;
    lcell_.x = 1.01*(rc+rs);
    nCells.x = (int) floor (box.x/lcell_.x);

```

```

lcell_.x = (box.x/nCells.x);

lcell_.y = 1.01*(rc+rs);
nCells.y = (int) floor (box.y/lcell_.y);
lcell_.y = (box.y/nCells.y);

lcell_.z = 1.01*(rc+rs);
nCells.z = (int) floor (box.z/lcell_.z);
lcell_.z = (box.z/nCells.z);

if (lcell_.x <= (rc+rs) || lcell_.y <= (rc+rs) || lcell_.z < (rc+rs)) {
    throw customException("Cell width must exceed sum of
        cutoff and skin radius");
    return;
}

if (lcell_.x < 1) {
    throw customException ("Box dimension x too small
        relative to skin and cutoff radius to use cell lists");
    return;
}
if (lcell_.y < 1) {
    throw customException ("Box dimension y too small
        relative to skin and cutoff radius to use cell lists");
    return;
}
if (lcell_.z < 1) {
    throw customException ("Box dimension z too small
        relative to skin and cutoff radius to use cell lists");
    return;
}

if (nCells.x < 3 || nCells.y < 3 || nCells.z < 3) {
    throw customException("Must be able to have at least 3
        cells in each direction, change box size, skin, or cutoff radius");
    return;
}

try {
    head_.resize(nCells.x*nCells.y*nCells.z, -1);
} catch (std::exception &e) {
    std::cerr << e.what() << std::endl;
    throw customException ("Unable to initialize head for
        cell list");
    return;
}

// build neighbors for each cell
neighbor_.resize(nCells.x*nCells.y*nCells.z);
for (unsigned int cellID = 0; cellID < nCells.x*nCells.y*nCells
    .z; ++cellID) {
    const int zref = floor(cellID/(nCells.x*nCells.y));
    const int yref = floor((cellID - zref*(nCells.x*nCells.y))/
        nCells.y);
    const int xref = floor(cellID - zref*(nCells.x*nCells.y) -
        yref*nCells.x);
    for (int dx = -1; dx <= 1; ++dx) {
        int xcell = xref + dx;
        if (xcell >= nCells.x) xcell = 0;
        if (xcell < 0) xcell = nCells.x-1;
        for (int dy = -1; dy <= 1; ++dy) {
            int ycell = yref + dy;
            if (ycell >= nCells.y) ycell = 0;
            if (ycell < 0) ycell = nCells.y-1;
            for (int dz = -1; dz <= 1; ++dz) {
                int zcell = zref + dz;
                if (zcell >= nCells.z) zcell = 0;
                if (zcell < 0) zcell = nCells.z-1;
                const int cellID2 = xcell + ycell*nCells.x + zcell*(
                    nCells.x*nCells.y);
                neighbor_[cellID].push_back(cellID2);
            }
        }
    }
}

for (unsigned int cellID = 0; cellID < nCells.x*nCells.y*nCells
    .z; ++cellID) {
    if (neighbor_[cellID].size() != 27) {
        throw customException ("Cell list initial build
            failed to find 27 neighbors (including self)");
        return;
    }
}
}

```

### 4.2.3 Member Function Documentation

#### 4.2.3.1 `int cellList_cpu::cell ( const float3 & pos )`

Calculate the cell in which a given coordinate is located.

Calculates the cell (linear index of it) a position belongs to in a periodic box. The position does not need to be "inside" the box, boundary conditions are applied.

##### Parameters

<code>in</code>	<code>pos</code>	Position of atom
-----------------	------------------	------------------

##### Returns

`cell`

Definition at line 250 of file `cellList.cpp`.

References `nCells`.

Referenced by `checkUpdate()`, and `head()`.

```

{
    float3 inBox = pbc(pos, box_);
    const int x = (int) floor(inBox.x/lcell_.x);
    const int y = (int) floor(inBox.y/lcell_.y);
    const int z = (int) floor(inBox.z/lcell_.z);
    return x + y*nCells.x + z*nCells.x*nCells.y;
}

```

#### 4.2.3.2 `void cellList_cpu::checkUpdate ( const systemDefinition & sys )`

Check if the neighbor list requires updating.

Checks to see if the cell list needs to be updated and if so, rebuilds Uses linked list, so algorithm in O(N)

##### Parameters

<code>in</code>	<code>sys</code>	System definition
-----------------	------------------	-------------------

Definition at line 264 of file `cellList.cpp`.

References `systemDefinition::atoms`, `systemDefinition::box()`, `cell()`, and `systemDefinition::numAtoms()`.

Referenced by `integrator::calcForce()`.

```

{
    int build = 0;
    if (start_) {
        const int natoms = sys.numAtoms();
        try {
            list_.resize(natoms, -1);
        } catch (std::exception& e) {
            std::cerr << e.what() << std::endl;
            throw customException ("Unable to initialize list
for cell list");
            return;
        }
        try {
            posAtLastBuild_.resize(natoms);
        } catch (std::exception& e) {
            std::cerr << e.what() << std::endl;
            throw customException ("Unable to initialize
position list for cell list");
            return;
        }
        start_ = 0;
        build = 1;
    }
}

```

```

} else {
    // check max displacements
    float drMax1_ = 0.0;
    float drMax2_ = 0.0;
    float3 dummy;
    for (unsigned int i = 0; i < sys.numAtoms(); ++i) {
        const float dr2 = pbcDist2 (sys.atoms[i].pos,
posAtLastBuild_[i], dummy, sys.box());
        if (dr2 > drMax1_*drMax1_) {
            drMax2_ = drMax1_;
            drMax1_ = sqrt(dr2);
        } else if (dr2 > drMax2_*drMax2_) {
            drMax2_ = sqrt(dr2);
        }
    }
    if (drMax1_+drMax2_ > rs_) {
        build = 1;
    } else {
        build = 0;
    }
}

if (build) {
    if (sys.numAtoms() != list_.size()) {
        throw customException ("Number of atoms in
simulation has changed");
        return;
    }
    for (unsigned int i = 0; i < head_.size(); ++i) {
        head_[i] = -1;
    }
    for (unsigned int i = 0; i < sys.numAtoms(); ++i) {
        const int icell = cell(sys.atoms[i].pos);
        list_[i] = head_[icell];
        head_[icell] = i;
        posAtLastBuild_[i] = sys.atoms[i].pos;
    }
}

return;
}

```

The documentation for this class was generated from the following files:


- /Users/nathanmahynski/Desktop/CBEMDGPU/cellList.h
- /Users/nathanmahynski/Desktop/CBEMDGPU/cellList.cpp

## 4.3 customException Class Reference

Error reporting.

```
#include <common.h>
```

Inheritance diagram for customException:



### Public Member Functions

- const char \* [what](#) () const throw ()  
*Return a message pertaining to what went wrong.*
- [customException](#) (std::string m="custom exception occurred")  
*Instantiate the object with a user specified message.*

### 4.3.1 Detailed Description

Error reporting.

Common values, structures, etc.

Date

11/17/13

Definition at line 13 of file common.h.

The documentation for this class was generated from the following file:

- /Users/nathanmahynski/Desktop/CBEMDGPU/common.h

## 4.4 float3 Struct Reference

3 floating point numbers, same as defined for GPUs

```
#include <dataTypes.h>
```

### Public Attributes

- float **x**
- float **y**
- float **z**

### 4.4.1 Detailed Description

3 floating point numbers, same as defined for GPUs

Requisite 'optimal' data types.

Date

11/21/13

Definition at line 15 of file dataTypes.h.

The documentation for this struct was generated from the following file:

- /Users/nathanmahynski/Desktop/CBEMDGPU/dataTypes.h

## 4.5 int3 Struct Reference

3 integers, same as defined for GPUs

```
#include <dataTypes.h>
```

### Public Attributes

- int **x**
- int **y**
- int **z**



### 4.5.1 Detailed Description

3 integers, same as defined for GPUs

Definition at line 21 of file `dataTypes.h`.

The documentation for this struct was generated from the following file:


- `/Users/nathanmahynski/Desktop/CBEMDGPU/dataTypes.h`

## 4.6 integrator Class Reference

Base class for integrators such as NVT (Nose-Hoover) or NVE ensembles.

```
#include <integrator.h>
```

Inheritance diagram for `integrator`:



### Public Member Functions

- void `setTimestep` (const float dt)  
*Set the integrator timestep.*
- void `calcForce` (`systemDefinition` &sys)  
*Calculate the forces on each atom.*
- virtual void `step` (`systemDefinition` &sys)=0  
*Move the system forward a step in time.*

### Protected Attributes

- `cellList_cpu` cl\_  
*Cell or neighbor list.*
- `std::vector< float3 >` lastAccelerations\_  
*Acceleration of particles on previous timestep (useful for NVE integrator)*
- float dt\_  
*Timestep size.*
- int start\_  
*Flag for whether this object has been initialized or not.*

### 4.6.1 Detailed Description

Base class for integrators such as NVT (Nose-Hoover) or NVE ensembles.

Integrator

Date

11/17/13

Definition at line 14 of file `integrator.h`.

## 4.6.2 Member Function Documentation

### 4.6.2.1 void integrator::calcForce ( systemDefinition & sys )

Calculate the forces on each atom.

Integration

Date

11/19/13

Calculate the pairwise forces in a system. This also calculates the potential energy of a system. The kinetic energy is calculated during the verlet integration.

Parameters

in, out	sys	System definition
---------	-----	-------------------

Definition at line 22 of file integrator.cpp.

References systemDefinition::atoms, systemDefinition::box(), cellList\_cpu::checkUpdate(), cl\_, cellList\_cpu::head(), cellList\_cpu::list(), systemDefinition::mass(), cellList\_cpu::nCells, cellList\_cpu::neighbors(), systemDefinition::numAtoms(), systemDefinition::potential, systemDefinition::potentialArgs(), systemDefinition::rcut(), and systemDefinition::setPotE().

Referenced by nve::step(), and nvt\_NH::step().

```

{
// For cache coeherency allocate new space for calculations
float3 empty;
empty.x = 0; empty.y = 0; empty.z = 0;
std::vector <float3> acc (sys.numAtoms(), empty);
const float rc = sys.rcut();

// every time, check if the cell list needs to be updated first
cl_.checkUpdate(sys);

float Up = 0.0;
const float3 box = sys.box();
const float invMass = 1.0/sys.mass();

// traverse cell list and calculate total system potential energy
std::vector <float> args = sys.potentialArgs();
#pragma omp parallel for reduction(+:Up) schedule(dynamic, 1)
for (unsigned int cellID = 0; cellID < cl_.nCells.x*cl_.nCells
.y*cl_.nCells.z; ++cellID) {
    int atom1 = cl_.head(cellID);
    while (atom1 >= 0) {
        std::vector < int > neighbors = cl_.neighbors(cellID);
        for (int index = 0; index < neighbors.size(); ++index) {
            const int cellID2 = neighbors[index];
            int atom2 = cl_.head(cellID2);
            while (atom2 >= 0) {
                if (atom1 > atom2) {
                    float3 pf;
                    Up += sys.potential (&sys.atoms[atom1].
pos, &sys.atoms[atom2].pos, &pf, &box, &args[0], &rc);
                    acc[atom1].x -= pf.x*invMass;
                    acc[atom1].y -= pf.y*invMass;
                    acc[atom1].z -= pf.z*invMass;
                    acc[atom2].x += pf.x*invMass;
                    acc[atom2].y += pf.y*invMass;
                    acc[atom2].z += pf.z*invMass;
                }
                atom2 = cl_.list(atom2);
            }
        }
        atom1 = cl_.list(atom1);
    }
}

// save acceleration in array of atoms in system
#pragma omp parallel for
for (int i = 0; i < sys.numAtoms(); ++i) {
    sys.atoms[i].acc.x = -acc[i].x;
}
}

```

```

        sys.atoms[i].acc.y = -acc[i].y;
        sys.atoms[i].acc.z = -acc[i].z;
    }

    // set Up
    sys.setPotE(Up);
}

```

The documentation for this class was generated from the following files:


- /Users/nathanmahynski/Desktop/CBEMDGPU/integrator.h
- /Users/nathanmahynski/Desktop/CBEMDGPU/integrator.cpp

## 4.7 nve Class Reference

Integration scheme that preserves total energy of the system.

```
#include <nve.h>
```

Inheritance diagram for nve:



### Public Member Functions

- void [step](#) ([systemDefinition](#) &sys)
- void [setTimestep](#) (const float dt)  
*Set the integrator timestep.*
- void [calcForce](#) ([systemDefinition](#) &sys)  
*Calculate the forces on each atom.*

### Protected Attributes

- [cellList\\_cpu](#) [cl\\_](#)  
*Cell or neighbor list.*
- [std::vector< float3 > lastAccelerations\\_](#)  
*Acceleration of particles on previous timestep (useful for NVE integrator)*
- float [dt\\_](#)  
*Timestep size.*
- int [start\\_](#)  
*Flag for whether this object has been initialized or not.*

#### 4.7.1 Detailed Description

Integration scheme that preserves total energy of the system.

NVE integration.

Date

11/18/13

Definition at line 13 of file nve.h.

## 4.7.2 Member Function Documentation

### 4.7.2.1 void integrator::calcForce ( systemDefinition & sys ) [inherited]

Calculate the forces on each atom.

Integration

Date

11/19/13

Calculate the pairwise forces in a system. This also calculates the potential energy of a system. The kinetic energy is calculated during the verlet integration.

Parameters

in, out	sys	System definition
---------	-----	-------------------

Definition at line 22 of file integrator.cpp.

References systemDefinition::atoms, systemDefinition::box(), cellList\_cpu::checkUpdate(), integrator::cl\_, cellList\_cpu::head(), cellList\_cpu::list(), systemDefinition::mass(), cellList\_cpu::nCells, cellList\_cpu::neighbors(), systemDefinition::numAtoms(), systemDefinition::potential, systemDefinition::potentialArgs(), systemDefinition::rcut(), and systemDefinition::setPotE().

Referenced by step(), and nvt\_NH::step().

```

{
// For cache coeherency allocate new space for calculations
float3 empty;
empty.x = 0; empty.y = 0; empty.z = 0;
std::vector <float3> acc (sys.numAtoms(), empty);
const float rc = sys.rcut();

// every time, check if the cell list needs to be updated first
cl_.checkUpdate(sys);

float Up = 0.0;
const float3 box = sys.box();
const float invMass = 1.0/sys.mass();

// traverse cell list and calculate total system potential energy
std::vector <float> args = sys.potentialArgs();
#pragma omp parallel for reduction(+:Up) schedule(dynamic, 1)
for (unsigned int cellID = 0; cellID < cl_.nCells.x*cl_.nCells
.y*cl_.nCells.z; ++cellID) {
    int atom1 = cl_.head(cellID);
    while (atom1 >= 0) {
        std::vector <int > neighbors = cl_.neighbors(cellID);
        for (int index = 0; index < neighbors.size(); ++index) {
            const int cellID2 = neighbors[index];
            int atom2 = cl_.head(cellID2);
            while (atom2 >= 0) {
                if (atom1 > atom2) {
                    float3 pf;
                    Up += sys.potential (&sys.atoms[atom1].
pos, &sys.atoms[atom2].pos, &pf, &box, &args[0], &rc);
                    acc[atom1].x -= pf.x*invMass;
                    acc[atom1].y -= pf.y*invMass;
                    acc[atom1].z -= pf.z*invMass;
                    acc[atom2].x += pf.x*invMass;
                    acc[atom2].y += pf.y*invMass;
                    acc[atom2].z += pf.z*invMass;
                }
                atom2 = cl_.list(atom2);
            }
        }
        atom1 = cl_.list(atom1);
    }
}

// save acceleration in array of atoms in system
#pragma omp parallel for
for (int i = 0; i < sys.numAtoms(); ++i) {
    sys.atoms[i].acc.x = -acc[i].x;
}
}

```

```

        sys.atoms[i].acc.y = -acc[i].y;
        sys.atoms[i].acc.z = -acc[i].z;
    }

    // set Up
    sys.setPotE(Up);
}

```

#### 4.7.2.2 void nve::step ( systemDefinition & sys ) [virtual]

Do NVE integration

Date

11/18/13

Integrate a single timestep forward using Velocity-Verlet integration scheme. Update the positions and velocities using velocity verlet integration. This uses the accelerations stored on each atom. Creates a cell list the first time it is called.

Parameters

in, out	sys	System definition
---------	-----	-------------------

Implements [integrator](#).

Definition at line 22 of file nve.cpp.

References [systemDefinition::atoms](#), [integrator::calcForce\(\)](#), [integrator::dt\\_](#), [integrator::lastAccelerations\\_](#), [systemDefinition::mass\(\)](#), [systemDefinition::numAtoms\(\)](#), [systemDefinition::setKinE\(\)](#), [integrator::start\\_](#), and [systemDefinition::updateInstantTemp\(\)](#).

```

{
    if (start_) {
        try {
            lastAccelerations_.resize(sys.numAtoms())
        } catch (std::exception &e) {
            std::cerr << e.what() << std::endl;
            throw customException("Failed to initialize
            integrator due to memory constraints");
            return;
        }
        // calculate the forces initially (sets Up)
        calcForce (sys);

        // also get initial T
        #pragma omp parallel
        {
            #pragma omp for shared(sys.atoms) schedule(dynamic, OMP_CHUNK)
            for (unsigned int i = 0; i < sys.numAtoms(); ++i) {
                sys.atoms[i].vel.x += dt_*0.5*(lastAccelerations_
[i].x+sys.atoms[i].acc.x);
                sys.atoms[i].vel.y += dt_*0.5*(lastAccelerations_
[i].y+sys.atoms[i].acc.y);
                sys.atoms[i].vel.z += dt_*0.5*(lastAccelerations_
[i].z+sys.atoms[i].acc.z);
            }
        }

        float tmp = 0.0, Uk = 0.0;
        #pragma omp parallel
        {
            #pragma omp reduction(+:Uk) schedule(dynamic, OMP_CHUNK)
            for (unsigned int i = 0; i < sys.numAtoms(); ++i) {
                Uk += (sys.atoms[i].vel.x*sys.atoms[i].vel.x)+(sys.
atoms[i].vel.y*sys.atoms[i].vel.y)+(sys.atoms[i].vel.z*sys.atoms
[i].vel.z);
            }
        }
        Uk *= sys.mass();
        tmp = Uk;
        Uk *= 0.5;
        tmp /= (3.0*(sys.numAtoms()-1.0));
    }
}

```

```

        sys.updateInstantTemp(tmp);
        sys.setKinE(Uk);
        start_ = 0;
    }

    // update positions based on current positions
#pragma omp parallel
    {
        #pragma omp for shared(sys.atoms) schedule(dynamic, OMP_CHUNK)
        for (unsigned int i = 0; i < sys.numAtoms(); ++i) {
            sys.atoms[i].pos.x += dt_*(sys.atoms[i].vel.x+0.5*dt_
            *sys.atoms[i].acc.x);
            sys.atoms[i].pos.y += dt_*(sys.atoms[i].vel.y+0.5*dt_
            *sys.atoms[i].acc.y);
            sys.atoms[i].pos.z += dt_*(sys.atoms[i].vel.z+0.5*dt_
            *sys.atoms[i].acc.z);
            lastAccelerations_[i] = sys.atoms[i].acc;
        }
    }

    // calculate new forces at new positions
    calcForce (sys);

    // update velocities and get Uk and kinetic temperature
#pragma omp parallel
    {
        #pragma omp for shared(sys.atoms) schedule(dynamic, OMP_CHUNK)
        for (unsigned int i = 0; i < sys.numAtoms(); ++i) {
            sys.atoms[i].vel.x += dt_*0.5*(lastAccelerations_
            [i].x+sys.atoms[i].acc.x);
            sys.atoms[i].vel.y += dt_*0.5*(lastAccelerations_
            [i].y+sys.atoms[i].acc.y);
            sys.atoms[i].vel.z += dt_*0.5*(lastAccelerations_
            [i].z+sys.atoms[i].acc.z);
        }
    }

    // get temperature and kinetic energy
    float tmp = 0.0, Uk = 0.0;
#pragma omp parallel
    {
        #pragma omp reduction(+:Uk) schedule(dynamic, OMP_CHUNK)
        for (unsigned int i = 0; i < sys.numAtoms(); ++i) {
            Uk += (sys.atoms[i].vel.x*sys.atoms[i].vel.x)+(sys.atoms
            [i].vel.y*sys.atoms[i].vel.y)+(sys.atoms[i].vel.z*sys.atoms[i].
            vel.z);
        }
    }
    Uk *= sys.mass();
    tmp = Uk;
    Uk *= 0.5;
    tmp /= (3.0*(sys.numAtoms()-1.0));
    sys.updateInstantTemp(tmp);
    sys.setKinE(Uk);
}

```

The documentation for this class was generated from the following files:


- /Users/nathanmahynski/Desktop/CBEMDGPU/nve.h
- /Users/nathanmahynski/Desktop/CBEMDGPU/nve.cpp

## 4.8 nvt\_NH Class Reference

Uses Nose-Hover integration method to thermostat a system (constant T rather than E)

```
#include <nvt.h>
```

Inheritance diagram for nvt\_NH:



## Public Member Functions

- [nvt\\_NH](#) (const float Q)
- void [step](#) ([systemDefinition](#) &sys)
- void [setTimestep](#) (const float dt)  
*Set the integrator timestep.*
- void [calcForce](#) ([systemDefinition](#) &sys)  
*Calculate the forces on each atom.*

## Protected Attributes

- [cellList\\_cpu](#) [cl\\_](#)  
*Cell or neighbor list.*
- [std::vector< float3 >](#) [lastAccelerations\\_](#)  
*Acceleration of particles on previous timestep (useful for NVE integrator)*
- float [dt\\_](#)  
*Timestep size.*
- int [start\\_](#)  
*Flag for whether this object has been initialized or not.*

### 4.8.1 Detailed Description

Uses Nose-Hoover integration method to thermostat a system (constant T rather than E)  
NVT integration with Nose-Hoover thermostat.

#### Date

11/18/13

Definition at line 13 of file nvt.h.

### 4.8.2 Constructor & Destructor Documentation

#### 4.8.2.1 [nvt\\_NH::nvt\\_NH](#) ( const float Q )

Do NVT integration with Nose-Hoover thermostat.

#### Date

11/18/13

Initialize integrator

#### Parameters

<a href="#">in</a>	<a href="#">Q</a>	Thermal mass for thermostat
--------------------	-------------------	-----------------------------

Definition at line 20 of file nvt.cpp.

References [integrator::start\\_](#).

```

{
    Q_ = Q;
    gamma_ = 0.0;
    start_ = 1;
}
```

### 4.8.3 Member Function Documentation

#### 4.8.3.1 void integrator::calcForce ( systemDefinition & sys ) [inherited]

Calculate the forces on each atom.

Integration

Date

11/19/13

Calculate the pairwise forces in a system. This also calculates the potential energy of a system. The kinetic energy is calculated during the verlet integration.

Parameters

in, out	sys	System definition
---------	-----	-------------------

Definition at line 22 of file integrator.cpp.

References systemDefinition::atoms, systemDefinition::box(), cellList\_cpu::checkUpdate(), integrator::cl\_, cellList\_cpu::head(), cellList\_cpu::list(), systemDefinition::mass(), cellList\_cpu::nCells, cellList\_cpu::neighbors(), systemDefinition::numAtoms(), systemDefinition::potential, systemDefinition::potentialArgs(), systemDefinition::rcut(), and systemDefinition::setPotE().

Referenced by nve::step(), and step().

```

{
    // For cache coeherency allocate new space for calculations
    float3 empty;
    empty.x = 0; empty.y = 0; empty.z = 0;
    std::vector<float3> acc (sys.numAtoms(), empty);
    const float rc = sys.rcut();

    // every time, check if the cell list needs to be updated first
    cl_.checkUpdate(sys);

    float Up = 0.0;
    const float3 box = sys.box();
    const float invMass = 1.0/sys.mass();

    // traverse cell list and calculate total system potential energy
    std::vector<float> args = sys.potentialArgs();
    #pragma omp parallel for reduction(+:Up) schedule(dynamic, 1)
    for (unsigned int cellID = 0; cellID < cl_.nCells.x*cl_.nCells
        .y*cl_.nCells.z; ++cellID) {
        int atom1 = cl_.head(cellID);
        while (atom1 >= 0) {
            std::vector<int> neighbors = cl_.neighbors(cellID);
            for (int index = 0; index < neighbors.size(); ++index) {
                const int cellID2 = neighbors[index];
                int atom2 = cl_.head(cellID2);
                while (atom2 >= 0) {
                    if (atom1 > atom2) {
                        float3 pf;
                        Up += sys.potential (&sys.atoms[atom1].
pos, &sys.atoms[atom2].pos, &pf, &box, &args[0], &rc);
                        acc[atom1].x -= pf.x*invMass;
                        acc[atom1].y -= pf.y*invMass;
                        acc[atom1].z -= pf.z*invMass;
                        acc[atom2].x += pf.x*invMass;
                        acc[atom2].y += pf.y*invMass;
                        acc[atom2].z += pf.z*invMass;
                    }
                    atom2 = cl_.list(atom2);
                }
            }
            atom1 = cl_.list(atom1);
        }
    }

    // save acceleration in array of atoms in system
    #pragma omp parallel for
    for (int i = 0; i < sys.numAtoms(); ++i) {
        sys.atoms[i].acc.x = -acc[i].x;
    }
}

```



```

        sys.atoms[i].acc.y = -acc[i].y;
        sys.atoms[i].acc.z = -acc[i].z;
    }

    // set Up
    sys.setPotE(Up);
}

```

#### 4.8.3.2 void nvt\_NH::step ( systemDefinition & sys ) [virtual]

Integrate a single timestep forward using Velocity-Verlet integration scheme. This is NOT identical since some intermediate bookkeeping needs to be handled for thermostat. Creates a cell list the first time it is called.

##### Parameters

in, out	sys	System definition
---------	-----	-------------------

Implements [integrator](#).

Definition at line 32 of file nvt.cpp.

References [systemDefinition::atoms](#), [systemDefinition::box\(\)](#), [integrator::calcForce\(\)](#), [integrator::cl\\_](#), [integrator::dt\\_](#), [systemDefinition::instantT\(\)](#), [systemDefinition::mass\(\)](#), [systemDefinition::numAtoms\(\)](#), [systemDefinition::rcut\(\)](#), [systemDefinition::rskin\(\)](#), [systemDefinition::setKinE\(\)](#), [integrator::start\\_](#), [systemDefinition::targetT\(\)](#), and [systemDefinition::updateInstantTemp\(\)](#).

```

{
    int chunk = OMP_CHUNK;
    if (start_) {
        try {
            cellList_cpu tmpCL (sys.box(), sys.rcut(), sys.
            rskin());
            cl_ = tmpCL;
        } catch (std::exception &e) {
            std::cerr << e.what() << std::endl;
            throw customException("Failed to integrate on first
            step");
        }

        gamma_ = 0.0;
        for (unsigned int i = 0; i < sys.numAtoms(); ++i) {
            gamma_ += (sys.atoms[i].vel.x*sys.atoms[i].vel.x)+(sys.
            atoms[i].vel.y*sys.atoms[i].vel.y)+(sys.atoms[i].vel.z*sys.atoms
            [i].vel.z);
        }
        gamma_ -= (3.0*(sys.numAtoms()-1.0))*sys.instantT();
        gamma_ /= Q_;

        // get initial temperature
        calcForce(sys);
        float tmp=0.0, Uk = 0.0;
        #pragma omp parallel for reduction(+:Uk)
        for (unsigned int i = 0; i < sys.numAtoms(); ++i) {
            Uk += (sys.atoms[i].vel.x*sys.atoms[i].vel.x)+(sys.atoms
            [i].vel.y*sys.atoms[i].vel.y)+(sys.atoms[i].vel.z*sys.atoms[i].
            vel.z);
        }
        Uk *= sys.mass();
        tmp = Uk;
        Uk *= 0.5;
        tmp /= (3.0*(sys.numAtoms()-1.0));
        sys.updateInstantTemp(tmp);
        sys.setKinE(Uk);
        start_ = 0;
        gammadot_ = 0.0;
        gammadd_ = 0.0;
    }

    tau2_ = Q_/ ((3.0*(sys.numAtoms()-1.0))*sys.targetT());
    gammadd_ = 1/tau2_* (sys.instantT()/sys.targetT()-1);

    // (1) update thermostat velocity and thermostat position
    // velocity half-step
    gammadot_ += dt_*0.5*gammadd_;

    // position step
    gamma_ += gammadot_*dt_;
}

```

```

// (2) evolve particle velocities
#pragma omp parallel shared(sys)
{
    #pragma omp for schedule(dynamic,OMP_CHUNK)
    for (unsigned int i = 0; i < sys.numAtoms(); ++i) {
        sys.atoms[i].vel.x = sys.atoms[i].vel.x*exp(-gammadot_*
dt_*0.5) + 0.5*dt_*(sys.atoms[i].acc.x);
        sys.atoms[i].vel.y = sys.atoms[i].vel.y*exp(-gammadot_*
dt_*0.5) + 0.5*dt_*(sys.atoms[i].acc.y);
        sys.atoms[i].vel.z = sys.atoms[i].vel.z*exp(-gammadot_*
dt_*0.5) + 0.5*dt_*(sys.atoms[i].acc.z);
    }

    // (3) evolve particle positions
    #pragma omp for schedule(dynamic,OMP_CHUNK)
    for (unsigned int i = 0; i < sys.numAtoms(); ++i) {
        sys.atoms[i].pos.x += sys.atoms[i].vel.x*dt_;
        sys.atoms[i].pos.y += sys.atoms[i].vel.y*dt_;
        sys.atoms[i].pos.z += sys.atoms[i].vel.z*dt_;
    }
}

// (4) calc force
calcForce(sys);

// (5) evolve particle velocities
#pragma omp parallel shared(sys)
{
    #pragma omp for schedule(dynamic,OMP_CHUNK)
    for (unsigned int i = 0; i < sys.numAtoms(); ++i) {
        sys.atoms[i].vel.x = (sys.atoms[i].vel.x+sys.atoms[i].
acc.x*dt_*0.5)*exp(-gammadot_*dt_*0.5);
        sys.atoms[i].vel.y = (sys.atoms[i].vel.y+sys.atoms[i].
acc.y*dt_*0.5)*exp(-gammadot_*dt_*0.5);
        sys.atoms[i].vel.z = (sys.atoms[i].vel.z+sys.atoms[i].
acc.z*dt_*0.5)*exp(-gammadot_*dt_*0.5);
    }
}
float Uk = 0.0;
float tmp = 0.0;

#pragma omp parallel for reduction(+:Uk)
// get temperature and kinetic energy
for (unsigned int i = 0; i < sys.numAtoms(); ++i) {
    Uk += (sys.atoms[i].vel.x*sys.atoms[i].vel.x)+(sys.atoms
[i].vel.y*sys.atoms[i].vel.y)+(sys.atoms[i].vel.z*sys.atoms[i].
vel.z);
}

Uk *= sys.mass();
tmp = Uk;
Uk *= 0.5;
tmp /= (3.0*(sys.numAtoms()-1.0));
sys.updateInstantTemp(tmp);
sys.setKinE(Uk);

// (6) update thermostat velocity
gammadd_ = 1/tau2_*(sys.instantT()/sys.targetT()-1);
gammadot_ += dt_*0.5*gammadd_;
}

```

The documentation for this class was generated from the following files:

- /Users/nathanmahynski/Desktop/CBEMDGPU/nvt.h
- /Users/nathanmahynski/Desktop/CBEMDGPU/nvt.cpp

## 4.9 systemDefinition Class Reference

Contains all information pertaining to a system being simulated.

```
#include <system.h>
```

### Public Member Functions

- void [initRandom](#) (const int N, const int rngSeed)

- void `initThermal` (const int N, const float Tset, const int rngSeed, const float dx)
- void `updateInstantTemp` (const float T)  
*Manually set the instantaneous temperature.*
- void `setTemp` (const float T)  
*Assign the target temperature for NVT simulations.*
- void `setMass` (const float m)  
*Assign the mass of each particle.*
- void `setRcut` (const float rc)  
*Assign the cutoff radius of the pair potential.*
- void `setRskin` (const float rs)  
*Assign the skin radius as a buffer for the neighbor/cell lists.*
- void `setBox` (const float x, const float y, const float z)  
*Assign the simulation box size.*
- void `printBox` ()  
*Print the box dimesions to stdout.*
- float3 `box` () const  
*Report the box dimensions.*
- float `instantT` () const  
*Report the instantaneous temperature.*
- float `targetT` () const  
*Report the target temperature for NVT simulations.*
- float `mass` () const  
*Report the particle's mass.*
- float `PotE` () const  
*Report the instantaneous potential energy of the system.*
- void `setPotE` (const float Up)  
*Assign the potential energy.*
- void `setKinE` (const float Uk)  
*Assign the kinetic energy.*
- float `KinE` () const  
*Report the instantaneous kinetic energy of the system.*
- float `rskin` () const  
*Report the skin radius for the neighbor/cell lists.*
- float `rcut` () const  
*Report the pair potential function cutoff radius.*
- void `writeSnapshot` ()  
*Print a snapshot of the system.*
- int `numAtoms` () const  
*Report the pair potential function cutoff radius.*
- void `setPotentialArgs` (const std::vector< float > args)  
*Assign additional arguments to the pair potential function.*
- std::vector< float > `potentialArgs` ()  
*Report additional arguments to the pair potential function.*
- void `setPotential` (pointFunction\_t pp)  
*Assign pair potential function.*

## Public Attributes

- pointFunction\_t `potential`  
*Pointer to pair potential function.*
- std::vector< atom > `atoms`  
*Vector of atoms in the system.*

### 4.9.1 Detailed Description

Contains all information pertaining to a system being simulated.

System definition

Date

11/17/13

Definition at line 16 of file system.h.

### 4.9.2 Member Function Documentation

#### 4.9.2.1 void systemDefinition::initRandom ( const int *N*, const int *rngSeed* )

Initialize a system of *N* atoms with random velocities and positions on a lattice. Net momeentum is automatically initialized to zero.

Parameters

in	<i>N</i>	Number of atoms to create
in	<i>rngSeed</i>	Random number generator seed

Definition at line 31 of file system.cpp.

References atoms.

```

{
    float3 totMomentum;
    totMomentum.x = 0; totMomentum.y = 0; totMomentum.z = 0;

    if (N < 1) {
        throw customException ("N must be > 0");
        return;
    }

    srand(rngSeed);
    int chunk = OMP_CHUNK;
    unsigned int i;
    atoms.resize(N);
    #pragma omp parallel private(i)
    {
        #pragma omp for schedule(dynamic, chunk)
        for (i = 0; i < N; ++i) {
            if (i < N-1) {
                atoms[i].vel.x = (RNG-0.5);
                atoms[i].vel.y = (RNG-0.5);
                atoms[i].vel.z = (RNG-0.5);
                totMomentum.x += atoms[i].vel.x;
                totMomentum.y += atoms[i].vel.y;
                totMomentum.z += atoms[i].vel.z;
            } else {
                atoms[i].vel.x = -totMomentum.x;
                atoms[i].vel.y = -totMomentum.y;
                atoms[i].vel.z = -totMomentum.z;
            }
            atoms[i].pos.x = (RNG)*box_.x;
            atoms[i].pos.y = (RNG)*box_.y;
            atoms[i].pos.z = (RNG)*box_.z;
            atoms[i].acc.x = 0;
            atoms[i].acc.y = 0;
            atoms[i].acc.z = 0;
        }
    }
}

```

#### 4.9.2.2 void systemDefinition::initThermal ( const int *N*, const float *Tset*, const int *rngSeed*, const float *dx* )

Initialize a system of *N* atoms with random velocities to meet a desired temperature and positions on a lattice. Net momentum is automatically initialized to zero.

## Parameters

in	$N$	Number of atoms to create
in	<i>rngSeed</i>	Random number generator seed

Definition at line 77 of file system.cpp.

References atoms.

```

{
    float3 totMomentum;
    totMomentum.x = 0; totMomentum.y = 0; totMomentum.z = 0;

    if (N < 1) {
        throw customException ("N must be > 0");
        return;
    }

    srand(rngSeed);
    atoms.resize(N);

    // maxwell boltzmann distribution has mean 0 stdev kT/m in each dimension
    typedef std::tr1::linear_congruential<int, 16807, 0, (int)((1U << 31) -1 )
    > Myceng;
    Myceng eng;
    float sig = sqrt(Tset/mass_);
    std::tr1::normal_distribution<float> distribution(0.0,sig);
    float rannum = 0.0;
    float tmpT = 0.0;
    int index = 0;
    const int xs = floor(box_.x/dx);
    const int ys = floor(box_.y/dx);
    const int zs = floor(box_.z/dx);

    // initialize particle positions on a simple cubic lattice
    for (unsigned int x = 0; x < xs; ++x) {
        for (unsigned int y = 0; y < ys; ++y) {
            for (unsigned int z = 0; z < zs; ++z) {
                if (index < N) {
                    atoms[index].pos.x = x*dx;
                    atoms[index].pos.y = y*dx;
                    atoms[index].pos.z = z*dx;
                } else {
                    x = xs;
                    y = ys;
                    z = zs;
                    break;
                }
                index++;
            }
        }
    }

    for (unsigned int i = 0; i < N; ++i) {
        atoms[i].acc.x = 0;
        atoms[i].acc.y = 0;
        atoms[i].acc.z = 0;
        if (i < N-1) {
            atoms[i].vel.x = distribution(eng);
            atoms[i].vel.y = distribution(eng);
            atoms[i].vel.z = distribution(eng);
            totMomentum.x += atoms[i].vel.x;
            totMomentum.y += atoms[i].vel.y;
            totMomentum.z += atoms[i].vel.z;
        } else {
            atoms[i].vel.x = -totMomentum.x;
            atoms[i].vel.y = -totMomentum.y;
            atoms[i].vel.z = -totMomentum.z;
        }
        tmpT += (atoms[i].vel.x*atoms[i].vel.x + atoms[i].vel.y*
        atoms[i].vel.y + atoms[i].vel.z*atoms[i].vel.z);
    }

    // do velocity rescaling to get exactly the right T
    tmpT *= mass_/(3.0*(N-1));
    tmpT /= Tset;
    tmpT = 1.0/tmpT;
    for (unsigned int i = 0; i < N; i++) {
        atoms[i].vel.x = atoms[i].vel.x*sqrt(tmpT);
        atoms[i].vel.y = atoms[i].vel.y*sqrt(tmpT);
        atoms[i].vel.z = atoms[i].vel.z*sqrt(tmpT);
    }
}

```

#### 4.9.2.3 void systemDefinition::setPotential ( pointFunction\_t pp )

Assign pair potential function.

Sets the "host" pair potential function which also sets the GPU equivalent in integrator.cu if using CUDA.

##### Parameters

in	pp	Pointer to pair potential function
----	----	------------------------------------

Definition at line 20 of file system.cpp.

References potential.

```

    {
        potential = pp;
    }

```

#### 4.9.2.4 void systemDefinition::writeSnapshot ( )

Print a snapshot of the system.

Write instantaneous snapshot of the system to a file called "trajectory.xyz" This file is appended not overwritten consecutively.

Definition at line 154 of file system.cpp.

References atoms.

```

    {
        static int snapNum = 0;
        if (snapFile_ == NULL) {
            snapFile_ = fopen("trajectory.xyz", "w");
        }

        fprintf(snapFile_, "%d\nSnapshot #d\n", atoms.size(), snapNum);

        for (unsigned int i = 0; i < atoms.size(); ++i) {
            fprintf(snapFile_, "%s\t%g\t%g\t%g\n", "A", atoms[i].pos.x, atoms
                [i].pos.y, atoms[i].pos.z);
        }

        snapNum++;
    }

```

The documentation for this class was generated from the following files:

- /Users/nathanmahynski/Desktop/CBEMDGPU/system.h
- /Users/nathanmahynski/Desktop/CBEMDGPU/system.cpp

## 4.10 systemProps Class Reference

Holds all information about the CPU and GPU the simulation is being performed on.

```
#include <cudaHelper.h>
```

### Public Member Functions

- **systemProps** (std::string fname)
- void [displayAllProps](#) ()  
*Display cpu host and device (if using GPUs) properties.*
- \_\_host\_\_ void [displayCudaProps](#) ()

*Display the properties of the GPU being used.*

- void `displayHost` ()

*Display host name and other properties.*

- int `maxThreadsPerBlock` (const int devID)

*Returns the maximum number of threads per block on the GPU.*

- int `maxGridDimX` (const int devID)

*Returns the maximum number of blocks per grid on the GPU.*

- int `numDevices` () const

*Returns the number of GPUs found attached to the CPU.*

#### 4.10.1 Detailed Description

Holds all information about the CPU and GPU the simulation is being performed on.

Functions to assist in using CUDA and/or GPUs

Date

11/21/13


Definition at line 25 of file `cudaHelper.h`.

The documentation for this class was generated from the following file:

- `/Users/nathanmahynski/Desktop/CBEMDGPU/cudaHelper.h`

## 4.11 SystemTest Class Reference

Inheritance diagram for SystemTest:



#### Protected Member Functions

- virtual void `SetUp` ()

#### Protected Attributes

- `systemDefinition` a
- int `natoms`
- float `mass`
- float `L`
- float `eps`
- float `sigma`
- `nvt_NH` integrate

#### 4.11.1 Detailed Description

Definition at line 11 of file unittests.cpp.

The documentation for this class was generated from the following file:

- /Users/nathanmahynski/Desktop/CBEMDGPU/unittests.cpp