hesian

briefly

[called by: xspech.] [calls: packxi and dforce.]

contents

1	hesian		1
	1.0.1	construction of Hessian matrix	1
	1.0.2	construction of eigenvalues and eigenvectors	1

1.0.1 construction of Hessian matrix

- 1. The routine dforce is used to compute the derivatives, with respect to interface geometry, of the force imbalance harmonics, $[[p+B^2/2]]_j$, which may be considered to be the "physical" constraints, and if **Igeometry.eq.3** then also the derivatives of the "artificial" spectral constraints, $I_j \equiv (R_\theta X + Z_\theta Y)_j$.
- 2. The input variable Lconstraint determines how the enclosed fluxes, $\Delta \psi_t$ and $\Delta \psi_p$, and the helicity multiplier, μ , vary as the geometry is varied; see global and mp00ac for more details.

1.0.2 construction of eigenvalues and eigenvectors

- 1. If LHevalues .eq. T then the eigenvalues of the Hessian are computed using the NAG routine NAG: F02EBF.
- 2. If LHevectors.eq.T then the eigenvalues and the eigenvectors of the Hessian are computed.
- 3. Note that if **Igeometry.eq.3**, then the derivative-matrix also contains information regarding how the "artificial" spectral constraints vary with geometry; so, the eigenvalues and eigenvectors are not purely "physical".
- 4. The eigenvalues and eigenvectors (if required) are written to the file +.ext.GF.ev as follows:

```
open(hunit,file="."//trim(ext)//".GF.ev",status="unknown",form="unformatted")
write(hunit)NGdof,Ldvr,Ldvi
                                   ! integers; if only the eigenvalues were computed then Ldvr=Ldvi=1;
write(hunit)evalr(1:NGdof)
                                   ! reals
                                              ; real
                                                          part of eigenvalues;
write(hunit)evali(1:NGdof)
                                              ; imaginary part of eigenvalues;
                                   ! reals
write(hunit)evecr(1:NGdof,1:NGdof) ! reals
                                                          part of eigenvalues; only if Ldvr=NGdof;
                                              : real
write(hunit)eveci(1:NGdof,1:NGdof) ! reals
                                              ; imaginary part of eigenvalues; only if Ldvi=NGdof;
close(hunit)
```

5. The eigenvectors are saved in columns of evecr, eveci, as described by the NAG documentation for NAG: F02EBF.

hesian.h last modified on 8-07-26 10:29:21.62;

 ${\bf SPEC\ subroutines};$