

Technical drawing of a road cross-section showing a drainage ditch and a prefabricated mountain inlet. The drawing includes dimensions, elevations, and material specifications.

**Dimensions and Elevation:**

- Top width: 3.75m, 3.25m, 0.50m
- Bottom width: 0.98m, 0.40m, 10.75m, 0.15m, 0.60m, 0.15m, 0.86m
- Overall bottom width: 13.03m
- Elevations: 213.60, 213.64, 213.66, 214.80, 214.83
- Slopes: 22.5%, 1:1.75, 4%, 0.3%, 0.5%, 8%, 1:2.5, 40%

**Materials and Components:**

- BET. OBRUBNÍK 250/150 DO BET. LOŽE TL. 0,15m
- OCELOVÉ SVODIDLO JS/H1
- ROZPROSTŘENÍ REKULTIVAČNÍ ZEMINY TL. 0,15m + OSETÍ TRAVNÍM SEMENEM
- ŽB TROUBA DN 600 TZH-Q 600/2500, 6ks
- OBETONOVÁNÍ TRUB TL. 0,15m
- PODSYP ZE ŠTĚRKODRTĚ TL. 0,20m
- PATKA Z BETONU C20/25nXF3 0,4m x 0,8m
- DLAŽBA Z LOMOVÉHO KAMENE DO BETONU TL. 0,30m
- BETONOVÉ LOŽE TL. 0,15m
- PODSYP ZE ŠTĚRKODRTĚ TL. 0,15m
- PREFABRIKOVANÁ HORSKÁ VPUŠŤ, VIZ TZ

215.01

OBRUBNÍK

KORUNA

213.60

0.08 0.50 0.08

210.00

212.00

Diagram showing a cross-section of a road structure (ŘEZ A-A'). The structure is built into a trapezoidal embankment. The top surface is labeled 'VOZOVKA' (roadway) with an elevation of 214.83. Below the roadway is the 'TERÉN' (ground level). The structure consists of a central pipe section (ŽB TROUBA DN 600 TZH-Q 600/2500, 6ks) with an internal elevation of 213.65. The pipe is surrounded by concrete (OBETONOVÁNÍ TRUB TL. 0,15m) and is supported by a base of gravel (PODSYP ZE ŠTĚRKODRTĚ TL. 0,20m). The entire structure is filled with suitable non-frosty compacted soil (ZÁSYP VHODNOU NENAMRZAVOU ZEMINOU HUTNĚNOU PO VRSTVÁCH TL. MAX. 0,20m). The bottom of the structure is at an elevation of 213.00.