

VERTEX PAINTS

ISO 9001:2008 Certified Company

VERTEX® Clear-Stone Concrete Protective Sealer is a ready-to-use premium sealer that penetrates deeply to seal and protect painted, stained or bare concrete. It goes on pale clear white and dries to a clear finish, enhancing the natural character of your surface. Clear-Stone is a durable urethane-fortified sealer with low odor, and low VOCs, so it's easy to work with and safe for the environment. It has excellent chemical resistance and repels stains, making it ideal for pool decks, patios, porches, driveways, garages or anywhere you want to protect and beautify painted, stained or bare concrete. Available in satin or gloss sheens.

- Extends Life of Painted, Stained, Textured & Bare Concrete Surfaces
 - Resistant to Moisture, Salt, Chlorine, Oil & Hot Tire Pick-Up
 - Highly Durable Non-Yellowing Acrylic
- TYPICAL USES** ✓ Pool Decks ✓ Brick & Stone ✓ Patios & Porches ✓ Exposed Aggregate ✓ Driveways & Garages ✓ Slate & Slatillo ✓ Pavers & Stamped Concrete

Please take note that for the application of Vertex – Clear Stone system, proper and adequate substrate preparation is a must. Surfaces to be painted should be sufficiently dry and clean of loose materials, grease, wax or other contaminants such as pre-existing efflorescence and mildew growth. Also please avoid painting under conditions which are not conducive for paint application and drying process i.e. Extreme temperatures, high humidity or poor ventilation as these may impair film formation.

Technical Data	
Composition	PU-Alkyd resin, aromatic solvents, fungicide, UV-resistance and surfaces additives.
Appearance	Clear liquid.
Dry Thickness/Coat	15-20 microns.
Theoretical Coverage/Coat	16.3 square meters/litre (subject to surface profile and absorption).
Drying Times	Tough Dry : 15-20 minutes; Hard Dry : Below 3 hours; Recoating : After 4 hours.
Recommended System	2-3 coats (no primer required).
Cleaning/Thinning	Vertex Thinner TNo/1.

CLEAR-STONE

CONCRETE PROTECTIVE SEALER

SELLADOR PROTECTOR PARA HORMIGON

GLOSS

PROTECH PAINTED, STAINED & BARE CONCRETE
RESISTS MOISTURE, STAINS
UV, CHLORINE, SALES & HOT
TIRE PICKUP
HIGHLY DURABLE URETHANE
FORTIFIED NON-TELLOWING
ACRYLIC

No.607
Clear

Low VOC
Formula



First in India
to launch VOC FREE Colourants
Tinting Technology with Italtinto, ITALY



Manufactured by
Vertex Paint and Coatings Industries
13, Abdul Ghani Chowk, Mumbai-400025
Website : www.vertexpaints.in
Email : info@vertexpaints.com, vertexpaints@gmail.com
Customer Care Cell No. +91-8054324583

GLOSS FINISH

1 Lt. Net

VERTEX PAINTS

ISO 9001:2008 Certified Company

VERTEX® Clear-Stone Concrete Protective Sealer is a ready-to-use premium sealer that penetrates deeply to seal and protect painted, stained or bare concrete. It goes on pale clear white and dries to a clear finish, enhancing the natural character of your surface. Clear-Stone is a durable urethane-fortified sealer with low odor, and low VOCs, so it's easy to work with and safe for the environment. It has excellent chemical resistance and repels stains, making it ideal for pool decks, patios, porches, driveways, garages or anywhere you want to protect and beautify painted, stained or bare concrete. Available in satin or gloss sheens.

- Extends Life of Painted, Stained, Textured & Bare Concrete Surfaces
 - Resistant to Moisture, Salt, Chlorine, Oil & Hot Tire Pick-Up
 - Highly Durable Non-Yellowing Acrylic
- TYPICAL USES** ✓ Pool Decks ✓ Brick & Stone ✓ Patios & Porches ✓ Exposed Aggregate ✓ Driveways & Garages ✓ Slate & Slatillo ✓ Pavers & Stamped Concrete

Please take note that for the application of Vertex – Clear Stone system, proper and adequate substrate preparation is a must. Surfaces to be painted should be sufficiently dry and clean of loose materials, grease, wax or other contaminants such as pre-existing efflorescence and mildew growth. Also please avoid painting under conditions which are not conducive for paint application and drying process i.e. Extreme temperatures, high humidity or poor ventilation as these may impair film formation.

Technical Data	
Composition	PU-Alkyd resin, aromatic solvents, fungicide, UV-resistance and surfaces additives.
Appearance	Clear liquid.
Dry Thickness/Coat	15-20 microns.
Theoretical Coverage/Coat	16.3 square meters/litre (subject to surface profile and absorption).
Drying Times	Tough Dry : 15-20 minutes; Hard Dry : Below 3 hours; Recoating : After 4 hours.
Recommended System	2-3 coats (no primer required).
Cleaning/Thinning	Vertex Thinner TNo/1.

CLEAR-STONE

CONCRETE PROTECTIVE SEALER

SELLADOR PROTECTOR PARA HORMIGON

GLOSS

PROTECH PAINTED, STAINED & BARE CONCRETE
RESISTS MOISTURE, STAINS
UV, CHLORINE, SALES & HOT
TIRE PICKUP
HIGHLY DURABLE URETHANE
FORTIFIED NON-TELLOWING
ACRYLIC

No.607
Clear

Low VOC
Formula



First in India
to launch VOC FREE Colourants
Tinting Technology with Italtinto, ITALY



Manufactured by
Vertex Paint and Coatings Industries
13, Abdul Ghani Chowk, Mumbai-400025
Website : www.vertexpaints.in
Email : info@vertexpaints.com, vertexpaints@gmail.com
Customer Care Cell No. +91-8054324583

GLOSS FINISH

1 Lt. Net

VERTEX[®] Titanium ONE

SPECIALIST COATINGS FOR BUILDINGS

Andura Titanium ONE interior paints are available in an almost unlimited range of colours and 3 beautiful finishes: **Matt, Low Sheen & Satin** The Titanium ONE range is designed with 3 key benefits in mind:

Save time



20 min

Fast recoat times.
Typically between 20
60 minutes.



Environmentally friendly
water based formula
With virtually no odour or
VOCs.

Use less product



100%

Excellent opacity, self
priming and superior
coverage rates of up to
18m² per litre per coat.



Highly water resistant.
Our paint can be used in
living areas, bedrooms,
kitchens and bathrooms.

Protect for longer



100%

Extremely durable
protection for walls,
ceilings and wood.



Easy clean - Wipe or
scrub down walls with
confidence.

VERTEX[®]

SPECIALIST COATINGS FOR BUILDINGS

Titanium ONE

VERTEX [®] SPECIALIST COATINGS FOR BUILDINGS	Pure Acrylic Matt	Pure Acrylic Low Sheen	Pure Acrylic Satin
Suitability for substrates			
Interiors	*	*	*
Solid plaster	*	*	*
Fibrous plaster	*	*	*
Gypsum plaster	*	*	*
Plasterboard	*	*	*
Interior Timber	*	*	*
MDF	*	*	*
Concrete & Brick	*	*	*
Kitchen and Bathroom	*	*	*
PVC ¹	*	*	*
Exterior masonry	*	*	*
Exterior Timber	*	*	*
Timber cladding	*	*	*
Ferrous & non-ferrous metal ²	*	*	*
Key features			
Coverage	18m ² per litre per coat (dependent on porosity of substrate and background colour)		
Touch dry & recoat time	Between 20 - 60 minutes		
Opacity	Excellent		
Odour and VOCs	Virtually no odour or VOCs		
Cleaning ability	Extremely durable to washing and scrubbing		
Colours	All colours		
Formula	Environmentally friendly water based		

Key:
* Recommended
1 - 100% by volume

¹ Apply a proprietary metal primer prior to top coat

² Surfaces must be cleaned and sandblasted prior to
application of paint

³ All product claims are based on typical UK weather conditions and this correct and proper installation in accordance with relevant guidelines

1 Ltr Net