

```
[
/* ===== DB2 ===== */

{
  "zowe_command": "zowe db2 list databases",
  "category": "metadata",
  "command_family": "DB2",
  "subsystem": "DB2",
  "ibm_artifact": "DB2 System Catalog (SYSIBM.SYSDATABASE)",
  "operation": "READ",
  "access_pattern": "REST",
  "data_returned": "List of DB2 databases with owner and status",
  "response_format": "JSON",
  "intended_agent": "DiscoveryAgent",
  "constraints": "Read-only; no PII",
  "artifact_granularity": "SYSTEM",
  "data_scope": "SYSTEM",
  "idempotent": true,
  "produces_identifier": null,
  "execution_cost": "LOW",
  "confidence_level": 0.95
},
{
  "zowe_command": "zowe db2 list tables",
  "category": "metadata",
  "command_family": "DB2",
  "subsystem": "DB2",
  "ibm_artifact": "DB2 System Catalog (SYSTABLES)",
  "operation": "READ",
  "access_pattern": "REST",
  "data_returned": "List of tables within a DB2 database",

```

```

"response_format": "JSON",
"intended_agent": "DiscoveryAgent",
"constraints": "Read-only; metadata only",
"artifact_granularity": "TABLE",
"data_scope": "DATABASE",
"idempotent": true,
"produces_identifier": null,
"execution_cost": "LOW",
"confidence_level": 0.95
},
{
  "zowe_command": "zowe db2 execute query",
  "category": "database",
  "command_family": "DB2",
  "subsystem": "DB2",
  "ibm_artifact": "DB2 User Tables",
  "operation": "READ",
  "access_pattern": "REST",
  "data_returned": "Tabular query result set",
  "response_format": "JSON",
  "intended_agent": "IngestAgent",
  "constraints": "PII risk; SELECT-only queries allowed",
  "artifact_granularity": "TABLE",
  "data_scope": "TABLE",
  "idempotent": true,
  "produces_identifier": null,
  "execution_cost": "MEDIUM",
  "confidence_level": 0.95
},

```

```

/* ===== CICS ===== */

```

```
{
  "zowe_command": "zowe cics list regions",
  "category": "metadata",
  "command_family": "CICS",
  "subsystem": "CICS",
  "ibm_artifact": "CICS Region Control Table",
  "operation": "READ",
  "access_pattern": "REST",
  "data_returned": "List of CICS regions and runtime status",
  "response_format": "JSON",
  "intended_agent": "DiscoveryAgent",
  "constraints": "Read-only",
  "artifact_granularity": "SYSTEM",
  "data_scope": "SYSTEM",
  "idempotent": true,
  "produces_identifier": null,
  "execution_cost": "LOW",
  "confidence_level": 0.97
},
{
  "zowe_command": "zowe cics list programs",
  "category": "metadata",
  "command_family": "CICS",
  "subsystem": "CICS",
  "ibm_artifact": "CICS Program Definition Table (PCT)",
  "operation": "READ",
  "access_pattern": "REST",
  "data_returned": "List of CICS programs with enablement status",
  "response_format": "JSON",
  "intended_agent": "DiscoveryAgent",
```

```
"constraints": "Read-only",
"artifact_granularity": "PROGRAM",
"data_scope": "SYSTEM",
"idempotent": true,
"produces_identifier": null,
"execution_cost": "LOW",
"confidence_level": 0.97
},
{
  "zowe_command": "zowe cics list transactions",
  "category": "metadata",
  "command_family": "CICS",
  "subsystem": "CICS",
  "ibm_artifact": "CICS Transaction Definition Table",
  "operation": "READ",
  "access_pattern": "REST",
  "data_returned": "List of CICS transactions and status",
  "response_format": "JSON",
  "intended_agent": "MonitoringAgent",
  "constraints": "Read-only",
  "artifact_granularity": "TRANSACTION",
  "data_scope": "SYSTEM",
  "idempotent": true,
  "produces_identifier": null,
  "execution_cost": "LOW",
  "confidence_level": 0.96
},
{
  "zowe_command": "zowe cics start program",
  "category": "transaction",
  "command_family": "CICS",
```

```
"subsystem": "CICS",
"ibm_artifact": "CICS Program Control Definition",
"operation": "EXECUTE",
"access_pattern": "REST",
"data_returned": "Confirmation of program start",
"response_format": "JSON",
"intended_agent": "ControlAgent",
"constraints": "State-changing; admin privilege required",
"artifact_granularity": "PROGRAM",
"data_scope": "PROGRAM",
"idempotent": false,
"produces_identifier": null,
"execution_cost": "MEDIUM",
"confidence_level": 0.90
```

```
},
```

```
{
```

```
"zowe_command": "zowe cics stop program",
"category": "transaction",
"command_family": "CICS",
"subsystem": "CICS",
"ibm_artifact": "CICS Program Control Definition",
"operation": "EXECUTE",
"access_pattern": "REST",
"data_returned": "Confirmation of program stop",
"response_format": "JSON",
"intended_agent": "ControlAgent",
"constraints": "State-changing; admin privilege required",
"artifact_granularity": "PROGRAM",
"data_scope": "PROGRAM",
"idempotent": false,
"produces_identifier": null,
```

```
"execution_cost": "MEDIUM",
"confidence_level": 0.90
},

/* ===== IMS ===== */

{
  "zowe_command": "zowe ims list regions",
  "category": "metadata",
  "command_family": "IMS",
  "subsystem": "IMS",
  "ibm_artifact": "IMS Region Definition",
  "operation": "READ",
  "access_pattern": "REST",
  "data_returned": "List of IMS regions",
  "response_format": "JSON",
  "intended_agent": "DiscoveryAgent",
  "constraints": "Read-only",
  "artifact_granularity": "SYSTEM",
  "data_scope": "SYSTEM",
  "idempotent": true,
  "produces_identifier": null,
  "execution_cost": "LOW",
  "confidence_level": 0.96
},
{
  "zowe_command": "zowe ims list transactions",
  "category": "metadata",
  "command_family": "IMS",
  "subsystem": "IMS",
  "ibm_artifact": "IMS Transaction Definition Table",
```

```
"operation": "READ",
"access_pattern": "REST",
"data_returned": "List of IMS transactions and status",
"response_format": "JSON",
"intended_agent": "MonitoringAgent",
"constraints": "Read-only",
"artifact_granularity": "TRANSACTION",
"data_scope": "SYSTEM",
"idempotent": true,
"produces_identifier": null,
"execution_cost": "LOW",
"confidence_level": 0.96
},
{
  "zowe_command": "zowe ims start transaction",
  "category": "transaction",
  "command_family": "IMS",
  "subsystem": "IMS",
  "ibm_artifact": "IMS Transaction Control Block",
  "operation": "EXECUTE",
  "access_pattern": "REST",
  "data_returned": "Confirmation of transaction start",
  "response_format": "JSON",
  "intended_agent": "ControlAgent",
  "constraints": "State-changing; high privilege required",
  "artifact_granularity": "TRANSACTION",
  "data_scope": "TRANSACTION",
  "idempotent": false,
  "produces_identifier": "transactionId",
  "execution_cost": "HIGH",
  "confidence_level": 0.90
```

```
,  
{  
  "zowe_command": "zowe ims stop transaction",  
  "category": "transaction",  
  "command_family": "IMS",  
  "subsystem": "IMS",  
  "ibm_artifact": "IMS Transaction Control Block",  
  "operation": "EXECUTE",  
  "access_pattern": "REST",  
  "data_returned": "Confirmation of transaction stop",  
  "response_format": "JSON",  
  "intended_agent": "ControlAgent",  
  "constraints": "State-changing; high privilege required",  
  "artifact_granularity": "TRANSACTION",  
  "data_scope": "TRANSACTION",  
  "idempotent": false,  
  "produces_identifier": "transactionId",  
  "execution_cost": "HIGH",  
  "confidence_level": 0.90  
}  
]
```