

##RAML 1.0

title: Example Flights API

types:

ExampleFlight: **!include**

/exchange_modules/68ef9520-24e9-4cf2-b2f5-620025690913/training-Example-flight-data-type/1.0.1/ExampleFlightDataType.raml

traits:

client-id-required:

headers:

client id:

type: string

client secret:

type: string

responses:

401:

description: Unauthorized, The client id or client secret are not valid or the client does not have access.

429:

description: The client used all of its request quota for the current period.

500:

description: An error occurred, see the specific message (Only if it is a WSDL endpoint).

503:

description: Contracts Information Unreachable.

/flights:

is: **[client-id-required]**

get:

queryParameters:

destination:

required: false

enum:

- DEL

- CCU

- BOM

responses:

200:

body:

application/json:

type: ExampleFlight[]

examples:

output: **!include**

/exchange_modules/68ef9520-24e9-4cf2-b2f5-620025690913/training-Example-flights-example/1.0.1/ExampleFlightsExample.raml

post:

body:

application/json:

type: ExampleFlight
examples:
input: !include /examples/ExampleFlightNoIDExample.raml
responses:
201:
body:
application/json:
example:
message: Flight added (but not really) - A dummy response

/{ID}:
is: [client-id-required]
get:
responses:
200:
body:
application/json:
type: ExampleFlight
examples:
output: !include /examples/ExampleFlightExample.raml
delete:
responses:
200:
body:
application/json:
example:
message: Flight deleted (but not really) - A dummy response
put:
body:
application/json:
type: ExampleFlight
examples:
input: !include examples/ExampleFlightNoIDExample.raml
responses:
200:
body:
application/json:
example:
message: Flight updated (but not really) - A dummy response