

# eRTMAC-NWIS Synthetic Drilling Report

## Daily Drilling Report — Well W105

**Field:** Demo North Field  
**Location:** Synthetic Block A  
**Well ID:** W105  
**Total Depth:** 3010 m  
**Primary Formation:** Barail Formation

### Drilling Parameters

| Parameter      | Recorded value |
|----------------|----------------|
| Average ROP    | 16.2 m/hr      |
| Mud Weight     | 1.19 SG        |
| Average Torque | 12.0 kN·m      |
| Maximum Torque | 16.0 kN·m      |
| Pump Rate      | 1900 L/min     |
| ECD            | 1.25 SG        |

### Historical Drilling Events

- At 2580 m MD, a 3 m³/hr increase in mud losses was recorded for approximately 25 minutes.
- At 2630 m MD, a transient torque spike reached 16 kN·m.
- At 2642 m MD, drag increased while pulling out of hole.
- The well was circulated at 1900 L/min before drilling resumed.

### Operational Conclusions

- Historical instability was concentrated between approximately 2580 and 2642 m MD.
- Mud-loss and torque-related events occurred in the same depth interval.

**Prototype notice:** This synthetic report is created only for testing the NWIS RAG pipeline. It is not an actual Oil India Limited operational record and must not be used for real drilling decisions.