

# eRTMAC-NWIS Synthetic Drilling Report

## Daily Drilling Report — Well W104

**Field:** Demo North Field  
**Location:** Synthetic Block A  
**Well ID:** W104  
**Total Depth:** 2850 m  
**Primary Formation:** Barail Formation

### Drilling Parameters

| Parameter      | Recorded value |
|----------------|----------------|
| Average ROP    | 17.5 m/hr      |
| Mud Weight     | 1.18 SG        |
| Average Torque | 11.2 kN·m      |
| Maximum Torque | 14.0 kN·m      |
| Pump Rate      | 1850 L/min     |
| ECD            | 1.23 SG        |

### Historical Drilling Events

- At 2410 m MD, partial mud loss was observed at an estimated 4–6 m³/hr.
- At 2465 m MD, torque increased from 9 kN·m to 14 kN·m during a connection.
- A short wiper trip was performed from 2470 m to 2380 m MD.
- Mud weight was increased from 1.16 SG to 1.18 SG after the mud-loss event.

### Operational Conclusions

- The interval around 2410–2470 m MD should be treated as a historical problem zone in this synthetic dataset.
- The main recorded events were partial mud loss and a torque spike.

**Prototype notice:** This synthetic report is created only for testing the NWIS RAG pipeline. It is not an actual Oil India Limited operational record and must not be used for real drilling decisions.