ARYA QUADRUPED ROBOT
MECHANICAL & HARDWARE INVENTORY STATUS

S.No.	Component	BOM Qty	Status	Use Category	Remarks
1	Upper Chassis / Upper Plate	1	To be printed	A – Current Project	250×150×5 mm; Nylon 101; 199.69 g; main structural chassis.
2	Lower Chassis / Lower Plate	1	To be printed	A – Current Project	250×150×3 mm; Nylon 101; 140 g.
3	Electronics / Mounting Plate	1	To be printed	A – Current Project	250×150×30 mm; Nylon 101; 109.2 g; physical plate only.
4	Hip Servo Bracket	4	To be printed	A – Current Project	4 required for hip joints; servo envelope ≈40×28×34 mm; Nylon 101.
5	Thigh / Upper Leg Link	4	To be printed	A – Current Project	73×15×6 mm; Nylon 101; 14.56 g each.
6	Knee Servo Bracket	4	To be printed	A – Current Project	4 required for knee joints; servo envelope ≈35×28×34 mm; Nylon 101.
7	Shin / Lower Leg Link	4	To be printed	A – Current Project	73×15×6 mm; Nylon 101; 4.97 g each.
8	Lower Joint Support	4	Available	A – Current Project	Lower joint support; Nylon 101.
9	Lower Joint Connection	4	Available	A – Current Project	Lower joint connection; Nylon 101.
10	Ground-Contact / Foot Component	4	To be printed	A – Current Project	Rubber foot; radius 25 mm, height 6 mm; ≈2.54 g each.
11	Foot Connector	4	To be printed	A – Current Project	Radius 12 mm, height 16 mm; Nylon 101; ≈0.37 g each.
12	Battery Tray	1	To be printed	A – Current Project	110×40×28 mm; Nylon 101; ≈37.12 g.
13	Camera Mount	1	To be printed	A – Current Project	50×35×29 mm; Nylon 101; ≈15.53 g.
14	IMU Holder	1	To be printed	A – Current Project	45×45×11 mm; Nylon 101; ≈18.75 g.
15	Servo Horn	8	To be printed	Mechanical Accessory	25T spline aluminium; 8 required for 8 servos.
16	Servo Mounting Screw Set	8	To be printed	Mechanical Hardware	Servo-specific mounting screws; final size follows selected servo.
17	Joint Bearings	8	To be verified	Mechanical Hardware	Ball bearings; final part number and ID×OD×width from released CAD.
18	M3 Socket Head Cap Screw	4	Available	Fasteners	ISO 4762; M3×30 mm.
19	M3 Socket Head Cap Screw	36	Available	Fasteners	ISO 4762; M3×8 mm.
20	M3 Socket Head Cap Screw	4	Available	Fasteners	ISO 4762; M3×12 mm.
21	M3 Hex Nut	44	Available	Fasteners	ISO 4032; M3.
22	M6 Clevis Pin	8	Available	Fasteners	ISO 2341; M6×30 mm.
23	M6 Plain Washer	8	Available	Fasteners	ISO 7089; M6.
24	M2 Hex Screw	8	Available	Fasteners	ISO 4017; M2×8 mm.
25	M2 Hex Nut	8	Available	Fasteners	M2.
26	M6 Socket Head Cap Screw	4	Available	Fasteners	ISO 4762; M6×10 mm.
27	Heat-Set Threaded Insert	20	To be verified	Mechanical Hardware	Brass M3 insert; planning quantity, reconcile with CAD.
28	Electronics Standoff / Spacer	8	To be verified	Mechanical Hardware	M3-compatible; final height from mounting CAD.
29	XT60 Connector Set	1	To be verified	Power Hardware	Physical connector pair; electronics excluded.
30	JST-XH Balance Extension	1	To be verified	Power Hardware	3S balance extension; final length to suit assembly.