Started on	Monday, 5 October 2026, 7:27 PM
State	Finished
Completed on	Monday, 5 October 2026, 7:31 PM
Time taken	4 mins 18 secs

Question 1 | Complete Marked out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}


print(set1)
```

a. It will throw an error as there are two 0 while creating the set.

b. {9}

c. {0,0,9}

d. {0,9}

Question 2 | Complete Marked out of 1.00

Which of the following options will not result in an error when performed on tuples in Python where tupl=(5,2,7,0,3)?

a. tupl.append(2)

b. tupl.sort()

c. tupl1=tupl+tupl

d. tupl[1]=2

Question 3 | Complete Marked out of 1.00

What will be the output of following Python code?

```
list1=[1,3,4,2]

x=list1.pop(2)

print(set([x]))
```

a. {1,3,4}

b. {2}

c. {1,3,2}

d. {4}

Question 4 | Complete Marked out of 1.00

Which of the following is a Python tuple?

a. ("Wonder")

b. {1,3,8,9,41}

c. [1,2,3,4]

d. (1,4,5,6,7)

Question 5 | Complete Marked out of 1.00

What is the output of the following code

```
aSet = {1, 'rec', ('cse', 'ece'), True}
print(aSet)
```

a. {‘rec’, True, (‘cse’, ‘ece’)}

b. {‘rec’, 1, (‘cse’, ‘ece’),True}

c. Error

d. {‘rec’, 1, (‘cse’, ‘ece’)}

Question 6 | Complete Marked out of 1.00

Find the output of the given Python program?

```
t1 = (1,2,3,(4,5))
t2 = (3,2,1,(4,5))
print(t1>t2)
```

a. Error
b. False
c. True
d. Error

Question 7 | Complete Marked out of 1.00

Find the output of the given Python program?

t = (11, 3)

x = 3 * t

print(x)

a. (11,3)(11,3)(11,3)
b. (11,3,11,11,3,11,11,11,3)
c. (11, 3, 11, 3, 11, 3)
d. [11,11,11,3,3,3]

Question 8 | Complete Marked out of 1.00

What will be the output of the below Python code?

t1=(55,12,78,64,25)

t1.pop(12)

print(tuple1)

a. Error
b. 12
c. (12)
d. (55,78,64,25)

Question 9 | Complete Marked out of 1.00

Find the output of the given Python program?

```
>>>t = (1, 2, 4, 3, 8, 9)
>>>[t[i] for i in range(0, len(t), 2)]
```

a. [1, 2, 4, 3, 8, 9]
b. (1, 4, 8)
c. [1, 4, 8]
d. [2, 3, 9]

Question 10 | Complete Marked out of 1.00

What is printed when the following code is run?

```
tup = ('30', '3', '2', '8')
print(sorted(tup,reverse = True))
```

a. ['2', '3', '30', '8']
b. ['30', '8', '3', '2']
c. ['8', '30', '3', '2']
d. ['2', '3', '8', '30']

Question 11 | Complete Marked out of 1.00

What is the output of the following

```
set1 = {1, 2, 3, 4, 5}
set2 = {6, 7, 1, 3, 4, 8, 2, 5}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. False
True

b. True
True

c. False
False

d. True
False

Question 12 | Complete Marked out of 1.00

Select which is true for Python tuple?

a. We can change the tuple once created

b. A tuple is unordered

c. None of these

d. A tuple maintains the order of items

Question 13 | Complete Marked out of 1.00

Which of the following options will produce the same output?

```
t = (15, 83, 21, 49, 60,45,52,85,100)
# options i, ii, iii, or iv
print(t[:-1])
print(t[0:5])
print(t[0:8])
print(t[-7:])
```

a. iii,iv

b. ii,iv

c. i,iii

d. i,ii

Question 14 | Complete Marked out of 1.00

If a=(15,16,17,18,19,25), then a[1:-1] will be

Note :

a=(15,16,17,18,19,25)

print((a[1:-1]))

a. (16,17,18)

b. (16,17,18,19)

c. (25,19,18,17)

d. Error

Question 15 | Complete Marked out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

b. TypeError: update() doesn't allow list as a argument.

c. Name Error

d. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'}