Started on	Saturday, 10 October 2026, 6:35 PM
State	Finished
Completed on	Saturday, 10 October 2026, 6:42 PM
Time taken	6 mins 58 secs

Question 1 | Complete Marked out of 1.00

What is the output of the following code?

```
f = open("test.txt", "w")
f.write("Hello, world!")
f.close()
f = open("test.txt", "r")
print(f.read())
f.close()
```

a. An error is raised

b. world

c. Hello

d. Hello, world!

Question 2 | Complete Marked out of 1.00

What does the following code do?

fo = open("foo.txt", "w")

a. Opens a file in binary mode

b. Creates a new file for writing

c. Opens an existing file in read mode

d. Appends to an existing file

Question 3 | Complete Marked out of 1.00

Which of the following modes opens a file for writing in binary format?

a. wb

b. r+

c. w

d. rb

Question 4 | Complete Marked out of 1.00

Default EOL character of text file in python is ,

- a. ,
- b. \t
- c. \n
- d. space

Question 5 | Complete Marked out of 1.00

What is the default mode in which the open() function opens a file?

- a. Binary
- b. Write
- c. Read
- d. Append

Question 6 | Complete Marked out of 1.00

Select the correct method to write a list of lines to a file

- a. write(list)
- b. None of the mentioned
- c. writelist(list)
- d. writelines(list)

Question 7 | Complete Marked out of 1.00

What does the mode attribute of a file object indicate?

- a. The name of the file
- b. The access mode in which the file was opened
- c. The size of the file
- d. The current position of the file cursor

Question 8 | Complete Marked out of 1.00

What is the purpose of the with statement in Python file handling?

- a. To delete a file
- b. To write data to a file
- c. To automatically close the file after its suite finishes
- d. To read data from a file

Question 9 | Complete Marked out of 1.00

What happens if you try to open a file in read mode ('r') that does not exist?

- a. A new file is created
- b. An empty file object is returned
- c. An error is raised
- d. The operation is ignored

Question 10 | Complete Marked out of 1.00

Which method is used to read file line by line

- a. readline()
- b. line()
- c. readlines(1)
- d. read(1)

Question 11 | Complete Marked out of 1.00

What does the seek() method do in file handling?

- a. Deletes the file
- b. Moves the file cursor to the specified position
- c. Reads the file line by line
- d. Writes data to the file

Question 12 | Complete Marked out of 1.00

What happens if you try to open a file in write mode ('w') and the file already exists?

- a. It raises an error
- b. It does nothing
- c. It clears the old data and starts fresh
- d. It appends data to the file

Question 13 | Complete Marked out of 1.00

Which method is used to sets the position of a file pointer

- a. tell()
- b. ftell()
- c. seek()
- d. fseek()

Question 14 | Complete Marked out of 1.00

If the file is opened in write mode and already exists, it truncates the existing content and places the filehandle at the beginning of the file.

Select one:

- True
- False

Question 15 | Complete Marked out of 1.00

The readlines() method returns _____

a. a list of integers

b. a list of lines

c. str

d. a list of single characters