

Precedence Group	Operator	Description	Associativity (Binding Direction)
Highest	(expressions...), [expressions...], {key: value...}, 'string', variable	Parentheses for grouping, list/dict/set displays, literal constants	N/A (Atomic)
1	x[index], x[index:index], x(arguments...), x.attribute	Subscription, slicing, function call, attribute reference	Left-to-Right
2	await	Await expression	N/A (Unary)
3	**	Exponentiation	Right-to-Left
4	+x, -x, ~x	Unary positive, unary negative, bitwise NOT	N/A (Unary)
5	*, /, //, %	Multiplication, division, floor division, modulo	Left-to-Right
6	+, -	Addition and subtraction	Left-to-Right
7	<<, >>	Bitwise shifts (left and right)	Left-to-Right
8	&	Bitwise AND	Left-to-Right
9	^	Bitwise XOR	Left-to-Right
10	~	~	Bitwise OR
11	in, not in, is, is not, <, <=, >, >=, !=, ==	Comparisons, identity, and membership tests	Left-to-Right (Chaining Allowed)
12	not	Boolean NOT	N/A (Unary)
13	and	Boolean AND	Left-to-Right
14	or	Boolean OR	Left-to-Right
15	if/else	Conditional expression (x if C else y)	Left-to-Right
16	lambda	Lambda expression	N/A
Lowest	:=, =, +=, -=, *=, /=, %=, **=, etc.	Assignment operators (including walrus operator)	Right-to-Left

Shortcut in VS Code

Trigger Multi-Cursor: Press Ctrl+Shift+L (Cmd+Shift+L on Mac):

This instantly creates a separate cursor at the end of every matching word in the entire file.

Finish: Press Esc to exit the multi-cursor mode.

Change Selected Occurrences Interactively (Skip Some)

Select the First Word: Double-click (or select) the first instance of the word you want to change.

Add Next Match: Press Ctrl+D (Cmd+D on Mac).

Finish: Press Esc to exit the multi-cursor mode.