



NEXUS URJA SOLUTIONS

Office: Flat No. G-1403, Yashada Splendid Park, Dudulgaon, Moshi, Pune-412105

Sales: +91 8668250720 / 8983328537 | Email: sales@nexusurjasolutions.com | GST: 27EPUPM4088H1Z2

Quotation For 35 kVA 3 Phase Diesel Generator

Quote Ref No. NUS/QTN/00013/2026-2027

Date- 04/06/2026

To,

Mob:

Subject: Proposal For 35 kVA 3Ph EICHER-TMTL Make Silent Diesel Engine Generator

Dear Sir,

This has reference to your enquiry of Silent DG Set. We are pleased to introduce ourselves as one of the largest genset manufacturer in India having manufacturing range of 2 KVA to 2000 KVA Genset providing custom built power solutions.

DG sets are powered by 'EICHER/TMTL ENGINES', a unit of TAFE Motors and Tractors Limited, well known for their ruggedness, economics of performance & high reliability. Eicher Engines are based on AIR/WATER-COOLED technology and have powered more than 2,0,000 DG Sets running across the country.

Eicher Engines have earned the trust of millions of users as these engines can be operated for long periods without stopping the engine, require lowest maintenance cost, offer best-in-class fuel economy and meet the latest emission norms.

We are the OEM of Eicher Engines powered PERFECT DG set. TMTL has created an enviable position for themselves in the industry because of our commitment towards product quality and total customer satisfaction. Our state-of-the-art design & manufacturing facilities, strong service support and customer friendly attitude have made 'PERFECT' DG sets the first choice for most telecom corporates such as Bharti Infratel, Indus Towers, Vodafone, Reliance JIO, Idea, IDMC, ICICI Bank, Axis Bank, Aditya Birla Retail, HDFC Bank, Kotak Mahindra Bank, IOCL, SBI and many others.

We have also developed capability to execute the complete project including civil works, Installation, electrical cabling & earthing etc. Our team of expert engineers and installers shall guide you appropriately for installation of complete genset in the most economical way.

Our manufacturing plants, located at M-7, Additional, MIDC, Satara - 415004, are equipped with the latest machinery such as Amada/Muratech make CNC Cutting, CNC Bending and a fully automated powder coating facility with pure Polyester powder and baking on automatic conveyORIZED plant resulting in good surface finish and protection against corrosion. All the products coming out of our plants conform to stringent quality control norms and are thoroughly tested for performance. DG Sets are manufactured as per technical guidelines of Tafe Motors & Tractors Limited.

We are also pleased to inform you that all models of DG Sets manufactured by us, are tested and certified as per latest Sound & Emission norms, issued by CPCB.

Assuring you of our best attention at all times.

EICHER/TMTL Engines Powered PERFECT Silent DG set shall comprise of the following:

DIESEL ENGINE:

1500 RPM under NTP conditions of BS: 5514. The engine shall be provided with electrical starting arrangement & shall give the electrical output at 0.8 power factor. The engine is complete with:

- Starter motor.
- Battery charging alternator.
- Dry type air cleaner.
- Mico fuel pump.
- A1 class governing.
- Flywheel with flywheel housing.
- Residential silencer.
- First fill of lube oil.
- Engine protections: Low lube oil pressure & High Cylinder temperature.

ALTERNATOR:

Suitable make (CG/Stamford/LS/MCAL), 50 cycles, self-regulated, self-excited, screen protected, alternator of rated capacity at 0.8 power factor. The alternator will conform to relevant BS/IS standard. The choice of alternator is to us unless specifically agreed upon.

CONTROL PANEL : - Manual / ASAS / AMF

Manual Panel – Standard Control Panel, louvered, Steel construction control panel, dust & vermin proof comprising of MCB, Indicators & ignition key.

ASAS Panel – Auto Start & Auto Stop Panel, louvered, steel construction control panel, dust & vermin proof comprising of MCB, indicators, ignition key and auto sensor. Auto-changeover switch is to be provided by customer in LT Panel.

AMF Panel – Auto Mains Failure Control Panel with microprocessor-based logic controller, switch gears, MCB/MCCB/CT coil, Contactors, indicating lamps, ignition key.

ESSENTIAL ACCESSORIES:

- Fuel tank with drain valve, breather, inlet and outlet connections.
- Battery with leads.
- Anti vibration mountings.
- Operator manuals & test certificates.

SOUNDPROOF CANOPY

Our soundproof canopies are made using the best quality steel purchased directly from manufacturers in sealed packets.

Our state-of-the-art manufacturing plant includes machinery and equipment such as CNC Punching, CNC Bending, Fully automated conveyORIZED powder coating plant with automatic PLC based 9 tank pre-treatment process.

This ensures consistency in quality and results in an extremely aesthetic looking product.

BASE:

2.5 mm Thick CRCA sheet is used for Base.

CANOPY:

Doors & Roof shall be fabricated from MS CRCA of adequate thickness with airtight EPDM foam gasket. MS/Zinc die cast hinges will be provided.

INSULATION:

The insulation material will be PU Foam. The material is fire retardant.

WINDOW FOR CONTROL PANEL:

Windows for control panel will be with glass/acrylic and sealed with neoprene rubber gasket.

AIR INLET & AIR OUTLET:

Air inlet and outlet louvers, with special sound reduction dampers for proper air ventilation will be provided.

CONSTRUCTION:

The construction will be modular, bolted construction and will have access from all sides. All fasteners will have washers. The fasteners will be SS/Zinc coated MS.

LIGHTING:

1 no. lamp with ON/OFF switch and socket inside the canopy will be provided.

EARTHING:

The Earthing arrangements for DG set / Canopy will be homogenous.

PAINTING:

All metal surfaces will be thoroughly treated with degreasing, derusting and phosphating in our in-house fully-automated, 9 tank pre-treatment process, conveyorized powder coating plant, before final powder coating. The finish will be suitable for outdoor use.

NOISE LEVEL PERFORMANCE:

The maximum noise level permitted during full load will be 75 dB, measured at 1 meter distance from the edge of canopy. The product shall be certified by CPCB as per latest sound norms.

FUEL FILLING & DRAIN:

Suitable external fuel filling and drainage connections with locking facility will be provided.

FUEL TANK:

The fuel tank shall be removable type. The tank shall be fabricated from CRCA / HR Pickled / MS, minimum 2 mm thick sheet.

TEMPERATURE RISE INSIDE CANOPY:

The maximum permissible temperature rise above the ambient will be 5°C to 7°C as per IS standard.

VENTILATION:

The canopy is equipped with a forced air circulation fan of reputed make.

ANTI VIBRATION PADS:

The anti-vibration pads will be provided below diesel engine and alternator.

EMERGENCY PUSH STOP BUTTON:

The canopy will have provision of emergency push button which shall be housed in a protective enclosure with a glass front.

Design / Specifications are subject to change due to continual improvement process.

EARTHING:

The Earthing arrangements for DG set / Canopy will be homogenous.

PAINTING:

All metal surfaces will be thoroughly treated with degreasing, derusting and phosphating in our in-house fully-automated, 9 tank pre-treatment process, conveyorized powder coating plant, before final powder coating. The finish will be suitable for outdoor use.

NOISE LEVEL PERFORMANCE:

The maximum noise level permitted during full load will be 75 dB, measured at 1 meter distance from the edge of canopy. The product shall be certified by CPCB as per latest sound norms.

FUEL FILLING & DRAIN:

Suitable external fuel filling and drainage connections with locking facility will be provided.

FUEL TANK:

The fuel tank shall be removable type. The tank shall be fabricated from CRCA / HR Pickled / MS, minimum 2 mm thick sheet.

TEMPERATURE RISE INSIDE CANOPY:

The maximum permissible temperature rise above the ambient will be 5°C to 7°C as per IS standard.

VENTILATION:

The canopy is equipped with a forced air circulation fan of reputed make.

ANTI VIBRATION PADS:

The anti-vibration pads will be provided below diesel engine and alternator.

EMERGENCY PUSH STOP BUTTON:

The canopy will have provision of emergency push button which shall be housed in a protective enclosure with a glass front.

Design / Specifications are subject to change due to continual improvement process.

Commercial:

S.N.	Product Description	Unit Price	Qty	Amount
1	Diesel Genset, PECH-35 KVA, 3 PH, Auto Start - Auto Stop Panel Provision, 47.5 BHP, Eicher - TMTL Engines, 329A0-EG035 EGR + DOC	₹ 4,47,426	1	₹ 4,47,426
2	GST @18%	₹ 80,537	-	₹ 80,537
3	Transportation	Extra	1	At Actual

Sub Total	₹ 4,47,426
GST @18%	₹ 80,537
Grand Total	₹ 5,27,963
Advance Amount	₹ 0
Balance Amount	₹ 0

TERMS & CONDITIONS

GOODS & SERVICES TAX:

Goods & Services tax @18%.

PAYMENT TERMS:

30% Advance and balance 70% against Proforma Invoice before Dispatch.

DELIVERY/FREIGHT:

Extra

DELIVERY PERIOD:

Within 1-2 Weeks

APPROVALS:

Approvals from concerned authorities shall be to customer's account.

SCOPE OF SUPPLY:

Our offer is confined to whatever is specifically included and stipulated in the technical and commercial clauses and is subject to changes as may be mutually agreed upon finalization of the contract.

INSTALLATION:

Installation, Diesel Filling, Statutory approvals are customer Scope (or) Extra as per site visit. Installation quote shall be sent separately if required.

UNLOADING:

Excluded

VALIDITY:

Offer is valid for a period of 30 days from the date of offer.

JURISDICTION:

All disputes are subject to our registered office Jurisdiction only.

GENERAL:

- Order received is subject to acceptance in writing by us.
- In case of your cancellation of the order or inability to lift the material within fifteen days of intimation, we shall have the right to forfeit your advance and dispose of the materials at your risk & cost and claim any further losses.
- Price prevailing at the time of supply shall be charged.

PURCHASE ORDER:

The purchase order shall be released in the name & address as given below:

Regards,

Mr. Harshal Mahajan

+91 8668250720 / 8983328537

mail-sales@nexusurjasolutions.com

For NEXUS URJA SOLUTIONS

Reach us at - www.nexusurjasolutions.com