Priti Yadav CSE/DS SE3

Roll no -69

Experiment 6

Title

Create a webpagethatretrieves,displays,andupdatesuserdatafromaMySQLdatabase. Implement CRUD operations (Create, Read, Update, Delete) using PHP & MySQL. Ensure user input is validatedandsecurelystoredinthedatabase.AddSession&Cookies.

Theory:

Modern web applications often require interaction with databases to store, retrieve, and manage user informationefficiently.Thisexperimentfocusesondevelopingadynamicwebapplication using PHPandMySQLthatperformsCRUDoperations(Create,Read,Update,Delete)onuser data. Additionally,theapplicationensuresinputvalidation,securedatastorage,andincorporates Sessions and Cookies for user management

A. PHPandMySQLIntegrationPHP(HypertextPreprocessor)isaserver-sidescripting language widely used for web development. It is especially suitable for database-driven applications because it can easily interact with databases like MySQL. MySQL is an open-source relational database management system (RDBMS) used to store structured data in tables. PHP communicates with MySQL using extensions such as MySQLi or PDO (PHP Data Objects) to execute SQL queries. In this experiment, PHP scripts handle database connections, execute SQL commands, anddynamicallygenerateHTMLoutputbasedondatabaserecords.

B. CRUDOperationsCRUDrepresentsthefourfundamentaldatabaseoperations:

1. Create(Insert)TheCreateoperationisusedtoaddnewuserrecordsintothedatabase.User data is collectedthroughHTMLformsandsenttotheserverusingHTTPPOSTmethod.PHP processes the input and inserts validated data into the MySQL table using the INSERT SQL statement. 2. Read(Select)TheReadoperationretrievesuserdatafromthedatabaseanddisplaysitonthe webpage. PHP executes the SELECT SQL query and fetches records, which are displayed dynamically intabularformat.Thisoperationallowsuserstoviewstoreddata. 3. UpdateTheUpdateoperationmodifiesexistinguserrecords.Theselectedrecordisloaded into an HTMLform,allowingtheusertoeditdata.PHPthenupdatestherecordinthedatabase using theUPDATESQLstatement.

4. Delete The Deleteoperationremovesunwantedrecordsfromthedatabaseusingthe DELETESQL

statement. This operation helps maintain accurate and relevant data. C. Database Structure A MySQL database typically contains: ● A database to store application data ● A table to store user information such as ID, name, email, and password ● A primary key to uniquely identify each record Relational databases ensure data consistency and integrity through structured schema and constraints. D. Input Validation Input validation is essential to ensure that user-provided data is correct and safe. Validation includes: ● Checking for empty fields ● Validating email format ● Restricting input length ● Allowing only valid characters

Validation can be implemented using both client-side validation (HTML/JavaScript) and server-side validation (PHP). Server-side validation is critical, as client-side validation can be bypassed.

E. Security Measures

SQL Injection Prevention

SQL Injection is a common attack where malicious SQL code is inserted into input fields. To prevent this:

● Prepared statements
● Parameterized queries

are used to securely execute SQL commands.

Password Security

Passwords should never be stored in plain text. PHP provides hashing functions such as password_hash() to securely store passwords and password_verify() to authenticate users.

F. Sessions

A session is a server-side mechanism used to store user data temporarily across multiple pages. Sessions are commonly used for:

● User login systems
● Authentication
● Maintaining user state

In PHP, sessions are created using session_start() and data is stored in session variables. Session data is automatically destroyed when the browser is closed or the session expires.

G.Cookies

A cookie is a small piece of data stored on the client's browser. Cookies are used to:

● Remember user preferences

●Store login information
●Track user activity
Unlike sessions, cookies have an expiration time and remain stored even after the browser is closed. PHP uses the setcookie() function to create cookies.
H.Dynamic Web Page Behavior
The application dynamically updates content based on database operations. PHP fetches updated records after every CRUD operation, ensuring that the displayed data always reflects the current state of the database.
Algorithm/Procedure:
A. Database Creation
1. Start XAMPP/WAMP server.
2. Open phpMyAdmin.
3. Create a database named userdb.
B. CRUD Operations Flow
4. Create a table users with fields:
○ id (INT, Primary Key, Auto Increment)
○ name (VARCHAR)
○ email (VARCHAR)
○ password (VARCHAR)
Steps:
1. User enters details in HTML form.
2. PHP validates user input.
3. Data is securely inserted into MySQL database.
4. Existing records are fetched and displayed.
5. User can update or delete records.
6. Sessions manage login state.
7. Cookies store user preference.

Program/Code:

1. Database Connection (db.php)

```
<?php
$conn = mysqli_connect("localhost", "root", "", "userdb");
if (!$conn) {

 die("Database connection failed");
}
?>
```

2.Create (Insert) User

```
<?php
include "db.php";
if (isset($_POST['submit'])) {
$name = trim($_POST['name']);
```

```
$email = trim($_POST['email']);
$pass = password_hash($_POST['password'], PASSWORD_DEFAULT);
if(!empty($name) && !empty($email)) {
$query = "INSERT INTO users(name,email,password) VALUES('$name','$email','$pass')";
mysqli_query($conn, $query);
header("Location: index.php");
}
}
?>
```

3.Read (Display Data) – index.php

```
<?php include "db.php"; ?>
<html>
<body>
<h2>User List</h2>
<table border="1">
<tr>
<th>ID</th><th>Name</th><th>Email</th><th>Action</th>
</tr>
<?php
$result = mysqli_query($conn, "SELECT * FROM users");
while ($row = mysqli_fetch_assoc($result)) {
?>
<tr>
<td><?= $row['id']; ?></td>
<td><?= $row['name']; ?></td>
<td><?= $row['email']; ?></td>
<td>
<a href="edit.php?id=<?= $row['id']; ?>">Edit</a> |
<a href="delete.php?id=<?= $row['id']; ?>">Delete</a>
</td>
</tr>
<?php } ?>
</table>
</body>
</html>
```

4.Update Operation (edit.php)

```
<?php
include "db.php";
$id = $_GET['id'];
if (isset($_POST['update'])) {

 $name = $_POST['name'];
```

```
 $email = $_POST['email'];
 mysqli_query($conn, "UPDATE users SET name='$name', email='$email' WHERE id=$id");
 header("Location: index.php");
}
$data = mysqli_fetch_assoc(mysqli_query($conn, "SELECT * FROM users WHERE id=$id"));
?>
<form method="post">
<input type="text" name="name" value="<?= $data['name']; ?>">
<input type="email" name="email" value="<?= $data['email']; ?>">
<button name="update">Update</button>
</form>
```

5. Delete Operation (delete.php)

```
<?php
include "db.php";
$id = $_GET['id'];
mysqli_query($conn, "DELETE FROM users WHERE id=$id");
header("Location: index.php");
?>
```

6. Session Management (session.php)

```
<?php
session_start();
$_SESSION['user'] = "Admin";
?>
```

Cookie Example

```
<?php
setcookie("username", "Student", time() + 3600);
?>
```

Output:

User List

ID	Name	Email	Action
1	Rahul	rahul@gmail.com	Edit | Delete
2	Priya	priya@gmail.com	Edit | Delete

Add User

Rahul

rahul@gmail.com

******

Submit

User inserted successfully!



Conclusion

Thus, a dynamic database-driven web application was successfully developed using PHP and MySQL. CRUD operations were implemented with secure data handling, input validation, and session & cookie management. This experiment demonstrates real-world server-side web development concepts.