

Lab Report : 07

Lab report name : Implementation of FCFS scheduling algorithm.

ID : IT-17010

Objective:- To understand the first come first serve (FCFS) scheduling algorithm technique in detail.

FCFS:- It is an operating system process scheduling algorithm and a network routing management mechanism that automatically executes queued requests and processes by the order of their arrival.

FIFO simply queues processes in the order they arrive in the ready queue. Here, the process that comes first will be executed first and next process will start only after the previous gets fully executed.

1. Completion Time: Time at which process completes its execution.
2. Turn Around Time: Time Difference between completion time and arrival time. $\text{Turn Around Time} = \text{Completion Time} - \text{Arrival Time}$
3. Waiting Time (W.T): Time Difference between turn-around time and burst time. $\text{Waiting Time} = \text{Turn Around Time} - \text{Burst Time}.$

Gantt chart:

P1		P2	P3
0	18	21	24

process	Arrival time	Burst time	Completion time	Turn-around time	Waiting time
P1	0	18	18	18	0
P2	1	3	21	20	17
P3	2	3	24	22	19

Average waiting time = $(0+17+19)/3$

=12ms

Average turn-around time = $(18+20+22)/3$

=20ms

Code:-

```
#include<stdio.h>
```

```
findWaitingTime(int pro[],int n,int burst[],int wt[],int ar[])
```

```
{
```

```
    int i=1;
```

```
    wt[0]=0;
```

```
    burst[0]=0;
```

```
    ar[0]=0;
```

```
    while( i<=n)
```

```
    {
```

```
        wt[i]=burst[i-1]+wt[i-1]+ar[i-1]-ar[i];
```

```
        i++;
```

```
    }
```

```
}
```

```
findTurnAroundTime(int pro[],int n,int burst[],int tat[],int wt[])
```

```
{
```

```
    int i=1;
```

```
    while(i<=n)
```

```

    {
        tat[i]=burst[i]+wt[i];

        i++;
    }
}

findavgTime(int pro[],int n,int burst[],int ar[])
{
    int wt[n],tat[n],total_wt=0,total_tat=0,i=1;

    findWaitingTime(pro,n,burst,wt,ar);

    findTurnAroundTime(pro,n,burst,tat,wt);

    printf("Processes Burst-time Waiting-time Turn around-time \n");

    while(i<=n)
    {
        total_wt=total_wt+wt[i];

        total_tat=total_tat+tat[i];

        printf("%d\t",i);

        printf(" %d\t\t",burst[i]);

        printf(" %d\t\t",wt[i]);

        printf(" %d\n",tat[i]);

        i++;
    }

    float s=(float)total_wt/n;

```

```

float t=(float)total_tat/n;

printf("\nAverage waiting time = %.3f\n",s);

printf("\nAverage Turn Around time=%.3f\n",t);
}

int main()
{
    int n;

    printf("number of processes= ");

    scanf("%d",&n);

    printf("process arrival Brust\n");

    int pro[n],burst[n],ar[n],i=1;

    while(i<=n)
    {
        scanf("%d",&pro[i]);

        scanf("%d",&ar[i]);

        scanf("%d",&burst[i]);

        i++;
    }

    findavgTime(pro,n,burst,ar);

    return 0;
}

```

Output:

```

number of processes= 3
process arrival Burst
1 0 18
2 1 3
3 2 3
Processes Burst-time Waiting-time Turn around-time
1 18 0 18
2 3 17 20
3 3 19 22

Average waiting time = 12.000

Average Turn Around time=20.000

Process returned 0 (0x0) execution time : 27.282 s
Press any key to continue.

```

Conclusion:- This algorithm is about first come first serve (FCFS) scheduling algorithm technique. The main characteristics of first come first serve (FCFS) scheduling algorithm technique are that they are Non-preemptive, ready queue just a FIFO queue, careers coming are positioned at queue's end, dispatcher selects job in this work and line works to end of CPU burst.