



Technische Hochschule
Ingolstadt

Bachelor Thesis

Faculty of computer science

**Development of a Frontend Application for Real-Time and
24-Hour Monitoring and Recording of Electrocardiographic Data
with Communication via Bluetooth Low Energy**

First- and Lastname : **Eric Horacsek**

Registered on : xx.yy.zzzz

Submitted on : xx.yy.zzzz

First examiner : Prof. Dr.-Ing. Georg Passig

Second examiner : Prof. Dr. Ulrich Margull

AFFIDAVIT

I hereby declare that I have written this thesis independently, have not used any sources or aids other than those stated, have not submitted it elsewhere for examination purposes and have expressly identified all quotations from the sources used, either verbatim or in spirit. I have marked verbatim and indirect quotations as such.

Ingolstadt, _____

Firstname Lastname

ACKNOWLEDGEMENTS

This is the sentimental part where you get to thank all the persons who were a part of your thesis journey in one or the other way!

Eric Horacsek
Ingolstadt, Deutschland
November xx 2024

ABSTRACT

The human heart is the central organ of the circulatory system and plays a vital role in supplying the body with oxygen and nutrients. Rhythmic contractions pump blood through the body, laying the foundation for all vital functions. An essential part of medical diagnostics in connection with heart function and health is the electrocardiogram (ECG). The ECG measures the electrical activity of the heart and provides valuable information about the heart rhythm and possible irregularities or diseases. As technology has advanced, the way in which ECG data can be collected and monitored has also evolved significantly. Mobile health monitoring in particular now makes it possible to record ECG data not only at specific points of time, but also in real time and over longer periods of time. Wireless transmission via Bluetooth Low Energy (BLE) enables reliable and energy-efficient transfer of data to mobile devices. This opens up new possibilities for applications that offer real-time and long-term monitoring and provide users with relevant information through graphical processing and alarm functions. The goal of this thesis is the conception and implementation of a frontend application, which realises continuous and mobile ECG monitoring. Moreover this dissertation is particularly focused on implementing the communication and data transmission via BLE as well as realising an 24-hour-mode, where the user is able to record his own electrocardiographic data for up to 24-hours. It also provides an broad insight into the given requirements, designprincipals, and technical challenges which accured during the implementation. In addition shows the potential for modern healthsuveillance.

CONFIDENTIALITYCLAUSE

Optional.

Ingolstadt, _____
(Date)

(Signature)
Firstname Lastname

LIST OF FIGURES

LIST OF TABLES

LIST OF CONTENTS

Affidavit	I
Acknowledgements	II
Abstract	III
Confidentialityclause	IV
List of figures	VI
List of tables	VII
1 Introduction	1
1.1 Motivation	1
1.2 Scope and Framework	1
2 Verwandte Arbeiten	2
2.1 Research direction 1	2
2.1.1 Relevanz für die eigene Arbeit - Direction 1	2
2.2 Research direction 2	2
2.2.1 Relevanz für die eigene Arbeit - Direction 2	3
2.3 Schlussfolgerung	3
3 Diskussion	4
4 Conclusion	5
4.1 Outlook	5
4.2 Einschränkungen	5
Literature references	VI

1 INTRODUCTION

This chapter will give a small introduction on what the thesis and the implemented application is about. This covers an explanation for the application's motivation and the environment the application will be used in.

1.1 Motivation

The aim of this work is create a new version of an Android App developed by fellow students from the faculty of Electrical and Information Technology. It's core functionality is to receive and display ECG data in real time, via Bluetooth. With the completion of this work, the new version will be able to receive and display ECG data in real time, via BLE. In addition it will be capable of an 24-hour mode which records ECG data for up to 24 hours, so the collected data can be analyzed later.

1.2 Scope and Framework

2 VERWANDTE ARBEITEN

Lorem ipsum Lorem ipsum.

2.1 Research direction 1

Riener [Riener et al. \[2013\]](#) hat sich die Frage gestellt, was sich aus dem Einsatz von Autopilotensystemen in der Luftfahrt für den Bereich des (teil)automatisierten Fahrens in der Automobilindustrie übertragen/lernen lässt und was man für die Gestaltung der Interaktion übertragbar machen könnte. usw. usw. Gold et al. thematisierten die Frage, “zu welchem Zeitpunkt, vor dem Auftreten einer Systemgrenze, muss das FAS die Aufmerksamkeit des Fahrers auf sich ziehen, um eine erfolgreiche Übernahme durch den Fahrer auch dann sicherzustellen, wenn er sich nicht im Loop befindet.” [Gold et al. \[2013\]](#) Hierzu wurde eine Studie mit 32 Probanden in einem High-Fidelity-Fahrsimulator bei BMW durchgeführt. Das Szenario beschreibt eine Fahrt mit 120 km/h auf einer dreispurigen Autobahn, bei der das vorausfahrende Auto einen Unfall verursacht und somit den Fahrer zu handeln zwingt. 17 Probanden haben dieses Szenario als Referenz manuell durchfahren, wobei der Unfall zum Einen fünf Sekunden, zum Anderen 7 Sekunden entfernt war. Die gleichen Zeiten wurden für die Probanden der hochautomatisierten Zeit eingehalten um die Übergabe einzuleiten.

Folgende Ergebnisse konnten aus dieser Studie gezogen werden:

1. Die geringe Zeit bis zur Übernahme lässt die Probanden schneller zu einer Entscheidung und Reaktion kommen, dennoch ist deren Qualität schlecht.
2. Mit der sich verringernden Zeit bis zur Übernahme nehmen die Kontrollblicke in Spiegel und über die Schulter ab, hingegen nimmt die Beschleunigung zu, sowie auch das Betätigen der Bremse.
3. Vergleicht man die Probanden aus der Referenzfahrt und der hochautomatisierten Fahrt, wird deutlich, dass bei den Probanden der hochautomatisierten Fahrt bis zu dreimal so hohe Beschleunigungen erzielt wurden. Auch werden hier viele plötzliche Bremsmanöver durchgeführt.

Die Studie belegt unter diesen experimentellen Bedingungen, dass bei vollständiger Ablenkung des Fahrers bei hochautomatisierter Fahrt noch bei sieben Sekunden Übernahmezeit ein Automatisierungseffekt auftritt. Das bedeutet, dass der Fahrer durch die fahr-fremde Nebentätigkeit stark abgelenkt ist und der automatisierten Fahrt vertraut. Dies führt zu solchen Reaktionen bei unerwarteter Bekanntmachung von Übernahmen.

2.1.1 Relevanz für die eigene Arbeit - Direction 1

Lorem ipsum Lorem ipsum.

2.2 Research direction 2

[Wintersberger et al. \[2017\]](#) befasst sich mit einer umfassenden und klar definierten Taxonomie der zwei Hauptprozesse “handover” und “handback”. Er kommt zu folgender Schlussfolgerung:

1. Handover - von der automatisierten zur manuellen Fahrt

2. Handback - von der manuellen zur automatisierten Fahrt

2.2.1 Relevanz für die eigene Arbeit - Direction 2

Lorem ipsum Lorem ipsum.

2.3 Schlussfolgerung

Zusammenfassung des Kapitels, Ableitung von Empfehlungen, etc. für die eigene Arbeit.

- Lorem ipsum subsection 2.1.
- Lorem ipsum lorem ipsum subsection 2.1.
- Lorem ipsum subsection 2.2.
- ...
- Lorem ipsum lorem ipsum lorem ipsumsubsection 2.2.

3 DISKUSSION

Diskussion der Resultate im Vergleich zu Ergebnissen der Related work-Analyse und Reflektion auf die Forschungsfragen/Hypothesen.

Hypothese **H1** kann angenommen werden. Bla bla Begründung/Argumentation.

Andererseits zeigen die Ergebnisse der Evaluation aber keinen signifikanten Unterschied (siehe **Field**) zwischen X und Y - somit kann auch **H2** angenommen werden. Da hier bla bla Argumentation.

Durch die Ergebnisse des Fragebogens wird Hypothese **H3** nicht bestätigt. Es sind keine signifikanten Unterschiede über die ...

4 CONCLUSION

Diese Arbeit befasste sich grundsätzlich mit der Frage, welche Anforderungen an ... gestellt werden. Der Lösungsvorschlag war... Benutzerstudien haben gezeigt, dass es einen signifikanten Unterschied... gibt. Diese Ergebnisse motivieren, um ...

4.1 Outlook

In dieser Arbeit haben wir uns mit ... beschäftigt. Durch zwei Benutzerstudien wurde festgestellt, dass sich die Aufteilung und Positionierung der Informationen innerhalb der Anzeige der beiden Gruppen aufgrund bla bla ändert. Das entwickelte Konzept ist zwar bla bla, müsste aber für eine Wiederholung der Studien bla bla zur Erhebung quantitativer Daten wie folgt angepasst werden:

- xxx
- yyy
- xzz

Des Weiteren wurde festgestellt, dass bla bla. Auch das müssten zukünftige Varianten besser berücksichtigen, z. B., indem sie bla bla. Für Studien sollte zudem eine neutrale(re) Umgebung gewählt werden. Somit sollte sichergestellt werden können, dass beispielsweise ein möglicher Bias der Marke des Fahrzeugs sich nicht auf das HMI-Konzept auswirkt...

4.2 Einschränkungen

Hinsichtlich Einschränkungen, die eine breite Anwendung der Ergebnisse verhindern, sind zwei getrennte Bereiche zu betrachten. Zum einen die Evaluation, welche sich nur auf den ersten Teil der Arbeit bezieht, zum anderen das ausgearbeitete Konzept für die Anzeige, das auf dem ersten Teil der Arbeit aufbaut.

Evaluation Bla bla.

Konzept Bla bla. Das wurde etwa in beschrieben...

LITERATURE REFERENCES

- Mirjam Bick. 7,1 % weniger verkehrstote im jahr 2016, February 2017. URL https://www.destatis.de/DE/PresseService/Presse/Pressemitteilungen/2017/02/PD17_065_46241.html. Zugriff: 05.09.2017.
- Andy Field. *Discovering Statistics Using SPSS*. SAGE Publications Ltd, 3 edition. ISBN 978-84787-906-6.
- Christian Gold, Daniel Damböck, Lutz Lorenz, and Klaus Bengler. "take over!" how long does it take to get the driver back into the loop? In *Proceedings of the Human Factors and Ergonomics Society 57th Annual Meeting*, pages 1938–1942, 2013. doi: 10.1177/1541931213571433. URL <https://mediatum.ub.tum.de/doc/1308108/1308108.pdf>.
- A. Riener, A. Ferscha, F. Bachmair, P. Hagmüller, A. Lemme, D. Muttenthaler, D. Pühringer, H. Rogner, A. Tappe, and F. Weger. Standardization of the in-car gesture interaction space. In *Proceedings of the 5th International Conference on Automotive User Interfaces and Interactive Vehicular Applications, AutomotiveUI '13*, pages 14–21, New York, NY, USA, 2013. ACM. ISBN 978-1-4503-2478-6. doi: 10.1145/2516540.2516544. URL <http://doi.acm.org/10.1145/2516540.2516544>.
- Stefan Schlott. Automatisiert den fahrer überfordern. *Im Fokus*, January 2016. URL <https://www.springerprofessional.de/automatisiertes-fahren/ergonomie---hmi/automatisiert-den-fahrer-ueberfordern/11104124?searchResult=1.automatisiert%20den%20fahrer%20%C3%BCberfordern&searchBackButton=true>. Zugriff: 15.01.2018.
- Philipp Wintersberger, Paul Green, and Andreas Riener. Am i driving or are you or are we both? a taxonomy for handover and handback in automated driving. In *Proceedings of the Ninth International Driving Symposium on Human Factors in Driver Assessment, Training and Vehicle Design*, Driving Assessment Conference. University of Iowa, June 2017. URL <http://drivingassessment.uiowa.edu/sites/default/files/DA2017/papers/51.pdf>.