

111058

Base Elevator Package	
Job Number	ON1012P263841
Elevator Type	GMV North America, EDGE Passenger Elevator
Drive System	1:1 Direct Acting Hydraulic
Compliance	ASME A17.1/CSA B44 2019
Complete Package	GMV-NA elevator packages are as complete as we can make them We include: - Factory tested wiring harnesses with plug-in connections. - All wiring trough required.
Warranty	1 Year Standard Warranty
Capacity	2500 LB (1134 kg)
Door Hand	Left Hand
Cab Configuration	Front Only
Speed	100 FPM
Pit	60" (1524 mm)
Total Travel	125" (3175 mm)
Travel 1->2	125" (3175 mm)
Number of Floors Served	2 Floors Front: 1(*G) 2(2)
Clear Overhead	150" (3810 mm)
Under Travel	11" (279 mm)
Over Travel	5" (127 mm)
Machine Location	Adjacent Machine Room
Power Supply	208 V 3 Phase 3 PH 60 HZ
Cab Lighting Power Supply	120V 1 PH 60 HZ
Operation	Selective/Collective
Starts per Hour	25

[GREEN] Capacity -> S1.1 CAPACITY, S1.7 engraving capacity (2500lb / 1134kg)

[GREEN] Travel 1->2 -> S1.2 *G TO 2 = 125"

[GREEN] Floors served -> S1.1 floors/openings, S1.7 openings & floor markings, S1.8 top floor label

[GREEN] Drive system 1:1 direct acting -> S1.1 SYSTEM (removed "TWIN")

GMV-NA Inc.
4 Cochran Drive
Ayr, Ontario CA
N0B 1E0



Landing	Landing Wall Construction	Landing Frame & Door Panel Finish	FS	PI	FL	HA
FRONT 1 (*G)	Masonry	Powder Coat	X	X		
FRONT 2 (2)	Masonry	Powder Coat				X

Landing Entrances Details	
Type	Two Speed Horizontal Side
Size	Nominal 42" (1065 mm) X Nominal 84 5/8" (2150 mm)
Sill	Satin (Brushed) Aluminum
Fire Rating	1 1/2 Hour UL

[GREEN] Landings Front 1 (*G), Front 2 (2) -> S1.7 FLOOR MARKINGS / OPENINGS
[GREEN] Door size 42" x 84 5/8" -> S1.5 ENTRANCE size

GMV-NA Inc.
4 Cochran Drive
Ayr, Ontario CA
N0B 1E0



Cab Details	
Nom. Cab Interior Dim.	81" (2057 mm) W x 51" (1295 mm) D x 90" (2286 mm) H
Floor	Plywood Unfinished Floor. 5/8" (16mm). Provisions made for supply and installation of cab floors by others.
Entrance (Door & Frame)	Brushed Stainless Steel with two speed side door operation.
Walls	Applied Plastic Laminated Panels. Standard Formica Selection. Thermo Walnut (6402)
Handrail	Flat Satin (Brushed) Stainless Steel (2" x 1/4")
Ceiling and Lighting	LED
Ceiling Reveal	Stainless Steel
Cab Reveal	Black Powder Coat
Cab Pads	NO
In-Cab Security Cable	NO

[GREEN] Cab interior 81" x 51" -> S1.1 DIMENSIONS, S1.5 INSIDE CAB SIZE (2500lbs F layer)
[GREEN] Cab reveal Black Powder Coat -> S1.5 CAB REVEALS
[GREEN] Ceiling and lighting: LED -> S1.1 CAB LIGHT

GMV-NA Inc.
4 Cochran Drive
Ayr, Ontario CA
N0B 1E0



Car Operating Panel (COP)	
Finish	Satin (Brushed) Stainless Steel
Signal	Digital Directional (DI) and Position Indicator (PI)
Push Buttons	Door Open, Door Close, Floor Call Buttons Help and Alarm
Floor Designation	Floor identifications complete with Braille tag
Firefighter Service	Phase II
Run/Stop	Key switch with Braille Tag
Independent Service	Key switch
Emergency Telephone	Push button with Braille tag and call acknowledge indicator
Push Button Finish	Satin (Brushed) Stainless Steel bezel with LED Illumination

Directional Lantern	Located on Car Strike Jamb. Visible from inside the cab and the landing entrance when the door starts to open.
----------------------------	---

Hall Stations General	
Type	Flat Plate
Finish	Satin (Brushed) Stainless Steel
Push Button	Satin (Brushed) Stainless Steel bezel with LED Illumination
Signal	Digital Directional (DI) and Position Indicator (PI) at the top of each Landing.

Door Operator	Closed loop, 24 VDC Drive with adjustable soft start, soft stop, opening speed and closing speed.
----------------------	---



Controller	
Controller	360 Controller Non proprietary, Micro controller-based system
Operation	Selective/ Collective A form of elevator operation whereby the Controller recognizes, accepts, and answers all calls in one direction of travel, irrespective of the sequence of the calls, before reversing direction.
Homing	Field programmable to any floor, typically the main floor.
Nudging	Provides a warning sound and causes the doors to close at a slow speed, if the doors are obstructed from closing for longer than the pre-set time.
Independent Service	Key Activation will eliminate the possibility to place hall calls. Car operation is controlled by the rider. Doors will only close by applying constant pressure to the call button on the COP. When the doors fully close, the car will move to the floor selected.

Floor Selector	
Floor Selector	Steel perforated tape and single magnet at each floor.

Safety Fixture	
Controller	Meet or exceed all safety requirements detailed in ASME A17.1 and CSA B-44 • CSA/UL Approved Door Interlocks • UL 1 ½ hr fire rated landing entrances • Car Door Restrictor to prevent riding passengers from opening the doors when the car is not at the landing • Test and Inspection panel at top landing in Hoistway wall accessible from landing • Terminal Limit switches to prevent the car from running past the terminal landings • Power Loss emergency lowering supported by building emergency power • Emergency light in car in case of power failure • Hoistway Access as standard, making it easy for elevator mechanic to step on top of the elevator car when completing service or maintenance