


CHANGE LOG - text fields updated from customer proposal (Job ON1012P263841, GMV-5809)

SHEET	FIELD	BEFORE	AFTER
S1.1	CAPACITY lb [kg]	2300 [1043]	2500 [1134]
S1.1	NO. OF FLOORS	4	2
S1.1	NO. OF OPENINGS	FRONT: 4 / REAR: 0	FRONT: 2 / REAR: 0
S1.1	CAB DIMENSIONS	58.5 [1486] W x 68 [1727] D x 90 [2286] H	81 [2057] W x 51 [1295] D x 90 [2286] H
S1.2	Floor-to-floor label (row 1)	*G TO 1	*G TO 2
S1.2	Floor-to-floor distance (row 1)	162"	125"
S1.5 Cab Detail	INSIDE CAB SIZE	58.5" (1486 mm) W X 68" (1727 MM) D	81" (2057 mm) W X 51" (1295 mm) D
S1.5 Cab Detail	CAB REVEALS - Black Powder Coat mark	-	X
S1.5 Cab Detail	CAB REVEALS - Satin Stainless mark	X	-
S1.7 COP Detail	CAPACITY (COP plate)	2300 [1043]	2500 [1134]
S1.7 COP Detail	OPENINGS	4	2
S1.7 COP Detail	FLOOR MARKINGS	*G / 1 / 2 / 3	*G / 2


Drawings/geometry, layers, footers and title-block fields were NOT changed. Viewport drawings are not shown in these renders (text/table fields only).

S1.1 - ENG CALCS - BEFORE (standard template)

GENERAL	CAR ID	1	CAB	CAB CONFIGURATION	FRONT ONLY				
	CODE COMPLIANCE ASME A17.1/CSA B44	2019		DIMENSIONS	58.5 [1486] W x 68 [1727] D x 90 [2286] H				
	CLASSIFICATION	EDGE		ENCLOSURE MATERIAL	16GA STEEL				
	SYSTEM	TWIN 1:1 DIRECT ACTING HYDRAULIC		DOOR OPERATOR	GMV 2 SPEED - CSA#1172862				
	CAPACITY lb [kg]	2300 [1043]		INTERLOCK	CONTACT ONLY				
	NOMINAL CAR SPEED FPM [m/s]	100 [0.50]		DOOR RE-OPENING	FULL LENGTH CURTAIN + 3D DEVICE				
	NO. OF FLOORS	4		DOOR SILL	SATIN BRUSHED ALUMINUM				
	NO. OF OPENINGS	FRONT: 4 / REAR: 0		COP FINISH	SATIN STAINLESS STEEL				
	POWER SUPPLY	208 3PH 60HZ		CAB LIGHT	DIFFUSER PANEL				
	FULL LOAD AMPERAGE	84		CEILING	STAINLESS STEEL REVEAL				
	OPERATION	SELECTIVE COLLECTIVE		HAND RAIL	FLAT BRUSHED STAINLESS STEEL				
	HOISTWAY CONSTRUCTION	MASONRY		WALL PANELS	HANG ON LAMINATED WALL PANELS				
	BUFFER TYPE AND STROKE in [mm]	2X BUFFER, ACLA 300401F4, 2.83 [72]		DOOR PANEL FINISH	BRUSHED STAINLESS STEEL				
	RAIL WEIGHT lb/ft	8		FINISHED FLOOR MATERIAL	UNFINISHED PLYWOOD				
MACHINE	CONTROLLER	360 CONTROLLER - CSA#1511880	CARFRAME & PLATFORM	FINISHED FLOOR FIRE RATING	FIRE RATING SPECIFICATION - CLASS 1				
	DRIVE	GMV TYPE 3		JOISTS/STRINGERS	16GA FORMED STEEL				
	CONTROL VALVE	GMV 3010S - CSA#1032097		CROSSHEAD	7GA 8 X 2 FORMED STEEL				
	PUMP TYPE	3 SPINDLE SCREW		STILE	7GA 7 X 2½ FORMED STEEL				
	FEED FLOW GPM [LPM]	67 [254]		PLANK	7GA 7 X 2 FORMED STEEL				
	FULL LOAD STATIC PRESSURE psi [bar]	408 [27.73]		LANDING ENTRANCE CONSTRUCTION	MASONRY				
	FULL LOAD DYNAMIC PRESSURE psi [bar]	448 [30.86]		DOOR TYPE	2 SPEED				
	RELIEF PRESSURE psi [bar]	530 [36.53]		DOOR SIZE in [mm]	42" [1065] W x 84 ⅝"[2150] H				
	MOTOR SIZE HP [kW]	25 [18.4] 60Hz - CSA#1095178		DOOR INTERLOCK	GMV - CSA#200342				
	FEED LINE in [mm]	2 [50.8] SCHED. 40 A53-B/A106-B		FIRE RATING	UL 1½ HR - UL#R21049				
	MACHINE HEAT OUTPUT PER 25 STARTS/HR BTU/HR [W]	14927 [1480]		MANUFACTURER	GMV				
	ITEM	WEIGHT lb [kg]		DOOR SAFETY RETAINER	INCLUDED				
	EQUIPMENT WEIGHTS	CAB		898 [407.3]	OTHER	BATTERY LOWERING	Y	EMERGENCY POWER	Y
		HANG ON PANELS		186 [84.4]		SEISMIC REQUIREMENT		DOOR OPERATOR NUDGING	
HAND RAILS		49 [22.2]	CERTIFICATE FRAME			PIT SHUT OFF VALVE			
TOC		7.7 [3.49]	INCLUDE LINE RUPTURE VALVE						
COP		42 [19.0]							
TOE GUARD		47.5 [21.5]							
CAB DOOR PANELS		90 [40.8]							
DOOR OPERATOR		100 [45.4]							
DROP DOWN CEILING		55 [24.9]							
CAR FRAME		617 [280]							
FINISH FLOOR ALLOWANCE		400 [181]							
TOTAL		2492 [1132]							
HYDRAULIC JACK (2 JACK SYSTEM)		JACK MODEL	TCS-3Y TELESCOPIC JACK						
		PLUNGER 1	ØOD in [mm]	2.4 [60.5]					
	WALL THK in [mm]		0.2 [4.3]						
	LENGTH in [mm]		150 [3809.9]						
	WEIGHT lb [kg]		78.2 [35.5]						
	PLUNGER 2	ØOD in [mm]	3.0 [75.5]						
		WALL THK in [mm]	0.2 [4.3]						
		LENGTH in [mm]	147.2 [3739.9]						
		WEIGHT lb [kg]	84.1 [38.1]						
	PLUNGER 3	ØOD in [mm]	3.6 [90.5]						
		WALL THK in [mm]	0.2 [4.3]						
		LENGTH in [mm]	147.2 [3739.9]						
		WEIGHT lb [kg]	107.2 [48.6]						
	CYLINDER	ØOD in [mm]	4.2 [106.0]						
WALL THK in [mm]		0.2 [4.5]							
LENGTH in [mm]		143.7 [3649.9]							
WEIGHT lb [kg]		133 [60.6]							
TOTAL PLUNGER WEIGHT lb [kg]	324.8 [147.3]								
REACTION FORCES		FORCE	REACTION						
		PIT (R) lb [kN]	16100 [71.62]						
		F1 lb [kN]	375 [1.67]						
		F2 lb [kN]	180 [0.80]						
		REACTION FORCES ARE DOUBLED FOR IMPACT (PIT)							
		PROJECT NAME:	HARVEST CHURCH OF NEW YORK			DRAWN BY: TL			
		PROJECT NUMBER	NY1922P263798			CHECKED BY: AL			
		LOCATION	54-47 LITTLE NEAK, FLUSHING NY			DATE:			
		ELEVATOR COMPANY	K & J LIFT INC.			8/27/2026			
		GENERAL CONTRACTOR	-			SCALE: NTS REV: 0			
DRAWINGS FOR REVIEW		ARCHITECT	-			SHEET: S1-P1/9			
		DRAWING:	TECHNICAL DATA						

S1.1 - ENG CALCS - AFTER (updated fields in green)

GENERAL	CAR ID	1	CAB	CAB CONFIGURATION	FRONT ONLY				
	CODE COMPLIANCE ASME A17.1/CSA B44	2019		DIMENSIONS	[81 [2057]] W x [51 [1295]] D x [90 [2286]] H				
	CLASSIFICATION	EDGE		ENCLOSURE MATERIAL	16GA STEEL				
	SYSTEM	TWIN 1:1 DIRECT ACTING HYDRAULIC		DOOR OPERATOR	GMV 2 SPEED - CSA#1172862				
	CAPACITY lb [kg]	[2500 [1134]]		INTERLOCK	CONTACT ONLY				
	NOMINAL CAR SPEED FPM [m/s]	100 [0.50]		DOOR RE-OPENING	FULL LENGTH CURTAIN + 3D DEVICE				
	NO. OF FLOORS	[2 -]		DOOR SILL	SATIN BRUSHED ALUMINUM				
	NO. OF OPENINGS	[FRONT: 2 / REAR: 0]		COP FINISH	SATIN STAINLESS STEEL				
	POWER SUPPLY	208 3PH 60HZ		CAB LIGHT	DIFFUSER PANEL				
	FULL LOAD AMPERAGE	84		CEILING	STAINLESS STEEL REVEAL				
	OPERATION	SELECTIVE COLLECTIVE		HAND RAIL	FLAT BRUSHED STAINLESS STEEL				
	HOISTWAY CONSTRUCTION	MASONRY		WALL PANELS	HANG ON LAMINATED WALL PANELS				
	BUFFER TYPE AND STROKE in [mm]	2X BUFFER, ACLA 300401F4, 2.83 [72]		DOOR PANEL FINISH	BRUSHED STAINLESS STEEL				
	RAIL WEIGHT lb/ft	8		FINISHED FLOOR MATERIAL	UNFINISHED PLYWOOD				
MACHINE	CONTROLLER	360 CONTROLLER - CSA#1511880	CARFRAME & PLATFORM	JOISTS/STRINGERS	16GA FORMED STEEL				
	DRIVE	GMV TYPE 3		CROSSHEAD	7GA 8 X 2 FORMED STEEL				
	CONTROL VALVE	GMV 3010S - CSA#1032097		STILE	7GA 7 X 2½ FORMED STEEL				
	PUMP TYPE	3 SPINDLE SCREW		PLANK	7GA 7 X 2 FORMED STEEL				
	FEED FLOW GPM [LPM]	67 [254]		LANDING ENTRANCE CONSTRUCTION	MASONRY				
	FULL LOAD STATIC PRESSURE psi [bar]	408 [27.73]		DOOR TYPE	2 SPEED				
	FULL LOAD DYNAMIC PRESSURE psi [bar]	448 [30.86]		DOOR SIZE in [mm]	42" [1065] W x 84 ⅝" [2150] H				
	RELIEF PRESSURE psi [bar]	530 [36.53]		DOOR INTERLOCK	GMV - CSA#200342				
	MOTOR SIZE HP [kW]	25 [18.4] 60Hz - CSA#1095178		FIRE RATING	UL 1½ HR - UL#R21049				
	FEED LINE in [mm]	2 [50.8] SCHED. 40 A53-B/A106-B		MANUFACTURER	GMV				
	MACHINE HEAT OUTPUT PER 25 STARTS/HR BTU/HR [W]	14927 [1480]		DOOR SAFETY RETAINER	INCLUDED				
	EQUIPMENT WEIGHTS	ITEM		WEIGHT lb [kg]	OTHER	BATTERY LOWERING	☒	EMERGENCY POWER	☐
		CAB		898 [407.3]		SEISMIC REQUIREMENT	☐	DOOR OPERATOR NUDGING	☒
		HANG ON PANELS		186 [84.4]		CERTIFICATE FRAME	☐	PIT SHUT OFF VALVE	☒
HAND RAILS		49 [22.2]	INCLUDE LINE RUPTURE VALVE	☐					
TOC		7.7 [3.49]							
COP		42 [19.0]							
TOE GUARD		47.5 [21.5]							
CAB DOOR PANELS		90 [40.8]							
DOOR OPERATOR		100 [45.4]							
DROP DOWN CEILING		55 [24.9]							
CAR FRAME		617 [280]							
FINISH FLOOR ALLOWANCE		400 [181]							
TOTAL		2492 [1132]							
HYDRAULIC JACK (2 JACK SYSTEM)		JACK MODEL	TCS-3Y TELESCOPIC JACK						
	PLUNGER 1	ØOD in [mm]	2.4 [60.5]						
		WALL THK in [mm]	0.2 [4.3]						
		LENGTH in [mm]	150 [3809.9]						
		WEIGHT lb [kg]	78.2 [35.5]						
	PLUNGER 2	ØOD in [mm]	3.0 [75.5]						
		WALL THK in [mm]	0.2 [4.3]						
		LENGTH in [mm]	147.2 [3739.9]						
		WEIGHT lb [kg]	84.1 [38.1]						
	PLUNGER 3	ØOD in [mm]	3.6 [90.5]						
		WALL THK in [mm]	0.2 [4.3]						
		LENGTH in [mm]	147.2 [3739.9]						
		WEIGHT lb [kg]	107.2 [48.6]						
	CYLINDER	ØOD in [mm]	4.2 [106.0]						
WALL THK in [mm]		0.2 [4.5]							
LENGTH in [mm]		143.7 [3649.9]							
WEIGHT lb [kg]		133 [60.6]							
TOTAL PLUNGER WEIGHT lb [kg]	324.8 [147.3]								

REACTION FORCES		FORCE	REACTION
		PIT (R) lb [kN]	16100 [71.62]
		F1 lb [kN]	375 [1.67]
		F2 lb [kN]	180 [0.80]
		REACTION FORCES ARE DOUBLED FOR IMPACT (PIT)	

DRAWINGS FOR REVIEW	PROJECT NAME:	HARVEST CHURCH OF NEW YORK	DRAWN BY:	TL
	PROJECT NUMBER	NY1922P263798	CHECKED BY:	AL
	LOCATION	54-47 LITTLE NEAK, FLUSHING NY	DATE:	8/27/2026
	ELEVATOR COMPANY	K & J LIFT INC.	SCALE:	NTS
	GENERAL CONTRACTOR	-	REV:	0
	ARCHITECT	-	SHEET:	S1-P1/9
	DRAWING:	TECHNICAL DATA		

S1.2 - ELEVATION VIEW - AFTER (updated fields in green)

NOTE:
HOISTWAY BEAM SUITABLE FOR SUPPORT OF
FALL PROTECTION. 5000LBS CAPACITY.
LEAVE A 2" GAP (MIN.) BETWEEN THE
UNDERSIDE OF THE FINISHED CEILING AND
THE BEAM.

SECTION 1 NOT TO BE USED FOR BUILDING CONSTRUCTION

RAIL MAX BRACKET
SPACING 64" [1625mm]

HOISTWAY SECTION VIEW

FLOORS	DISTANCE (INCH)
*G TO 2	125"
1 TO 2	126"
2 TO 3	120"

		PROJECT NAME:	HARVEST CHURCH OF NEW YORK	DRAWN BY: TL
		PROJECT NUMBER	NY1922P263798	CHECKED BY: AL
		LOCATION	54-47 LITTLE NEAK, FLUSHING NY	DATE:
		ELEVATOR COMPANY	K & J LIFT INC.	8/27/2026
		GENERAL CONTRACTOR	-	SCALE: NTS REV: 0
		ARCHITECT	-	SHEET: S1-P3/9
DRAWINGS FOR REVIEW		DRAWING:	ELEVATION VIEW	

S1.5 - CAB DETAIL - BEFORE (standard template)

[illegible]

S1.5 - CAB DETAIL - AFTER (updated fields in green)

[illegible]

S1.7 - COP DETAIL - BEFORE (standard template)

SECTION 1 NOT TO BE USED FOR BUILDING CONSTRUCTION

X2 KEY LOCKS

FIRE FIGHTER INDICATOR LIGHT

EMERGENCY LIGHT

ENGRAVING PLATE

DIGITAL DIRECTION POSITION INDICATOR

TWO-WAY VISUAL COMMUNICATION SYSTEM

CALL ACKNOWLEDGED

PHASE II FIRE SERVICE BEHIND LOCKED PANEL, ALL FIRE SERVICE KEYED TO FEOK1

DIRECTION INDICATOR ON CAB STRIKE JAMB

SS REVEAL

LED ILLUMINATED RINGS

SS CENTER

FLOOR WITH BRAILLE DESIGNATION

VISUAL COMMUNICATION ACKNOWLEDGE

FRONT DOOR OPEN

ALARM

IN CAR STOP

ACCESS SWITCH

FLOOR BUTTON

VISUAL COMMUNICATION DECLINE

FRONT DOOR CLOSE

HANDS FREE PHONE

INDEPENDENT SERVICE

NOTE:
-STANDARD STYLE PUSH BUTTONS
-FINISH IS SATIN STAINLESS STEEL
-STANDARD ASME/A17.1 FIRE SERVICE UNLESS OTHERWISE NOTED (WHEN FIRE SERVICE IS PROVIDED)

COVER MATERIAL	BRUSHED STAINLESS STEEL		
PUSH BUTTONS	STANDARD		
OPENINGS	4		
FLOOR MARKINGS	*G / 1 / 2 / 3		
KEY SWITCHES	X	STANDARD	- ACCESS OFF/ON
	X	LIGHT (AUTO)	- DOOR HOLD
	X	FAN (AUTO)	- MED EMERG. LIGHT
	X	INDEPENDENT SERV.	- OTHER
STOP SWITCH	KEY SWITCH		
FIRE SERVICE	X	YES	- NO
TELEPHONE	INSIDE COMPARTMENT, CALL WITH PUSHBUTTON		
ENGRAVING	2300 [1043]		
NUDGING BUZZED	X	YES	- NO
SMARTVIEW SYSTEM	X	YES	- NO

PROJECT NAME: HARVEST CHURCH OF NEW YORK

PROJECT NUMBER: NY1922P263798

LOCATION: 54-47 LITTLE NEAK, FLUSHING NY

ELEVATOR COMPANY: K & J LIFT INC.

GENERAL CONTRACTOR: -

ARCHITECT: -

DRAWING: CAR OPERATING PANEL

DRAWN BY: TL

CHECKED BY: AL

DATE: 8/27/2026

SCALE: NTS

REV: 0

SHEET: S1-P8/9

DRAWINGS FOR REVIEW

S1.7 - COP DETAIL - AFTER (updated fields in green)

SECTION 1 NOT TO BE USED FOR BUILDING CONSTRUCTION

X2 KEY LOCKS

FIRE FIGHTER INDICATOR LIGHT

EMERGENCY LIGHT

ENGRAVING PLATE

DIGITAL DIRECTION POSITION INDICATOR

TWO-WAY VISUAL COMMUNICATION SYSTEM

CALL ACKNOWLEDGED

PHASE II FIRE SERVICE BEHIND LOCKED PANEL, ALL FIRE SERVICE KEYED TO FEOK1

DIRECTION INDICATOR ON CAB STRIKE JAMB

SS REVEAL

LED ILLUMINATED RINGS

SS CENTER

FLOOR WITH BRAILLE DESIGNATION

VISUAL COMMUNICATION ACKNOWLEDGE

FRONT DOOR OPEN

ALARM

IN CAR STOP

ACCESS SWITCH

FLOOR BUTTON

VISUAL COMMUNICATION DECLINE

FRONT DOOR CLOSE

HANDS FREE PHONE

INDEPENDENT SERVICE

NOTE:
-STANDARD STYLE PUSH BUTTONS
-FINISH IS SATIN STAINLESS STEEL
-STANDARD ASME/A17.1 FIRE SERVICE UNLESS OTHERWISE NOTED (WHEN FIRE SERVICE IS PROVIDED)

COVER MATERIAL	BRUSHED STAINLESS STEEL		
PUSH BUTTONS	STANDARD		
OPENINGS	2		
FLOOR MARKINGS	*G / 2		
KEY SWITCHES	X	STANDARD	- ACCESS OFF/ON
	X	LIGHT (AUTO)	- DOOR HOLD
	X	FAN (AUTO)	- MED EMERG. LIGHT
	X	INDEPENDENT SERV.	- OTHER
STOP SWITCH	KEY SWITCH		
FIRE SERVICE	X	YES	- NO
TELEPHONE	INSIDE COMPARTMENT, CALL WITH PUSHBUTTON		
ENGRAVING	2500 [1134]		
NUDGING BUZZED	X	YES	- NO
SMARTVIEW SYSTEM	X	YES	- NO

PROJECT NAME: HARVEST CHURCH OF NEW YORK

PROJECT NUMBER: NY1922P263798

LOCATION: 54-47 LITTLE NEAK, FLUSHING NY

ELEVATOR COMPANY: K & J LIFT INC.

GENERAL CONTRACTOR: -

ARCHITECT: -

DRAWING: CAR OPERATING PANEL

DRAWN BY: TL

CHECKED BY: AL

DATE: 8/27/2026

SCALE: NTS

REV: 0

SHEET: S1-P8/9

DRAWINGS FOR REVIEW