

Parisar — Production Readiness Report

Society management platform · Next.js + Expo + Supabase

Generated 2026-06-14 · Source: .planning/PRODUCTION-READINESS.md (1,660 lines)

Parisar — Production Readiness Report

Document type: Production-readiness audit **Audit date:** 2026-06-14 **Audited against:** v1.0 milestone, Phase 7 mid-execution (6 of 10 plans complete) **Repository:** `/home/nexapp/Documents/personal/parisar` **Audience:** Founder / engineering lead / product owner — decision-grade

1. Executive Summary

1.1 Product

Parisar is an Indian residential-society management platform spanning a **Next.js 15 web companion** and an **Expo SDK 55 React Native mobile app**, both backed by a single **Supabase Postgres + Auth + Realtime + Storage** project. The product replaces the WhatsApp + paper-notice + spreadsheet workflow most Indian societies use today with an attributed, status-traced, multi-tenant app for **complaints, notifications/polls, amenity bookings, flat-level actions (warning/fine/notify), and a moderated community feed**. Two roles drive everything: **Secretary** (and the mandatory **Co-Secretary** with identical powers) sets up the society and takes flat actions; **Members** (with **Board Members** as a powered-up subset) file complaints, vote in polls, book amenities, and post to the feed. The single non-negotiable loop the product must defend is **Member → Complaint → Board Member responds → Status updates → Member notified**.

1.2 Readiness verdict (plain words)

Nearly ready, not ready. Every v1 *feature phase* (1, 2, 3, 04.1, 4, 5, 6) is shipped, code-reviewed, and the schema/RPC/RLS layer is locked behind 16 isolation test suites (~4,585 lines, all green against the live local Supabase). Phase 7 — the cross-cutting i18n retrofit, dashboard live-data wiring, and web parity — is **6 of 10 plans complete**: the i18n runtime is live on both apps, every screen has been mechanically retrofitted to `useTranslation`, the dashboard summary RPC ships and is isolation-tested. What remains: dashboard live-data UI wiring (Plans 07-07 / 07-08), advisory-debt fixes (Plan 07-09), and the final responsive + Devanagari + Maestro UAT pass (Plan 07-10). After Phase 7, **Phase 8**

— **Launch Readiness** is wholly unstated: production OTP swap, captcha, Sentry, DPDP erasure, and DLT verification.

There are also ~40 outstanding **HUMAN-UAT items across phases 2, 3, 4, 04.1, 5, 6** — real-device walkthroughs (FCM delivery, Devanagari rendering on OEM Android, 2-device booking race, image-safety reject, Realtime auto-hide cross-device, audit-log review). None are code gaps; all need a phone in hand. They are *ship-blocking quality gates*, not engineering work.

1.3 Top 5 blockers to production

#	Blocker	Owner	Effort	Phase
1	OTP provider not chosen — production SMS adapter (MSG91 / Twilio / Firebase) and the DLT registration that gates it are a 2–6 week external clock. Dev stub <code>123456</code> blocks any real-user pilot.	User (procurement)	2–6 weeks calendar, ~1 day engineering after decision	Phase 8 — LAUNCH-01, LAUNCH-04
2	Phase 7 not finished — DASH-03 live-data tiles, advisory-debt unification, responsive audit, Devanagari golden-screenshot gate, Maestro language-switch + dashboard-preview flows.	Engineering	4 plans (Plans 07-07 → 07-10), est. 1.5–2.5 days at observed velocity	Phase 7
3	No production captcha / no Sentry / no DPDP erasure flow — captcha on OTP endpoint and crash reporting on both clients are launch-blockers; DPDP erasure has the RPC (<code>remove_member</code>) but no member-facing flow.	Engineering	1 day captcha + 0.5 day Sentry + 1 day DPDP UX	Phase 8 — LAUNCH-02/03/05
4	40+ HUMAN-UAT items across phases 2/3/4/04.1/5/6 are pending — every Phase reaches <code>human_needed</code> verification status because real-device behaviors (FCM, Devanagari on OEM Android, 2-device races, image-safety reject, cross-device auto-hide) cannot be verified headlessly.	Founder / QA tester with two Indian Android devices	4–6 hours hands-on with two devices	All shipped phases
5	No CI/CD to staging or production environments — CI has 5 jobs (lint, typecheck, unit tests, isolation, Devanagari-bundle) that block merges, but there is no deploy pipeline to Vercel/EAS, no staging Supabase project, no production secrets/env management. Today the app runs only against <code>localhost:54321</code> .	DevOps	1–2 days for Vercel + EAS + staging Supabase + secrets	Phase 8 (implied)

Honourable mentions, *not* in the top 5 but called out in §15 P1: visitor/gate/staff/vendor (Phases 9–11) are post-launch — they are scope, not a blocker — but the founder should resist scope creep until v1 ships.

2. Product Scope

2.1 Core value loop (the one thing that must work)

```
Member files a complaint → Board Member responds (atomic claim)
      ↓                      ↓
Status update written ← Status changes (Realtime + push)
      ↓
Member receives push → Opens app → Sees attributed trail
                                   ("Approved by Amit (A-102) at 14:32")
```

Concretely on the codebase:

- **Filing:** `apps/{mobile,web}` complaint form → `packages/api-client/src/complaints.js` `fileComplaint()` → `file_complaint()` SECURITY DEFINER RPC inserts complaint + (optional) attachment row + audit_log row in one transaction.
- **Realtime broadcast:** `complaints` and `complaint_responses` are in the `supabase_realtime` publication. Board members' lists patch in place via `subscribeToComplaints` / `subscribeToComplaintResponses` on a per-society channel.
- **Atomic claim:** First board member's tap fires `claim_complaint()` RPC → `UPDATE complaints SET owner_id = caller WHERE owner_id IS NULL RETURNING *` — the second concurrent caller's `RETURNING` is `NULL` and the UI surfaces the winner's name + flat. Verified by `tests/isolation/complaints.test.js` Test 6 (`Promise.all` race; exactly one winner).
- **Push fan-out:** `complaint_responses` AFTER INSERT trigger `notify_push_on_response()` fires `net.http_post` (pg_net, fire-and-forget) to the `push-fanout` Edge Function with sentinel header `x-push-trigger: true`. The function batches Expo Push API calls (≤ 100 /batch), handles `DeviceNotRegistered` cleanup.
- **Deep-link:** Mobile root `_layout.jsx` registers a notification-tap handler that routes on `data.screen` → `router.push('/(protected)/(tabs)/complaints/<id>')`.

Verified end-to-end except FCM delivery on a physical device (the only HUMAN-UAT gap on this loop).

2.2 Roles

Role	JWT claim	DB representation	Powers
Secretary	<code>role='secretary'</code>	<code>society_memberships.role='secretary'</code> (one per society at a time)	Full admin: create society, configure structure, add board, issue flat actions, waive fines, moderate community, remove members, rotate code, transfer role
Co-Secretary	<code>role='co_secretary'</code>	Auto-elevated on <code>redeem_society_code()</code> when caller phone matches <code>societies.co_secretary_phone</code>	Identical to Secretary (SETUP-08 contract; verified at RPC layer — every <code>secretary</code> - gated RPC also accepts <code>co_secretary</code>)
Board Member	<code>role='board_member'</code>	Added by Secretary during society setup	Can respond to complaints, approve/reject bookings, see flat actions (read-only), post society notices/polls. Cannot issue flat actions or waive fines.
Member	<code>role='member'</code>	Default for any user who redeems a society code	File complaints, vote in polls, request bookings, post to community feed, see own-flat actions, acknowledge own fines
Family Member	n/a — contact only	<code>family_members</code> row attached to a membership	No auth account, no push. Listed in directory; appears as a push recipient when an account-holding family member's flat receives a flat action (push lands on account-holding residents).

Role transfer is supported (`transfer_secretary_role()` RPC); the outgoing Secretary becomes a `member` and the named co-secretary or board member becomes `secretary` . There is **no in-app election** — that is explicitly v2 (ELEC-01).

2.3 Out of scope (explicitly punted in PROJECT.md / REQUIREMENTS.md)

Excluded	Reason
Payments / fine collection	User-explicit. Fines are recorded as text + amount + due date only. No gateway, no settlement, no PCI scope. Footer in en/hi/mr locked-verbatim per fine reading "Parisar does not collect payment" (FLAT-05).
Maintenance bills / dues ledger	Adjacent to payments; v1.1+.
Visitor / gate management (QR check-in)	MyGate's flagship — Phase 9 (post-launch). Not in v1.
Staff / help attendance	Phase 10 (post-launch).
Vendor directory	Phase 11 (post-launch).
Document vault	One attachment per notification only; bylaws/AGM archive deferred to v2 (DOC-01).
Cross-society messaging or admin tooling	Each society is an isolated tenant. No inter-society features.
Email notifications	Push + in-app only.
Offline support beyond minimal cache	App requires connectivity (Realtime is core).
In-app chat / DMs between members	Slack/WhatsApp territory.
In-app election workflow	v1 is manual Secretary handover via <code>transfer_secretary_role()</code> . ELEC-01 in v2.
Multi-society users	Schema supports it; the v1 auth hook picks the most-recent active membership. MULTI-01 in v2.
Owner-only polls	Schema reservation only; POLL-01 in v2.
Voice messages on complaints/posts	Schema reservation (<code>attachments.mime_type</code> , <code>duration_seconds</code>); VOICE-01 in v2.
Comments on community posts (as a feature)	The <code>post_comments</code> table exists and is RLS'd, but UX/promotion is v1.1+. CMNT-01 in v2.

3. Technology Stack (current state)

Versions verified by reading `apps/web/package.json` and `apps/mobile/package.json` at audit time.

3.1 Web (Next.js)

Layer	Library	Installed version	Notes
Framework	Next.js	15.2.4	App Router; React 19; Turbopack dev. Per CLAUDE.md do NOT jump to Next 16.
Runtime	React + React DOM	19.0.0	Pinned with Next 15.
Auth glue	@supabase/ssr	0.10.2	Cookie-based session, server actions, RSC-safe. Not the deprecated <code>auth-helpers-nextjs</code> .
Supabase client	@supabase/supabase-js	2.103.3	Same version on mobile.
Styling	Tailwind CSS	4.2.4 (via @tailwindcss/postcss@4.2.4)	v4.
UI primitives	@base-ui/react	^1.5.0	shadcn <code>base-nova</code> preset; copy-in components live in <code>apps/web/components/ui/</code> .
Forms	(none of RHF) — relies on server actions + native form state	n/a	RHF only ships in mobile.
Date	date-fns	^4.3.0	hi/mr locales used for relative time.
i18n runtime	i18next + react-i18next + i18next-resources-to-backend	26.3.0 / 17.0.8 / 1.2.1	Cookie-backed locale (<code>parisar_lang</code> , SameSite=Lax, Secure, non-HttpOnly so client can read).
Icons	lucide-react	^1.16.0	
Tooling	vitest + @testing-library/react + jsdom	2.1.8 / 16.1.0 / 25.0.1	Single test runner for the web app.
Lint	biome (root)	2.3.3	Replaces ESLint + Prettier monorepo-wide.
Client state	zustand	^5.0.2	Used in <code>apps/web/lib/wizard-store.js</code> for the multi-page setup wizard.

3.2 Mobile (Expo + React Native)

Layer	Library	Installed version	Notes
Runtime	Expo SDK	~55.0.0	New Architecture is mandatory and always-on.
React Native	(pinned by Expo 55)	0.83.0	Do NOT upgrade RN independently.
Router	expo-router	~5.0.0	File-based; powers FCM deep-link auto-config.
Local storage	@react-native-async-storage/async-storage	2.1.0	Stores parisar_lang .
Secure storage	expo-secure-store	~15.0.0	Backs Supabase auth session.
Localization seed	expo-localization	~17.0.7	Reads device locale → seeds i18next.
Notifications	expo-notifications	~55.0.23	FCM via Expo Push.
Image pipeline	expo-image-picker + expo-image-manipulator + expo-image + expo-file-system	bundled	Resize ≤1600px / quality 0.7 / base64 → ArrayBuffer → Supabase Storage.
Document picker	expo-document-picker	~55.0.13	Fine PDF attachments.
Devanagari fonts	@expo-google-fonts/noto-sans-devanagari + @expo-google-fonts/noto-sans	^0.4.0	Bundled so OEM ROM font fallbacks don't break conjuncts.
Styling	NativeWind + Tailwind	4.1.23 on tailwindcss @3.4.17	Tailwind 3 on mobile, Tailwind 4 on web — separate builds, shared tokens via @parisar/ui-tokens JS object (NOT a shared tailwind.config).
Animation	react-native-reanimated	~3.10.0	(CLAUDE.md prescribes 4.x; installed is 3.x — pinned by Expo 55.)
Forms	react-hook-form + @hookform/resolvers	^7.76.1 / ^5.4.0	Composers, joining flow, setup wizard.
i18n runtime	i18next + react-i18next + i18next-resources-to-backend	same as web	
Date	date-fns	^4.3.0	hi/mr locales.
Icons	lucide-react-native	0.469.0	Same set as web.

Layer	Library	Installed version	Notes
Test	<code>jest</code> (jest-expo preset) + <code>@testing-library/react-native</code>	<code>29.7.0</code> / <code>12.9.0</code>	Two test runners (Vitest web / Jest mobile) is intentional.

3.3 Backend (Supabase)

Component	What	Notes
Postgres	Local dev: <code>supabase</code> CLI (port 54321)	10 migrations, all applied; live DB matches migration set.
Extensions	<code>uuid-oss</code> , <code>pgcrypto</code> , <code>pg_net</code> , <code>btree_gist</code>	<code>pg_net</code> powers fire-and-forget push triggers; <code>btree_gist</code> powers the booking overlap exclusion constraint.
Auth hook	<code>inject_society_claims(jsonb)</code> as <code>pg-functions://postgres/public/inject_society_claims</code>	Fires on every sign-in AND refresh; injects <code>society_id</code> + <code>role</code> into <code>app_metadata</code> .
Auth SMS hook	<code>[auth.hook.send_sms]</code> → <code>send-sms</code> Edge Function	Dispatches to <code>OTP_PROVIDER</code> env var: <code>stub</code> (dev), <code>msg91</code> , <code>twilio</code> . The latter two are Phase 8 placeholders (throw <code>not yet implemented</code>).
Edge Functions	6 Deno functions under <code>supabase/functions/</code>	See §4.4.
Storage	Single bucket <code>parisar-attachments</code> , private, 50 MB file size limit	Prefix-RLS: first path segment = society UUID.
Realtime	<code>supabase_realtime</code> publication has 8 tables added	complaints, complaint_responses, notifications, poll_votes, bookings, flat_actions, posts, post_comments.
Auth provider config	<code>[auth.sms.twilio]</code> placeholder with <code>account_sid='dev-placeholder'</code>	Required workaround for Supabase CLI v2.98.2 to enable phone auth even when <code>[auth.sms.test_otp]</code> is set. Documented in 02-VERIFICATION.md; must be removed before production.

3.4 Tooling

Tool	Version	Use
pnpm	9.15.0	Workspace manager (<code>pnpm-workspace.yaml</code> covers <code>apps/*</code> , <code>packages/*</code> , <code>tests/*</code>).
Turborepo	2.3.3	Pipeline orchestration (<code>build</code> , <code>dev</code> , <code>lint</code> , <code>test</code> , <code>test:isolation</code> , <code>clean</code>).
Biome	2.3.3	Lint + format on every package.
Vitest	2.1.8	Web app + every JS package + isolation tests.
Jest + jest-expo	29.7.0 / ~55.0.0	Mobile app.
Supabase CLI	(local)	<code>supabase start</code> / <code>supabase db reset</code> .

3.5 What is NOT yet wired (gaps from CLAUDE.md stack)

The CLAUDE.md "Recommended Stack" lists several things that are not yet installed because they belong to Phase 8 or because the user picked a simpler default:

- **TanStack Query** — not installed. Realtime + Zustand + raw Supabase calls cover today's needs. Risk: optimistic-update boilerplate around mutations is hand-rolled per call site.
 - `@sentry/nextjs` + `@sentry/react-native/expo` — not installed. Belongs to Phase 8 LAUNCH-03.
 - **PostHog** — not installed; optional per CLAUDE.md.
 - **Maestro** — not yet installed; planned in Phase 7 Plan 07-10 for language-switch + dashboard-preview flows.
 - **Playwright** — not installed; reserved for Phase 8 e2e of web auth + complaints flow.
 - **EAS Build / EAS Submit** — not configured; Phase 8.
-

4. Repository & Workspace Layout

4.1 Top-level structure

```
parisar/
├── apps/
│   ├── web/           Next.js 15.2 App Router companion site
│   └── mobile/        Expo SDK 55 React Native iOS/Android app
├── packages/
│   ├── api-client/    Shared Supabase RPC wrappers + helpers (single source of truth)
│   ├── i18n/          en/hi/mr locale JSON shards + runtime factory + namespaces
│   ├── shared-types/  Shared JS enum constants (matches Postgres enums)
│   ├── ui-tokens/     Color + spacing JS object – feeds both Tailwind builds
│   └── config/         Shared biome.json template + tooling configs
├── supabase/
│   ├── migrations/    10 SQL files, schema-as-code
│   ├── functions/     6 Deno Edge Functions
│   ├── seed.sql       Two deterministic-UUID test societies
│   └── config.toml     Auth hooks, rate limits, SMS provider config
├── tests/
│   └── isolation/      16 Vitest test files (4,585 LOC) against live local Supabase
├── scripts/
│   ├── check-devanagari-bundle.mjs
│   ├── check-i18n-coverage.mjs
│   └── check-no-direct-locale-import.mjs
├── .github/workflows/
│   ├── ci.yml          5-job CI pipeline
│   └── devanagari-bundle-check.yml
├── .planning/          Local-only planning artifacts (NOT in git per user decision)
├── biome.json          Root lint+format config
├── turbo.json          Pipeline + globalEnv allowlist for Supabase env vars
├── pnpm-workspace.yaml
└── package.json        Root scripts: turbo run *
```

4.2 `packages/api-client/src/` (the shared call layer)

All 10 source files are pure JavaScript. Both `apps/web` and `apps/mobile` import via `workspace:*`:

```
api-client/src/
├── index.js           Re-exports every helper
├── supabase.js        createSupabaseClient factory (consumed by both apps with their own
├── otp.js             isValidIndianMobile, toE164, isValidOtp, isNewUser
├── society.js         19+ helpers for Phase 3 (create, finalize, bootstrap, list, redee
├── complaints.js      8 helpers: file, claim, respond, list, detail, subscribe x2, pus
├── notifications.js   fileNotification + listNotices + getNoticeDetail + subscribeToNo
├── polls.js           voteOnPoll, closePoll, subscribeToVotes
├── bookings.js        requestBooking, approveBooking (atomic), rejectBooking, listBook
├── preferences.js     ensureNotificationPreferences (UPSERT), getNotificationPreference
├── flat-actions.js     issueFlatAction, listFlatActions, getFlatAction, acknowledgeFine
├── community.js       createPost (quarantine→moderate→insert handoff), listPosts, getPo
├── dashboard.js       getDashboardSummary + envelope normalizer (Phase 7 Plan 07-02)
└── uuid.js            gen() shim
```

Tests live in `packages/api-client/src/__tests__` . Phase 5/6 summaries cite ~173 api-client unit tests; the file count confirms thorough coverage of utility branches (OTP regex, phone formatting, payload shapes).

4.3 `packages/i18n/` — locale shards

```
packages/i18n/
├── src/
│   ├── index.js
│   ├── namespaces.js      NAMESPACES = ['auth','complaints','dashboard','notifications
│   ├── backend.js         Static-map backend for resources-to-backend
│   └── create-instance.js  createI18nInstance(lng, resources, isClient)
└── locales/
    ├── en.json            Flat-top legacy bundle (auth/setup/dashboard-legacy/etc.) → T
    ├── hi.json
    ├── mr.json
    ├── en/{bookings,community,complaints,dashboard,flat-actions,moderation,notifications,p
    ├── hi/(same 9)
    └── mr/(same 9)
```

All 9 phase shards × 3 locales (= 27 shard files) have **verified key parity** (`scripts/check-i18n-coverage.mjs`). Devanagari coverage is enforced by `scripts/check-devanagari-bundle.mjs` (code-point scan over hi and mr shards). The FLAT-05 no-payment footer is byte-exact across all three locales — proven by `packages/i18n/__tests__/locked-verbatim.test.js` .

4.4 supabase/functions/ (Edge Functions)

Function	Trigger	Auth	Job
send-sms	[auth.hook.send_sms] Auth Hook	StandardWebhooks (built-in)	Dispatch on OTP_PROVIDER env var: stub (no-op, dev) / msg91 / twilio (latter two are throw-not-implemented Phase 8 placeholders); enforces per-phone rate limit via otp_requests table (MAX 5/hr).
push-fanout	complaint_response AFTER INSERT trigger via net.http_post	sentinel header x-push-trigger: true	Resolves recipients (reporter), batches Expo Push (≤100), deletes DeviceNotRegistered tokens.
notification-fanout	notifications AFTER INSERT trigger	sentinel	Resolves recipients via eligible_push_recipients() RPC (mute + IST quiet-hours wrap + rolling 24h cap), batches Expo Push, logs to push_deliveries .
booking-ack-fanout	bookings AFTER UPDATE OF status (pending → approved/rejected)	sentinel	Single-recipient push to requester with generic body.
flat-action-fanout	flat_actions AFTER INSERT trigger	sentinel	Flat-scoped recipients via flat_action_recipients() RPC; generic body "Your flat has a new notice" (no amount/kind leak on lock screen).
moderate-image	RPC-invoked by community.js createPost (sync, blocking)	service-role	Swappable adapter (MODERATION_PROVIDER : stub / vision / rekognition); quarantine → moderate → move-on-PASS / remove-on-REJECT; fail-closed {ok:false, error:'check_failed'} ; key-prefix guard {society}/quarantine/{postId}/ .

All 6 are Node- --check clean and have unit tests inside supabase/functions/<name>/__tests__/ or covered indirectly via isolation tests.

4.5 CI/CD status

CI (GitHub Actions, .github/workflows/ci.yml): 5 jobs on every push.

Job	Tool	Blocking?
lint	biome check .	Yes
typecheck	tsc --noEmit (jsconfig.json type-check)	Yes
unit-tests	turbo run test (Vitest web/api-client/i18n + Jest mobile)	Yes
isolation-test	pnpm --filter @parisar/isolation-test run test:isolation against ephemeral Supabase	Yes — the cross-tenant gate
devanagari-bundle	scripts/check-devanagari-bundle.mjs	Yes
i18n-gates (added Phase 7 Plan 07-01)	scripts/check-i18n-coverage.mjs + scripts/check-no-direct-locale-import.mjs --dir apps	Yes (promoted in Plan 07-06)

The intended regenerate-types-check job from Phase 1's plan was intentionally omitted when the user picked plain JavaScript over TypeScript (recorded as an override in 01-VERIFICATION.md).

CD: None. There is no GitHub Action that deploys to Vercel, no eas.json , no staging Supabase project, no production secrets management. The user's git workflow is also configured for no commits / no remote (per CLAUDE.md), so a CD pipeline would also need a hosting decision first.

5. Phase-by-Phase Status

Sourced from .planning/ROADMAP.md , each phase's *-VERIFICATION.md , and the SUMMARYs of completed plans.

5.1 Summary table

Phase	Plans complete	Status	Completed	Verification status
1. Foundation	4 / 4	Complete	2026-05-20	passed
2. Auth + OTP Adapter	4 / 4	Complete	2026-05-22	human_needed (4 mobile-on-device items)
3. Society Setup & Member Onboarding	10 / 10	Complete	2026-05-26	human_needed (7 multi-step UAT walkthroughs)
4. Complaints (Lighthouse)	5 / 5	Complete	2026-05-26	human_needed (mobile + web UAT)
04.1. Dashboard Shell (INSERTED)	6 / 6	Complete	2026-05-28	human_needed (6 device/browser items)
5. Notifications, Polls & Bookings	6 / 6	Complete	2026-05-29	human_needed (6 FCM/race/Devanagari items)
6. Flat Actions & Community Feed	6 / 6	Complete	2026-05-29	human_needed (6 FCM/image-safety/cross-device items)
7. Dashboards, i18n Polish & Web Parity	6 / 10	Executing	—	n/a (no VERIFICATION.md yet)
8. Launch Readiness	0 / 4	Not started	—	n/a
9–11. MyGate features (post-launch)	0 / TBD	Not started	—	n/a

Aggregate: 41 of 51 planned plans complete across 7 of 9 active phases. STATE.md self-reports 80% complete.

5.2 Phase 1 — Foundation (complete 2026-05-20)

Goal: Multi-tenant database, monorepo, and CI with provably-isolated tenancy. **Requirements:**

FOUND-01..05 (5/5 satisfied). **Plans:**

- 01-01 monorepo bootstrap — pnpm + Turborepo + Next 15.2 + Expo SDK 55 + 5 shared packages.
- 01-02 Supabase schema + RLS + Auth Hook — migrations 1–4 (init_tenancy, current_society_id helper, RLS policies, storage bucket RLS); inject_society_claims Postgres function; 2 seeded societies.
- 01-03 CI pipeline — 5 jobs (lint, typecheck, unit, isolation, devanagari).
- 01-04 apps boot + isolation test — web @supabase/ssr , mobile SecureStore , tests/isolation/cross-tenant-isolation.test.js (20 assertions, 756ms).

Shipped:

- 8 tenancy tables (societies, society_codes, wings, flats, profiles, society_memberships, family_members, push_tokens) — all RLS-enabled.

- `current_society_id()` and `current_membership_role()` STABLE SQL helpers reading `request.jwt.claims`.
- Storage bucket `parisar-attachments` (private, 50 MB) with prefix-based RLS using `storage.foldername(name)[1]::uuid`.
- "Hello {society name}" smoke screens on both apps reading the JWT-derived society.
- 20/20 isolation tests passing.

Outstanding: None. `01-VERIFICATION.md` accepts the JS-only override of the planned `regenerate-types-check` job.

Key files: `supabase/migrations/20260430000000{1,2,3,4}_*.sql`, `apps/web/lib/supabase/{server,client,middleware}.js`, `apps/mobile/lib/{supabase,secure-storage}.js`, `tests/isolation/cross-tenant-isolation.test.js`.

5.3 Phase 2 — Auth + OTP Adapter (*complete 2026-05-22*)

Goal: Phone-OTP auth on both apps, behind a swappable adapter. **Requirements:** AUTH-01..07 (7/7 satisfied). **Plans:**

- 02-01 Backend — migration `20260520000005_auth_phase2.sql` (profiles.signup_intent column + otp_requests rate-limit table); `[auth.sms]/[test_otp]/[send_sms]` config blocks; `send-sms` Edge Function with adapter seam.
- 02-02 Shared helpers — `packages/api-client/src/otp.js` (4 functions); 30 auth i18n keys × en/hi/mr.
- 02-03 Mobile — 5 screens (login, verify, onboard, dashboard placeholder, logout), Zustand auth store, `Stack.Protected` guard, SecureStore session.
- 02-04 Web — 5 pages, shadcn UI, server actions, server-component getUser() guard, `@supabase/ssr` cookie session, `<form action={signOutAction}>` logout.

Shipped:

- Dev OTP `123456` for 4 test phones (`+91900000000{0..3}`) via `[auth.sms.test_otp]`.
- OTP adapter abstraction (stub / msg91 / twilio); `msg91` and `twilio` are throw-not-implemented placeholders for Phase 8.
- Per-phone rate limit (`otp_requests` table, ≤5 OTP/hr enforced by Edge Function).
- Per-IP rate limit via `[auth.rate_limit]` (sms_sent=30/hr; sign_in_sign_ups=30/5min).
- `profiles.signup_intent` CHECK constraint (`'secretary' | 'member'`) consumed by Phase 3.
- 27/27 isolation tests (3 rate-limit + 4 OTP flow + 20 cross-tenant) green on fresh DB.

Outstanding (HUMAN-UAT):

1. Mobile OTP flow end-to-end on real device.
2. Mobile session persistence across kill-and-relaunch.
3. Mobile one-tap logout.
4. Devanagari rendering of auth strings on real OEM Android.

Key files: `supabase/migrations/20260520000005_auth_phase2.sql`, `supabase/functions/send-sms/{index.js,adapters/*.js}`, `apps/{web,mobile}/app/(auth)/*`,

`apps/{web,mobile}/app/(protected)/onboard.{jsx,page.jsx}` , `apps/web/app/actions/auth.js` , `apps/mobile/lib/auth-store.js` .

5.4 Phase 3 — Society Setup & Member Onboarding (*complete 2026-05-26*)

Goal: Secretary stands up a society end-to-end (structure, board, amenities, code); members self-onboard without abuse. **Requirements:** SETUP-01..10 + ONBD-01..08 (18/18 satisfied). **Plans (split to 10 per checker revision 2026-05-25):**

- 03-01 Backend migration + 12 SECURITY DEFINER functions + 5 isolation suites.
- 03-02 api-client `society.js` (19+ helpers) + en/hi/mr i18n keys.
- 03-03 shadcn primitives + cross-cutting components (WizardProgress, DestructiveConfirmDialog, JoinedPercentGauge, PhonePrivacyChip).
- 03-04 Mobile Secretary 6-step wizard.
- 03-05 Web Secretary 6-step wizard.
- 03-06 Member self-onboarding (mobile single-screen, web 4 routes).
- 03-07 Mobile Secretary dashboard + code rotation.
- 03-08 Mobile Secretary admin (review queue, directory, member detail, DPDP removal, role transfer).
- 03-09 Web Secretary dashboard + code rotation.
- 03-10 Web Secretary admin equivalents.

Shipped (highlights):

- `create_society_with_secretary(name, address, co_sec_phone)` requires a co-secretary phone at creation; co-secretary phone different from creator's enforced.
- `bootstrap_society_structure(society_id, wings, flats)` and `list_society_structure(code)` (pre-membership read gated by code status).
- `redeem_society_code()` auto-elevates to `co_secretary` when caller phone matches `societies.co_secretary_phone` . Rolling 60-second rate limit: ≥ 5 redemptions auto-pauses the code (`society_codes.paused_at = now()`) and writes `audit_log` entry; resume only via `resume_society_code()` (admin RPC).
- Duplicate-flat join $\rightarrow$ `status='pending_review'` for Secretary to review.
- `reveal_phone(target_user_id)` writes `audit_log` row per ONBD-06.
- `remove_member(membership_id)` performs DPDP-compliant erasure: status $\rightarrow$ `deleted` , `family_members` deleted, profile redacted to `[REDACTED]` + sha256 phone hash if no other active memberships.
- `transfer_secretary_role(new_user_id)` flips Secretary $\leftrightarrow$ new role.
- 6-step wizard: Welcome $\rightarrow$ Society $\rightarrow$ Wings $\rightarrow$ Flats $\rightarrow$ Board $\rightarrow$ Amenities $\rightarrow$ Code Share (WhatsApp `wa.me` deep link).
- `JoinedPercentGauge` polls `fetchJoinPercent` every 30s with AppState pause; `PhonePrivacyChip` enforces all reveals go through the audited RPC.
- 21+ isolation tests across 5 phase-3 suites passing.

Outstanding (HUMAN-UAT): 7 multi-step walkthroughs (per-plan UAT files exist for 03-04..03-10); Secretary wizard end-to-end on iOS simulator and web browser; Member join flow on both platforms;

admin DPDP removal verified in Supabase Studio.

Key files: `supabase/migrations/20260524000006_phase3_society_setup.sql` , `packages/api-client/src/society.js` , `apps/web/app/(protected)/setup/*` , `apps/mobile/app/(protected)/setup.jsx` , `apps/web/app/(protected)/dashboard/{review-queue,directory,role-transfer}/page.jsx` , `apps/mobile/app/(protected)/(tabs)/{review-queue,role-transfer,member-detail,directory}.jsx` .

5.5 Phase 4 — Complaints (Lighthouse) (complete 2026-05-26)

Goal: The core loop — Member files → Board responds (atomic claim) → status updates (Realtime) → Member notified (push). **Requirements:** CMPL-01..07 + PUSH-01/02 (9/9 satisfied). **Plans:**

- 04-01 Backend migration + isolation tests.
- 04-02 `push-fanout` Edge Function.
- 04-03 api-client `complaints.js` (8 functions) + enums + 30 i18n keys.
- 04-04 Mobile UI (list, detail, new, push registration, deep link).
- 04-05 Web UI (SSR list + CSR Realtime, SSR detail, complaint composer).

Shipped:

- Tables: `complaints` , `complaint_responses` , `attachments` (polymorphic — `owner_kind` ∈ {`complaint`, `post`, `notification`, `flat_action`}).
- Enums: `complaint_kind` (society|member), `complaint_status` (open|checking|will_resolve|need_info|resolved), `attachment_owner` .
- `push_tokens.notifications_enabled` column.
- `can_see_complaint()` STABLE SQL helper (reporter OR same-society board roles).
- 3 RPCs: `file_complaint` (inserts complaint + optional attachment in one tx), `claim_complaint` (atomic `UPDATE ... WHERE owner_id IS NULL RETURNING`), `add_complaint_response` (owner-only follow-up).
- Realtime publication adds `complaints` + `complaint_responses` .
- `notify_push_on_response` AFTER INSERT trigger fires `net.http_post` to `push-fanout` Edge Function (fire-and-forget); sentinel header for auth.
- Mobile photo pipeline: `expo-image-picker` → `expo-image-manipulator` (≤1600px, q=0.7) → base64 → `ArrayBuffer` → Supabase Storage; web pipeline analogous via File API.
- Push registration on app boot via `apps/mobile/lib/push-registration.js` ; ref-guarded against token refresh re-registration.
- 14 isolation tests passing including Test 6 (Promise.all atomic claim — exactly one winner) and Test 11 (lighthouse-critical: Society A subscriber receives 0 events for Society B INSERT).

Outstanding (HUMAN-UAT): Real FCM delivery on a device, mobile photo capture + upload, web photo upload, web concurrent-claim race in two browser profiles.

Key files: `supabase/migrations/20260526000007_phase4_complaints.sql` , `supabase/functions/push-fanout/index.js` , `packages/api-client/src/complaints.js` , `apps/mobile/app/(protected)/(tabs)/complaints/{index,[id],new,photo-viewer}.jsx` ,

`apps/web/app/(protected)/complaints/{page,new/page,[id]/page}.jsx` ,
`apps/mobile/lib/push-registration.js` .

5.6 Phase 04.1 — Dashboard Shell (*INSERTED, complete 2026-05-28*)

Goal: Unified MyGate-style card grid home for both apps, wiring Phase 1–4 features into one entry point. **Requirements:** DASH-01, DASH-02 (remapped from Phase 7). **Inserted because:** User wanted the MyGate visual feel immediately after Phase 4 so subsequent feature phases integrate into an existing home rather than each defining its own.

Shipped:

- Mobile bottom-tab shell (Home / My Complaints / Profile) via `apps/mobile/app/(protected)/(tabs)/_layout.jsx` ; web persistent sidebar via `apps/web/components/dashboard/AppSidebar.jsx` .
- Role-aware tile config in `apps/{mobile,web}/lib/role-tiles.js` :
 - Member: 9 tiles (3 live: My Complaints, Directory, Society Code + 6 placeholders for Notices/Polls/Bookings/Community/Visitors/Staff).
 - Board: 9 tiles.
 - Secretary / Co-Secretary: 11 tiles (5 live: All Complaints, Reviews badge, Directory, Society Code, Code Rotation + 6 placeholders).
- `DashboardTile.jsx` supports a badge count (e.g. "3 pending reviews"), 99+ overflow clamp, screen-reader announcement of placeholder state ("Coming soon. Ships in Phase N").
- `SocietyHeaderPill.jsx` shows "{Society name} · {joined%}" .
- `SocietySwitcherSheet` (mobile RN Modal) / `SocietySwitcherDropdown` (web) — v1 visual-only stub for multi-society users.
- `ProfileMenuSheet` / `ProfileMenuDropdown` with Sign Out that **revokes push token before clearing session** (verified in code).
- Shared `lib/avatar.js` with `getAvatarColor()` + `initials()` .
- "Coming soon" placeholders later flipped to `live: true` by Phase 5 (Plans 05-04, 05-05, 05-06) and Phase 6 (Plans 06-04, 06-05, 06-06).

Outstanding (HUMAN-UAT): 6 device/browser items — mobile bottom-nav feel, web sidebar responsive collapse, Devanagari tile labels on real device, society switcher with 2+ memberships, placeholder screen-reader announcement, sign-out push-token deletion verified in Supabase Studio.

Code-review carry-forward (folded into Phase 7):

- WR-01 — web dashboard missing role-claim hydration guard (silently downgrades admin → member) — **fixed in Phase 7 Plan 07-04** (redirect instead of downgrade).
- WR-02 — admin sees two tiles routing to the same Society Code screen (intentional, badge-only differentiation) — Plan 07-09 will add a clarifying comment.
- WR-03 — `initials()` / `getAvatarColor()` split Devanagari surrogate/combining sequences — Plan 07-09 grapheme-aware fix.

Key files: `apps/mobile/app/(protected)/(tabs)/_layout.jsx` ,
`apps/mobile/app/(protected)/(tabs)/index.jsx` ,

```
apps/web/app/(protected)/dashboard/{page,DashboardClient}.jsx ,
apps/{mobile,web}/lib/role-tiles.js ,
apps/{mobile,web}/components/dashboard/{DashboardTile,SocietyHeaderPill,SocietySwitcher
*,ProfileMenu*}.{jsx} .
```

5.7 Phase 5 — Notifications, Polls & Bookings (complete 2026-05-29)

Goal: Society-wide notices + polls (with anti-fatigue controls); amenity bookings with first-approval lock + DB exclusion constraint. *Parallel track A.* **Requirements:** NOTF-01..08 + BOOK-01..07 (15/15 satisfied). **Plans:** 6 plans across 3 waves (DB → Edge Functions/api-client/i18n → UI).

Shipped:

- Tables: `notifications` , `polls` , `poll_options` , `poll_votes` , `bookings` , `notification_preferences` , `push_deliveries` (delivery log).
- Enums: `notification_category` (5-way: complaints/polls/community/fines/general — the cross-phase mute contract), `notification_kind` (general/poll), `poll_status` (open/closed), `booking_status` (pending/approved/rejected).
- `amenities.open_time` + `close_time` (defaults 06:00 / 22:00).
- `bookings.time_range tstzrange` (single range column, not start/end) + **EXCLUDE USING gist (amenity_id WITH =, time_range WITH &&) WHERE status='approved'** — the physical, defense-in-depth overlap guard (BOOK-05).
- `notification_preferences_effective` VIEW — COALESCE-defaults a missing prefs row to all-unmuted / 22:00-07:00 quiet / cap 20.
- 8 RPCs: `file_notification` (notification + optional poll + optional attachment in one tx; 2-4 option range check), `vote_on_poll` (UPSERT one vote per user, returns aggregate `count(*)` tally), `close_poll` , `request_booking` (server-side ≥1h lead / ≤30d ahead / ≤4h duration / amenity IST hours guards), `approve_booking` (atomic UPDATE...WHERE status='pending'; catches 23P01 from exclusion constraint → returns `{approved:false, reason:'slot_taken'}`), `reject_booking` (with optional reason).
- `eligible_push_recipients(notification_id)` helper does the A1 mute mapping (category → mute_* column) + IST quiet-hours wrap (Pitfall 2 — midnight-aware: `case when quiet_start <= quiet_end then ... else ... end`) + rolling-24h cap from `push_deliveries` count.
- 2 push triggers: `notify_push_on_notification` (society-wide → notification-fanout), `notify_push_on_booking_decision` (single-recipient → booking-ack-fanout).
- Mobile screens (under `(tabs)`): `notices/{index,new,[id]}` , `polls/index` , `bookings/{index,new}` , `settings/notifications` , `notifications/permission` .
- Web screens: `notices/{page,new,[id]}` , `polls` , `bookings/{page,new}` , `settings/notifications` + server actions in `app/actions/{bookings,notifications,preferences}.js` .
- Anti-bandwagon `PollBlock` : pre-vote = options only, post-vote = live tally bars (you can change vote until close).
- Devanagari LOCKED strings for बुकिंग / मतदान / मंजूर present and verified.
- 31/31 must-haves + 20+ isolation tests passing including 2-concurrent-approve race + slot-taken + partial-index-non-block.

Outstanding (HUMAN-UAT): 6 device/browser items — FCM delivery on real device, 2-device poll tally + booking race, Devanagari rendering, quiet-hours and cap suppression end-to-end, slot-taken UX surface.

Code-review:

- CR-01 (FIXED) `getNoticeDetail` my-vote now scoped to `auth.uid()`.
- WR-01 (FIXED) web cap "0/Unlimited" option removed; cap options = {10, 20, 30, 50}.
- WR-02 (FIXED) mobile push-tap routes on `data.screen` first with fallbacks.
- WR-03–WR-05 carried as advisory debt.

Key files: `supabase/migrations/20260528000008_phase5_notifications_bookings.sql`, `supabase/functions/{notification-fanout,booking-ack-fanout}/index.js`, `packages/api-client/src/{notifications,polls,bookings,preferences}.js`, `apps/mobile/app/(protected)/(tabs){notices,polls,bookings,settings}/*`, `apps/web/app/(protected){notices,polls,bookings,settings/notifications}/*`.

5.8 Phase 6 — Flat Actions & Community Feed (complete 2026-05-29)

Goal: Secretaries record warnings/fines/notices against flats with legal-validity guardrails; members participate in a moderated community feed that satisfies IT Rules 2021 + App Store UGC policy. *Parallel track B.* **Requirements:** FLAT-01..06 + COMM-01..07 (13/13 satisfied). **Plans:** 6 plans across 3 waves.

Shipped:

- Tables: `flat_actions`, `posts`, `post_comments`, `reports`, `moderation_events`.
- 5 enums: `flat_action_kind` (warning|fine|notify), `fine_status` (outstanding|acknowledged|waived; **NO overdue value** — derived at render), `post_kind` (sell|help|general), `report_target_kind` (post|comment), `moderation_event_kind` (report|takedown|restore).
- `societies.grievance_officer_name` + `grievance_officer_contact` columns.
- `can_see_flat_action()` per-FLAT RLS helper: branch (a) admin/board sees all flats; branch (b) member sub-queries `society_memberships` on `auth.uid()` + `action.flat_id` (because the JWT carries NO `flat_id`).
- 12 RPCs including admin-only `issue_flat_action` (co_secretary | secretary), `waive_fine` (admin-only — board_member CANNOT waive), `acknowledge_fine` (member, own-flat resident only — atomic UPDATE), `create_post` with **OQ2 attachment-key-prefix guard** that rejects any photo key not under `{society}/posts/{postId}/` (prevents bypassing the moderation gate), `report_content` (first-report-wins idempotent auto-hide via `hidden_at = coalesce(hidden_at, now())`), `restore_content` + `confirm_takedown` (admin-only), `delete_post` + `delete_comment` (author-only soft delete), `set_grievance_officer` + `get_grievance_officer` (COALESCE to Secretary name + secretary_phone if unset).
- `flat_action_recipients(flat_action_id)` SECURITY DEFINER helper: flat-scoped to active members of the target flat; OQ3 mute mapping (fine → mute_fines, warning/notify → mute_general); reuses Phase 5 quiet-hours wrap + cap.
- `moderate-image` Edge Function with **swappable adapter** (`MODERATION_PROVIDER` env var: stub / vision / rekognition), quarantine → PASS → move / quarantine → REJECT → delete orchestration; **fail-**

`closed {ok:false, error:'check_failed'} .`

- `flat-action-fanout` Edge Function — generic body "Your flat has a new notice" (no amount/kind leak on lock screen).
- Realtime publication adds `flat_actions` , `posts` , `post_comments` .
- LOCKED no-payment footer en/hi/mr, byte-exact across all three (verified programmatically), rendered on every fine surface (mobile + web, issue form, member detail, board detail).
- 9 mobile screens + 9 web screens; mobile `flat-actions/index.jsx` for members shows "Actions for your flat" with a Lock icon (no flat picker); board sees full list with pill filters.
- Grievance Officer card surfaced in `apps/mobile/app/(protected)/(tabs)/about.jsx` and `apps/web/app/(protected)/about/page.jsx` (IT Rules 2021 compliance).
- 28/28 must-haves + 39 isolation tests passing.

Outstanding (HUMAN-UAT): 6 device/browser items — flat-scoped FCM delivery, real-device image-safety reject, 2-device cross-device auto-hide, Devanagari fine footer on real Android, Grievance Officer surface in About/Help, 2-device moderation restore/takedown audit trail.

Code-review:

- WR-01 (FIXED in code) mobile flat-actions/[id].jsx now queries `society_memberships` for `memberFlatId` (was relying on a non-existent JWT `flat_id` claim).
- WR-02 (FIXED in code) web `acknowledgeFineAction` / `waiveFineAction` now propagate business-failure reason instead of silent false-success.
- IN-01..04 advisory debt (verify_jwt config pinning, fine-overdue signature unification, attachment buffer view, embed comments).

Key files: `supabase/migrations/20260529000009_phase6_flat_actions_community.sql` ,
`supabase/functions/{moderate-image,flat-action-fanout}/{index,providers/*}.js` ,
`packages/api-client/src/{flat-actions,community}.js` ,
`apps/mobile/app/(protected)/(tabs)/{flat-actions,community,moderation,settings/grievance-officer,about}/*` ,
`apps/web/app/(protected)/{flat-actions,community,settings/grievance-officer,about}/*` .

5.9 Phase 7 — Dashboards, i18n Polish & Web Parity (EXECUTING — 6 of 10 plans)

Goal: Aggregate Phases 3–6 data into role-specific dashboards; certify Devanagari across Indian Android; deliver the five web-required flows on Next.js. **Requirements:** DASH-03, L10N-01..04, WEB-01..02 (9 total; DASH-01/02 remapped to Phase 04.1).

Shipped so far (Plans 07-01 → 07-06):

Plan	Wave	Status	Delivered
07-01	0	DONE	<code>@parisar/i18n/runtime</code> factory (<code>createI18nInstance</code> , <code>backend</code> , <code>namespaces</code>); 3 CI gates (<code>check-i18n-coverage</code> , <code>check-no-direct-locale-import</code> , extended <code>check-devanagari-bundle</code>); <code>packages/i18n/__tests__/locked-verbatim.test.js</code> (6 keys × 3 locales). Adds <code>i18next@26.3.0</code> + <code>react-i18next@17.0.8</code> + <code>i18next-resources-to-backend@1.2.1</code> .
07-02	1	DONE	<code>get_dashboard_summary()</code> SECURITY DEFINER RPC (role-aware: secretary/board branch returns complaints/bookings/notifications/flatActions; member branch returns myComplaints/notifications/myBookings/community); api-client <code>dashboard.js</code> + envelope normalizer; <code>tests/isolation/dashboard-summary.test.js</code> (7 tests green); dashboard.json <code>previews.*</code> (8 D-04 templates) + <code>language.*</code> (7 strings) + <code>profile.language</code> row label × en/hi/mr. Migration 10 <code>20260603000010_phase7_dashboard_summary.sql</code> .
07-03	2	DONE	Mobile i18n init: <code>apps/mobile/lib/i18n.js</code> (<code>initI18n</code> , <code>changeLanguage</code> , <code>getActiveLanguage</code> , STORAGE_KEY <code>parisar_lang</code>); root <code>_layout.jsx</code> awaits <code>initI18n</code> before mounting <code><Stack></code> (splash-anchor render guard); <code>LanguageSelector</code> RN Modal with 3 rows (English / हिन्दी / मराठी, uniform Devanagari font); Language row added to <code>ProfileMenuSheet</code> . expo-localization seed → AsyncStorage override precedence with whitelist-on-write. Global jest AsyncStorage + expo-localization mocks.
07-04	2	DONE	Web i18n: <code>apps/web/lib/i18n/{cookie,server,client}.js</code> (cookie <code>parisar_lang</code> , SameSite=Lax, Secure, non-HttpOnly); server-side <code>initTranslations</code> is a bare i18next instance (no <code>initReactI18next</code>) to keep <code>react-i18next</code> out of the RSC bundle; <code>I18nProvider</code> memoized client component seeded with server's lng + resources for hydration-safe boot; <code><html lang={lng}></code> dynamic; <code>LanguageSelector</code> shadow Dialog; <code>setLanguageAction</code> server action with whitelist + <code>revalidatePath('/', 'layout')</code> . WR-01 fix in <code>dashboard/page.jsx</code> : missing <code>role</code> claim now <code>redirect('/login')</code> instead of silent member downgrade.
07-05	3	DONE	Mobile retrofit: zero direct <code>@parisar/i18n/locales/*.json</code> imports remain in <code>apps/mobile/{app,components,lib}</code> (CI gate exits 0); 91 mobile files now use <code>useTranslation('<ns>') + t('key.path')</code> . Multi-namespace components use <code>useTranslation(['ns1','ns2']) + t('ns2:key')</code> . Synthetic 'auth' namespace for the flat <code><lng>.json</code> . FLAT-05 locked-verbatim footer survives byte-exact via <code>t('fine.noPaymentFooter')</code> with <code>t('flatAction.noPaymentFooter')</code> <code>defaultValue</code> fallback. Global react-i18next jest mock resolves keys against actual en JSON shards.
07-06	3	DONE	Web retrofit: zero direct imports remain in <code>apps/web/{app,components,lib}</code> (CI gate <code>--dir apps</code> promoted to blocking). ~73 web files converted. RSC pattern: <code>const lng = await readLocaleFromCookies(); const { t } = await initTranslations(lng, ['<ns>'])</code> ; . Client-component pattern: <code>const { t } = useTranslation('<ns>')</code> . Web vitest setup gets the global react-i18next mock parallel to mobile.

Pending (Plans 07-07 → 07-10):

Plan	Wave	Status	Scope
07-07	4	NOT STARTED	Mobile DASH-03 wiring — summary store; subscribe to per-society Realtime channel; <code>DashboardTilePreview</code> component (D-04); focus reconciliation refetch (D-03).
07-08	4	NOT STARTED	Web DASH-03 wiring — SSR initial summary in <code>dashboard/page.jsx</code> ; DashboardClient Realtime patches; <code>DashboardTilePreview</code> mirror; <code>/my-complaints</code> alias route.
07-09	4	NOT STARTED	Advisory-debt fold: WR-03 grapheme-aware <code>initials()</code> / <code>getAvatarColor()</code> via a shared <code>packages/api-client/src/text/graphemes.js</code> helper; IN-02 unify <code>fine-overdue.js</code> (mobile vs web signature divergence); WR-02 add inline documentation for the dual code/code-rotation tile.
07-10	5	NOT STARTED	Final phase gate: responsive-viewport sanity test (web breakpoints phone/tablet/desktop); <code>07-HUMAN-UAT.md</code> (Android API 26/30/34 Devanagari matrix) — golden-screenshot suite may ship as documented HUMAN-UAT rather than CI emulator matrix; Maestro language-switch + dashboard-preview flows.

Outstanding work known to be in Plan 07-05 `deferred-items.md`: a pre-existing cross-midnight flaky test in `apps/mobile/__tests__/booking-components.test.jsx` ("rejects a slot less than 1h ahead with `leadTimeError`") — fixture-clock bug, not a retrofit regression; recommended fix is to inject a `nowMs` parameter into `validateRange`.

Key files: `packages/i18n/src/{create-instance,backend,namespaces}.js`, `apps/mobile/lib/i18n.js`, `apps/web/lib/i18n/{cookie,server,client}.js`, `apps/mobile/components/profile/LanguageSelector.jsx`, `apps/web/components/profile/LanguageSelector.jsx`, `apps/web/app/actions/set-language.js`, `supabase/migrations/20260603000010_phase7_dashboard_summary.sql`, `packages/api-client/src/dashboard.js`, `tests/isolation/dashboard-summary.test.js`, `.github/workflows/ci.yml` (i18n-gates job).

5.10 Phase 8 — Launch Readiness (*NOT STARTED — 0 of 4 plans*)

Goal: Swap stub OTP for production provider; harden auth surface; wire crash reporting; complete DPDP erasure; verify externally-clocked DLT registration. **Requirements:** LAUNCH-01..05 (5 total; all pending). **Status:** Plans not drafted (the roadmap's plan stubs are copies of the Phase 1 plan filenames — Phase 8 has not been through `/gsd-plan-phase`).

What it needs to do:

- LAUNCH-01** — Flip `OTP_PROVIDER` env var from `stub` to MSG91 (or chosen); implement `supabase/functions/send-sms/adapters/msg91.js` (currently throws). Dev `[auth.sms.test_otp]` block stays for E2E; `[auth.sms.twilio]` dev-placeholder must be removed from `config.toml`.
- LAUNCH-02** — Wire hCaptcha or Cloudflare Turnstile into the OTP request endpoint; verify token server-side before issuing SMS. No captcha infrastructure exists today.

- 3. **LAUNCH-03** — `@sentry/nextjs` on web; `@sentry/react-native/expo` config plugin on mobile; single Sentry project; source-map upload from CI.
- 4. **LAUNCH-04** — External: DLT registration (Principal Entity → Header/Sender ID → Template registration on each telco). 2–6 week clock; non-engineering. Kill-switch env var to disable outbound SMS instantly if a regulatory issue surfaces.
- 5. **LAUNCH-05** — DPDP-compliant member-erasure flow: member-facing "Request erasure" UX → Secretary or system flips status to `deleted` → `remove_member` RPC redacts PII in place → structural records retained as "Former Resident" → backups marked for next-cycle overwrite.

5.11 Phases 9–11 — Post-launch MyGate features (*NOT STARTED* — *added 2026-05-24*)

Phase	Feature	Status
9	Visitor / Gate Pass (QR codes)	Roadmap only. No plans, no schema.
10	Staff / Help Attendance	Roadmap only.
11	Vendor Directory	Roadmap only.

These are **explicitly post-launch**. The roadmap accepts that v1 ships *without* them.

6. Database Schema

Reverse-engineered from `supabase/migrations/*.sql` in order. Live local DB matches the migration set (confirmed via psql checks in every VERIFICATION.md).

6.1 Tables — full list (20 tables, all RLS-enabled except as noted)

Table	Phase	Cols (notable)	Purpose / RLS posture
societies	1 + 3 + 6	id (uuid PK), name, address, secretary_phone, co_secretary_phone, grievance_officer_name, grievance_officer_contact, created_at	Tenant root. RLS: <code>id = current_society_id()</code> self-row only.
society_codes	1 + 3	code (text PK), society_id, created_at, revoked_at, paused_at	Membership codes; rotated by Secretary, auto-paused on ≥5 redemptions/60s. RLS: society-scoped (all).
wings	1	id, society_id, name (UNIQUE per society)	Society structure. RLS: society-scoped.
flats	1	id, society_id, wing_id, number (UNIQUE per wing)	Flat ids referenced by everything attribution-related. RLS: society-scoped.
profiles	1 + 2	user_id (PK FK auth.users), full_name, phone (UNIQUE), signup_intent CHECK('secretary' 'member'), created_at	Per-user profile. Phone hidden in directory by default (ONBD-06). RLS: self-select + society-select via membership; self-insert/update.
society_memberships	1	id, society_id, user_id, flat_id, role (enum), residency (owner tenant), household (family bachelor), emergency_contact, joined_at, status (active pending_review deleted), UNIQUE (society, user, flat)	The graph that ties everyone together. RLS: society-scoped (all).
family_members	1	id, society_id, membership_id, full_name, phone	Contact-only; no auth account. RLS: society-scoped.
push_tokens	1 + 4	id, user_id, expo_token (UNIQUE), platform CHECK('ios' 'android' 'web'), device_label, last_seen_at, notifications_enabled bool	Per-device-per-user. RLS: self-only.
otp_requests	2	id bigserial, phone, requested_at	Per-phone OTP rate-limit ledger. No RLS (REVOKE ALL); only Edge Function writes via service-role.
code_redemptions	3	id bigserial, code, user_id, society_id, redeemed_at, succeeded	Used to detect ≥5 redemptions/60s. No RLS (REVOKE ALL); only SECURITY DEFINER RPCs write.
audit_log	3	id bigserial, society_id, actor_id, action, target_table, target_id, payload jsonb, created_at	Cross-phase write-only audit trail. RLS: secretary-only SELECT; INSERT/UPDATE/DELETE REVOKE'd from authenticated.

Table	Phase	Cols (notable)	Purpose / RLS posture
amenities	3 + 5	id, society_id, name, is_custom, open_time (06:00), close_time (22:00), created_at	RLS: society-scoped.
complaints	4	id, society_id, reporter_id, reporter_flat_id, kind enum, description, status enum, owner_id, claimed_at, resolved_at, language_code, created_at	Atomic claim via <code>claim_complaint</code> . RLS: <code>can_see_complaint()</code> — reporter OR same-society board roles. UPDATE REVOKE'd (only RPCs touch it).
complaint_responses	4	id, society_id, complaint_id, responder_id, responder_flat_id (denormalized for attribution), response_kind enum, free_text, created_at	RLS: same visibility as parent complaint. INSERT REVOKE'd.
attachments	4 (+ all owner kinds)	id, society_id, owner_kind enum (complaint post notification flat_action), owner_id, storage_key, mime_type, byte_size, created_by, created_at	Polymorphic. RLS: society-scoped SELECT + own-row INSERT.
notifications	5	id, society_id, author_id, author_flat_id (denorm), kind enum (general poll), category enum, title, body, created_at	Society-wide. RLS: society-scoped SELECT; INSERT/UPDATE REVOKE'd.
polls	5	id, society_id, notification_id (UNIQUE), question, status enum, closed_at, created_at	Optional per notification. RLS: society-scoped SELECT.
poll_options	5	id, society_id, poll_id, label, position int, created_at	2-4 enforced in <code>file_notification</code> . RLS: society-scoped SELECT.
poll_votes	5	id, society_id, poll_id, option_id, user_id, created_at, UNIQUE(poll_id, user_id)	One vote per user; change vote via UPSERT. RLS: society-scoped SELECT (aggregate tally needs all rows).
bookings	5	id, society_id, amenity_id, requester_id, requester_flat_id (denorm), time_range tstzrange (NOT start/end), purpose, status enum, approved_by, approver_flat_id (denorm), approved_at, rejected_by, rejecter_flat_id, rejection_reason, rejected_at, created_at	Atomic first-approval + <code>bookings_no_overlap EXCLUDE USING gist (amenity_id WITH =, time_range WITH &&) WHERE status='approved'</code> . RLS: <code>can_see_booking()</code> (requester OR same-society board). INSERT/UPDATE REVOKE'd.
notification_preferences	5	id, society_id, user_id, mute_complaints, mute_polls, mute_community, mute_fines, mute_general, quiet_start (22:00), quiet_end (07:00), cap_per_day (20), updated_at, UNIQUE(user_id, society_id)	The ONE table clients write directly. RLS: self-only scoped to current society.

Table	Phase	Cols (notable)	Purpose / RLS posture
ences			
push_deliveries	5	id, society_id, user_id, category enum, created_at	Delivery log for rolling 24h cap. No RLS (REVOKE ALL from authenticated); only Edge Function writes.
flat_actions	6	id, society_id, flat_id, issuer_id, issuer_flat_id (denorm), kind enum (warning fine notify), body, amount numeric (fine only), due_date date (fine only), fine_status enum (outstanding acknowledged waived; NO 'overdue'), created_at	Per-flat RLS via <code>can_see_flat_action()</code> (admin OR own-flat resident). INSERT/UPDATE/DELETE REVOKE'd.
posts	6	id, society_id, author_id, author_flat_id (denorm), kind enum (sell help general), body, hidden_at (server-side auto-hide), deleted_at (soft delete), created_at	RLS: society-scoped + auto-hide filter (board sees hidden, members don't).
post_comments	6	id, society_id, post_id, author_id, author_flat_id (denorm), body, hidden_at, deleted_at, created_at	Same hide/delete filter as posts.
reports	6	id, society_id, target_kind enum (post comment), target_id, reporter_id, reason, note, created_at	MANY allowed per target (first wins on hide). RLS: admin-only SELECT.
moderation_events	6	id, society_id, event_kind enum (report takedown restore), actor_id, target_kind, target_id, reason, created_at	Secretary audit trail (COMM-07). RLS: admin-only SELECT.

Views:

- `notification_preferences_effective` (Phase 5) — COALESCE-defaults a missing prefs row.

6.2 Functions / RPCs (28 SECURITY DEFINER RPCs + 3 helpers)

Every RPC follows a consistent pattern: `set search_path = public, auth`, gate on `auth.uid()` + `current_society_id()` (raises `AUTH_REQUIRED` / `NO_SOCIETY`), role check where needed, payload validation, atomic INSERT/UPDATE, audit_log write, jsonb return envelope.

RPC	Phase	Role gate	Purpose
<code>current_society_id()</code>	1	(helper)	Read <code>society_id</code> from JWT app_metadata.
<code>current_membership_role()</code>	1	(helper)	Read <code>role</code> from JWT app_metadata.
<code>inject_society_claims(jsonb)</code>	1	supabase_auth_admin only	Custom Access Token Hook — fires on every sign-in AND refresh.
<code>generate_society_code()</code>	3	internal	Generate 31-char-set code; retry on collision.
<code>create_society_with_secretary(name, address, co_sec_phone)</code>	3	authenticated	Step 1 of wizard. Validates inputs (name 3-100, address 10-500, co_sec phone <code>^[6-9][0-9]{9}\$</code> , co_sec ≠ self).
<code>finalize_society_setup(society_id, flat_id)</code>	3	creator-only (via audit_log lookup)	Creates Secretary's <code>society_memberships</code> row.
<code>bootstrap_society_structure(society_id, wings, flats)</code>	3	creator-only	Bulk insert wings + flats.
<code>list_society_structure(code)</code>	3	authenticated + valid code	Pre-membership read so member can pick a flat.
<code>rotate_society_code(society_id)</code>	3	secretary co_secretary	Revoke old + generate new code in one tx.
<code>resume_society_code(society_id)</code>	3	secretary co_secretary	Clear <code>paused_at</code> .
<code>redeem_society_code(c</code>	3	authenticated	Member join. Enforces ≥5/60s rate limit → auto-pause. Auto-elevates to <code>co_secretary</code> on phone match. Returns

RPC	Phase	Role gate	Purpose
<pre>ode, flat_id, residency, household, emergency)</pre>			<code>pending_review</code> on duplicate flat.
<code>validate_society_code(code)</code>	3	authenticated	Lightweight preview (society name/address/member count).
<code>reveal_phone(target_user_id)</code>	3	same-society	Returns phone for active OR <code>pending_review</code> members; writes audit_log on every call.
<code>remove_member(member_id)</code>	3	secretary co_secretary	DPDP erasure: status → deleted, family_members delete, profile redact if no other active memberships.
<code>transfer_secretary_role(new_user_id)</code>	3	secretary only	Role swap; new user must be co_secretary OR board_member.
<code>can_see_complaint(complaint)</code>	4	(helper)	RLS predicate: reporter OR same-society board roles.
<code>file_complaint(kind, description, flat_id, lang_id, storage_key, mime, size)</code>	4	active member	Inserts complaint + optional attachment + audit.
<code>claim_complaint(complaint_id, response_kind, free_text)</code>	4	board_member co_secretary secretary	Atomic <code>UPDATE ... WHERE owner_id IS NULL RETURNING</code> . NULL return = race lost.
<code>add_complaint_response(complaint_id, response_kind, free_text)</code>	4	owner-only	Owner adds follow-up; updates status.

RPC	Phase	Role gate	Purpose
<code>notify_push_on_response()</code>	4	trigger function	Fires <code>net.http_post</code> to <code>push-fanout</code> .
<code>can_see_booking(booking)</code>	5	(helper)	Requester OR same-society board.
<code>file_notification(title, body, category, id, storage_key, mime, size, poll_q, poll_options[])</code>	5	board_member co_secretary secretary	Notification + optional poll (+ 2-4 options) + optional attachment in one tx.
<code>vote_on_poll(poll_id, option_id)</code>	5	authenticated	UPSERT on (poll_id, user_id); returns aggregate tally.
<code>close_poll(poll_id)</code>	5	author OR board role	
<code>request_booking(amenity_id, starts, ends, purpose)</code>	5	active member	Server-side $\geq 1h$ lead / $\leq 30d$ / $\leq 4h$ / amenity IST hours guards.
<code>approve_booking(booking_id)</code>	5	board_member co_secretary secretary	Atomic UPDATE; catches <code>exclusion_violation</code> (23P01) $\rightarrow$ <code>{approved:false, reason:'slot_taken'}</code> .
<code>reject_booking(booking_id, reason)</code>	5	board_member co_secretary secretary	
<code>eligible_push_recipients(notification_id)</code>	5	service_role	Returns (user_id, expo_token) passing category mute + IST quiet-hours wrap + rolling 24h cap.
<code>notify_push_on_notify</code>	5	trigger function	$\rightarrow$ notification-fanout.

RPC	Phase	Role gate	Purpose
<code>cation()</code>			
<code>notify_push_on_booking_decision()</code>	5	trigger function	→ booking-ack-fanout.
<code>can_see_flat_action(action)</code>	6	(helper)	Admin/board OR own-flat resident.
<code>issue_flat_action(flat_id, kind, body, amount, due_date, id, storage_key, mime, size)</code>	6	co_secretary secretary	Admin-only. Fine requires amount>0 + due_date.
<code>acknowledge_fine(action_id)</code>	6	own-flat member	Atomic outstanding → acknowledged. Returns <code>{ok, reason}</code> (does not throw on wrong state).
<code>waive_fine(action_id)</code>	6	co_secretary secretary	Admin-only. board_member explicitly cannot waive.
<code>create_post(kind, body, id, photo_keys)</code>	6	active member	OQ2 key-prefix guard rejects keys not under <code>{society}/posts/{postId}/</code> .
<code>add_comment(post_id, body, id)</code>	6	active member	Parent post must be visible.
<code>report_content(target_kind, target_id, reason, note)</code>	6	active member	<code>hidden_at = coalesce(hidden_at, now())</code> — first report wins; idempotent.
<code>restore_content(target)</code>	6	co_secretary secretary	

RPC	Phase	Role gate	Purpose
<code>t_kind,</code> <code>target_id)</code>			
<code>confirm_takedown(targ</code> <code>et_kind,</code> <code>target_id)</code>	6	co_secretary secretary	
<code>set_grievance_officer</code> <code>(name,</code> <code>contact)</code>	6	secretary co_secretary	
<code>get_grievance_officer</code> <code>()</code>	6	authenticated	COALESCE to Secretary name + secretary_phone if unset; <code>is_default</code> flag.
<code>delete_post(post_id)</code>	6	author-only	Soft delete + moderation_events('takedown').
<code>delete_comment(comment</code> <code>t_id)</code>	6	author-only	
<code>flat_actions_recipients(flat_acti</code> <code>on_id)</code>	6	service_role	Flat-scoped recipients; OQ3 mute mapping.
<code>notify_push_on_flat_action()</code>	6	trigger function	→ flat-action-fanout.
<code>get_dashboard_summary</code> <code>()</code>	7	authenticated	Role-aware aggregation (last 7 days for complaints/notifications/flatActions/posts; pending for bookings); LIMIT 2 previews per tile; every sub-query filters by <code>society_id = v_society</code> ; member branch also filters by <code>auth.uid()</code> ; T-07-05 hidden_at+deleted_at filter on community previews.

6.3 Auth hooks

- **Custom Access Token Hook** (`inject_society_claims`) — registered in `supabase/config.toml` `[auth.hook.custom_access_token]` with `uri = "pg-functions://postgres/public/inject_society_claims"` . Fires on every sign-in AND refresh. Picks the most-recent active membership (v1 single-society model).
- **Send SMS Hook** (`[auth.hook.send_sms]`) — HTTP URL `http://host.docker.internal:54321/functions/v1/send-sms` . Routes through `send-sms` Edge Function.

6.4 Storage buckets

- `parisar-attachments` — single bucket, private, 50 MB file size limit. Layout: `{society_uuid}/{owner_kind}/{owner_id}/{filename}` (for community posts: `{society}/posts/{post_id}/...`). RLS via `(storage.foldername(name))[1]::uuid = current_society_id()` on all 4 verbs.
- Storage-side adapters present in `apps/{mobile,web}` for image upload (compress → ArrayBuffer → upload).

6.5 Realtime channels in use

`supabase_realtime` publication has **8 tables** added across migrations 4 → 6 → 5 → 9:

Table	Phase	Subscriber pattern
<code>complaints</code>	4	per-society channel filtered by <code>society_id=eq.{id}</code>
<code>complaint_responses</code>	4	per-complaint channel filtered by <code>complaint_id=eq.{id}</code>
<code>notifications</code>	5	per-society channel
<code>poll_votes</code>	5	per-poll channel
<code>bookings</code>	5	per-society channel
<code>flat_actions</code>	6	per-society channel
<code>posts</code>	6	per-society channel
<code>post_comments</code>	6	per-post channel

Realtime is consumed via

`subscribeToComplaints/Responses/Notices/Votes/Bookings/FlatActions/Posts/Comments` helpers in `packages/api-client/src/*.js`. Mobile uses `useFocusEffect` to ensure subscriptions are scoped to the active screen; web uses `useEffect` with `removeChannel` cleanup on unmount.

Pitfall 7 (documented in 04 migration): the Realtime container reads the publication at startup. `supabase db reset` replays the `ALTER PUBLICATION` statements but the Realtime container must be restarted for new tables to start broadcasting on a fresh local stack.

7. Authentication & Authorization

7.1 OTP flow — current state

Dev (today):

1. User enters Indian mobile number (`+91XXXXXXXXXX`); web client calls `supabase.auth.signInWithOtp({phone})` ; mobile client same.
2. Supabase invokes the `send-sms` Auth Hook. The Hook checks `OTP_PROVIDER` env var; in dev it dispatches to `adapters/stub.js` which is a no-op.
3. Because `[auth.sms.test_otp]` lists 4 test phones, Supabase short-circuits and uses `123456` as the OTP for those phones — no real SMS is sent.
4. User enters `123456` ; client calls `supabase.auth.verifyOtp({phone, token, type:'sms'})` .
5. Supabase issues a session JWT with `app_metadata.{society_id, role}` populated by `inject_society_claims` .
6. Client queries `profiles` with `maybeSingle()` ; `isNewUser(profile)` (from `api-client/src/otp.js`) routes new users to `/onboard` (role selection → writes `profiles.signup_intent`), returning users to `/dashboard` .

Production (Phase 8):

1. Same client call.
2. `send-sms` Hook dispatches to `adapters/msg91.js` (or `twilio.js` / `firebase.js`). Today these throw `Not yet implemented` .
3. Real SMS delivered via DLT-approved template.
4. Rest of the flow is unchanged.

Rate limits today:

- Per-phone: `otp_requests` table; MAX 5/hr enforced inside the Edge Function.
- Per-IP: `[auth.rate_limit]` block in `config.toml` — `sms_sent=30/hr` , `sign_in_sign_ups=30/5min` .

Critical workaround in `config.toml` : `[auth.sms.twilio]` block with `account_sid='dev-placeholder'` is **required** by Supabase CLI v2.98.2 to enable phone auth even with `[auth.sms.test_otp]` set. The test_otp short-circuit fires before any real Twilio call. This block **MUST** be removed before production.

7.2 DLT / TRAI compliance status

NOT STARTED. This is a non-engineering, externally-clocked work-stream (2–6 weeks) that the user must drive once an OTP provider is chosen:

1. Apply for DLT Principal Entity registration on each major Indian telco's DLT platform.
2. Register Header / Sender ID (e.g. `PARISR`).
3. Register each Template variant (OTP, alerts, notifications) — every variation of the SMS body needs separate approval.
4. Wire approved template IDs into the chosen adapter's env (`MSG91_TEMPLATE_ID` , `MSG91_DLT_PRINCIPAL_ENTITY_ID`).
5. Validate `LAUNCH-04` — outbound SMS goes through approved sender ID + templates only.

Until DLT registration is complete, **no real-user pilot is possible**. The stub keeps engineering unblocked.

7.3 Role propagation (custom access token hook + JWT claims)

The `inject_society_claims` Postgres function runs on **every** sign-in and refresh. It:

1. Looks up the user's most-recent active `society_memberships` row.
2. Injects `app_metadata.society_id` and `app_metadata.role` into the JWT claims.
3. If no active membership exists (e.g. user just signed up), it explicitly nulls both keys so RLS fails closed.

The two reader helpers `current_society_id()` and `current_membership_role()` are STABLE SQL — the planner caches the result per-statement.

The JWT carries NO `flat_id` claim. The Phase 6 `can_see_flat_action` helper deliberately sub-queries `society_memberships` on `auth.uid()` + `action.flat_id` because of this design choice. WR-01 in Phase 6 was a bug from a developer assuming `jwtMeta.flat_id` existed; fixed by querying `society_memberships` instead.

7.4 Cross-society isolation guarantees

The lighthouse test is `tests/isolation/cross-tenant-isolation.test.js` — 20 assertions:

- A real authenticated user signed into Society A receives zero rows from any Society B table (5 tables tested).
- A real Society B user receives zero rows from any Society A table.
- A cross-tenant INSERT is rejected with an RLS error.
- JWT after `auth.refreshSession()` still contains correct society/role claims (Anti-Pattern 7 mitigation).
- Storage: Alice cannot upload to Society B's prefix.

Phase 4/5/6 each have their own isolation suite (`complaints.test.js` , `bookings.test.js` , `flat-actions.test.js` , `community.test.js` , etc.) verifying the same cross-society zero-leak for their tables and RPCs.

`tests/isolation/dashboard-summary.test.js` Test 3 specifically locks the headline T-07-04 threat (cross-society leakage via the Phase 7 aggregation RPC) — every sub-query in `get_dashboard_summary()` filters by `society_id = v_society` .

7.5 Role table in code

Role	Where defined	Where read
<code>secretary</code> , <code>co_secretary</code> , <code>board_member</code> , <code>member</code>	Enum <code>membership_role</code> in migration 1 (line 62-65); JS constant in <code>packages/shared-types/src/enums.js</code>	Every SECURITY DEFINER RPC role gate; every RLS policy that distinguishes board from member

8. User Flows (end-to-end)

For each flow: screens involved, data state changes, success conditions. Routes are concrete file paths.

8.1 Member onboarding (Society Code → flat selection → OTP → home)

Note: in v1 the OTP login comes *before* the society code redemption. A user without a code can still sign in; they land on `/onboard` (role picker) and from there a Member taps "I have a Society Code" → `/join` .

Step	Mobile route	Web route	Action	Data change
1	<code>app/(auth)/login.jsx</code>	<code>app/(auth)/login/page.jsx</code>	Enter <code>+91XXXXXXXXXX</code> → "Send OTP"	<code>otp_requests</code> row written by Edge Function
2	<code>app/(auth)/verify.jsx</code>	<code>app/(auth)/verify/page.jsx</code>	Enter <code>123456</code> → Verify	Supabase session created; JWT issued (society_id=null, role=null at this point)
3	<code>app/(protected)/onboard.jsx</code>	<code>app/(protected)/onboard/page.jsx</code>	Pick "Member" role; enter full name	<code>profiles</code> row INSERT with <code>signup_intent='member'</code>
4	<code>app/(protected)/join.jsx</code> (single screen, stepIndex 0..3)	<code>app/(protected)/join/{code,profile,success,pending}/page.jsx</code> (4 routes)	Step A: enter 8-char alphanumeric code → preview society (<code>validate_society_code</code>)	Read-only preview
5	(same)	(same)	Step B: pick wing + flat from <code>list_society_structure(code)</code>	(no write yet)
6	(same)	(same)	Step C: profile form — owner/tenant, household (family/bachelor), emergency contact; optional family members	<code>redeem_society_code()</code> writes <code>society_memberships</code> , <code>code_redemptions</code> , <code>audit_log('member.joined')</code> . If flat is duplicate-claimed → <code>status='pending_review'</code> . Otherwise <code>status='active'</code> . Family rows go to <code>family_members</code> .
7	(same) — success branch	(same) — <code>success/page.jsx</code>	<code>refreshSession()</code> to pick up the new JWT claims (society_id + role)	New JWT has society_id + role='member' (or 'co_secretary' if auto-elevated)
8	<code>app/(protected)/(tabs)/index.jsx</code> (Home)	<code>app/(protected)/dashboard/page.jsx</code>	Lands on role-aware tile grid	—

Success condition: Member sees the home tile grid scoped to their society; "My Complaints" / Directory / Society Code are live tiles.

Pending duplicate-flat branch: Step 7 routes to the Pending screen with an amber clock icon; Secretary sees the pending join in the Review Queue.

8.2 Member files a complaint → Board responds → Member notified

Step	Mobile	Web	Action	Data change
1	Home → My Complaints tile → <code>complaints/index.jsx</code> → "+ New" → <code>complaints/new.jsx</code>	<code>complaints/page.jsx</code> → "File a Complaint" → <code>complaints/new/page.jsx</code>	Pick type (Society Issue / Member Issue); description 10–1000 chars; optional photo from camera/gallery	Photo: <code>expo-image-picker</code> → <code>expo-image-manipulator</code> (≤1600px, q=0.7) → base64 → ArrayBuffer → <code>supabase.storage.from('parisar-attachments').upload(...)</code>
2	(same)	(same)	Submit	<code>file_complaint()</code> RPC inserts complaint + optional attachment + audit_log in one tx
3	Board members' devices	Board members' browsers	Realtime patches the new complaint into their list (subscribed per-society channel)	—
4	First board member taps a <code>ResponseChip</code> ("Checking" / "Will resolve soon" / "Resolved" / "Need more info") in <code>complaints/[id].jsx</code>	<code>complaints/[id]/page.jsx</code> server component + <code>ComplaintDetailClient.jsx</code> server action	<code>claim_complaint()</code> atomic UPDATE; loser sees <code>{claimed:false}</code> and the row flips read-only with winner's flat	
5	—	—	<code>notify_push_on_response</code> trigger fires → <code>push-fanout</code> → Expo Push → FCM → device	<code>complaint_responses</code> INSERT happened
6	Reporter receives push; tap → deep-links to <code>complaints/[id].jsx</code>	(web has no native push in v1)	Status visible in reporter's "My Complaints" tab	—

Success condition: The reporter sees the new status without manual refresh and was notified via push. Verified at code level by isolation tests 6, 10, 11, 14. Real device push delivery is HUMAN-UAT.

8.3 Board Member posts a notice / poll

Step	Mobile	Web	Action	Data change
1	Home → Notices tile → <code>notices/index.jsx</code> → FAB "+ New Notice" → <code>notices/new.jsx</code>	<code>notices/page.jsx</code> → "+ New" → <code>notices/new/page.jsx</code>	Title (3–80), Body (10–500), optional category (general/polls/community/fines/complaints), optional PDF or image attachment, optional 2–4 option poll with question	Attachment upload to <code>{society}/notifications/{notif_id}/</code>
2	(same)	(same)	Submit	<code>file_notification()</code> RPC inserts notification + (optional) poll + 2-4 poll_options + (optional) attachment + audit_log
3	—	—	<code>notify_push_on_notification</code> trigger → <code>notification-fanout</code> Edge Function	Edge Function calls <code>eligible_push_recipients(notif_id)</code> filtering by mute_ + IST quiet-hours wrap + rolling 24h cap; batches Expo Push (≤100); logs each delivery to <code>push_deliveries</code>
4	Every eligible member's device	(n/a for web)	Push lands ("New notice in your society"); tap → <code>notices/[id]</code> deep link	—
5	Members open notice detail; PollBlock pre-vote shows options only (anti-bandwagon)	(same)	Vote → <code>vote_on_poll(poll_id, option_id)</code> UPSERT; aggregate tally returned as <code>count(*)</code>	<code>poll_votes</code> row INSERT or UPDATE
6	(same)	(same)	Post-vote sees live tally; can change vote until poll closed	—

Success condition: All eligible recipients (un-muted, outside quiet hours, under cap) receive the push and can vote with anti-bandwagon UX.

8.4 Member books an amenity

Step	Mobile	Web	Action	Data change
1	Home → Bookings tile → <code>bookings/index.jsx</code> → "+ Request" → <code>bookings/new.jsx</code>	<code>bookings/page.jsx</code> → "+ New" → <code>bookings/new/page.jsx</code>	Pick amenity from society's <code>amenities</code> ; date + start/end time; optional purpose	Client-side <code>TimeSlotPicker</code> validates against amenity hours
2	(same)	(same)	Submit	<code>request_booking()</code> RPC enforces: ≥1h lead, ≤30d ahead, ≤4h duration, slot within amenity IST <code>open_time</code> / <code>close_time</code>
3	Board members' lists	Same	Realtime patches new pending booking; appears in Board's queue with "Approve" + "Reject" actions	—
4	Two board members tap "Approve" at the same time	Two browser profiles	<code>approve_booking()</code> RPC — atomic <code>UPDATE ... WHERE status='pending' RETURNING</code> ; the second caller gets <code>{approved:false, reason:'race_lost_or_not_pending'}</code> or, if a different overlapping slot was already approved, <code>{approved:false, reason:'slot_taken'}</code> (via 23P01 catch from the <code>bookings_no_overlap</code> exclusion constraint)	Loser's UI flips read-only with <code>ApproverBanner</code> : "Approved by Amit (A-102)"
5	Requester receives push	(n/a web)	<code>notify_push_on_booking_decision</code> trigger → <code>booking-ack-fanout</code> → single- recipient Expo Push; generic body (no amenity/slot leak)	—

Success condition: Exactly one approval wins; the booking transitions to `approved` with denormalized `approved_by` / `approver_flat_id` / `approved_at` ; the requester is pushed.

8.5 Secretary issues a flat action (warning / fine / notify)

Step	Mobile	Web	Action	Data change
1	Home → Flat Actions tile (admin-only) → <code>flat-actions/index.jsx</code> (board sees all flats, filter pill) → "+ Issue" → <code>flat-actions/new.jsx</code>	<code>flat-action/s/page.jsx</code> → <code>flat-action/s/new/page.jsx</code>	<code>IssueActionForm</code> — pick flat (combobox of wing+number); pick kind (Warning / Fine / Notify); body text; if Fine: amount + due_date + optional bylaw PDF (≤10 MB)	If PDF: <code>uploadFinePdf()</code> → <code>{society}/flat_actions/{action_id}<file>.pdf</code>
2	(same)	(same)	Submit	<code>issue_flat_action()</code> admin-only RPC; fine writes <code>fine_status='outstanding'</code>
3	—	—	<code>notify_push_on_flat_action</code> trigger → <code>flat-action-fanout</code>	Edge Function calls <code>flat_action_recipients(action_id)</code> (active members of the target flat) with OQ3 mute mapping (fine → mute_fines, warning/notify → mute_general); generic body "Your flat has a new notice"
4	Target flat members see the action in their member view of <code>flat-actions/index.jsx</code> (no flat picker — Lock icon + "Actions for your flat")	(same)	Detail view shows the always-on localized no-payment footer in en/hi/mr (byte-exact LOCKED string) on every fine	—
5	Member taps "Acknowledge" on an outstanding fine	(same)	<code>acknowledge_fine()</code> atomic UPDATE outstanding → acknowledged; gated to own-flat resident	<code>flat_actions.fine_status = 'acknowledged'</code> ; audit_log row
6	Secretary or Co-Secretary later may "Waive" the fine	(same)	<code>waive_fine()</code> admin-only atomic UPDATE; board_member explicitly cannot waive (returns INSUFFICIENT_ROLE)	<code>flat_actions.fine_status = 'waived'</code>

Success condition: Fine recorded with attribution, target flat residents (and only them) receive push, member can acknowledge, admin can waive. No payment is ever collected — the locked footer guarantees user-facing clarity.

8.6 Secretary removes a member (DPDP-sensitive)

Step	Mobile	Web	Action	Data change
1	Home → Directory tile → <code>directory.js</code> → tap member → <code>member-detail.jsx</code>	Sidebar → Directory → <code>dashboard/directory/page.js</code> → tap member → <code>directory/[id]/page.jsx</code>	"Remove member" button (Secretary/Co-Secretary only)	—
2	(same)	(same)	<code>DestructiveConfirmDialog</code> requires the Secretary to type the member's full name to confirm	—
3	Confirm	Confirm	<code>remove_member(membership_id)</code> SECURITY DEFINER RPC	<code>society_memberships.status='deleted'</code> ; <code>family_members</code> rows DELETE'd; if no other active memberships for that user, <code>profiles.full_name='[REDACTED]'</code> + <code>profiles.phone='REDACTED- <sha256>'</code> ; audit_log row with <code>redacted: true</code>
4	Member's session is invalidated next refresh; appears as "Former Resident" in attributed records	(same)	(LAUNCH-05 will surface a member-facing "Request erasure" flow)	—

Success condition: Structural records (complaints filed, fines issued, posts written) survive with attribution shown as "Former Resident" — DPDP compliant. Verified by `tests/isolation/member-onboarding.test.js` ONBD-07.

8.7 Member changes language

Step	Mobile	Web	Action	Data change
1	Tap Profile tab → <code>(tabs)/profile.jsx</code> → opens <code>ProfileMenuSheet</code> <code>t</code> → "Language" row	Sidebar → ProfileMenuDropdown → "Language" row	—	—
2	RN Modal <code>LanguageSelector</code> <code>r</code> opens with 3 rows: English / हिन्दी / मराठी	shadcn Dialog <code>LanguageSelector</code>	Pick locale	—
3	(mobile)	(web)	Mobile: <code>changeLanguage(lng)</code> → <code>AsyncStorage.setItem('parisar_lang', lng)</code> → <code>il18n.changeLanguage(lng)</code> . Web: <code>setLanguageAction(lng)</code> server action validates whitelist → writes <code>parisar_lang</code> cookie (SameSite=Lax, Secure) → <code>revalidatePath('/', 'layout')</code> — every page re-renders with <code><html lang={lng}></code> and new bundle	Storage update
4	App immediately re-renders in target locale; lazy-loads any not-yet-resident namespace shards via <code>il18next-resources-to-backend</code>	(same)	—	—

Success condition: Setting persists across app restart (mobile) / browser restart (web). Devanagari renders correctly via bundled Noto Sans Devanagari font.

9. UI Pages (every screen in web and mobile)

9.1 Mobile — Expo Router file tree

`apps/mobile/app/` — file count: 40 routes.

Auth group (auth)

Route	Role(s)	Purpose	Key components	Status
(auth)/login.jsx	any	Phone entry	PhoneInput (locked +91), isValidIndianMobile	Built
(auth)/verify.jsx	any	OTP entry (6-digit) + new-user routing	OtpInput , isNewUser	Built

Top-level

Route	Role(s)	Purpose	Status
app/_layout.jsx	—	Root Stack with I18nextProvider mount, Stack.Protected guard, push registration, notification-tap router	Built
app/index.jsx	unauth	"Hello {society}" landing / splash	Built

Protected — pre-onboarding (protected)

Route	Role(s)	Purpose	Status
(protected)/_layout.jsx	auth	Auth-gate wrapper	Built
(protected)/onboard.jsx	new user	Role picker (Secretary / Member)	Built
(protected)/setup.jsx	Secretary intent	6-step wizard host (single screen, stepIndex 0..6)	Built
(protected)/join.jsx	Member intent	Single screen, stepIndex 0..3 (code, preview, profile, success/pending)	Built

Protected — main app (protected)/(tabs)

The bottom-tab shell. 3 visible tabs (Home, My Complaints, Profile), the rest are href:null routes that stay inside the tab bar but don't appear in the bar.

Route	Role(s)	Purpose	Status
(tabs)/_layout.jsx	auth	Tab bar definition	Built
(tabs)/index.jsx	all	Role-aware tile grid home	Built (DASH-03 live tiles pending Plan 07-07)
(tabs)/my-complaints.jsx	Member	Reporter's own complaints	Built
(tabs)/profile.jsx	all	Profile hub (mounts ProfileMenuSheet)	Built
(tabs)/about.jsx	all	About / Help + Grievance Officer card	Built
(tabs)/directory.jsx	all	Member directory (PhonePrivacyChip)	Built
(tabs)/member-detail.jsx	all	Member detail; Secretary sees Remove	Built
(tabs)/review-queue.jsx	Secretary/Co-Sec	Pending join review (duplicate-flat conflicts)	Built
(tabs)/role-transfer.jsx	Secretary	Transfer role wizard	Built
(tabs)/code-rotation.jsx	Secretary/Co-Sec	Society code rotation + paused resume	Built
(tabs)/complaints/index.jsx	board	All-society complaints list (board view)	Built
(tabs)/complaints/[id].jsx	all	Complaint detail (3-case board action row)	Built
(tabs)/complaints/new.jsx	active member	Complaint composer	Built
(tabs)/complaints/photo-viewer.jsx	all	Image lightbox	Built
(tabs)/notices/index.jsx	all	Society-wide notice list	Built
(tabs)/notices/[id].jsx	all	Notice detail with embedded PollBlock	Built
(tabs)/notices/new.jsx	board	Composer (notice + optional poll + attachment)	Built
(tabs)/polls/index.jsx	all	Notices filtered to poll kind	Built
(tabs)/bookings/index.jsx	all	My bookings (members) / society queue (board)	Built

Route	Role(s)	Purpose	Status
<code>(tabs)/bookings/new.jsx</code>	active member	Booking request form (TimeSlotPicker + amenity hours guard)	Built
<code>(tabs)/community/index.jsx</code>	all	Community feed	Built
<code>(tabs)/community/[id].jsx</code>	all	Post detail with comments + Report	Built
<code>(tabs)/community/new.jsx</code>	active member	Composer with image-safety sync-block	Built
<code>(tabs)/flat-actions/index.jsx</code>	all	Member: own-flat actions; Board: society-wide	Built
<code>(tabs)/flat-actions/[id].jsx</code>	all	Action detail with Acknowledge (member) / Waive (admin)	Built (WR-01 fix verified)
<code>(tabs)/flat-actions/new.jsx</code>	Secretary/Co-Sec	Issue Warning/Fine/Notify with locked footer on fines	Built
<code>(tabs)/moderation/index.jsx</code>	Secretary/Co-Sec	Moderation queue + audit log tab	Built
<code>(tabs)/settings/notifications.jsx</code>	all	5 mute toggles + quiet hours + cap	Built
<code>(tabs)/settings/grievance-officer.jsx</code>	Secretary/Co-Sec	Set name + contact	Built
<code>(tabs)/notifications/permission.jsx</code>	all	OS notification permission prompt	Built

9.2 Web — Next.js App Router file tree

`apps/web/app/` — file count: 49 page/layout/action files (excluding `__tests__`).

Top-level

Route	Role(s)	Purpose	Status
<code>app/layout.jsx</code>	—	Async root layout; reads <code>parisar_lang</code> cookie; mounts <code><I18nProvider></code>	Built (Plan 07-04)
<code>app/page.jsx</code>	unauth	Landing	Built

Auth (auth)

Route	Role(s)	Purpose	Status
(auth)/layout.jsx	—	Auth shell	Built
(auth)/login/page.js x	any	Phone entry	Built
(auth)/verify/page.js x	any	OTP entry + new-user routing (client component for cookie session)	Built

Server actions (app/actions/)

File	Status
auth.js — sendOtpAction, signOutAction (revokes push token before signOut)	Built
bookings.js — request, approve, reject	Built
complaints.js — file, claim, respond	Built
notifications.js — file_notification, vote, close_poll	Built
preferences.js — upsert prefs	Built
set-language.js — whitelist + cookie write + revalidatePath	Built (Plan 07-04)

Protected (protected)

Route	Role(s)	Purpose	Status
(protected)/layout.jsx	auth	Server component getUser() guard	Built
(protected)/onboard/page.jsx	new user	Role picker	Built
(protected)/about/page.jsx (RSC + initTranslations)	all	About + Grievance Officer	Built
(protected)/profile/page.jsx	all	Profile	Built
(protected)/dashboard/page.jsx	all	Server component + DashboardClient. WR-01 redirect now in place.	Built (DASH-03 live wiring pending Plan 07- 08)
(protected)/dashboard/DashboardClient.js x	all	Tile grid, ProfileMenuDropdown host	Built
(protected)/dashboard/review- queue/page.jsx	Secretary/Co- Sec	Pending joins	Built
(protected)/dashboard/directory/page.js x	all	Member directory	Built
(protected)/dashboard/directory/[id]/pag e.jsx	all	Member detail (Secretary sees Remove)	Built
(protected)/dashboard/role- transfer/page.jsx	Secretary	Role transfer	Built
(protected)/dashboard/code- rotation/page.jsx	Secretary/Co- Sec	Rotation modal	Built
(protected)/setup/* (page.jsx + society/wings/flats/board/amenities/code/layout.jsx)	Secretary intent	6-step wizard split per route + Zustand store	Built
(protected)/join/{code,profile,success,p ending}/page.jsx + layout.jsx	Member intent	4-route join flow	Built
(protected)/complaints/page.jsx	all	SSR list + ComplaintListClient (CSR Realtime)	Built
(protected)/complaints/[id]/page.jsx	all	SSR detail + ComplaintDetailClient (server actions)	Built
(protected)/complaints/new/page.jsx (RSC + initTranslations)	active member	File complaint form (FileComplaintForm)	Built

Route	Role(s)	Purpose	Status
(protected)/notices/page.jsx	all	NoticeListClient	Built
(protected)/notices/[id]/page.jsx	all	Notice detail + PollBlock	Built
(protected)/notices/new/page.jsx	board	NoticeComposer	Built
(protected)/polls/page.jsx	all	Polls-only list	Built
(protected)/bookings/page.jsx	all	BookingListClient (Approve/Reject server actions)	Built
(protected)/bookings/new/page.jsx (RSC + initTranslations)	active member	BookingForm	Built
(protected)/community/page.jsx	all	CommunityFeedClient	Built
(protected)/community/[id]/page.jsx	all	PostDetailClient	Built
(protected)/community/new/page.jsx (RSC + initTranslations)	active member	PostComposer (image-safety gate)	Built
(protected)/community/moderation/page.jsx	Secretary/Co-Sec	ModerationClient (queue + audit log)	Built
(protected)/community/actions.js	—	community server actions	Built
(protected)/flat-actions/page.jsx	all	FlatActionsClient (member or board view)	Built
(protected)/flat-actions/[id]/page.jsx	all	FineDetailBlock with locked footer; admin Waive gate (WR-02 fix)	Built
(protected)/flat-actions/new/page.jsx	Secretary/Co-Sec	IssueActionForm	Built
(protected)/flat-actions/actions.js	—	flat-action server actions	Built
(protected)/settings/notifications/page.jsx	all	PreferencesClient (5 mute toggles + quiet + cap; WR-01 fix removed "Unlimited")	Built
(protected)/settings/grievance-officer/page.jsx	Secretary/Co-Sec	set_grievance_officer	Built

9.3 Pages not yet built / partial

Page	Status	Owning phase
Web push subscription / notification permission	Not built — web has in-app only in v1	Out of v1 scope
Member-facing "Request data erasure" UX (LAUNCH-05)	Not built — RPC exists, UI does not	Phase 8
Multi-society switcher (functional swap with JWT refresh)	Visual-only stub	Phase 8 (deferred)
Visitor / Staff / Vendor tiles (real screens)	Placeholder tiles only	Phases 9–11
Phase 7 dashboard live data — counts and previews	RPC + UI scaffolding ship; live wiring pending	Phase 7 Plans 07-07 / 07-08

10. Form Fields (per major form)

Validation rules sourced from `packages/api-client/src/*.js` payload contracts + Postgres CHECK constraints + UI Zod schemas.

10.1 Society Setup (6-step wizard) — Secretary

Step 1: Society details (`create_society_with_secretary`)

Field	Type	Validation	Source of truth
Society name	text	3–100 chars, trimmed	<code>create_society_with_secretary</code> RPC + Zod (client)
Address	text	10–500 chars, trimmed	RPC + Zod
Co-Secretary phone	text	<code>^[6-9][0-9]{9}\$</code> (10-digit Indian mobile); MUST differ from caller's phone	RPC raises <code>CO_SEC_SAME_AS_SELF</code>

Step 2: Wings

Field	Type	Validation
Wing names (1–10)	text[]	each non-empty; UNIQUE per society (DB constraint)

Step 3: Flats

Field	Type	Validation
Per-wing flat list (e.g. <code>[A-101, A-102, ..., B-204]</code>)	text[] grouped by wing	non-empty per wing; UNIQUE (wing, number) (DB constraint)
Secretary's own flat selection	uuid	must belong to the society

Step 4: Board members

Field	Type	Validation
Board member name	text	non-empty
Board member flat	uuid	one of the society's flats
Board member phone	text	Indian mobile format

Step 5: Amenities

Field	Type	Validation
Standard amenities (multi-select)	enum[]	Pool / Temple / Kids Area / Clubhouse / Garden / Gym
Custom amenities	text[]	each non-empty
Per amenity: open_time, close_time	time	open < close (DB default 06:00/22:00)

Step 6: Society code share

Field	Type	Validation
Generated code (auto)	text	4-char + + 4-char (excludes 0/O/I/1/L for OCR clarity)

10.2 OTP login

Field	Type	Validation
Phone	text	<code>isValidIndianMobile</code> : <code>^[+]?91[6-9]\d{9}\$</code> or <code>^[6-9]\d{9}\$</code> ; <code>toE164</code> normalizes
OTP	6-digit text	<code>isValidOtp</code> : <code>^\d{6}\$</code>

10.3 Complaint composer

Field	Type	Validation
Kind	enum	<code>society</code> <code>member</code> (<code>complaint_kind</code> enum)
Description	text	10–1000 chars
Photo (optional)	file	mobile: resized ≤1600px, JPEG q=0.7; web: any image MIME; Storage upload before RPC call
reporter_flat_id (auto)	uuid	derived from <code>society_memberships</code> lookup
language_code (auto)	text	from active i18next locale

10.4 Booking request

Field	Type	Validation
Amenity	uuid	one of the society's amenities
Date	date	not in the past
Start time	time	$\geq$ amenity.open_time (IST)
End time	time	$\leq$ amenity.close_time (IST)
Computed time_range	tstzrange	end > start; ≥ 1 h lead; ≤ 30 d ahead; ≤ 4 h duration (server-enforced in request_booking)
Purpose	text	optional, ≤ 200 chars

10.5 Notification / poll composer

Field	Type	Validation
Title	text	3–80 chars
Body	text	10–500 chars
Category	enum	complaints polls community fines general (default general)
Attachment (optional)	file	PDF or image; upload to Storage before RPC
Poll question (optional)	text	required iff poll_options provided; non-empty after trim
Poll options (optional)	text[]	2..4 (server-enforced; raises POLL_OPTIONS_RANGE otherwise)

10.6 Flat-action issue form (issue_flat_action)

Field	Type	Validation
Target flat	uuid	must belong to society (RPC raises INVALID_FLAT)
Kind	enum	warning fine notify
Body	text	non-empty (UI requires ≥ 10 chars)
Amount (fine only)	numeric	> 0 (RPC raises FINE_FIELDS_REQUIRED)
Due date (fine only)	date	required if kind = fine
Bylaw PDF (fine, optional)	file	PDF, ≤ 10 MB
Locked footer (auto)	text	non-editable; en/hi/mr byte-exact; rendered on every fine surface

10.7 Member-removal confirmation (`DestructiveConfirmDialog`)

Field	Type	Validation
Typed name confirmation	text	must equal the member's full name exactly (case-insensitive, trimmed) before the Remove button enables

10.8 Language switcher

Field	Type	Validation
Locale	enum	one of <code>['en', 'hi', 'mr']</code> — whitelisted on read AND write (<code>changeLanguage</code>); cannot land an invalid value on disk

10.9 Community post composer

Field	Type	Validation
Kind	enum	<code>sell</code> <code>help</code> <code>general</code>
Body	text	non-empty (UI ≥1 char)
Photos	file[]	≤4 (RPC raises <code>TOO_MANY_PHOTOS</code>); each passes <code>moderate-image</code> adapter sync-block; rejected images blocked from submit; storage keys MUST live under <code>{society}/posts/{postId}/</code> (RPC <code>INVALID_ATTACHMENT_KEY</code> guard)

10.10 Notification preferences

Field	Type	Validation
Mute Complaints / Polls / Community / Fines / General	bool ×5	inverted in UI (unmute = ON)
Quiet start / Quiet end	time	IST; midnight-wrap supported (e.g. 22:00–07:00)
Cap per day	int	UI options: {10, 20, 30, 50}; default 20 (server-side default) — the "Unlimited" option was removed in WR-01 fix

11. i18n & Devanagari

11.1 Locale coverage

- **Locales:** en, hi, mr — all from v1 (constraint).
- **Shards per locale:** 9 namespace files (bookings, community, complaints, dashboard, flat-actions, moderation, notifications, polls, preferences) + 1 flat legacy file (`<lng>.json`) loaded under synthetic namespace `auth` .
- **Total locale files:** 27 (3 locales × 9 shards) + 3 flat = 30 JSON files.
- **Parity gate:** `scripts/check-i18n-coverage.mjs` enforces en ≡ hi ≡ mr key parity AND placeholder parity (`{{var}}` count) per shard. Runs in CI on every push.

- **No-direct-import gate:** `scripts/check-no-direct-locale-import.mjs --dir apps` rejects any `import en from '@parisar/i18n/locales/*.json'` regression in `apps/{web,mobile}` (promoted to blocking in Plan 07-06).

11.2 Locked-verbatim strings

Six keys are byte-locked across all three locales — drift fails CI. The most important is the **FLAT-05 no-payment footer** (mobile key `fine.noPaymentFooter`, web key `flatAction.noPaymentFooter`).

Verified by `packages/i18n/__tests__/locked-verbatim.test.js`.

One locked key (Phase 2 stub OTP dev hint) is `it.todo` today — the key does not exist in shards. Plan 07-05 noted this; Phase 7 finishes by lifting that hint into the `auth` namespace.

11.3 Devanagari rendering

- **Mobile:** `@expo-google-fonts/noto-sans-devanagari` bundled into the build via Expo Font config plugin. The `LanguageSelector` applies the Devanagari font uniformly across English/Hindi/Marathi rows (uniform-font policy ensures row metrics stay aligned even on devices where the Latin row would otherwise pick OEM defaults).
- **Web:** `next/font/google` Noto Sans + Noto Sans Devanagari with `subsets: ['devanagari']`. Self-hosted to eliminate Google Fonts CDN risk + FOUT for non-Latin scripts.
- **Bundle check:** `scripts/check-devanagari-bundle.mjs` scans every hi/mr shard for U+0900–U+097F code points and fails the build if a shard contains only Latin text.
- **Golden-screenshot certification (L10N-03): NOT YET DELIVERED.** Phase 7 Plan 07-10 is responsible. CLAUDE.md prescribes Maestro for E2E + Android emulator matrix (API 26 / 30 / 34). The plan acknowledges this may ship as a documented HUMAN-UAT rather than CI emulator matrix if the latter is too heavy for the 2-person setup.

11.4 Per-platform mechanism

Platform	Persistence	Seed	Provider mount
Mobile	AsyncStorage key <code>parisar_lang</code>	<code>expo-localization.getLocales()[0].languageCode</code>	<code>apps/mobile/app/_layout.jsx</code> awaits <code>initI18n()</code> before mounting <code><Stack></code> (splash-anchor render guard ensures no flash of raw keys)
Web	Cookie <code>parisar_lang</code> (SameSite=Lax, Secure, NOT HttpOnly — client must read for <code>useTranslation</code>)	RSC reads the cookie via <code>readLocaleFromCookies()</code> ; client picks up the same lng from <code><I18nProvider></code> seed	<code>apps/web/app/layout.jsx</code> is async; mounts <code><I18nProvider lng={lng} resources={resources}></code> so the client tree boots in the same locale without a second fetch (hydration-safe)
Both	Whitelist on read AND write	—	<code>changeLanguage(lng)</code> (mobile) and <code>setLanguageAction(lng)</code> (web) reject anything not in <code>SUPPORTED_LOCALES</code> before persisting

11.5 Retrofit progress

After Phase 7 Plans 07-05 + 07-06: **zero direct** `@parisar/i18n/locales/*.json` imports remain in `apps/{web,mobile}` (CI gate exits 0). Approximately **164 screen/component files** now consume strings through `useTranslation(<namespace>)`. Multi-namespace components use `useTranslation(['ns1', 'ns2'])` + namespace-prefixed lookups (`t('ns2:key')`).

12. Realtime & Dashboards

12.1 DASH-03 status

Migration shipped, UI wiring pending. The Phase 7 Plan 07-02 migration `20260603000010_phase7_dashboard_summary.sql` adds `get_dashboard_summary()` and the api-client wrapper. Plans 07-07 (mobile DASH-03 UI) and 07-08 (web DASH-03 UI) are not yet started.

12.2 RPC contract

`public.get_dashboard_summary()` returns a role-aware jsonb envelope:

Secretary / Co-Secretary / Board branch (DASH-01):

```
{
  "role": "secretary",
  "complaints": { "count": N, "previews": [{"id","title","flat"}, ...] },
  "bookings": { "count": N, "previews": [{"id","amenity","slot","flat"}, ...] },
  "notifications": { "count": N, "previews": [{"id","title"}, ...] },
  "flatActions": { "count": N, "previews": [{"id","kind","flat"}, ...] }
}
```

Member branch (DASH-02):

```
{
  "role": "member",
  "myComplaints": { "count": N, "previews": [{"id","title","status"}, ...] },
  "notifications": { "count": N, "previews": [{"id","title"}, ...] },
  "myBookings": { "count": N, "previews": [{"id","amenity","slot","status"}, ...] },
  "community": { "count": N, "previews": [{"id","author","flat","title"}, ...] }
}
```

Windows:

- complaints / notifications / flat_actions / posts: last 7 days
- bookings: pending only (no time cap — Secretary's queue)
- previews: LIMIT 2 per tile (D-04 contract)
- Slot rendered in IST (`Asia/Kolkata`) — `to_char(lower(b.time_range) at time zone 'Asia/Kolkata', 'Mon DD HH24:MI')` .
- Community previews filter both `hidden_at IS NULL` AND `deleted_at IS NULL` (T-07-05 mitigation).

12.3 What tiles surface (per role)

Role	Live tiles (after Phase 7 Plans 07-07 / 07-08 wired)
Member	My Complaints (count), Notifications (count), My Bookings (status), Community (count + recent) — plus the live Phase 1-3 tiles My Complaints / Directory / Society Code
Board Member	+ All Complaints, Bookings queue (pending), Notifications
Secretary / Co-Secretary	+ All the above + Reviews badge + Code Rotation badge + Flat Actions

12.4 Refresh model (D-01 / D-02 / D-03)

- **D-01 — Single round-trip:** one `get_dashboard_summary()` call returns counts + previews for all relevant tiles.
- **D-02 — Incremental Realtime patches:** per-tile Realtime subscriptions patch counts/previews in place (no full refetch per event).
- **D-03 — Focus + reconnect reconciliation:** full refetch on screen focus / Realtime reconnect heals any missed-event drift. Mobile uses `useFocusEffect` ; web uses `visibilitychange` + Realtime `system` event listener.

- **D-04 — Preview row format:** "New complaint: {{title}} · {{flat}}" — strings are i18n'd under `dashboard.previews.*`.

13. Testing & Verification

13.1 Test infrastructure

Layer	Tool	Notes
Web unit	Vitest 2.1.8 + @testing-library/react + jsdom	Single runner for <code>apps/web</code>
Mobile unit	Jest 29.7.0 + jest-expo + @testing-library/react-native	Different runtime (Hermes), separate runner
Shared packages	Vitest	All <code>packages/*</code> use Vitest
Isolation	Vitest against live local Supabase	<code>tests/isolation/</code> package; <code>pnpm test:isolation</code>
Edge Functions	Deno <code>node --check</code> + per-function unit tests	
Devanagari bundle	<code>scripts/check-devanagari-bundle.mjs</code>	CI gate
i18n key parity	<code>scripts/check-i18n-coverage.mjs</code>	CI gate
No-direct-import	<code>scripts/check-no-direct-locale-import.mjs --dir apps</code>	CI gate (Plan 07-06 promoted to blocking)
Maestro (mobile E2E)	Not installed	Planned in Plan 07-10
Playwright (web E2E)	Not installed	Planned in Phase 8

13.2 Coverage by phase (test counts cited in VERIFICATION.md files)

Phase	Isolation tests	Unit tests	Notes
1	20 (cross-tenant)	6 web + 6 mobile + 3 web	All green; 756 ms
2	27 (cross-tenant + rate-limit + OTP flow)	27 api-client + 8 web + 9 mobile	All green
3	21+ across 5 suites	78 api-client + ~30 mobile + ~25 web	All green
4	14	~30 api-client + ~30 mobile + ~25 web	All green; Test 6 locks atomic claim; Test 11 locks cross-society Realtime
04.1	(reuses Phase 1-3 + role-tiles unit)	41 must-haves verified	All green
5	20+ across 6 suites	173 api-client + ~120 mobile + ~80 web (per VERIFICATION)	All green; 23P01 → slot_taken locked
6	39 across 4 suites	adds to 173 api-client total + ~140 mobile + ~66 web	All green; byte-exact LOCKED footer locked
7	7 (dashboard-summary)	i18n locked-verbatim suite + dashboard preview tests	Green so far
Total isolation	~150 across 16 files		4,585 LOC of isolation tests

13.3 HUMAN-UAT outstanding (across phases)

Phase 2 — 4 items (mobile OTP flow, session persistence, logout, Devanagari). Phase 3 — 7 items (Secretary wizard mobile + web, Member join both platforms, mobile dashboard, mobile admin, web dashboard, web admin). Phase 4 — mobile + web walkthroughs (per-plan UAT files). Phase 04.1 — 6 items (bottom-nav, sidebar collapse, Devanagari tile labels, society switcher, placeholder a11y, sign-out push revoke verification). Phase 5 — 6 items (FCM delivery, 2-device poll tally, booking race UX, Devanagari, quiet-hours suppression, slot-taken UX). Phase 6 — 6 items (FCM to flat residents, image-safety reject, 2-device auto-hide, Devanagari footer, Grievance Officer surface, moderation restore/takedown audit).

Total: ~35 HUMAN-UAT items across 6 phases. All are runtime-on-device checks (FCM, Devanagari on OEM Android, 2-device races, image-safety, Realtime cross-device). None are code gaps — they need a tester with two Indian Android devices + a web browser pair.

13.4 Known flaky / skipped tests

- `apps/mobile/__tests__/booking-components.test.jsx` — "rejects a slot less than 1h ahead with leadTimeError" — flaky between ~23:00–23:59 local time (fixture cross-midnight bug). Documented in `.planning/phases/07-dashboards-i18n-polish-web-parity/deferred-items.md`. Fix: inject `nowMs` parameter into `validateRange`.
- Two Phase 3 dashboard tests intentionally archived to `*.skip.{js,jsx}` after Phase 04.1 replaced the dashboard pattern:

- `apps/mobile/__tests__/dashboard-03-07-PRE-04.1-archived.skip.js`
- `apps/web/app/__tests__/dashboard-03-09-PRE-04.1-archived.skip.jsx`

13.5 Test idempotency note

Isolation tests are **NOT** idempotent across repeated runs without a fresh `supabase db reset --local`. `otp-phone-flow.test.js` creates an auth user that `afterAll` deletes, but orphaned state from a prior run may cause failures. CI does a fresh DB on every run; local developers should reset before re-running.

14. Security Posture

14.1 Threat model coverage

Each phase's CONTEXT/VALIDATION docs reference a T-level threat model (T-04-19 Realtime cross-society leakage, T-05-05 sentinel header bypass, T-05-08 raw poll_votes inference, T-07-04 dashboard summary cross-society leakage, T-07-05 hidden-post leak via preview, etc.). Mitigations are coded and isolation-tested. The codebase is **ASVS Level 1 equivalent** at the RPC/RLS layer; ASVS L2 (key management, hardening) is Phase 8 work.

14.2 RLS posture

- **17 of 17 tenant-scoped tables have RLS enabled.** 3 internal tables (`otp_requests` , `code_redemptions` , `push_deliveries`) deliberately have no RLS and instead `REVOKE ALL` from `anon`, `authenticated` — only service-role / SECURITY DEFINER RPCs touch them.
- **Every RLS policy is keyed on `current_society_id()` from JWT.** No row-level policy reads raw `auth.uid()` for tenant scoping (it only narrows further inside the tenant).
- **Per-flat RLS via `can_see_flat_action()`** uses the JWT `auth.uid()` to sub-query `society_memberships` for the caller's flat. WR-01 in Phase 6 corrected a developer's incorrect assumption that the JWT carried `flat_id`.
- **Storage RLS** enforces society prefix on read/write/update/delete (`(storage.foldername(name))[1]::uuid = current_society_id()`).

14.3 SECURITY DEFINER discipline

Every SECURITY DEFINER RPC follows the pattern (verified per-migration):

1. `set search_path = public, auth` (Pitfall 1 — prevents search_path attacks).
2. Gate on `auth.uid()` + `current_society_id()` (raise `AUTH_REQUIRED` / `NO_SOCIETY`).
3. Role check via `current_membership_role()` where needed.
4. Input validation.
5. The actual atomic operation (UPDATE...WHERE...RETURNING for races).
6. `audit_log` write.
7. JSON return envelope.

8. Explicit `revoke all from public` ; explicit `grant execute to authenticated` (or `service_role` for fan-out helpers).

14.4 Cookie security (web)

- Auth session cookie — managed by `@supabase/ssr` , HttpOnly + Secure + SameSite=Lax.
- Locale cookie `parisar_lang` — NOT HttpOnly (client needs read access for `useTranslation`), SameSite=Lax, Secure. Whitelist-validated on write.
- Sidebar state cookie — only persistence concern.

14.5 Secrets handling

- All client envs are `NEXT_PUBLIC_*` / `EXPO_PUBLIC_*` allow-listed in `turbo.json` `globalEnv` .
- Service-role key never leaves the Edge Function runtime.
- Adapter API keys (MSG91, Twilio) wired via env vars per Edge Function — none committed.
- No hardcoded secrets in `.planning/` (planning docs are local-only anyway).

14.6 Open security debt

Item	Severity	Phase to fix
<code>[auth.sms.twilio]</code> <code>account_sid='dev-placeholder'</code> in <code>config.toml</code> must be removed before production	Medium (dev-only artifact; reaches production = no impact)	Phase 8
<code>msg91.js</code> and <code>twilio.js</code> adapters throw stubs	Blocks LAUNCH-01	Phase 8
No captcha on OTP endpoint	LAUNCH-02 blocker	Phase 8
<code>verify_jwt</code> per-function blocks not pinned in <code>config.toml</code> (IN-01 from Phase 6 review) — Supabase defaults <code>verify_jwt=true</code> ; in-function Bearer + <code>getUser()</code> is defense-in-depth. Carried as debt.	Low	Phase 8 hardening
Push Edge Functions positionally index Expo ticket responses without <code>result.data.length</code> guard (WR-05 from Phase 5 review)	Low (short responses could misattribute push_deliveries / staleTokens)	Phase 7 Plan 07-09 or Phase 8
No Sentry / no crash reporting	LAUNCH-03 blocker	Phase 8
No DPDP member-facing erasure flow (RPC exists, UI does not)	LAUNCH-05 blocker	Phase 8
No DLT registration	LAUNCH-04 blocker — external clock	Phase 8

15. What's NECESSARY before production (the punch list)

15.1 P0 — Blockers (without these, DO NOT ship)

ID	Item	Owner	Estimated effort	Dependency
P0-1	Choose OTP provider (MSG91 recommended for India per CLAUDE.md)	User decision	1 day to decide + procurement	None
P0-2	DLT / TRAI registration (Principal Entity + Header/Sender ID + Templates)	User-driven external	2–6 weeks calendar	P0-1
P0-3	Implement chosen OTP adapter in <code>supabase/functions/send-sms/adapters/<provider>.js</code> (replace throw stub)	Engineering	0.5 day	P0-1
P0-4	Remove <code>[auth.sms.twilio]</code> dev-placeholder from <code>supabase/config.toml</code> ; verify production deploy reads real provider config	Engineering	0.25 day	P0-3
P0-5	Wire captcha (hCaptcha or Turnstile) on OTP request endpoint; reject without valid token	Engineering	1 day	None
P0-6	Wire Sentry on web (<code>@sentry/nextjs</code>) and mobile (<code>@sentry/react-native/expo</code>); source-map upload from CI	Engineering	0.5 day	None
P0-7	Complete Phase 7 Plans 07-07 / 07-08 — DASH-03 live data wiring on both apps	Engineering	1 day per plan	None (Phase 7 in-flight)
P0-8	Finish HUMAN-UAT on a real Android device — at minimum: FCM delivery for each push type (complaint response, notice, booking ack, flat action), Devanagari rendering on OEM Android, 2-device booking race, image-safety reject, cross-device community auto-hide	Founder / QA	4–6 hours hands-on	Phase 7 done; two Android devices
P0-9	CI/CD to staging + production environments — Vercel deploy for web, EAS Build for mobile, staging Supabase project, production env management, deploy gating on isolation test pass	DevOps	1–2 days	Hosting decision
P0-10	DPDP-compliant member-facing erasure UX (LAUNCH-05) — wire the existing <code>remove_member</code> RPC into a member-initiated flow + Secretary approval + backup-overwrite marker	Engineering	1 day	None
P0-11	Verify the lighthouse loop end-to-end on real hardware — Member files complaint on phone A → Board responds on phone B → Member receives push within ~5s → Tap deep-links into detail	Founder + tester	1 hour	All above

15.2 P1 — Must-haves (ship-blocking quality)

ID	Item	Estimated effort
P1-1	Phase 7 Plan 07-09 advisory-debt fold — WR-03 grapheme-aware avatar, IN-02 fine-overdue unification	0.5 day
P1-2	Phase 7 Plan 07-10 — responsive viewport sanity tests (phone/tablet/desktop) + Maestro language-switch + dashboard-preview flows + Devanagari API 26/30/34 matrix (documented HUMAN-UAT if CI emulator matrix too heavy)	1 day
P1-3	Fix flaky cross-midnight test (<code>booking-components.test.jsx</code>) via <code>nowMs</code> injection	0.25 day
P1-4	Resolve <code>verify_jwt</code> per-function pinning in <code>config.toml</code> (Phase 6 IN-01)	0.25 day
P1-5	Fix push Edge Function positional-index race (WR-05)	0.25 day
P1-6	Accessibility deep audit on both apps (the 04.1 placeholder a11y + sign-out flow + screen-reader on tile preview rows)	1 day
P1-7	Mobile app icon, splash screen, store assets (App Store + Google Play screenshots in en/hi/mr)	1 day
P1-8	Privacy policy + terms of service in en/hi/mr (DPDP requires localized)	0.5 day (drafting); legal review separate
P1-9	Onboarding error-message refinement — every RPC failure path has a user-friendly localized message, not a raw <code>INSUFFICIENT_ROLE</code> / <code>INVALID_FLAT</code> exception text	0.5 day
P1-10	Performance audit — Next.js bundle size, first-paint timing on a slow 3G Indian network; image lazy-loading on community feed	0.5 day

15.3 P2 — Should-haves (polish, observability, docs)

ID	Item
P2-1	PostHog (or equivalent) product analytics so the founder can measure "did the member-files-complaint loop actually fire?"
P2-2	Operational runbook (rotate OTP provider, rotate Supabase service role, restore from backup)
P2-3	On-call playbook for SMS provider outage → kill-switch toggle
P2-4	Per-society backup / restore documentation
P2-5	Migration to <code>react-native-mmkv</code> for hot-path key/value (auth tokens, active society id) — perf only
P2-6	TanStack Query introduction if mutation patterns get hand-rolled in too many places
P2-7	Moti / Reanimated 4 for richer status transitions (if user UAT shows desire)
P2-8	Onboarding video / GIF demo for the Secretary 6-step wizard
P2-9	Auto-pruning of <code>push_deliveries</code> rows older than 24h (currently grows unbounded — deferred to Phase 8 in 05 migration comment)
P2-10	Auto-pruning of <code>otp_requests</code> rows older than 24h (same comment)
P2-11	Verified status-trail badging ("Posted by Rahul (B-203)" emphasized in UI) — already coded, polish only
P2-12	Dark mode (post-launch nice-to-have)
P2-13	Web push notifications for board members (currently web has in-app only)

16. What's DONE (concrete deliverables already in the repo)

Every claim below is anchored to a file path.

16.1 Foundation

- 10 SQL migrations apply cleanly on `supabase db reset --local` (audit_log row count + table count match expectations).
- Multi-tenant RLS verified on **17 of 17 tenant-scoped tables** (3 internal tables deliberately `REVOKE ALL`).
- `inject_society_claims` Postgres function injects `society_id` + `role` into JWT app_metadata on sign-in and refresh (`supabase/migrations/20260430000003_rls_policies.sql:103-153`).
- `parisar-attachments` Storage bucket private + prefix-RLS (`supabase/migrations/20260430000004_storage_bucket_rls.sql`).

- pnpm + Turborepo + Biome monorepo with 5 packages and 2 apps (`pnpm-workspace.yaml` , `turbo.json` , `biome.json`).
- 5-job CI pipeline (`.github/workflows/ci.yml`).
- 20-assertion isolation test (`tests/isolation/cross-tenant-isolation.test.js`); ~150 total isolation tests across 16 files.

16.2 Auth

- Phone-OTP login on both apps (`apps/mobile/app/(auth)/{login,verify}.jsx` , `apps/web/app/(auth)/{login,verify}/page.jsx`).
- Swappable OTP adapter (`supabase/functions/send-sms/{index.js,adapters/{stub,msg91,twilio}.js}`); MSG91/Twilio are throw stubs for Phase 8.
- Per-phone + per-IP rate limits (`otp_requests` table + `[auth.rate_limit]` block).
- SecureStore session (mobile) + cookie session via `@supabase/ssr` (web) — both verified for cross-restart persistence in code.
- Logout revokes push token before clearing session (`apps/mobile/lib/auth-store.js` , `apps/web/app/actions/auth.js`).
- Role picker on first signup writes `profiles.signup_intent` .

16.3 Society setup + member onboarding

- Mandatory co-secretary phone at society creation (`create_society_with_secretary` RPC).
- 6-step wizard on both apps (`apps/mobile/app/(protected)/setup.jsx` , `apps/web/app/(protected)/setup/*`).
- Society Code auto-generated, rotatable, rate-limited (`generate_society_code` , `rotate_society_code` , ≥5/60s auto-pause inside `redeem_society_code`).
- Member join with duplicate-flat → `pending_review` (`redeem_society_code`).
- Co-secretary auto-elevation on phone match.
- Phone-privacy reveal with `audit_log` entry per reveal (`reveal_phone` RPC + `PhonePrivacyChip` on both platforms).
- DPDP-compliant member removal (`remove_member` RPC + `DestructiveConfirmDialog` on both platforms).
- Role transfer (`transfer_secretary_role`).
- Joined-percent gauge with 30s poll + AppState pause (mobile) / interval (web).

16.4 Complaints (lighthouse)

- Atomic first-responder claim (`claim_complaint` RPC; isolation test 6 verifies exactly-one-winner under Promise.all race).
- Realtime patches new complaints + responses into board lists (`subscribeToComplaints` , `subscribeToComplaintResponses`).
- Push fan-out via `push-fanout` Edge Function (`supabase/functions/push-fanout/index.js`), batched ≤100, DeviceNotRegistered cleanup.
- Photo capture → resize → ArrayBuffer → Supabase Storage upload chain (mobile + web).
- Deep-link from push tap to complaint detail (`apps/mobile/app/_layout.jsx` notification handler).

16.5 Dashboard shell (04.1)

- Role-aware tile config + placeholder cards with screen-reader announcements
(`apps/{web,mobile}/lib/role-tiles.js` ,
`apps/{web,mobile}/components/dashboard/DashboardTile.jsx`).
- Mobile bottom-nav (`( tabs )/_layout.jsx`) + web sidebar
(`apps/web/components/dashboard/AppSidebar.jsx`).
- Society switcher (visual-only v1 stub).
- ProfileMenu (sheet on mobile, dropdown on web) with Sign Out + push-token revoke.
- Avatar helper + Reviews badge with 99+ clamp.

16.6 Notifications, polls, bookings

- Notification + optional 2-4 option poll in one transaction (`file_notification`).
- Anti-bandwagon PollBlock — pre-vote = options only, post-vote = live tally
(`apps/{web,mobile}/components/notices/PollBlock.jsx`).
- Mute + IST quiet-hours wrap + rolling-24h cap server-side via `eligible_push_recipients`
(`supabase/migrations/20260528000008_phase5_notifications_bookings.sql:768-821`).
- Booking request with server-side lead/duration/hours guards (`request_booking`).
- Atomic first-approval (`approve_booking`) + `bookings_no_overlap` exclusion constraint catching 23P01 → clean `slot_taken` .
- Devanagari LOCKED strings for बुकिंग / मतदान / मंजूर present (verified by parity gate).

16.7 Flat actions + community feed

- Admin-only flat actions; `co_secretary` = secretary, `board_member` CANNOT issue or waive
(`issue_flat_action` , `waive_fine`).
- Member acknowledge own fine (`acknowledge_fine`).
- Per-flat RLS via `can_see_flat_action()` .
- LOCKED no-payment footer byte-exact en/hi/mr, rendered on every fine surface
(`packages/il8n/___tests___/locked-verbatim.test.js`).
- Optional bylaw PDF (`uploadFinePdf{,Web}`).
- Community post composer with quarantine → moderate-image → create_post handoff
(`packages/api-client/src/community.js`).
- Swappable image-safety adapter + fail-closed (`supabase/functions/moderate-image/{index,providers/*}.js`).
- First-report-wins server-side auto-hide via `hidden_at = coalesce(hidden_at, now())`
(`report_content`); RLS filters `hidden_at` for non-admins.
- Moderation queue + audit log (`apps/{mobile,web}/.../moderation/index.{jsx,page.jsx}`).
- Grievance Officer config + About/Help surface with COALESCE-to-Secretary default
(`get_grievance_officer`).
- Author-only soft delete (`delete_post` , `delete_comment`).

16.8 Phase 7 (in flight, 6/10 done)

- i18next runtime live on both apps with `i18next-resources-to-backend` lazy-load.
- 164 screen files retrofitted to `useTranslation` (zero direct shard imports remain).
- CI gates `check-i18n-coverage` , `check-no-direct-locale-import --dir apps` , extended `check-devanagari-bundle` all green and blocking.
- Language switcher on both apps with whitelist-on-read-AND-write, AsyncStorage (mobile) / cookie (web) persistence.
- `get_dashboard_summary()` RPC + isolation test (`tests/isolation/dashboard-summary.test.js` , 7 tests green).
- Web `dashboard/page.jsx` WR-01 redirect (no more silent admin → member downgrade).

16.9 Cross-cutting

- 6 Edge Functions all node --check clean: `send-sms` , `push-fanout` , `notification-fanout` , `booking-ack-fanout` , `flat-action-fanout` , `moderate-image` .
 - `audit_log` table written by every state-changing RPC; Secretary-only SELECT.
 - ~4,585 LOC of isolation tests across 16 files; all green against fresh `supabase db reset --local` .
-

17. What's NOT YET in scope (deferred — clearly stated)

These are **out of v1 by design** per PROJECT.md and REQUIREMENTS.md. Do not let them creep into Phase 8.

Feature	Reason
Payments / fine collection	User-explicit; PCI scope avoidance. Fines are notices only. The LOCKED no-payment footer is the user-facing contract.
Maintenance bills / dues ledger	Adjacent to payments; v1.1+.
Visitor / gate management (QR check-in)	Phase 9 (post-launch). MyGate's flagship — not v1.
Staff / help attendance	Phase 10 (post-launch).
Vendor directory	Phase 11 (post-launch).
Document vault	Single attachment per notification only; bylaws/AGM archive deferred to v2 (DOC-01).
Cross-society messaging or admin tooling	Each society is an isolated tenant.
Email notifications	Push + in-app only.
Native iOS- or Android-only features	Same feature set both platforms via Expo.
Offline support beyond minimal caching	App requires connectivity (Realtime is core).
In-app chat / DMs between members	Slack/WhatsApp territory.
In-app election workflow	Manual <code>transfer_secretary_role()</code> in v1; ELEC-01 in v2.
Multi-society users	Schema supports it; v1 auth hook picks most-recent membership. MULTI-01 in v2.
Owner-only polls	Schema reservation; POLL-01 in v2.
Voice messages on complaints/posts	Schema reservation (<code>mime_type</code> , <code>duration_seconds</code>); VOICE-01 in v2.
Comments on posts as a promoted feature	<code>post_comments</code> table exists; CMNT-01 in v2 for UX promotion.
Functional multi-society switcher	Visual-only stub in v1; Phase 8 if multi-society demand emerges.
Dark mode	Post-launch polish.
Web push notifications	Mobile push is core; web push is post-launch.
Customer-facing analytics / reports for Secretary	Not in v1 (audit_log is internal).

18. Recommended Path to Production

Given Phase 7 is mid-flight and Phase 8 is greenfield, here is the path from "today" to "v1.0 in production". Effort estimates are at the observed plan-execution velocity (~1.5 hours per plan based on Phase 7 Plans 01–06 metrics).

Step 1 — Finish Phase 7 (*estimated 2–3 days engineering*)

1. **Plan 07-07** Mobile DASH-03 wiring — ~1 day. Summary store + per-society Realtime subscriptions + `DashboardTilePreview` component + focus reconciliation refetch.
2. **Plan 07-08** Web DASH-03 wiring — ~1 day. SSR initial summary in `dashboard/page.jsx`; DashboardClient Realtime patches; preview component mirror; `/my-complaints` alias route.
3. **Plan 07-09** Advisory debt — ~0.5 day. Grapheme-aware `initials()` / `getAvatarColor()` via shared `packages/api-client/src/text/graphemes.js`; unify `fine-overdue.js`; document the two-society-code-tiles intentional duplication.
4. **Plan 07-10** Final gate — ~0.5–1 day. Responsive sanity test; Maestro language-switch + dashboard-preview flows; produce `07-HUMAN-UAT.md` for Devanagari Android API 26/30/34 matrix.

Exit gate: `pnpm test:isolation` green, all CI gates green, `07-VERIFICATION.md` written with `human_needed` for the device matrix only.

Step 2 — Run the accumulated HUMAN-UAT pass (*estimated 4–6 hours hands-on*)

Two Indian Android devices (one preferably budget OEM with non-stock font ROM); two web browser profiles. Run the ~35 UAT items across Phases 2/3/4/04.1/5/6/7:

- Mobile OTP, session persistence, logout, Devanagari rendering (Phase 2).
- Secretary wizard mobile + web; Member join both platforms; admin DPDP removal verification in Supabase Studio (Phase 3).
- Complaint file → board respond → push delivery → tap deep link end-to-end (Phase 4).
- Bottom-nav, sidebar collapse, Devanagari tile labels, society switcher, placeholder a11y, sign-out push revoke verification (Phase 04.1).
- 2-device poll tally; 2-device booking race; quiet-hours and cap suppression (Phase 5).
- FCM to flat residents; image-safety reject; 2-device community auto-hide; Devanagari fine footer; Grievance Officer surface; moderation restore/takedown (Phase 6).
- Maestro language-switch + Devanagari golden-screenshot matrix (Phase 7 Plan 07-10).

Exit gate: Every HUMAN-UAT file has `result: passed` for the critical loop items. Document any new bugs as Phase 8 tasks.

Step 3 — Decide OTP provider + kick off DLT (*starts the 2–6 week external clock*)

- Choose MSG91 (recommended) or Twilio. Firebase changes adapter shape (verifyOtp returns Firebase ID token → exchange for Supabase session) — different work.
- Apply for DLT Principal Entity registration on each major Indian telco's DLT platform.
- Register Header / Sender ID (e.g. `PARISR`).

- Draft + register each Template variant (OTP, status alerts, notifications). Every variation needs separate approval.

Exit gate: Header and at least the OTP template approved on the chosen provider's DLT pipeline. (Other templates can land while engineering Phase 8.)

Step 4 — Phase 8 engineering work (*estimated 4–5 days, parallel with DLT*)

Run in parallel with Step 3's DLT clock.

1. **Plan 08-01 — Production OTP swap** — implement chosen adapter in `supabase/functions/send-sms/adapters/<provider>.js`; remove `[auth.sms.twilio]` dev-placeholder; smoke-test against a single test phone using approved DLT template.
2. **Plan 08-02 — Captcha** — pick hCaptcha or Cloudflare Turnstile; widget on `(auth)/login` (both apps); server-side token verification in the OTP request server action; reject without token.
3. **Plan 08-03 — Sentry** — install `@sentry/nextjs` + `@sentry/react-native/expo` config plugin; single Sentry project; source-map upload in CI.
4. **Plan 08-04 — DPDP erasure UX** — member-facing "Request data erasure" screen in both apps; Secretary approval queue; `remove_member` RPC consumption; backup-overwrite marker (likely a `pending_backup_overwrite` column on a future `dmdp_requests` table — design at planning time).
5. **DLT verification + kill-switch** — env var to disable outbound SMS instantly; doc + runbook for SMS-provider outage.
6. **CI/CD to staging + production** — Vercel deploy for web, EAS Build for mobile, staging Supabase project (separate from local), production env management, deploy gating on `pnpm test:isolation` pass.

Exit gate: `08-VERIFICATION.md` confirms LAUNCH-01..05 satisfied; OTP delivery rate $\geq 95\%$ in beta; Sentry receiving events from both clients; DPDP request flows end-to-end.

Step 5 — Beta + launch (*estimated 1–2 weeks beta + soft launch*)

1. **Closed beta with 1–3 societies** (cooperative friends; well-known testers). Founder watches Sentry + PostHog (if installed) and the `audit_log`.
2. **Iterate on real-user feedback** for 1 week. Hot-fix issues via small `gsd-quick` plans.
3. **Soft launch** — App Store + Google Play submission + Vercel production. Capture feedback for 2 weeks before broader marketing.

Exit gate: Lighthouse loop verified on 3 real societies (Member → Complaint → Board responds → Status updates → Member notified within 60s end-to-end including push tap). Sentry shows no critical unhandled errors.

Total path estimate

Stage	Engineering	Calendar
Phase 7 finish	2–3 days	1 week
HUMAN-UAT pass	0.5 day hands-on + bug-fix slack	1 week (allow time for found-bug fixes)
Phase 8 engineering (parallel to DLT)	4–5 days	2–3 weeks
DLT external clock	n/a — procurement	2–6 weeks (overlaps Phase 8)
Closed beta	0.5 day support per week	1 week
Soft launch	App Store / Play Store review windows	1–2 weeks
Total	~8–9 engineering days	~6–10 calendar weeks (DLT is the long pole)

19. Appendix: Key Artefacts & Where to Find Them

19.1 Canonical planning docs

Doc	Path
Product vision + scope + decisions	<code>/home/nexapp/Documents/personal/parisar/.planning/PROJECT.md</code>
Roadmap (all phases, success criteria)	<code>/home/nexapp/Documents/personal/parisar/.planning/ROADMAP.md</code>
Every v1 requirement (81 total, traceability table)	<code>/home/nexapp/Documents/personal/parisar/.planning/REQUIREMENTS.md</code>
Current state snapshot (status, decisions log)	<code>/home/nexapp/Documents/personal/parisar/.planning/STATE.md</code>
Project conventions (JS-only, MyGate reference, git policy)	<code>/home/nexapp/Documents/personal/parisar/CLAUDE.md</code>

19.2 Per-phase artifacts

```
.planning/phases/
├── 01-foundation/
│   ├── 01-{01..04}-SUMMARY.md
│   └── 01-VERIFICATION.md
├── 02-auth-otp-adapter/
│   ├── 02-{01..04}-SUMMARY.md
│   ├── 02-UI-SPEC.md
│   ├── 02-HUMAN-UAT.md
│   └── 02-VERIFICATION.md
├── 03-society-setup-member-onboarding/
│   ├── 03-{01..10}-SUMMARY.md
│   ├── 03-{04..10}-HUMAN-UAT.md (per-plan)
│   ├── 03-UI-SPEC.md
│   └── 03-VERIFICATION.md
├── 04-complaints-lighthouse/
│   ├── 04-{01..05}-SUMMARY.md
│   ├── 04-{04,05}-HUMAN-UAT.md
│   ├── 04-UI-SPEC.md
│   └── 04-VERIFICATION.md
├── 04.1-dashboard-shell-unified-mygate-style-home-wiring-existing-ph/
│   ├── 04.1-{00..05}-SUMMARY.md
│   ├── 04.1-CONTEXT.md
│   ├── 04.1-UI-SPEC.md
│   ├── 04.1-HUMAN-UAT.md
│   └── 04.1-VERIFICATION.md
├── 05-notifications-polls-bookings-parallel-track-a/
│   ├── 05-{01..06}-SUMMARY.md
│   ├── 05-CONTEXT.md
│   ├── 05-UI-SPEC.md
│   ├── 05-HUMAN-UAT.md
│   └── 05-VERIFICATION.md
├── 06-flat-actions-community-feed-parallel-track-b/
│   ├── 06-{01..06}-SUMMARY.md
│   ├── 06-CONTEXT.md
│   ├── 06-UI-SPEC.md
│   ├── 06-HUMAN-UAT.md
│   └── 06-VERIFICATION.md
└── 07-dashboards-il8n-polish-web-parity/
    ├── 07-{01..06}-SUMMARY.md (DONE)
    ├── 07-{07..10}-PLAN.md (PENDING – no SUMMARY yet)
    ├── 07-CONTEXT.md
    ├── 07-RESEARCH.md
    ├── 07-UI-SPEC.md
    ├── 07-DISCUSSION-LOG.md
    ├── 07-VALIDATION.md
    └── deferred-items.md
```

19.3 Code anchors for top-line claims

Claim	File
Atomic first-responder claim	<code>supabase/migrations/20260526000007_phase4_complaints.sql</code> <code>claim_complaint</code> (lines 267–336)
Booking overlap exclusion	<code>supabase/migrations/20260528000008_phase5_notifications_bookings.sql</code> <code>bookings_no_overlap</code> constraint (lines 215–225)
Eligible-recipients filter (mute + IST wrap + cap)	<code>supabase/migrations/20260528000008_phase5_notifications_bookings.sql</code> <code>eligible_push_recipients</code> (lines 768–821)
Per-flat RLS	<code>supabase/migrations/20260529000009_phase6_flat_actions_community.sql</code> <code>can_see_flat_action</code> (lines 231–253)
Server-side first-report-wins auto-hide	<code>supabase/migrations/20260529000009_phase6_flat_actions_community.sql</code> <code>report_content</code> (lines 647–706)
Dashboard summary RPC + RLS-respecting filters	<code>supabase/migrations/20260603000010_phase7_dashboard_summary.sql</code> (whole file)
Custom Access Token Hook	<code>supabase/migrations/20260430000003_rls_policies.sql</code> <code>inject_society_claims</code> (lines 103–161)
Auth hook config	<code>supabase/config.toml</code> <code>[auth.hook.custom_access_token]</code> + <code>[auth.hook.send_sms]</code>
Cross-tenant isolation lighthouse test	<code>tests/isolation/cross-tenant-isolation.test.js</code>
Push fan-out (complaints)	<code>supabase/functions/push-fanout/index.js</code>
Notification fan-out (society-wide)	<code>supabase/functions/notification-fanout/index.js</code>
Flat-action fan-out (per-flat)	<code>supabase/functions/flat-action-fanout/index.js</code>
Image moderation (swappable adapter, fail-closed)	<code>supabase/functions/moderate-image/{index,providers/*.js}</code>
Mobile root layout (i18n + auth + push)	<code>apps/mobile/app/_layout.jsx</code>
Web root layout (i18n cookie + provider)	<code>apps/web/app/layout.jsx</code>
Web protected guard	<code>apps/web/app/(protected)/layout.jsx</code>
Mobile dashboard home	<code>apps/mobile/app/(protected)/(tabs)/index.jsx</code>
Web dashboard home	<code>apps/web/app/(protected)/dashboard/page.jsx</code> + <code>DashboardClient.jsx</code>
Role-aware tile config	<code>apps/{web,mobile}/lib/role-tiles.js</code>

Claim	File
Shared call layer	<code>packages/api-client/src/{complaints,notifications,polls,bookings,flat-actions,community,society,otp,preferences,dashboard}.js</code>
i18n shards	<code>packages/i18n/locales/{en,hi,mr}/{9 namespaces}.json</code>
Locked-verbatim snapshot suite	<code>packages/i18n/__tests__/locked-verbatim.test.js</code>
CI pipeline	<code>.github/workflows/ci.yml</code>
Devanagari bundle check	<code>scripts/check-devanagari-bundle.mjs</code>
i18n parity gate	<code>scripts/check-i18n-coverage.mjs</code>
No-direct-import gate	<code>scripts/check-no-direct-locale-import.mjs</code>

19.4 Reading order for a new engineer joining the project

1. `CLAUDE.md` — conventions, stack, **JS not TS**, no git.
2. `.planning/PROJECT.md` — product vision, the core loop.
3. `.planning/ROADMAP.md` — what's done, what's next.
4. `supabase/migrations/*.sql` in order — schema as code, the contract everything else honors.
5. `packages/api-client/src/index.js` — the API surface.
6. `apps/mobile/app/_layout.jsx` + `apps/web/app/layout.jsx` — root composition (i18n, auth, push, providers).
7. `apps/{mobile,web}/lib/role-tiles.js` — what the user sees.
8. `tests/isolation/cross-tenant-isolation.test.js` — the security gate.
9. Pick a phase you'll touch → read its `*-CONTEXT.md`, `*-UI-SPEC.md`, `*-VERIFICATION.md`, and the relevant plan SUMMARIES.

End of report.

Audit performed against the codebase at `/home/nexapp/Documents/personal/parisar` on 2026-06-14. No code was modified during this audit.