

DBMS/SQL

Lesson 10: Data
Manipulation Language

Lesson Objectives

- To understand the following topics:
 - Adding Data
 - Removing Data
 - Modifying Data



10.1: Concept of Data Manipulation Language

Data Manipulation Language

- Data Manipulation Language (DML) is used to perform the following routines on database information:
 - Retrieve
 - Insert
 - Modify
- DML changes data in an object. If you insert a row into a table, that is DML.
- All DML statements change data, and must be committed before the change becomes permanent.

10.1: Addition of Data into Tables

INSERT

- **INSERT command:**

- INSERT is a DML command. It is used to add rows to a table.
- In the simplest form of the command, the values for different columns in the row to be inserted have to be specified.
- Alternatively, the rows can be generated from some other tables by using a SQL query language command.



Copyright © Capgemini 2015. All Rights Reserved 4

Addition of Data into Tables:

Requisites for using INSERT command:

If values are specified for all columns in the order specified at creation, then col_names could be omitted.

Values should match “data type” of the respective columns.

Number of values should match the number of column names mentioned.

All columns declared as NOT NULL should be supplied with a value.

Character strings should be enclosed in quotes.

Date values should be enclosed in quotes.

Values will insert one row at a time.

Query will insert all the rows returned by the query.

The table_name can be a “table” or a “view”. If table_name is a “view”, then the following restrictions apply:

The “view” cannot have a GROUP BY, CONNECT BY, START WITH, DISTINCT, UNION, INTERSECT, or MINUS clause or a join.

If the “view” has WITH CHECK OPTION clause, then a row, which will not be returned by the view, cannot be inserted.

10.1: Addition of Data into Tables

Inserting Rows into a Table

- Inserting by specifying values:

Example: To insert a new record in the DEPT table

```
INSERT INTO table_name[(col_name1,col_name2,...)]  
{VALUES (value1,value2,...) | query};
```

```
INSERT INTO Department_master  
VALUES (10, 'Computer Science');
```



Copyright © Capgemini 2015. All Rights Reserved 5

Inserting Rows into a Table:

Example:

Inserting a row in EMP table giving all values.

```
INSERT INTO student_master  
VALUES(1001,'Amit',10,'11-Jan-80','Chennai');
```

10 is a dept number which exists in DEPARTMENT_MASTER table

Inserting a row in STAFF_MASTER table giving some values.

```
INSERT INTO staff_master  
(staff_code,staff_name,design_code,dept_code)  
VALUES(100001,'Arvind',102,30);
```

This row will be created if all the constraints like NOT NULL are satisfied.

10.1: Addition of Data into Tables

Inserting Rows into a Table

- Inserting rows in a table from another table using Subquery:

Example: The example given below assumes that a new_emp_table exists. You can use a subquery to insert rows from another table.

```
INSERT INTO new_staff_table  
SELECT * FROM staff_master  
WHERE staff_master.hiredate > '01-jan-82';
```

10.1: Addition of Data into Tables

Inserting Rows into a Table

- Inserting by using “substitution variables”:

Example: In the example given below, when the command is run, values are prompted every time.

```
INSERT INTO department_master  
VALUES (&dept_code, '&dept_name');  
Enter a value for dept_code : 20  
Enter a value for dept_name : Electricals
```



Copyright © Capgemini 2015. All Rights Reserved 7

Inserting Rows into a Table:

Inserting by using “substitution variables”:

The problem with the INSERT statement is that it adds only “one row” to the table.

However, by using “substitution variables” the speed of data input can be increased.

Whenever a “substitution variable” is placed in a “value” field, the user will be prompted to enter the “actual value” when the command is executed.

10.2: Deletion of Data from Tables

DELETE

- The DELETE command is used to delete one or more rows from a table.
- The DELETE command removes all rows identified by the WHERE clause.

```
DELETE [FROM] {table_name | alias }  
[WHERE condition];
```



Copyright © Capgemini 2015. All Rights Reserved 8

Deletion of Data from Tables

The table_name can be a “table” or a “view”.

The DELETE command is used to delete one or more rows from a table.

The DELETE statement removes all rows identified by the WHERE clause.

This is another DML, which means we can rollback the deleted data, and that to make our changes permanent.

If WHERE clause is omitted, all rows from the table are removed. Else all rows which satisfy the condition are removed.

FROM clause can be omitted without affecting the statement.

10.2: Deletion of Data from Tables

Deleting Rows from Table

- Example 1: If the WHERE clause is omitted, all rows will be deleted from the table.
- Example 2: If we want to delete all information about department 10 from the Emp table:

```
DELETE  
FROM staff_master;
```

```
DELETE  
FROM student_master  
WHERE dept_code=10;
```



Copyright © Capgemini 2015. All Rights Reserved 9

Deletion of Data from Tables

Example 3:

```
DELETE staff_master WHERE staff_name = 'Anil';
```

10.3: Modifying / Updating existing Data in a Table

UPDATE

- Use the UPDATE command to change single rows, groups of rows, or all rows in a table.
- In all data modification statements, you can change the data in only “one table at a time”.

```
UPDATE table_name
SET col_name = value|
    col_name = SELECT_statement_returning_single_value|
    (col_name,...) = SELECT_statement
[WHERE condition];
```



Copyright © Capgemini 2015. All Rights Reserved 10

Modifying / Updating existing Data in a Table:

The table_name can be a “table” or a “view”.

The “value” can be a value, an expression, or a query, which returns a single value.

The UPDATE command provides automatic navigation to the data.

Note: If the WHERE clause is omitted, all rows in the table will be updated by a value that is currently specified for the field. Else only those rows which satisfy the condition will be updated.

10.3: Modifying / Updating existing Data in a Table

Updating Rows from Table

- Example 1: To UPDATE the column “dname” of a row, where deptno is 10, give the following command:

```
UPDATE department_master  
SET dept_name= 'Information Technology'  
WHERE dept_code=10;
```

10.3: Modifying / Updating existing Data in a Table

Updating Rows from Table

- Example 2: To UPDATE the subject marks details of a particular student, give the following command:

```
UPDATE student_marks  
SET subject1= 80 , subject2= 70  
WHERE student_code=1005;
```

10.3: Modifying / Updating existing Data in a Table

Using a Subquery to do an Update

- For making salary of “Anil” equal to that of staff member 100006, use the following command:

```
UPDATE staff_master  
SET staff_sal = (SELECT staff_sal FROM staff_master  
                WHERE staff_code = 100006 )  
WHERE staff_name = 'Anil';
```

10.3: Modifying / Updating existing Data in a Table

MERGE statement

- The MERGE statement, provides the ability to conditionally update or insert data into a database table.
- The MERGE statement, performs an UPDATE if the row exists, and an INSERT if it is a new row:
 - Increases performance and ease of use
 - Is useful in data warehousing applications
 - Avoids separate updates



Copyright © Capgemini 2015. All Rights Reserved 14

MERGE Statement

The MERGE statement is used mostly in data warehouse environments to build the data in warehouse

10.3: Modifying / Updating existing Data in a Table

MERGE statement

- You can conditionally insert or update rows in a table by using the MERGE statement

```
MERGE INTO table_name table_alias
USING (table|view|sub_query) alias
ON (join condition) WHEN MATCHED THEN
UPDATE SET
col1 = col_val1,
col2 = col2_val
WHEN NOT MATCHED THEN
INSERT (column_list)
VALUES (column_values);
```



Copyright © Capgemini 2015. All Rights Reserved 15

INTO : this is how we specify the target for the MERGE. The target must be either a table or an updateable view (an in-line view cannot be used here);

USING : the USING clause represents the source dataset for the MERGE. This can be a single table (as in our example) or an in-line view;

ON () : the ON clause is where we supply the join between the source dataset and target table. Note that the join conditions must be in parentheses;

WHEN MATCHED: this clause is where we instruct Oracle on what to do when we already have a matching record in the target table (i.e. there is a join between the source and target datasets). We obviously want an UPDATE in this case. One of the restrictions of this clause is that we cannot update any of the columns used in the ON clause (though of course we don't need to as they already match). Any attempt to include a join column will raise an unintuitive invalid identifier exception; and

WHEN NOT MATCHED : this clause is where we INSERT records for which there is no current match.

Note that sqlplus reports the number of rows merged. This includes both the updates and inserts. Oracle treats MERGE as a MERGE and not an UPDATE+INSERT statement. The same is true of SQL%ROWCOUNT in PL/SQL.

10.3: Modifying / Updating existing Data in a Table

Example on Merge

■ Example

```
CREATE table staff_copy as select staff_code,staff_name,dept_code  
FROM staff_master where 1=2;
```

```
MERGE into staff_copy using staff_master  
ON (staff_master.dept_code=staff_copy.dept_code)  
WHEN MATCHED THEN  
UPDATE SET staff_code=staff_master.staff_code,  
staff_name=staff_master.staff_name  
WHEN NOT MATCHED THEN  
INSERT (staff_code,staff_name,dept_code) values  
(staff_master.staff_code,staff_master.staff_name,staff_master.dept_code)
```


Summary

- In this lesson, you have learnt:
 - The concept of Data Manipulation Language
 - Inserting rows into a table
 - Deleting rows from a table
 - Updating rows in a table
 - Using Merge Statement



Review - Questions

- Question 1: Both TRUNCATE statement and DELETE without condition removes the entire data from a table
 - True/False
- Question 2: All DML statements are auto committed
 - True/False
- Question 3: In a transaction, DDL statement after DML statement commits the changes done by DML.
 - True/False



Review - Questions

- Question 4: Inserting rows in a table emp1 from another table can be done using ____.
- Option 1: insert into emp1(t1) as select empno from emp
- Option 2: insert into emp1(t1) select empno from emp
- Option 3: insert into emp1(t1) as select * from emp

