

DBMS/SQL

Lesson 12: Data Control Language

Lesson Objectives

- Data Control Language
 - Data Control
 - Object Privileges
 - Grant and Revoke Statements



12.1: Data Control Language

User Access Control

- With Oracle server you can maintain database security, by:
 - Controlling database access
 - Giving access to specific objects in the database
 - Confirming given and received privileges with the Oracle data dictionary



Copyright © Capgemini 2015. All Rights Reserved 3

In a typical multi-user environment, you need to maintain security of the database access and use. As far as Database Security is concerned it can be at System Level and Data Level. System Security concerns items in the database such as users, usage of disk space etc... Data Security would mean access and usage of database objects.

12.2: Object Privileges

Object Privileges

- Object Privileges are required to manipulate the content of the database objects
- Owner of the object has all the object privileges on that object.
- Owner can give or take out privileges on a particular object
- Object privileges can differ from object to object



Copyright © Capgemini 2015. All Rights Reserved 4

Object Privilege:


The right to execute a particular SQL statement is known as a Privilege. The DBA is a high level user who has access to all the objects in the database.

Object Privilege is a right to manipulate the content of database objects. In other words, object privilege is right to perform a particular action on a specific table, view etc.. Different object privileges are available for different types of objects. The owner of the object automatically has all object privileges on that object.

12.2: Object Privileges

Object Privileges

Object Privilege	Table	View	Sequence	Procedure
SELECT	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
UPDATE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		
DELETE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		
INSERT	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		
ALTER	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>	
INDEX	<input checked="" type="checkbox"/>			
REFERENCES	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		
EXECUTE				<input checked="" type="checkbox"/>


Copyright © Capgemini 2015. All Rights Reserved 5

Each object has a set of privileges which can be granted. The lists of privileges which can be granted on a particular object is shown on the slide.

You can refer to USER_TAB_PRIVS_RECD table to know which object privileges are granted to the user. Similarly you can also refer to USER_TAB_PRIVS_MADE for knowing which object privileges are granted on user's objects.

12.3 Grant and Revoke Statements


Data Control Language - Syntax

- Granting Object Privileges

```
GRANT object_privileges|ALL [(columnname)] ON object TO
{user|role|public} WITH GRANT OPTION
```

- Revoking Object Privileges

```
REVOKE {privilege,[privilege...]}|ALL ON object FROM
{user,[user,...]|role|public} [CASCADE CONSTRAINTS]
```

 Capgemini
CONSULTING TECHNOLOGY SERVICES

Copyright © Capgemini 2015. All Rights Reserved 6

Data Control Language:

The syntax of both the Grant and Revoke statements is given on the slide. A user can give privileges using the GRANT statement

Understanding GRANT Statement:

Object_privileges : the right/privilege that is to be given

ALL : specifies/indicates all object privileges

columnname : specifies the column name on which privilege is to be given

ON object : the object on which privilege is to be given

TO user|role|public: The username or rolenam to which the privilege is to be given. ALL grants privilege on the object to all users.

WITH GRANT OPTION : allows the grantee to grant the object privileges to other users and roles

To remove privileges the user can use REVOKE statement. This removes privileges that you mention from users specified and any other users to whom those privileges were granted through the WITH GRANT OPTION clause.

12.3 Grant and Revoke Statements

Data Control Language - Example

- Grant Query and Update privileges

```
GRANT SELECT ON student_master TO user1,user2;
```

```
GRANT UPDATE (subject1,subject2,subject3  
ON student_marks TO user1,user2;
```

- Grant privileges and allow to pass it on

```
GRANT SELECT, INSERT ON student_master  
TO user1  
WITH GRANT OPTION;
```



Copyright © Capgemini 2015. All Rights Reserved 7

The owner of the object can grant access to all users using the Public keyword
In the following example all the users will be able to query student_master table

```
GRANT SELECT ON student_master  
TO public;
```

12.3 Grant and Revoke Statements

Data Control Language -Example

- Revoking UPDATE privileges from user2

```
REVOKE UPDATE on student_marks FROM user2;
```

You can also revoke multiple privileges from multiple users/roles.

Summary

- In this lesson, you have learnt:
- Data Control Language
 - Grant
 - Revoke



Review Questions

- Question 1: Object Privileges are same on all objects
 - True/False
- Question 2 :REFERENCES privilege can be granted on
 - Option 1 :Table
 - Option 2 : View
 - Option 3 : Sequence



Add the notes here.