

## Example Function with default argument or optional argument

```
def sort(a:list,reverse=False):
    if reverse==False:
        for i in range(len(a)):
            for j in range(len(a)-1):
                if a[j]>a[j+1]:
                    a[j],a[j+1]=a[j+1],a[j]
    elif reverse==True:
        for i in range(len(a)):
            for j in range(len(a)-1):
                if a[j]<a[j+1]:
                    a[j],a[j+1]=a[j+1],a[j]
```

```
list1=[7,3,6,1,5,2,4,8,10,9]
print(f'before sorting {list1}')
sort(list1)
print(f'after sorting {list1}')
sort(list1,reverse=True)
print(f'after sorting {list1}')
```

### Output

```
before sorting [7, 3, 6, 1, 5, 2, 4, 8, 10, 9]
after sorting [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
after sorting [10, 9, 8, 7, 6, 5, 4, 3, 2, 1]
```

Python does not support pass by value, when ever function is called by sending object, PVM does not send object but it send reference/address of object.

### Example:

```
def swap(a:list,p1=None,p2=None):
    if p1==None or p2==None:
        print("Cannot Swap or interchange values")
    else:
        a[p1],a[p2]=a[p2],a[p1]
```

```
def main():  
    list1=[10,20,30,40,50]  
    print(f'Before Swaping {list1}')  
    swap(list1,0,-1)  
    print(f'After Swaping {list1}')
```

main()

**Output:**

Before Swaping [10, 20, 30, 40, 50]  
After Swaping [50, 20, 30, 40, 10]

**Example:**

```
def simple_interest(amt,t,r=1.5):  
    si=(amt*t*r)/100  
    return si
```

```
def main():  
    res1=simple_interest(45000,12)  
    res2=simple_interest(50000,24,2.0)  
    print(res1)  
    print(res2)
```

main()

**Output:**

8100.0  
24000.0

**Function with variable length arguments**

Variable length argument or parameters receives 0 or more values.  
Variable length argument is prefix with \*  
Variable length argument is of type tuple.  
A function is defined with one variable length argument.  
When more than one function performs similar operation on different number of values, use function with variable length argument.

**Syntax:**

```
def <function-name>(*arg-name):  
    statement-1  
    statement-2
```

**Example:**

```
def fun1(*a):  
    print(a)
```

```
fun1()  
fun1(10)  
fun1(10,20,30)  
fun1(1,2,3,4,5,6,7,8,9,10)
```

**Output:**

```
()  
(10,)  
(10, 20, 30)  
(1, 2, 3, 4, 5, 6, 7, 8, 9, 10)
```

**Packing and unpacking of collection****What is unpacking in Python?**

The process of splitting the packed values into individual elements is called 'unpacking'. The packed values are strings, lists, tuples, sets, and dictionaries. During unpacking the elements from RHS (Right Hand Side) are split into their relative position on the LHS (Left Hand Side).

We use two operators \* (for tuples) and \*\* (for dictionaries) for packing and unpacking.

### Example:

```
>>> a,b,c=(10,20,30)
```

```
>>> print(a,b,c)
```

```
10 20 30
```

```
>>> t1=(10,20,30,40,50)
```

```
>>> a,b=t1
```

Traceback (most recent call last):

File "C:\Program Files\JetBrains\PyCharm Community Edition  
2023.2.1\plugins\python-ce\helpers\pydev\pydevconsole.py", line 364, in  
runcode

```
    coro = func()
```

```
    ^^^^^
```

File "<input>", line 1, in <module>

ValueError: too many values to unpack (expected 2)

```
>>> a,b,*c=t1
```

```
>>> print(a,b,c)
```

```
10 20 [30, 40, 50]
```

```
>>> list1=[10,20,30,40,50]
```

```
>>> a,b,c,d,e=list1
```

```
>>> print(a,b,c,d,e)
```

```
10 20 30 40 50
```

```
>>> a,b,c,*d=list1
```

```
>>> print(a,b,c,d)
```

```
10 20 30 [40, 50]
```

### Example

```
def maximum(*values):
```

```
    if len(values)==0:
```

```
        return None
```

```
    if len(values)==1:
```

```
        return values[0]
```

```
    else:
```

```
m=values[0]
for value in values:
    if value>m:
        m=value
return m
```

```
res1=maximum()
print(res1)
res2=maximum(10)
print(res2)
res3=maximum(10,50,20,60,30,40)
print(res3)
```

**Output:**

None

10

60