

EX.NO:07
SLIDING WINDOW PROTOCOL

SOURCE CODE:

```
import threading
import random
import time

class Frame:
    def __init__(self, seq_num):
        self.seq_num = seq_num

class Sender:
    WINDOW_SIZE = 4
    MAX_FRAMES = 10
    TIMEOUT = 2 # seconds

    def __init__(self):
        self.frames = [Frame(i) for i in range(self.MAX_FRAMES)]
        self.base = 0
        self.next_seq_num = 0
        self.ack_received = [False] * self.MAX_FRAMES
        self.lock = threading.Lock()
        self.timer = None
        self.stop_sending = False

    def send_frame(self, frame):
        print(f"Sending frame: {frame.seq_num}")
        if random.random() < 0.9: # 90% chance to "send" successfully
            print(f"Frame {frame.seq_num} sent.")
        else:
            print(f"Frame {frame.seq_num} lost.")

    def receive_ack(self, ack_num):
        with self.lock:
            if ack_num < self.MAX_FRAMES and not self.ack_received[ack_num]:
                self.ack_received[ack_num] = True
                print(f"ACK received for frame {ack_num}")
```

```

        while self.base < self.MAX_FRAMES and self.ack_received[self.base]:
            self.base += 1
        if self.base < self.next_seq_num and not self.stop_sending:
            self.start_timer()

def start_timer(self):
    if self.timer is not None:
        self.timer.cancel()
    self.timer = threading.Timer(self.TIMEOUT, self.timeout)
    self.timer.start()
    print(f"Timer started at {self.base}")

def timeout(self):
    with self.lock:
        print(f"Timeout: Resending frames {self.base} to {self.next_seq_num - 1}")
        for i in range(self.base, self.next_seq_num):
            self.send_frame(self.frames[i])
        self.start_timer()

def run(self):
    def sender_thread():
        while self.base < self.MAX_FRAMES and not self.stop_sending:
            with self.lock:
                while self.next_seq_num < self.base + self.WINDOW_SIZE and self.next_seq_num < self.MAX_FRAMES:
                    self.send_frame(self.frames[self.next_seq_num])
                    self.next_seq_num += 1
                if self.base == self.next_seq_num - 1:
                    self.start_timer()
            time.sleep(0.1) # Adjusted sleep time for responsiveness

    threading.Thread(target=sender_thread).start()

def stop(self):
    self.stop_sending = True
    if self.timer is not None:
        self.timer.cancel()

class Receiver:

```

```

def __init__(self, sender):
    self.sender = sender
    self.expected_seq_num = 0
    self.stop_receiving = False

def receive_frame(self, frame):
    print(f"Received frame: {frame.seq_num}")
    if frame.seq_num == self.expected_seq_num:
        if random.random() < 0.9: # 90% chance to "acknowledge" successfully
            print(f"Acknowledging frame {frame.seq_num}")
            self.sender.receive_ack(frame.seq_num)
            self.expected_seq_num += 1
        else:
            print(f"ACK for frame {frame.seq_num} lost.")
    else:
        print(f"Unexpected frame {frame.seq_num}. Expected
{self.expected_seq_num}. Ignoring.")

def run(self):
    def receiver_thread():
        while not self.stop_receiving and self.sender.base <
Sender.MAX_FRAMES:
            for i in range(self.sender.base, self.sender.next_seq_num):
                if not self.sender.ack_received[i]:
                    self.receive_frame(self.sender.frames[i])
                time.sleep(0.5)

    threading.Thread(target=receiver_thread).start()

def stop(self):
    self.stop_receiving = True

if __name__ == "__main__":
    sender = Sender()
    receiver = Receiver(sender)

# Start the sender and receiver
    sender.run()
    receiver.run()

```

```
# Let the simulation run for a certain period
try:
    while sender.base < Sender.MAX_FRAMES:
        time.sleep(1)
except KeyboardInterrupt:
    pass
finally:
    sender.stop()
    receiver.stop()
    print("Simulation ended.")
```

OUTPUT:

```
Sending frame: 0
Frame 0 sent.
Timer started at 0
Sending frame: 1
Frame 1 sent.
Sending frame: 2
Frame 2 sent.
Sending frame: 3
Frame 3 sent.
Received frame: 0
Acknowledging frame 0
ACK received for frame 0
Timer started at 1
Received frame: 1
ACK for frame 1 lost.
Received frame: 2
Unexpected frame 2. Expected 1. Ignoring.
Received frame: 3
Unexpected frame 3. Expected 1. Ignoring.
Sending frame: 4
Frame 4 lost.
Received frame: 1
Acknowledging frame 1
ACK received for frame 1
Timer started at 2
Received frame: 2
Acknowledging frame 2
ACK received for frame 2
Timer started at 3
Received frame: 3
Acknowledging frame 3
ACK received for frame 3
Timer started at 4
Received frame: 4
Acknowledging frame 4
```

ACK received for frame 4
Sending frame: 5
Frame 5 sent.
Timer started at 5
Sending frame: 6
Frame 6 sent.
Sending frame: 7
Frame 7 sent.
Sending frame: 8
Frame 8 sent.
Received frame: 5
Acknowledging frame 5
ACK received for frame 5
Timer started at 6
Received frame: 6
ACK for frame 6 lost.
Received frame: 7
Unexpected frame 7. Expected 6. Ignoring.
Received frame: 8
Unexpected frame 8. Expected 6. Ignoring.
Sending frame: 9
Frame 9 sent.
Received frame: 6
Acknowledging frame 6
ACK received for frame 6
Timer started at 7
Received frame: 7
Acknowledging frame 7
ACK received for frame 7
Timer started at 8
Received frame: 8
Acknowledging frame 8
ACK received for frame 8
Timer started at 9
Received frame: 9
Acknowledging frame 9
ACK received for frame 9
Simulation ended