

Security Vulnerability Report

Executive Summary

- Scan Overview:**
- Scan ID: 651458a1-cdac-4677-9a28-c4695b9b5853
 - Date: 2025-11-09T06:37:45.217Z
 - Files Scanned: 1
 - Total Vulnerabilities: 6

- Severity Breakdown:**
- Critical: 0
 - High: 2
 - Medium: 4
 - Low: 0

Vulnerability Summary

File	Line	Type	Severity	CWE
files-1762670265240-903502794.py	25	sqlalchemy:execute() improper Neutralization of Special Elements used in an SQL Command	High	CWE-89
files-1762670265240-903502794.py	38	os.system() improper Neutralization of Special Elements used in an OS Command	High	CWE-78
files-1762670265240-903502794.py	25	for sqlalchemy:execute() improper Neutralization of Special Elements used in an SQL Command	Medium	CWE-89
files-1762670265240-903502794.py	46	eval() CWE-195: Improper Neutralization of Directives in Dynamically Evaluated Code	Medium	CWE-195
files-1762670265240-903502794.py	55	avoid-pickle	Medium	CWE-502
files-1762670265240-903502794.py	81	md5-used-as-password	Medium	CWE-327

Detailed Vulnerability Findings

Finding 1: sqlalchemy-execute-raw-query

File: files-1762670265240-903502794.py

Line: 25

Severity: High

CWE ID: CWE-CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')

Detection Tool: Semgrep

Confidence: 85%

Description:

Avoiding SQL string concatenation: untrusted input concatenated with raw SQL query can result in SQL Injection. In order to execute raw query safely, prepared statement should be used. SQLAlchemy provides TextualSQL to easily used prepared statement with named parameters. For complex SQL composition, use SQL Expression Language or Schema Definition Language. In most cases, SQLAlchemy ORM will be a better option. Recommendation: Use parameterized queries (prepared statements) instead of string concatenation. Example: ```python
cursor.execute("SELECT * FROM users WHERE id = %s", [user_id]) ```

Finding 2: subprocess-shell-true

File: files-1762670265240-903502794.py

Line: 38

Severity: High

CWE ID: CWE-CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')

Detection Tool: Semgrep

Confidence: 85%

Description:

Found 'subprocess' function 'call' with 'shell=True'. This is dangerous because this call will spawn the command using a shell process. Doing so propagates current shell settings and variables, which makes it much easier for a malicious actor to execute commands. Use 'shell=False' instead. Recommendation: Review the code for security implications and consider using secure coding practices appropriate for your use case.

Finding 3: formatted-sql-query

File: files-1762670265240-903502794.py

Line: 25

Severity: Medium

CWE ID: CWE-CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')

Detection Tool: Semgrep

Confidence: 85%

Description:

Detected possible formatted SQL query. Use parameterized queries instead. Recommendation: Use parameterized queries (prepared statements) instead of string concatenation. Example:

```
```python cursor.execute("SELECT * FROM users WHERE id = %s", [user_id]) ```
```

## Finding 4: eval-detected

**File:** files-1762670265240-903502794.py

**Line:** 46

**Severity:** Medium

**CWE ID:** CWE-CWE-95: Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection')

**Detection Tool:** Semgrep

**Confidence:** 85%

### Description:

Detected the use of eval(). eval() can be dangerous if used to evaluate dynamic content. If this content can be input from outside the program, this may be a code injection vulnerability. Ensure evaluated content is not definable by external sources. Recommendation: Review the code for security implications and consider using secure coding practices appropriate for your use case.

## Finding 5: avoid-pickle

**File:** files-1762670265240-903502794.py

**Line:** 55

**Severity:** Medium

**CWE ID:** CWE-CWE-502: Deserialization of Untrusted Data

**Detection Tool:** Semgrep

**Confidence:** 85%

### Description:

Avoid using `pickle`, which is known to lead to code execution vulnerabilities. When unpickling, the serialized data could be manipulated to run arbitrary code. Instead, consider serializing the relevant data as JSON or a similar text-based serialization format. Recommendation: Review the code for security implications and consider using secure coding practices appropriate for your use case.

## Finding 6: md5-used-as-password

**File:** files-1762670265240-903502794.py

**Line:** 81

**Severity:** Medium

**CWE ID:** CWE-CWE-327: Use of a Broken or Risky Cryptographic Algorithm

**Detection Tool:** Semgrep

**Confidence:** 85%

### Description:

It looks like MD5 is used as a password hash. MD5 is not considered a secure password hash because it can be cracked by an attacker in a short amount of time. Use a suitable password hashing function such as bcrypt. You can use `hashlib.bcrypt`. Recommendation: Move sensitive data to environment variables or a secure configuration management system: ```python import os password = os.environ.get("DB\_PASSWORD") ```

## AI-Generated Recommendations

- Implement parameterized queries for all database operations to prevent SQL injection
- Use environment variables for storing sensitive configuration data
- Implement proper input validation and output encoding
- Use strong cryptographic functions (bcrypt, scrypt, or Argon2) for password hashing
- Regular security code reviews and automated scanning
- Keep dependencies updated and monitor for known vulnerabilities