

TravelLink Frontend — Build Progress

Last Updated: 2026-06-04 22:58 IST

Architecture Plan: [travellink frontend architecture.md](#)

Phase 1: Foundation COMPLETE

Step	File(s)	Status
Scaffold Vite + React + TS	Project root	
Tailwind v4 + PostCSS	<code>postcss.config.js</code> , <code>index.css</code>	
TypeScript DTOs (30+ interfaces)	<code>src/types/*.ts</code> (8 files + barrel)	
Axios instance + JWT interceptors	<code>src/services/api.ts</code>	
Auth service	<code>src/services/authService.ts</code>	
Auth context (login/register/logout)	<code>src/context/AuthContext.tsx</code>	
Protected route guard	<code>src/components/ProtectedRoute.tsx</code>	
Wired up <code>main.tsx</code>	BrowserRouter + AuthProvider + Toaster	

Phase 2: Auth UI COMPLETE

Step	File(s)	Status
Login page — split-screen + glassmorphism	<code>src/features/auth/LoginPage.tsx</code>	
Register page — split-screen + glassmorphism	<code>src/features/auth/RegisterPage.tsx</code>	
Design tokens + custom CSS	<code>src/index.css</code>	
Background image	<code>public/bg-travel.png</code>	

Custom fonts (Cardo + Great Vibes)	<code>index.css @import</code>	✓
Nature gradient for "Link" text	<code>.text-nature-gradient class</code>	✓
<code>unwrap()</code> error toast fix	<code>src/services/api.ts</code>	✓
Login → backend tested & working	End-to-end verified	✓
Register → backend tested & working	End-to-end verified	✓

Bug Fix Applied This Session

`unwrap()` function in `api.ts` — error toasts not firing

Root cause: The original catch block used `!error.message.includes('Request failed')` to avoid double-toasting, but Axios's own error messages contain "Request failed" (e.g. "Request failed with status code 400"), so the guard accidentally suppressed ALL HTTP error toasts.

Fix: Replaced with `axios.isAxiosError(error)` check — clean separation:

- `AxiosError` (HTTP failures) → toast the backend message or fallback
- `Plain Error` (thrown after success:false toast in try block) → skip, already toasted

```
catch (error) {
  if (axios.isAxiosError(error)) {
    const msg = error.response?.data?.message || 'Something went wrong. Please try again.';
    toast.error(msg);
  }
  throw error;
}
```

Tailwind v4 spacing utilities not applying

Issue: `mt-14`, `pt-8`, `!mt-14` etc. on form children had no effect. Tailwind v4 uses CSS cascade layers (`@layer utilities`), and the `space-y-6` utility on the parent `<form>` was

overriding child margin utilities due to layer/specificity conflicts.

Workaround: Used inline `style={{ marginTop: '1.5rem' }}` on wrapper `<div>` s for the first form field and the submit button. This bypasses all cascade layer issues.

Note for future: Consider investigating Tailwind v4 `@layer` configuration or replacing `space-y-6` with explicit spacing on each child to avoid these conflicts long-term.

Design Decisions (Carried Over + Updated)

Decision	Detail
Layout	Split-screen: Login = branding left + form right. Register = form left + branding right (mirrored). Mobile = full-width background + centered card.
Background	AI-generated travel image (<code>public/bg-travel.png</code>) — sunset, ocean, mountains
Glass Card	Very light blur (<code>blur(5px)</code>), near-transparent (<code>rgba(255,255,255,0.02)</code>), top-left border highlight for 3D effect
Color Palette	Sky blue primary (<code>#0284c7</code>) for ocean/travel vibe
Fonts	<code>Cardo</code> (serif, bold) for "Travel" + <code>Great Vibes</code> (cursive, bold) for "Link"
"Link" gradient	5-stop nature gradient: Sky cyan → Ocean blue → Forest emerald → Mountain slate → Rock stone
Input padding	Explicit <code>padding-left: 2rem</code> in CSS to prevent icon/placeholder overlap
Form card	<code>max-w-sm</code> instead of <code>max-w-md</code> for tighter form
Heading	<code>text-9xl</code> on desktop, <code>text-6xl</code> on mobile
Spacing workaround	Inline styles for form child margins due to Tailwind v4 cascade layer conflicts



Next Up — Phase 3: App Shell & Dashboard

Step	Details
AppShell component	Bottom nav (mobile) + sidebar (desktop), uses <code><Outlet /></code>
Bottom nav tabs	Home, Friends, Groups, Expenses, Map
DashboardPage	Overview cards: groups count, pending requests, upcoming trips
Shared UI components	Button, Input, Modal, Card, Avatar, Badge

Remaining Phases (4-9)

Phase	Module	Status
4	Friends (service + UI)	☐
5	Groups (service + UI)	☐
6	Expenses (service + charts)	☐
7	Itinerary (service + timeline)	☐
8	Location (SignalR + Leaflet map)	☐
9	Profile + Polish (dark mode, skeletons, PWA)	☐

Key Architecture Decisions (Carried Over)

Decision	Detail
Vite proxy	<code>/api</code> → <code>https://localhost:7150</code> (secure: false for dev certs)
API base URL	<code>/api</code> (relative, goes through Vite proxy)
Token storage	<code>localStorage</code> keys: <code>tl_token</code> , <code>tl_refresh</code> , <code>tl_user</code>
Silent refresh	Queue-based — multiple 401s trigger single refresh, others wait

Force logout	<code>window.dispatchEvent(new Event('auth_logout'))</code> decouples API from React
Toast errors	<code>unwrap<T>()</code> uses <code>axios.isAxiosError()</code> to auto-toast HTTP errors
Styling	Tailwind v4 + custom CSS classes

Current File Structure

```
src/
├── components/
│   └── ProtectedRoute.tsx
├── context/
│   └── AuthContext.tsx
├── features/
│   └── auth/
│       ├── LoginPage.tsx      ← ✓ Split-screen + glassmorphism
│       └── RegisterPage.tsx  ← ✓ Split-screen + glassmorphism
(mirrored)
├── services/
│   ├── api.ts                ← ✓ Fixed unwrap() toast logic
│   └── authService.ts
├── types/
│   ├── auth.ts
│   ├── expenses.ts
│   ├── friends.ts
│   ├── groups.ts
│   ├── index.ts (barrel + ServiceResult<T>)
│   ├── itinerary.ts
│   ├── location.ts
│   └── users.ts
├── App.tsx (routing)
├── index.css (design tokens + Tailwind + custom classes)
└── main.tsx (entry: BrowserRouter + AuthProvider + Toaster)

public/
└── bg-travel.png (AI-generated travel background)
```

Dependencies

```
{
  "axios": "^1.17.0",
  "@microsoft/signalr": "^10.0.0",
  "react-router-dom": "^7.16.0",
  "sonner": "^2.0.7",
  "lucide-react": "^1.17.0",
  "tailwindcss": "^4.3.0 (dev)",
  "@tailwindcss/postcss": "^4.3.0 (dev)"
}
```

Working Mode

Important: The user prefers to write all code themselves. Provide code snippets with explanations/logic, but do NOT write directly to project files. Guide, don't execute.