

TravelLink Frontend — Build Progress

Last Updated: 2026-06-03 17:41 IST **Architecture Plan:**
[travellink_frontend_architecture.md](#)

☐ Completed

Phase 1 — Foundation (In Progress)

Step 1: Scaffold + Dependencies

- Scaffolded fresh Vite + React + TypeScript project in F:\Projects\TravelLink\Client
- Command: `npx -y create-vite@latest Client --template react-ts --no-interactive`
- Installed runtime deps: `axios, @microsoft/signalr, react-router-dom, sonner, lucide-react`
- Installed dev deps: `tailwindcss, @tailwindcss/postcss, postcss, autoprefixer`

Step 2: Tailwind v4 + PostCSS Configuration

- `postcss.config.js` → uses `@tailwindcss/postcss` (v4 moved the PostCSS plugin to a separate package)
- `src/index.css` → single line: `@import "tailwindcss"` (v4 replaces the old `@tailwind` directives)
- Deleted default `App.css` (Tailwind handles all styling)

Step 3: TypeScript Interfaces (All Backend DTOs)

All 8 type files created in `src/types/`:

File	Interfaces	Status
<code>auth.ts</code>	<code>AuthResponseDto</code> , <code>LoginDto</code> , <code>RefreshTokenRequestDt</code> <code>o</code> , <code>RegisterDto</code>	Verified
<code>users.ts</code>	<code>UserProfileDto</code>	Verified
<code>friends.ts</code>	<code>FriendDto</code> , <code>FriendRequestDto</code> , <code>SendFriendRequestDto</code>	Verified
<code>groups.ts</code>	<code>CreateGroupDto</code> , <code>GroupDto</code> ,	Verified

File	Interfaces	Status
	GroupMemberDto	
expenses.ts	BalanceDto, CreateExpenseDto, ExpenseDto, ExpenseSplitDto, ExpenseSplitInputDto, GroupAnalysisDto, CategoryBreakdownDto, MemberContributionDto, UserToUserDto, UserTransactionDto	Verified
itinerary.ts	AddSuggestionDto, AddGenerateItineraryD to, DroppedSuggestionDto, GenerateItineraryDto, GroupItineraryStatusD to, ItineraryDayDto, ItineraryItemDto, ItineraryResultDto, ReviewSuggestionDto, SuggestionDto	Verified
location.ts	LocationUpdatedDto	Verified
index.ts	ServiceResult<T> + barrel re-exports	Verified

Fixes applied during review:

- LoginDto.name → LoginDto.email (matched backend LoginDto.cs)
- BalanceDto.fromUserEmail/toUserEmail →
fromUserImageUrl/toUserImageUrl (matched backend)
- UserToUserDto.Transactions → transactions (camelCase for JSON
serialization)

☐ Remaining — Phase 1 (Foundation)

Step 4: Axios Instance + Interceptors

- ☐ Create src/services/api.ts
- ☐ Request interceptor: attach JWT Authorization: Bearer <token> header
- ☐ Response interceptor: on 401, attempt silent token refresh via refreshToken

- ☐ If refresh fails, fire global logout event
- ☐ Base URL pointing to backend (`https://localhost:7xxx/api/`)

Step 5: AuthContext

- ☐ Create `src/context/AuthContext.tsx`
- ☐ `login()` — calls auth endpoint, stores tokens + user in state & localStorage
- ☐ `register()` — same flow as login after successful registration
- ☐ `logout()` — clears tokens, state, and localStorage
- ☐ `refreshToken()` — silent refresh on 401
- ☐ Auto-restore session from localStorage on mount
- ☐ `useAuth()` custom hook for consuming context

Step 6: ProtectedRoute

- ☐ Create `src/components/ProtectedRoute.tsx`
- ☐ Checks `isAuthenticated` from `useAuth()`
- ☐ Shows loading spinner while auth state initializes
- ☐ Redirects to `/login` if not authenticated
- ☐ Uses `<Outlet />` to render child routes

☐ Future Phases

Phase	Focus	Status
Phase 2	Auth UI (Login + Register pages)	Not started
Phase 3	App Shell + Dashboard (Bottom nav, sidebar, overview)	Not started
Phase 4	Friends Module	Not started
Phase 5	Groups Module	Not started
Phase 6	Expenses Module	Not started
Phase 7	Itinerary Module (AI generation)	Not started
Phase 8	Location Module (SignalR + Leaflet maps)	Not started
Phase 9	Profile + Polish (dark mode, skeletons, PWA)	Not started

□ Current File Structure

```
Client/
├── postcss.config.js      ← @tailwindcss/postcss
├── package.json           ← all deps installed
├── vite.config.ts
├── tsconfig.json
├── src/
│   ├── index.css          ← @import "tailwindcss"
│   ├── main.tsx           ← default Vite entry
│   ├── App.tsx            ← default (to be replaced)
│   └── types/
│       ├── index.ts       ← ServiceResult<T> + barrel exports
│       ├── auth.ts
│       ├── users.ts
│       ├── friends.ts
│       ├── groups.ts
│       ├── expenses.ts
│       ├── itinerary.ts
│       └── location.ts
```

□ Backend Status (Pre-verified)

- All 6 controllers return consistent `ServiceResult<T>` wrapping
- **Fixed before frontend rebuild:**
 - `FriendController` — removed double wrapping (`Ok(new { response })` → `Ok(response)`)
 - `GroupController.GetById` — fixed inverted success/failure logic
 - `UserController` — wrapped profile & avatar in `ServiceResult`

□ Key Architecture Decisions

1. **Mobile-first** with bottom tab navigation (5 tabs) + desktop sidebar
2. **Feature-based folder structure** (not type-based)
3. **React Context + useReducer** for global state (Auth + Location only)
4. **Tailwind CSS v4** with `@tailwindcss/postcss`
5. **ServiceResult unwrapping** at the API interceptor level
6. **Barrel exports** via `types/index.ts` for clean imports