TravelBooker

Travel Booking Website

Code Documentation

Version 1.0

3/6/2026

Technology Stack:

- React 18 with TypeScript
- React Router for Navigation
- Tailwind CSS v4 for Styling
- Shadcn UI Components
- Context API for State Management
- Lucide React for Icons
- Date-fns for Date Handling
- Sonner for Toast Notifications

Table of Contents

1. Project Structure	Page 3
2. Core Application Setup (App.tsx)	Page 4
3. Routing Configuration	Page 5
4. CSS & Styling System	Page 6
5. State Management (Context API)	Page 8
6. Layout Components (Navbar & Footer)	Page 10
7. Page Components - Home	Page 12
8. Page Components - Hotels	Page 14
9. Page Components - Flights	Page 16
10. Page Components - Activities	Page 18
11. Cart & Checkout System	Page 20
12. Authentication Pages	Page 22
13. Shadcn UI Components	Page 24
14. Responsive Design Patterns	Page 26

1. Project Structure

The application follows a modular component-based architecture:

```
src/
├── app/
│   ├── App.tsx                 # Main application component
│   ├── components/             # Reusable UI components
│   │   ├── ui/                 # Shadcn UI components
│   │   │   ├── button.tsx
│   │   │   ├── input.tsx
│   │   │   ├── card.tsx
│   │   │   ├── select.tsx
│   │   │   ├── slider.tsx
│   │   │   ├── checkbox.tsx
│   │   │   ├── dialog.tsx
│   │   │   └── tabs.tsx
│   │   ├── Navbar.tsx          # Navigation header
│   │   ├── Footer.tsx          # Site footer
│   │   └── SearchBar.tsx       # Hero search component
│   ├── pages/                  # Page components (screens)
│   │   ├── Home.tsx            # Landing page
│   │   ├── Hotels.tsx          # Hotel search results
│   │   ├── HotelDetails.tsx    # Individual hotel page
│   │   ├── Flights.tsx         # Flight search & booking
│   │   ├── Activities.tsx      # Tours & activities
│   │   ├── Cart.tsx            # Shopping cart
│   │   ├── Checkout.tsx        # Checkout process
│   │   ├── Confirmation.tsx    # Booking confirmation
│   │   ├── Login.tsx           # Authentication
│   │   └── Profile.tsx         # User dashboard
│   ├── context/                # State management
│   │   └── BookingContext.tsx  # Global booking state
│   └── data/                   # Mock data
│       ├── hotels.ts           # Hotel listings
│       ├── flights.ts          # Flight data
│       └── activities.ts       # Activity data
├── styles/
│   ├── theme.css               # Design tokens & variables
│   └── fonts.css               # Font imports
└── index.css                   # Global styles & Tailwind imports
```

2. Core Application Setup (App.tsx)

The main application component sets up routing, state management, and layout:

App.tsx - Main Component

```
import { BrowserRouter as Router, Routes, Route } from 'react-router';
import { Toaster } from 'sonner';
import { BookingProvider } from './context/BookingContext';
import { Navbar } from './components/Navbar';
import { Footer } from './components/Footer';
import { Home } from './pages/Home';
import { Hotels } from './pages/Hotels';
import { HotelDetails } from './pages/HotelDetails';
import { Flights } from './pages/Flights';
import { Activities } from './pages/Activities';
import { Cart } from './pages/Cart';
import { Checkout } from './pages/Checkout';
import { Confirmation } from './pages/Confirmation';
import { Login } from './pages/Login';
import { Profile } from './pages/Profile';

export default function App() {
  return (
    <BookingProvider>
      <Router>
        <div className="min-h-screen flex flex-col bg-white">
          <Navbar />
          <main className="flex-1">
            <Routes>
              <Route path="/" element={<Home />} />
              <Route path="/hotels" element={<Hotels />} />
              <Route path="/hotel/:id" element={<HotelDetails />} />
              <Route path="/flights" element={<Flights />} />
              <Route path="/activities" element={<Activities />} />
              <Route path="/cart" element={<Cart />} />
              <Route path="/checkout" element={<Checkout />} />
              <Route path="/confirmation" element={<Confirmation />} />
              <Route path="/login" element={<Login />} />
              <Route path="/profile" element={<Profile />} />
            </Routes>
          </main>
          <Footer />
          <Toaster position="top-center" richColors />
        </div>
      </Router>
    </BookingProvider>
  );
}
```

Key Features:

- Wraps entire app with BookingProvider for global state
- Uses BrowserRouter for client-side routing
- Implements flex layout for sticky footer

- Includes Toaster for notifications

3. Routing Configuration

Route Structure

```
Route Path              Component           Purpose
_____________________________________________________________
/                       Home                Landing page with hero search
/hotels                 Hotels              Hotel search results & filters
/hotel/:id              HotelDetails        Individual hotel details & booking
/flights                Flights             Flight search & booking interface
/activities             Activities          Tours & activities listings
/cart                   Cart                Shopping cart with all bookings
/checkout               Checkout            Payment & guest information
/confirmation           Confirmation        Booking success page
/login                  Login               Sign in / Sign up authentication
/profile                Profile             User dashboard & booking history
/wireframes             Wireframes          Wireframe documentation (admin)
/code                   CodeDocumentation   Code documentation (admin)
```

Navigation Implementation

```
import { Link, useNavigate } from 'react-router';

// Using Link component for declarative navigation
<Link to="/hotels" className="nav-link">
  Hotels
</Link>

// Using useNavigate hook for programmatic navigation
const navigate = useNavigate();

const handleBooking = () => {
  addToCart(bookingData);
  navigate('/cart');
};

// Dynamic routes with parameters
<Link to={`/hotel/${hotel.id}`}>
  View Details
</Link>

// In the component:
import { useParams } from 'react-router';
const { id } = useParams();
```

4. CSS & Styling System

Tailwind CSS Configuration (v4)

The project uses Tailwind CSS v4 with custom design tokens defined in theme.css:

```
/* /src/styles/theme.css */
@import "tailwindcss";

/* Color Palette */
:root {
  --color-primary: #1e40af;
  --color-primary-hover: #1e3a8a;
  --color-secondary: #3b82f6;
  --color-accent: #f59e0b;
  --color-success: #10b981;
  --color-error: #ef4444;

  --color-gray-50: #f9fafb;
  --color-gray-100: #f3f4f6;
  --color-gray-200: #e5e7eb;
  --color-gray-300: #d1d5db;
  --color-gray-600: #4b5563;
  --color-gray-900: #111827;

  /* Spacing */
  --spacing-xs: 0.25rem;
  --spacing-sm: 0.5rem;
  --spacing-md: 1rem;
  --spacing-lg: 1.5rem;
  --spacing-xl: 2rem;

  /* Typography */
  --font-sans: -apple-system, BlinkMacSystemFont, "Segoe UI", Roboto, sans-serif;
  --font-size-sm: 0.875rem;
  --font-size-base: 1rem;
  --font-size-lg: 1.125rem;
  --font-size-xl: 1.25rem;
  --font-size-2xl: 1.5rem;

  /* Shadows */
  --shadow-sm: 0 1px 2px 0 rgb(0 0 0 / 0.05);
  --shadow-md: 0 4px 6px -1px rgb(0 0 0 / 0.1);
  --shadow-lg: 0 10px 15px -3px rgb(0 0 0 / 0.1);

  /* Border Radius */
  --radius-sm: 0.25rem;
  --radius-md: 0.5rem;
  --radius-lg: 0.75rem;
  --radius-xl: 1rem;
}

/* Base Styles */
body {
  font-family: var(--font-sans);
  color: var(--color-gray-900);
  line-height: 1.5;
}
```

```
h1 {
  font-size: 2.25rem;
  font-weight: 700;
  line-height: 1.2;
}

h2 {
  font-size: 1.875rem;
  font-weight: 600;
  line-height: 1.3;
}

h3 {
  font-size: 1.5rem;
  font-weight: 600;
  line-height: 1.4;
}
```

Utility Classes Usage

```
/* Layout */
<div className="container mx-auto px-4">         // Container with padding
<div className="grid grid-cols-3 gap-6">         // 3-column grid
<div className="flex items-center justify-between"> // Flexbox
<div className="max-w-6xl mx-auto">              // Max width container

/* Spacing */
<div className="p-6">                            // Padding all sides
<div className="px-4 py-8">                      // Padding x and y
<div className="mb-4">                           // Margin bottom
<div className="space-y-4">                      // Vertical spacing children

/* Typography */
<h1 className="text-3xl font-bold">             // Large bold heading
<p className="text-gray-600">                    // Gray body text
<span className="text-sm text-gray-500">        // Small gray text

/* Colors & Backgrounds */
<div className="bg-white">                       // White background
<div className="bg-blue-600 text-white">        // Blue bg, white text
<button className="bg-blue-600 hover:bg-blue-700"> // Hover state

/* Borders & Shadows */
<div className="border border-gray-200 rounded-lg"> // Border with radius
<div className="shadow-lg">                      // Large shadow
<div className="ring-2 ring-blue-500">          // Focus ring

/* Responsive Design */
<div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-3">
<div className="hidden md:block">               // Show on medium+
<div className="text-base md:text-lg">          // Responsive text
```

5. State Management (Context API)

BookingContext.tsx - Global State

```
import { createContext, useContext, useState, ReactNode } from 'react';

// Types
export interface CartItem {
  id: string;
  type: 'hotel' | 'flight' | 'activity';
  name: string;
  price: number;
  details: any;
  quantity?: number;
}

interface BookingContextType {
  cartItems: CartItem[];
  addToCart: (item: CartItem) => void;
  removeFromCart: (id: string) => void;
  clearCart: () => void;
  totalPrice: number;
  user: User | null;
  login: (userData: User) => void;
  logout: () => void;
}

// Context creation
const BookingContext = createContext<BookingContextType | undefined>(undefined);

// Provider component
export function BookingProvider({ children }: { children: ReactNode }) {
  const [cartItems, setCartItems] = useState<CartItem[]>([]);
  const [user, setUser] = useState<User | null>(null);

  const addToCart = (item: CartItem) => {
    setCartItems(prev => [...prev, item]);
  };

  const removeFromCart = (id: string) => {
    setCartItems(prev => prev.filter(item => item.id !== id));
  };

  const clearCart = () => {
    setCartItems([]);
  };

  const totalPrice = cartItems.reduce((sum, item) => sum + item.price, 0);

  const login = (userData: User) => {
    setUser(userData);
  };

  const logout = () => {
    setUser(null);
  };
```

```
  return (
    <BookingContext.Provider value={{
      cartItems,
      addToCart,
      removeFromCart,
      clearCart,
      totalPrice,
      user,
      login,
      logout
    }}>
      {children}
    </BookingContext.Provider>
  );
}

// Custom hook for consuming context
export function useBooking() {
  const context = useContext(BookingContext);
  if (!context) {
    throw new Error('useBooking must be used within BookingProvider');
  }
  return context;
}
```

Using Context in Components

```
import { useBooking } from '../context/BookingContext';

function HotelCard({ hotel }) {
  const { addToCart } = useBooking();

  const handleAddToCart = () => {
    addToCart({
      id: hotel.id,
      type: 'hotel',
      name: hotel.name,
      price: hotel.price,
      details: hotel
    });
  };

  return (
    <button onClick={handleAddToCart}>
      Add to Cart
    </button>
  );
}

function CartPage() {
  const { cartItems, totalPrice, removeFromCart } = useBooking();

  return (
    <div>
      {cartItems.map(item => (
        <div key={item.id}>
          <h3>{item.name}</h3>
          <p>${item.price}</p>
          <button onClick={() => removeFromCart(item.id)}>Remove</button>
        </div>
      ))}
      <p>Total: ${totalPrice}</p>
    </div>
  );
}
```

6. Layout Components

Navbar Component

```
import { Link } from 'react-router';
import { ShoppingCart, User, Menu } from 'lucide-react';
import { useBooking } from '../context/BookingContext';
import { Button } from './ui/button';

export function Navbar() {
  const { cartItems, user } = useBooking();
  const cartCount = cartItems.length;

  return (
    <nav className="bg-white border-b border-gray-200 sticky top-0 z-50">
      <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8">
        <div className="flex justify-between items-center h-16">

          {/* Logo */}
          <Link to="/" className="flex items-center space-x-2">
            <span className="text-2xl font-bold text-blue-600">
              TravelBook
            </span>
          </Link>

          {/* Desktop Navigation */}
          <div className="hidden md:flex items-center space-x-8">
            <Link to="/hotels" className="text-gray-700 hover:text-blue-600">
              Hotels
            </Link>
            <Link to="/flights" className="text-gray-700 hover:text-blue-600">
              Flights
            </Link>
            <Link to="/activities" className="text-gray-700 hover:text-blue-600">
              Activities
            </Link>
          </div>

          {/* Right Side Actions */}
          <div className="flex items-center space-x-4">
            {/* Cart */}
            <Link to="/cart" className="relative">
              <ShoppingCart className="w-6 h-6 text-gray-700" />
              {cartCount > 0 && (
                <span className="absolute -top-2 -right-2 bg-blue-600
                  text-white text-xs rounded-full w-5 h-5 flex items-center
                  justify-center">
                  {cartCount}
                </span>
              )}
            </Link>

            {/* User Menu */}
            {user ? (
              <Link to="/profile">
                <Button variant="ghost" size="sm">
```

```
                <User className="w-5 h-5" />
              </Button>
            </Link>
          ) : (
            <Link to="/login">
              <Button size="sm">Sign In</Button>
            </Link>
          )}

          {/* Mobile Menu */}
          <button className="md:hidden">
            <Menu className="w-6 h-6" />
          </button>
        </div>
      </div>
    </div>
  </nav>
);
}
```

Footer Component

```
import { Link } from 'react-router';

export function Footer() {
  return (
    <footer className="bg-gray-900 text-white mt-auto">
      <div className="max-w-7xl mx-auto px-4 py-12">
        <div className="grid grid-cols-1 md:grid-cols-4 gap-8">

          {/* Company Info */}
          <div>
            <h3 className="text-xl font-bold mb-4">TravelBook</h3>
            <p className="text-gray-400 text-sm">
              Your one-stop destination for hotels, flights, and activities.
            </p>
          </div>

          {/* Quick Links */}
          <div>
            <h4 className="font-semibold mb-4">Quick Links</h4>
            <ul className="space-y-2 text-sm">
              <li><Link to="/hotels" className="text-gray-400 hover:text-white">
                Hotels
              </Link></li>
              <li><Link to="/flights" className="text-gray-400 hover:text-white">
                Flights
              </Link></li>
              <li><Link to="/activities" className="text-gray-400 hover:text-white">
                Activities
              </Link></li>
            </ul>
          </div>

          {/* Support */}
          <div>
            <h4 className="font-semibold mb-4">Support</h4>
            <ul className="space-y-2 text-sm text-gray-400">
              <li>Help Center</li>
              <li>Contact Us</li>
              <li>Privacy Policy</li>
              <li>Terms of Service</li>
            </ul>
          </div>

          {/* Newsletter */}
          <div>
            <h4 className="font-semibold mb-4">Newsletter</h4>
            <p className="text-sm text-gray-400 mb-3">
              Get travel deals and updates
            </p>
            <input
              type="email"
              placeholder="Your email"
```

```
              className="w-full px-3 py-2 rounded text-gray-900"
            />
          </div>
        </div>

        {/* Copyright */}
        <div className="border-t border-gray-800 mt-8 pt-8 text-center text-sm text-gray-
          <p>&copy; 2024 TravelBook. All rights reserved.</p>
        </div>
      </div>
    </footer>
  );
}
```

7. Page Components - Home

Hero Section with Search

```
import { useState } from 'react';
import { useNavigate } from 'react-router';
import { Search, Calendar, Users } from 'lucide-react';
import { Button } from '../components/ui/button';
import { Input } from '../components/ui/input';

export function Home() {
  const navigate = useNavigate();
  const [searchType, setSearchType] = useState<'hotels' | 'flights' | 'activities'>('hote

  return (
    <div className="min-h-screen">
      {/* Hero Section */}
      <div className="relative bg-gradient-to-r from-blue-600 to-blue-800
        text-white py-24">
        <div className="max-w-6xl mx-auto px-4 text-center">
          <h1 className="text-5xl font-bold mb-6">
            Discover Your Next Adventure
          </h1>
          <p className="text-xl mb-12 text-blue-100">
            Search hotels, flights, and activities worldwide
          </p>

          {/* Search Bar */}
          <div className="bg-white rounded-xl shadow-2xl p-6 max-w-4xl mx-auto">
            {/* Tab Selector */}
            <div className="flex gap-4 mb-6">
              <button
                onClick={() => setSearchType('hotels')}
                className={`px-6 py-2 rounded-lg font-semibold ${
                  searchType === 'hotels'
                    ? 'bg-blue-600 text-white'
                    : 'bg-gray-100 text-gray-700'
                }`}
              >
                Hotels
              </button>
              <button
                onClick={() => setSearchType('flights')}
                className={`px-6 py-2 rounded-lg font-semibold ${
                  searchType === 'flights'
                    ? 'bg-blue-600 text-white'
                    : 'bg-gray-100 text-gray-700'
                }`}
              >
                Flights
              </button>
              <button
                onClick={() => setSearchType('activities')}
                className={`px-6 py-2 rounded-lg font-semibold ${
                  searchType === 'activities'
                    ? 'bg-blue-600 text-white'
```

```
                : 'bg-gray-100 text-gray-700'
            }`}
          >
            Activities
          </button>
        </div>

        {/* Search Form */}
        <div className="grid grid-cols-1 md:grid-cols-4 gap-4">
          <div className="relative">
            <Search className="absolute left-3 top-3 w-5 h-5 text-gray-400" />
            <Input
              placeholder="Where to?"
              className="pl-10 h-12 text-gray-900"
            />
          </div>

          <div className="relative">
            <Calendar className="absolute left-3 top-3 w-5 h-5 text-gray-400" />
            <Input
              type="date"
              className="pl-10 h-12 text-gray-900"
            />
          </div>

          <div className="relative">
            <Calendar className="absolute left-3 top-3 w-5 h-5 text-gray-400" />
            <Input
              type="date"
              className="pl-10 h-12 text-gray-900"
            />
          </div>

          <div className="relative">
            <Users className="absolute left-3 top-3 w-5 h-5 text-gray-400" />
            <Input
              placeholder="Guests"
              className="pl-10 h-12 text-gray-900"
            />
          </div>
        </div>

        <Button
          onClick={() => navigate(`/${searchType}`)}
          className="w-full mt-6 h-12 text-lg"
        >
          Search
        </Button>
      </div>
    </div>
  </div>

  {/* Features Section */}
```

```
      <div className="py-16 bg-gray-50">
        <div className="max-w-6xl mx-auto px-4">
          <h2 className="text-3xl font-bold text-center mb-12">
            Why Choose TravelBook?
          </h2>
          <div className="grid grid-cols-1 md:grid-cols-3 gap-8">
            <FeatureCard
              icon="🏨"
              title="Best Hotels"
              description="Find and book from millions of hotels worldwide"
            />
            <FeatureCard
              icon="✈️"
              title="Cheap Flights"
              description="Compare prices and book the best flights"
            />
            <FeatureCard
              icon="🎯"
              title="Top Activities"
              description="Discover and book amazing experiences"
            />
          </div>
        </div>
      </div>
    </div>
  );
}

function FeatureCard({ icon, title, description }) {
  return (
    <div className="bg-white p-6 rounded-xl shadow-md text-center">
      <div className="text-4xl mb-4">{icon}</div>
      <h3 className="text-xl font-semibold mb-2">{title}</h3>
      <p className="text-gray-600">{description}</p>
    </div>
  );
}
```

8. Page Components - Hotels

Hotel Search Results with Filters

```
import { useState } from 'react';
import { Link } from 'react-router';
import { Star, MapPin, Wifi, Coffee } from 'lucide-react';
import { Slider } from '../components/ui/slider';
import { Checkbox } from '../components/ui/checkbox';
import { Button } from '../components/ui/button';
import { hotels } from '../data/hotels';

export function Hotels() {
  const [priceRange, setPriceRange] = useState([0, 500]);
  const [selectedStars, setSelectedStars] = useState<number[]>([]);
  const [amenities, setAmenities] = useState<string[]>([]);

  const filteredHotels = hotels.filter(hotel => {
    const priceMatch = hotel.price >= priceRange[0] &&
                       hotel.price <= priceRange[1];
    const starsMatch = selectedStars.length === 0 ||
                       selectedStars.includes(hotel.stars);
    return priceMatch && starsMatch;
  });

  return (
    <div className="min-h-screen bg-gray-50">
      <div className="max-w-7xl mx-auto px-4 py-8">
        <div className="grid grid-cols-1 lg:grid-cols-4 gap-8">

          {/* Filters Sidebar */}
          <aside className="lg:col-span-1">
            <div className="bg-white rounded-lg shadow p-6 sticky top-24">
              <h2 className="text-xl font-bold mb-6">Filters</h2>

              {/* Price Range */}
              <div className="mb-6">
                <h3 className="font-semibold mb-3">Price per night</h3>
                <Slider
                  min={0}
                  max={500}
                  step={10}
                  value={priceRange}
                  onValueChange={setPriceRange}
                  className="mb-2"
                />
                <div className="flex justify-between text-sm text-gray-600">
                  <span>${priceRange[0]}</span>
                  <span>${priceRange[1]}</span>
                </div>
              </div>

              {/* Star Rating */}
              <div className="mb-6">
                <h3 className="font-semibold mb-3">Star Rating</h3>
                {[5, 4, 3, 2].map(stars => (
```

```
                <label key={stars} className="flex items-center mb-2">
                  <Checkbox
                    checked={selectedStars.includes(stars)}
                    onCheckedChange={(checked) => {
                      if (checked) {
                        setSelectedStars([...selectedStars, stars]);
                      } else {
                        setSelectedStars(selectedStars.filter(s => s !== stars));
                      }
                    }}
                  />
                  <div className="ml-2 flex">
                    {Array.from({ length: stars }).map((_, i) => (
                      <Star key={i} className="w-4 h-4 fill-yellow-400
                        text-yellow-400" />
                    ))}
                  </div>
                </label>
              ))}
            </div>

            {/* Amenities */}
            <div>
              <h3 className="font-semibold mb-3">Amenities</h3>
              <label className="flex items-center mb-2">
                <Checkbox />
                <span className="ml-2">Free WiFi</span>
              </label>
              <label className="flex items-center mb-2">
                <Checkbox />
                <span className="ml-2">Pool</span>
              </label>
              <label className="flex items-center mb-2">
                <Checkbox />
                <span className="ml-2">Parking</span>
              </label>
            </div>
          </div>
        </aside>

        {/* Hotel Results */}
        <div className="lg:col-span-3">
          <div className="mb-6">
            <h1 className="text-2xl font-bold">
              {filteredHotels.length} Hotels Found
            </h1>
          </div>

          <div className="space-y-6">
            {filteredHotels.map(hotel => (
              <HotelCard key={hotel.id} hotel={hotel} />
            ))}
          </div>
```

```
          </div>
        </div>
      </div>
    </div>
  );
}

function HotelCard({ hotel }) {
  return (
    <div className="bg-white rounded-lg shadow hover:shadow-lg
      transition-shadow overflow-hidden">
      <div className="flex flex-col md:flex-row">
        <img
          src={hotel.image}
          alt={hotel.name}
          className="w-full md:w-64 h-48 object-cover"
        />
        <div className="p-6 flex-1">
          <div className="flex justify-between items-start mb-2">
            <div>
              <h3 className="text-xl font-semibold mb-1">{hotel.name}</h3>
              <div className="flex items-center text-sm text-gray-600 mb-2">
                <MapPin className="w-4 h-4 mr-1" />
                {hotel.location}
              </div>
              <div className="flex mb-2">
                {Array.from({ length: hotel.stars }).map((_, i) => (
                  <Star key={i} className="w-4 h-4 fill-yellow-400
                    text-yellow-400" />
                ))}
              </div>
            </div>
            <div className="text-right">
              <div className="text-2xl font-bold text-blue-600">
                ${hotel.price}
              </div>
              <div className="text-sm text-gray-600">per night</div>
            </div>
          </div>

          <p className="text-gray-600 mb-4">{hotel.description}</p>

          <div className="flex items-center justify-between">
            <div className="flex gap-4 text-sm text-gray-600">
              <span className="flex items-center">
                <Wifi className="w-4 h-4 mr-1" /> Free WiFi
              </span>
              <span className="flex items-center">
                <Coffee className="w-4 h-4 mr-1" /> Breakfast
              </span>
            </div>
            <Link to={`/hotel/${hotel.id}`}>
              <Button>View Details</Button>
```

```
            </Link>
          </div>
        </div>
      </div>
    </div>
  );
}
```

9. Page Components - Flights

Flight Search & Booking Interface

```
import { useState } from 'react';
import { Plane, Clock, Calendar } from 'lucide-react';
import { Button } from '../components/ui/button';
import { useBooking } from '../context/BookingContext';
import { toast } from 'sonner';
import { flights } from '../data/flights';

export function Flights() {
  const { addToCart } = useBooking();
  const [tripType, setTripType] = useState<'roundtrip' | 'oneway'>('roundtrip');

  const handleBookFlight = (flight: Flight) => {
    addToCart({
      id: `flight-${flight.id}-${Date.now()}`,
      type: 'flight',
      name: `${flight.from} to ${flight.to}`,
      price: flight.price,
      details: flight
    });
    toast.success('Flight added to cart!');
  };

  return (
    <div className="min-h-screen bg-gray-50">
      {/* Search Header */}
      <div className="bg-white border-b shadow-sm">
        <div className="max-w-6xl mx-auto px-4 py-6">
          <div className="flex gap-4 mb-6">
            <button
              onClick={() => setTripType('roundtrip')}
              className={`px-4 py-2 rounded-lg font-medium ${
                tripType === 'roundtrip'
                  ? 'bg-blue-600 text-white'
                  : 'bg-gray-100 text-gray-700'
              }`}
            >
              Round Trip
            </button>
            <button
              onClick={() => setTripType('oneway')}
              className={`px-4 py-2 rounded-lg font-medium ${
                tripType === 'oneway'
                  ? 'bg-blue-600 text-white'
                  ; 'bg-gray-100 text-gray-700'
              }`}
            >
              One Way
            </button>
          </div>

          <div className="grid grid-cols-1 md:grid-cols-4 gap-4">
            <input
```

```
            type="text"
            placeholder="From"
            className="px-4 py-3 border rounded-lg"
          />
          <input
            type="text"
            placeholder="To"
            className="px-4 py-3 border rounded-lg"
          />
          <input
            type="date"
            className="px-4 py-3 border rounded-lg"
          />
          <Button className="h-auto py-3">Search Flights</Button>
        </div>
      </div>
    </div>

    {/* Flight Results */}
    <div className="max-w-6xl mx-auto px-4 py-8">
      <h2 className="text-2xl font-bold mb-6">Available Flights</h2>

      <div className="space-y-4">
        {flights.map(flight => (
          <div key={flight.id} className="bg-white rounded-lg shadow p-6">
            <div className="grid grid-cols-1 md:grid-cols-4 gap-6 items-center">

              {/* Departure */}
              <div>
                <div className="text-2xl font-bold">{flight.departureTime}</div>
                <div className="text-gray-600">{flight.from}</div>
                <div className="text-sm text-gray-500">{flight.airline}</div>
              </div>

              {/* Duration */}
              <div className="text-center">
                <div className="flex items-center justify-center mb-2">
                  <div className="border-t-2 border-gray-300 w-full"></div>
                  <Plane className="w-5 h-5 text-blue-600 mx-2" />
                  <div className="border-t-2 border-gray-300 w-full"></div>
                </div>
                <div className="text-sm text-gray-600">
                  {flight.duration}
                </div>
                <div className="text-xs text-gray-500">
                  {flight.stops === 0 ? 'Non-stop' : `${flight.stops} stop(s)`}
                </div>
              </div>

              {/* Arrival */}
              <div>
                <div className="text-2xl font-bold">{flight.arrivalTime}</div>
                <div className="text-gray-600">{flight.to}</div>
```

```
                  <div className="text-sm text-gray-500">
                    {flight.class}
                  </div>
                </div>

                {/* Price & Book */}
                <div className="text-right">
                  <div className="text-3xl font-bold text-blue-600 mb-2">
                    ${flight.price}
                  </div>
                  <Button
                    onClick={() => handleBookFlight(flight)}
                    className="w-full"
                  >
                    Book Now
                  </Button>
                </div>
              </div>
            </div>
          ))}
        </div>
      </div>
    </div>
  );
}
```

10. Page Components - Activities

Activities & Tours Listing

```
import { Clock, Users, Star } from 'lucide-react';
import { Button } from '../components/ui/button';
import { useBooking } from '../context/BookingContext';
import { toast } from 'sonner';
import { activities } from '../data/activities';

export function Activities() {
  const { addToCart } = useBooking();

  const handleBookActivity = (activity: Activity) => {
    addToCart({
      id: `activity-${activity.id}-${Date.now()}`,
      type: 'activity',
      name: activity.name,
      price: activity.price,
      details: activity
    });
    toast.success('Activity added to cart!');
  };

  return (
    <div className="min-h-screen bg-gray-50 py-8">
      <div className="max-w-7xl mx-auto px-4">
        <h1 className="text-3xl font-bold mb-8">
          Activities & Tours
        </h1>

        <div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-3 gap-6">
          {activities.map(activity => (
            <div key={activity.id} className="bg-white rounded-lg shadow
              hover:shadow-xl transition-shadow overflow-hidden">
              <img
                src={activity.image}
                alt={activity.name}
                className="w-full h-48 object-cover"
              />
              <div className="p-6">
                <div className="flex items-center justify-between mb-2">
                  <span className="px-3 py-1 bg-blue-100 text-blue-600
                    text-sm rounded-full">
                    {activity.category}
                  </span>
                  <div className="flex items-center">
                    <Star className="w-4 h-4 fill-yellow-400 text-yellow-400 mr-1" />
                    <span className="font-semibold">{activity.rating}</span>
                  </div>
                </div>

                <h3 className="text-xl font-semibold mb-2">{activity.name}</h3>
                <p className="text-gray-600 text-sm mb-4">
                  {activity.description}
                </p>
```

```
                <div className="flex items-center gap-4 text-sm text-gray-600 mb-4">
                  <span className="flex items-center">
                    <Clock className="w-4 h-4 mr-1" />
                    {activity.duration}
                  </span>
                  <span className="flex items-center">
                    <Users className="w-4 h-4 mr-1" />
                    Up to {activity.maxPeople}
                  </span>
                </div>

                <div className="flex items-center justify-between">
                  <div>
                    <span className="text-2xl font-bold text-blue-600">
                      ${activity.price}
                    </span>
                    <span className="text-gray-600 text-sm"> per person</span>
                  </div>
                  <Button onClick={() => handleBookActivity(activity)}>
                    Book Now
                  </Button>
                </div>
              </div>
            </div>
          ))}
        </div>
      </div>
    </div>
  );
}
```

11. Cart & Checkout System

Shopping Cart Page

```
import { useNavigate } from 'react-router';
import { Trash2, ShoppingBag } from 'lucide-react';
import { Button } from '../components/ui/button';
import { useBooking } from '../context/BookingContext';

export function Cart() {
  const navigate = useNavigate();
  const { cartItems, removeFromCart, totalPrice } = useBooking();

  if (cartItems.length === 0) {
    return (
      <div className="min-h-screen bg-gray-50 py-16">
        <div className="max-w-2xl mx-auto px-4 text-center">
          <ShoppingBag className="w-24 h-24 mx-auto text-gray-400 mb-4" />
          <h2 className="text-2xl font-bold mb-2">Your cart is empty</h2>
          <p className="text-gray-600 mb-8">
            Start exploring and add items to your cart
          </p>
          <Button onClick={() => navigate('/')}>
            Start Exploring
          </Button>
        </div>
      </div>
    );
  }

  return (
    <div className="min-h-screen bg-gray-50 py-8">
      <div className="max-w-4xl mx-auto px-4">
        <h1 className="text-3xl font-bold mb-8">Shopping Cart</h1>

        <div className="grid grid-cols-1 lg:grid-cols-3 gap-8">
          {/* Cart Items */}
          <div className="lg:col-span-2 space-y-4">
            {cartItems.map(item => (
              <div key={item.id} className="bg-white rounded-lg shadow p-6">
                <div className="flex justify-between items-start">
                  <div className="flex-1">
                    <div className="flex items-center gap-2 mb-2">
                      <span className="px-2 py-1 bg-blue-100 text-blue-600
                        text-xs rounded uppercase">
                        {item.type}
                      </span>
                    </div>
                    <h3 className="text-lg font-semibold mb-1">{item.name}</h3>
                    <p className="text-gray-600 text-sm">
                      {item.details.description || item.details.location}
                    </p>
                  </div>
                  <div className="text-right ml-4">
                    <div className="text-xl font-bold text-blue-600 mb-2">
                      ${item.price}
```

```
                </div>
                <button
                  onClick={() => removeFromCart(item.id)}
                  className="text-red-600 hover:text-red-700"
                >
                  <Trash2 className="w-5 h-5" />
                </button>
              </div>
            </div>
          </div>
        ))}
      </div>

      {/* Summary */}
      <div className="lg:col-span-1">
        <div className="bg-white rounded-lg shadow p-6 sticky top-24">
          <h2 className="text-xl font-bold mb-4">Order Summary</h2>

          <div className="space-y-3 mb-4 pb-4 border-b">
            <div className="flex justify-between text-gray-600">
              <span>Subtotal ({cartItems.length} items)</span>
              <span>${totalPrice}</span>
            </div>
            <div className="flex justify-between text-gray-600">
              <span>Taxes & Fees</span>
              <span>${(totalPrice * 0.1).toFixed(2)}</span>
            </div>
          </div>

          <div className="flex justify-between text-xl font-bold mb-6">
            <span>Total</span>
            <span className="text-blue-600">
              ${(totalPrice * 1.1).toFixed(2)}
            </span>
          </div>

          <Button
            onClick={() => navigate('/checkout')}
            className="w-full mb-3"
          >
            Proceed to Checkout
          </Button>

          <Button
            onClick={() => navigate('/')}
            variant="outline"
            className="w-full"
          >
            Continue Shopping
          </Button>
        </div>
      </div>
    </div>
```

```
      </div>
    </div>
  );
}
```

Checkout Page

```
import { useState } from 'react';
import { useNavigate } from 'react-router';
import { CreditCard, User, Mail, Phone } from 'lucide-react';
import { Button } from '../components/ui/button';
import { Input } from '../components/ui/input';
import { useBooking } from '../context/BookingContext';
import { toast } from 'sonner';

export function Checkout() {
  const navigate = useNavigate();
  const { totalPrice, clearCart } = useBooking();
  const [formData, setFormData] = useState({
    firstName: '',
    lastName: '',
    email: '',
    phone: '',
    cardNumber: '',
    expiry: '',
    cvv: ''
  });

  const handleSubmit = (e: React.FormEvent) => {
    e.preventDefault();
    // Simulate payment processing
    setTimeout(() => {
      clearCart();
      navigate('/confirmation');
      toast.success('Booking confirmed!');
    }, 1500);
  };

  return (
    <div className="min-h-screen bg-gray-50 py-8">
      <div className="max-w-4xl mx-auto px-4">
        <h1 className="text-3xl font-bold mb-8">Checkout</h1>

        <form onSubmit={handleSubmit} className="grid grid-cols-1 lg:grid-cols-3 gap-8">
          {/* Form Fields */}
          <div className="lg:col-span-2 space-y-6">
            {/* Guest Information */}
            <div className="bg-white rounded-lg shadow p-6">
              <h2 className="text-xl font-semibold mb-4">
                Guest Information
              </h2>
              <div className="grid grid-cols-2 gap-4">
                <Input
                  placeholder="First Name"
                  required
                  value={formData.firstName}
                  onChange={(e) => setFormData({...formData, firstName: e.target.value})}
                />
                <Input
```

```
                placeholder="Last Name"
                required
                value={formData.lastName}
                onChange={(e) => setFormData({...formData, lastName: e.target.value})}
              />
              <Input
                type="email"
                placeholder="Email"
                required
                className="col-span-2"
                value={formData.email}
                onChange={(e) => setFormData({...formData, email: e.target.value})}
              />
              <Input
                type="tel"
                placeholder="Phone"
                required
                className="col-span-2"
                value={formData.phone}
                onChange={(e) => setFormData({...formData, phone: e.target.value})}
              />
            </div>
          </div>

          {/* Payment Information */}
          <div className="bg-white rounded-lg shadow p-6">
            <h2 className="text-xl font-semibold mb-4">
              Payment Information
            </h2>
            <div className="space-y-4">
              <Input
                placeholder="Card Number"
                required
                maxLength={16}
                value={formData.cardNumber}
                onChange={(e) => setFormData({...formData, cardNumber: e.target.value})
              />
              <div className="grid grid-cols-2 gap-4">
                <Input
                  placeholder="MM/YY"
                  required
                  value={formData.expiry}
                  onChange={(e) => setFormData({...formData, expiry: e.target.value})}
                />
                <Input
                  placeholder="CVV"
                  required
                  maxLength={3}
                  value={formData.cvv}
                  onChange={(e) => setFormData({...formData, cvv: e.target.value})}
                />
              </div>
            </div>
```

```
            </div>
          </div>

          {/* Summary */}
          <div className="lg:col-span-1">
            <div className="bg-white rounded-lg shadow p-6 sticky top-24">
              <h2 className="text-xl font-semibold mb-4">Order Total</h2>
              <div className="text-3xl font-bold text-blue-600 mb-6">
                ${(totalPrice * 1.1).toFixed(2)}
              </div>
              <Button type="submit" className="w-full">
                Complete Booking
              </Button>
            </div>
          </div>
        </form>
      </div>
    </div>
  );
}
```

12. Authentication Pages

Login & Signup Page

```
import { useState } from 'react';
import { useNavigate } from 'react-router';
import { Mail, Lock, User } from 'lucide-react';
import { Button } from '../components/ui/button';
import { Input } from '../components/ui/input';
import { Tabs, TabsContent, TabsList, TabsTrigger } from '../components/ui/tabs';
import { useBooking } from '../context/BookingContext';
import { toast } from 'sonner';

export function Login() {
  const navigate = useNavigate();
  const { login } = useBooking();
  const [activeTab, setActiveTab] = useState('login');

  const handleLogin = (e: React.FormEvent) => {
    e.preventDefault();
    const formData = new FormData(e.target as HTMLFormElement);
    login({
      id: '1',
      name: 'John Doe',
      email: formData.get('email') as string
    });
    toast.success('Welcome back!');
    navigate('/profile');
  };

  const handleSignup = (e: React.FormEvent) => {
    e.preventDefault();
    const formData = new FormData(e.target as HTMLFormElement);
    login({
      id: '1',
      name: formData.get('name') as string,
      email: formData.get('email') as string
    });
    toast.success('Account created successfully!');
    navigate('/profile');
  };

  return (
    <div className="min-h-screen bg-gradient-to-br from-blue-50 to-blue-100
      flex items-center justify-center py-12 px-4">
      <div className="max-w-md w-full">
        <div className="text-center mb-8">
          <h1 className="text-3xl font-bold text-gray-900 mb-2">
            Welcome to TravelBook
          </h1>
          <p className="text-gray-600">
            Sign in to manage your bookings
          </p>
        </div>

        <Tabs value={activeTab} onValueChange={setActiveTab}
```

```
            className="bg-white rounded-xl shadow-lg p-6">
            <TabsList className="grid w-full grid-cols-2 mb-6">
              <TabsTrigger value="login">Sign In</TabsTrigger>
              <TabsTrigger value="signup">Sign Up</TabsTrigger>
            </TabsList>

            {/* Login Tab */}
            <TabsContent value="login">
              <form onSubmit={handleLogin} className="space-y-4">
                <div>
                  <label className="block text-sm font-medium mb-2">
                    Email
                  </label>
                  <div className="relative">
                    <Mail className="absolute left-3 top-3 w-5 h-5 text-gray-400" />
                    <Input
                      name="email"
                      type="email"
                      required
                      placeholder="your@email.com"
                      className="pl-10"
                    />
                  </div>
                </div>

                <div>
                  <label className="block text-sm font-medium mb-2">
                    Password
                  </label>
                  <div className="relative">
                    <Lock className="absolute left-3 top-3 w-5 h-5 text-gray-400" />
                    <Input
                      name="password"
                      type="password"
                      required
                      placeholder="••••••••"
                      className="pl-10"
                    />
                  </div>
                </div>

                <Button type="submit" className="w-full">
                  Sign In
                </Button>
              </form>
            </TabsContent>

            {/* Signup Tab */}
            <TabsContent value="signup">
              <form onSubmit={handleSignup} className="space-y-4">
                <div>
                  <label className="block text-sm font-medium mb-2">
                    Full Name
```

```
                </label>
                <div className="relative">
                  <User className="absolute left-3 top-3 w-5 h-5 text-gray-400" />
                  <Input
                    name="name"
                    required
                    placeholder="John Doe"
                    className="pl-10"
                  />
                </div>
              </div>

              <div>
                <label className="block text-sm font-medium mb-2">
                  Email
                </label>
                <div className="relative">
                  <Mail className="absolute left-3 top-3 w-5 h-5 text-gray-400" />
                  <Input
                    name="email"
                    type="email"
                    required
                    placeholder="your@email.com"
                    className="pl-10"
                  />
                </div>
              </div>

              <div>
                <label className="block text-sm font-medium mb-2">
                  Password
                </label>
                <div className="relative">
                  <Lock className="absolute left-3 top-3 w-5 h-5 text-gray-400" />
                  <Input
                    name="password"
                    type="password"
                    required
                    placeholder="••••••••"
                    className="pl-10"
                  />
                </div>
              </div>

              <Button type="submit" className="w-full">
                Create Account
              </Button>
            </form>
          </TabsContent>
        </Tabs>
      </div>
    </div>
```

```
  );
}
```

13. Shadcn UI Components

Button Component

```
import { forwardRef } from 'react';
import { Slot } from '@radix-ui/react-slot';

export interface ButtonProps
  extends React.ButtonHTMLAttributes<HTMLButtonElement> {
  variant?: 'default' | 'outline' | 'ghost' | 'destructive';
  size?: 'default' | 'sm' | 'lg';
  asChild?: boolean;
}

const Button = forwardRef<HTMLButtonElement, ButtonProps>(
  ({ className, variant = 'default', size = 'default', asChild = false, ...props }, ref) =
    const Comp = asChild ? Slot : 'button';

    const baseStyles = "inline-flex items-center justify-center rounded-lg font-medium tra

    const variants = {
      default: "bg-blue-600 text-white hover:bg-blue-700",
      outline: "border-2 border-gray-300 bg-white hover:bg-gray-50",
      ghost: "hover:bg-gray-100",
      destructive: "bg-red-600 text-white hover:bg-red-700"
    };

    const sizes = {
      default: "h-10 px-4 py-2",
      sm: "h-8 px-3 text-sm",
      lg: "h-12 px-8 text-lg"
    };

    return (
      <Comp
        className={`${baseStyles} ${variants[variant]} ${sizes[size]} ${className}`}
        ref={ref}
        {...props}
      />
    );
  }
);

Button.displayName = 'Button';
export { Button };
```

Input Component

```
import { forwardRef } from 'react';

export interface InputProps
  extends React.InputHTMLAttributes<HTMLInputElement> {}

const Input = forwardRef<HTMLInputElement, InputProps>(
  ({ className, type, ...props }, ref) => {
    return (
      <input
        type={type}
        className={`flex h-10 w-full rounded-lg border border-gray-300
          bg-white px-3 py-2 text-sm ring-offset-white
          file:border-0 file:bg-transparent file:text-sm file:font-medium
          placeholder:text-gray-400
          focus-visible:outline-none focus-visible:ring-2
          focus-visible:ring-blue-500 focus-visible:ring-offset-2
          disabled:cursor-not-allowed disabled:opacity-50
          ${className}`}
        ref={ref}
        {...props}
      />
    );
  }
);

Input.displayName = 'Input';
export { Input };
```

Card Component

```
import { forwardRef } from 'react';

const Card = forwardRef<HTMLDivElement, React.HTMLAttributes<HTMLDivElement>>(
  ({ className, ...props }, ref) => (
    <div
      ref={ref}
      className={`rounded-xl border border-gray-200 bg-white
        shadow-sm ${className}`}
      {...props}
    />
  )
);

const CardHeader = forwardRef<HTMLDivElement, React.HTMLAttributes<HTMLDivElement>>(
  ({ className, ...props }, ref) => (
    <div
      ref={ref}
      className={`flex flex-col space-y-1.5 p-6 ${className}`}
      {...props}
    />
  )
);

const CardTitle = forwardRef<HTMLParagraphElement, React.HTMLAttributes<HTMLHeadingElemen
  ({ className, ...props }, ref) => (
    <h3
      ref={ref}
      className={`text-xl font-semibold leading-none tracking-tight
        ${className}`}
      {...props}
    />
  )
);

const CardContent = forwardRef<HTMLDivElement, React.HTMLAttributes<HTMLDivElement>>(
  ({ className, ...props }, ref) => (
    <div ref={ref} className={`p-6 pt-0 ${className}`} {...props} />
  )
);

export { Card, CardHeader, CardTitle, CardContent };
```

14. Responsive Design Patterns

Breakpoint System

```
/* Tailwind CSS Breakpoints */
sm:  640px  // Small devices (phones)
md:  768px  // Medium devices (tablets)
lg:  1024px // Large devices (desktops)
xl:  1280px // Extra large devices
2xl: 1536px // 2X Extra large devices

/* Usage Examples */

// Mobile-first approach (default = mobile)
<div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-3">
  // 1 column on mobile
  // 2 columns on tablet
  // 3 columns on desktop
</div>

// Hide/show at breakpoints
<div className="hidden md:block">
  // Hidden on mobile, visible on tablet+
</div>

<div className="block md:hidden">
  // Visible on mobile, hidden on tablet+
</div>

// Responsive spacing
<div className="p-4 md:p-6 lg:p-8">
  // 16px padding on mobile
  // 24px padding on tablet
  // 32px padding on desktop
</div>

// Responsive text
<h1 className="text-2xl md:text-3xl lg:text-4xl">
  // Scales up at larger screens
</h1>
```

Mobile Navigation Pattern

```
import { useState } from 'react';
import { Menu, X } from 'lucide-react';

function ResponsiveNav() {
  const [isOpen, setIsOpen] = useState(false);

  return (
    <nav className="bg-white border-b">
      <div className="max-w-7xl mx-auto px-4">
        {/* Desktop Header */}
        <div className="flex justify-between items-center h-16">
          <div className="flex items-center">
            <span className="text-2xl font-bold">Logo</span>
          </div>

          {/* Desktop Menu */}
          <div className="hidden md:flex items-center space-x-8">
            <a href="/hotels">Hotels</a>
            <a href="/flights">Flights</a>
            <a href="/activities">Activities</a>
          </div>

          {/* Mobile Menu Button */}
          <button
            className="md:hidden"
            onClick={() => setIsOpen(!isOpen)}
          >
            {isOpen ? <X /> : <Menu />}
          </button>
        </div>

        {/* Mobile Menu */}
        {isOpen && (
          <div className="md:hidden py-4 space-y-2">
            <a href="/hotels" className="block py-2">Hotels</a>
            <a href="/flights" className="block py-2">Flights</a>
            <a href="/activities" className="block py-2">Activities</a>
          </div>
        )}
      </div>
    </nav>
  );
}
```

Responsive Grid Layouts

```
/* Product Grid - Responsive Columns */
<div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-3 xl:grid-cols-4 gap-6">
  {/* Cards adjust based on screen size */}
</div>

/* Sidebar Layout - Stack on Mobile */
<div className="grid grid-cols-1 lg:grid-cols-4 gap-8">
  <aside className="lg:col-span-1">
    {/* Sidebar - Full width on mobile, 1/4 on desktop */}
  </aside>
  <main className="lg:col-span-3">
    {/* Main content - Full width on mobile, 3/4 on desktop */}
  </main>
</div>

/* Flexbox Alternative */
<div className="flex flex-col lg:flex-row gap-8">
  <aside className="lg:w-64">Sidebar</aside>
  <main className="flex-1">Main Content</main>
</div>

/* Container Max Widths */
<div className="container mx-auto px-4 max-w-7xl">
  {/* Responsive container with consistent padding */}
</div>
```

Touch-Friendly Interactions

```
/* Minimum Touch Target Size: 44x44 pixels */

// Buttons
<button className="h-12 px-6 text-lg">
  {/* Large enough for touch */}
</button>

// Form Inputs
<input className="h-12 px-4 text-base" />

// Cards with hover states (disable on touch)
<div className="hover:shadow-lg active:shadow-lg transition-shadow">
  {/* Works on both mouse and touch */}
</div>

// Swipe gestures (with react-swipeable)
import { useSwipeable } from 'react-swipeable';

const handlers = useSwipeable({
  onSwipedLeft: () => console.log('Swiped left'),
  onSwipedRight: () => console.log('Swiped right'),
});

<div {...handlers} className="touch-pan-x">
  {/* Swipeable content */}
</div>
```

Installation & Setup

Package Dependencies

```
{
  "dependencies": {
    "react": "^18.2.0",
    "react-dom": "^18.2.0",
    "react-router": "^6.22.0",
    "@radix-ui/react-checkbox": "^1.0.4",
    "@radix-ui/react-dialog": "^1.0.5",
    "@radix-ui/react-select": "^2.0.0",
    "@radix-ui/react-slider": "^1.1.2",
    "@radix-ui/react-slot": "^1.0.2",
    "@radix-ui/react-tabs": "^1.0.4",
    "lucide-react": "^0.344.0",
    "date-fns": "^3.3.1",
    "sonner": "^1.4.3",
    "class-variance-authority": "^0.7.0",
    "clsx": "^2.1.0",
    "tailwind-merge": "^2.2.1"
  },
  "devDependencies": {
    "@types/react": "^18.2.0",
    "@types/react-dom": "^18.2.0",
    "@vitejs/plugin-react": "^4.2.1",
    "typescript": "^5.3.0",
    "vite": "^5.1.0",
    "tailwindcss": "^4.0.0"
  }
}
```

Installation Steps

```
# 1. Install dependencies
npm install

# 2. Run development server
npm run dev

# 3. Build for production
npm run build

# 4. Preview production build
npm run preview
```

Environment Configuration

```
# Create .env file for API keys (optional)
VITE_API_URL=https://api.example.com
VITE_STRIPE_KEY=pk_test_...

# Access in code:
const apiUrl = import.meta.env.VITE_API_URL;
```

Important Notes:

- This is a prototype with mock data - not production-ready
- Payment processing is simulated - no real transactions
- Authentication is client-side only - implement server auth for production
- Cart data is not persisted - add localStorage or backend persistence
- Images use placeholder URLs - replace with real assets

Development Best Practices

Code Organization

Component Structure

- Keep components small and focused (single responsibility)
- Use descriptive component and prop names
- Extract reusable logic into custom hooks
- Organize related components in folders

State Management

- Use Context for truly global state
- Keep local state close to where it's used
- Avoid prop drilling - lift state or use Context
- Consider using reducers for complex state logic

Performance

- Use React.memo for expensive components
- Implement code splitting with lazy loading
- Optimize images (use WebP, proper sizing)
- Debounce search inputs and API calls

Accessibility Guidelines

```
/* Semantic HTML */
<nav>...</nav>
<main>...</main>
<footer>...</footer>
<article>...</article>

/* ARIA Labels */
<button aria-label="Close menu">
  <X className="w-5 h-5" />
</button>

/* Keyboard Navigation */
<div
  role="button"
  tabIndex={0}
  onKeyDown={(e) => e.key === 'Enter' && handleClick()}
>
  Clickable Div
</div>

/* Focus Styles */
className="focus:ring-2 focus:ring-blue-500 focus:outline-none"

/* Alt Text for Images */
<img src={hotel.image} alt={`${hotel.name} exterior view`} />

/* Form Labels */
<label htmlFor="email">Email Address</label>
<input id="email" type="email" />
```

Testing Recommendations

```
/* Unit Tests - Components */
import { render, screen } from '@testing-library/react';
import { Button } from './Button';

test('renders button with text', () => {
  render(<Button>Click me</Button>);
  expect(screen.getByText('Click me')).toBeInTheDocument();
});

/* Integration Tests - User Flows */
test('add hotel to cart flow', async () => {
  render(<App />);

  // Navigate to hotels
  fireEvent.click(screen.getByText('Hotels'));

  // Click on first hotel
  fireEvent.click(screen.getAllByText('View Details')[0]);

  // Add to cart
  fireEvent.click(screen.getByText('Add to Cart'));

  // Verify cart badge
  expect(screen.getByText('1')).toBeInTheDocument();
});

/* E2E Tests - Critical Paths */
describe('Booking Flow', () => {
  it('completes full booking journey', () => {
    cy.visit('/');
    cy.get('[data-testid="search-hotels"]').click();
    cy.get('[data-testid="hotel-card"]').first().click();
    cy.get('[data-testid="add-to-cart"]').click();
    cy.get('[data-testid="cart-icon"]').click();
    cy.get('[data-testid="checkout-btn"]').click();
    cy.get('[data-testid="complete-booking"]').click();
    cy.url().should('include', '/confirmation');
  });
});
```

Code Documentation Complete

Travel Booking Website - Full Stack Reference

What's Included:

✓ Complete React component code

✓ Tailwind CSS styling examples

✓ Context API state management

✓ React Router navigation setup

✓ Shadcn UI component library

✓ Responsive design patterns

✓ Best practices and guidelines

✓ Installation and setup instructions

Next Steps:

→ Add real API integration for hotels/flights data

→ Implement server-side authentication

→ Add database for booking persistence

→ Integrate real payment gateway (Stripe)

→ Add email notifications

→ Implement user reviews and ratings

→ Add advanced filters and sorting

→ Create admin dashboard

TravelBooker

Your trusted partner for unforgettable travel experiences around the world.

Quick Links

About Us

Destinations

Special Offers

Contact

Support

Help Center

Privacy Policy

Terms of Service

FAQs

Connect With Us

Subscribe to our newsletter for exclusive deals and travel tips.

© 2026 TravelBooker. All rights reserved.

Wireframes Code Documentation